NPG Display Ltd. Taiwan Branch 香港商恩倍福股份有限公司台灣分公司 音で用るILT THAT STOP HAT STOP A FIND STOP A



Tel:+886 2 703 8282 Fax: +886 2 702 9472

Date: Feb. 19, 2000

To:			Б. (
			Ref:
(Fax:		)	Date
Attn:			CC;
From:	,		Page

Federal Communications Commission Authorization and Evaluation Division 7435 Oakland Mills Rd. Columbia, MD. 21046

Attention: Authorization and Evaluation Division

Subject: RFI related modifications incorporated into unit with - FCC ID: M6JN9702

Dear Sirs:

This letter serves as our declaration that all modifications listed below were implemented in the sample submitted for testing. We further declare that the same modifications will be implemented into all production units to enhance compliance of the units to FCC limits.

- 1. Added two ferrite cores on the video cable, one inside and one outside the
- monitor. (see photo 2 and 9)
  2. Added a metal cover on the rear side of CRT board and it was connected to chassis by eight ground wires. (see photo 5)
- 3. Added a ferrite core on the wire connected between mainboard and CRT board with one turn. (see photo 3)
- 4. Added a ferrite core on the focus wires with one turn. (see photo 9)
  5. Added a ferrite core on the G2 wire with one turn. (see photo 9)
- 6. Added a ferrite core on the wires connected to mainboard. (see photo 9)
- 7. Added two capacitors for EMI, three capacitors, two jump wires and two bead core on the solder side of mainboard for electrical improvement only and not for EMI.
- They will be built into component side after circuit relayout. (see photo 10)

  8. Added three capacitors and one bead core on the solder side of CRT board for EMI. It will be built into component side after circuit relayout. (see photo 12)

If you have any further questions or comments regarding the above, please don't hesitate to contact Mr. Johnson Ho of Spectrum Research and Testing Laboratory at (301) 855-2262.

Sincerely yours,

Johnson Shieh / Executive Engineer of R&D Div. NPG DISPLAY LTD. TAIWAN BRANCH

cc. Mr. Mike Su - Advance Data Technology Corporation