



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Applicant : Graco Children's Products Inc.

Address : 150 Oaklands Boulevard, Exton PA 19341.

Product Name : Baby monitor

Model Name : PD160487

Brand Name : Graco

FCC ID : M6YPD160487

Report No. : MOST101005F2

Date of Issue : October. 30, 2010

Issued by : Most Technology Service Co., Ltd.

Address : No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China

Tel : 86-755-8617 0306

Fax : 86-755-8617 0310

The report consists 44 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by MOST. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	3
2. GENERAL INFORMATION	4
2.1 PRODUCT INFORMATION	4
2.2 OBJECTIVE	5
2.3 TEST STANDARDS AND RESULTS	5
2.4 ENVIRONMENTAL CONDITIONS	5
3. TEST FACILITY	6
3.1 TEST FACILITY	6
3.2 GENERAL TEST PROCEDURES	6
3.3 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	7
4. SETUP OF EQUIPMENT UNDER TEST	8
4.1 SUPPORT EQUIPMENT	8
4.2 TEST EQUIPMENT LIST	9
5. 47 CFR PART 15C 15.249 REQUIREMENTS	10
5.1 SPURIOUS EMISSION TEST	10
5.1.1 REQUIREMENT	10
5.1.2 TEST DESCRIPTION	11
5.1.3 TEST DESCRIPTION	12
5.1.4 TEST RESULT	13
5.2 BAND EDGE	23
5.2.1 REQUIREMENT	23
5.2.2 TEST DESCRIPTION	23
5.2.3 TEST RESULT	23
5.3 ANTENNA REQUIREMENT	25
5.3.1 DEFINITION	25
5.3.2 EVALUATION PROCEDURE	25
5.3.3 EVALUATION CRITERIA	25
5.3.4 EVALUATION RESULTS	25
5.4 POWER LINE CONDUCTED EMISSION TEST	26
5.4.1 LIMITS OF LINE CONDUCTED EMISSION TEST	26
5.4.2 BLOCK DIAGRAM OF TEST SETUP	26
5.4.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	27
5.4.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	27
5.4.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST	28
APPENDIX 1	32
PHOTOGRAPHS OF TEST SETUP	32
APPENDIX 2	36
PHOTOGRAPHS OF EUT	36


1. VERIFICATION OF CONFORMITY

Equipment Under Test: Baby monitor
Brand Name: Graco
Model Number: PD160487
FCC ID: M6YPD160487
Applicant: Graco Children's Products Inc.
150 OAKLANDS BOULEVARD, EXTON PA 19341.
Manufacturer: Hone Tone Electronic Ltd.
HonorTone Ltd. No.15-16, Western Zone, DayaWan, Huizhou City,
Guangdong Province, China.
Technical Standards: 47 CFR Part 15 Subpart C
File Number: MOST101005F2
Date of test: October. 19, 2010 – October. 29, 2010
Deviation: None
Condition of Test Sample: Normal
Test Result: PASS

The above equipment was tested by MOST for compliance with the requirements set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Tested by (+ signature):




Petter Ping October. 30, 2010

Review by (+ signature):



July Wen October. 30, 2010

Approved by (+ signature):



Terry Yang October. 30, 2010

2. GENERAL INFORMATION

2.1 Product Information

Product	Baby monitor
Trade Name	Graco
Model Number	PD160487
Series Number:	N/A
Description of Differences:	N/A
Power Supply	DC 6V by AC Adapter 120V/60Hz DC 3.6V by battery(3 x AAA)
Frequency Range	907MHz – 927 MHz
Modulation Type	FSK
Antenna Type:	Internal Fixed
Channel Number	6 (907.001MHz, 911.001MHz, 915.001MHz, 919.001MHz, 923.001MHz, 927.001MHz)
Temperature Range	-20°C ~ 50°C

NOTE:

1. Please refer to Appendix I for the photographs of the EUT. For a more detailed features description about the EUT, please refer to User's Manual.

2.2 Objective

The objective of the report is to perform tests according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-05 Edition)	Radio Frequency Devices

2.3 Test Standards and Results

Test items and the results are as bellow:

No.	Section	Description	Result	Date of Test
1	15.249(a)	Spurious Emission	PASS	2010-10-29
2	15.249(a)	Band Edge	PASS	2010-10-29
3	15.203	Antenna Requirement	PASS	2010-10-29
4	15.207	Power Line Conducted Emission Test	PASS	2010-10-19

Note: 1. The test result judgment is decided by the limit of measurement standard
 2. The information of measurement uncertainty is available upon the customer's request.

2.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa

3. TEST FACILITY

3.1 TEST FACILITY

Test Site: Most Technology Service Co., Ltd.

Location: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park, Nanshan, Shenzhen, Guangdong, China

Description: There is one 3m semi-anechoic an area test sites and two line conducted labs for final test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003 and CISPR 16 requirements.

The FCC Registration Number is **490827**.

The IC Registration Number is **46405-7103**.

The CNAS Registration Number is **CNAS L3573**.

Site Filing: The site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.

Instrument Tolerance: All measuring equipment is in accord with ANSI C63.4:2003 and CISPR 16 requirements that meet industry regulatory agency and accreditation agency requirement.

Ground Plane: Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna.

3.2 GENERAL TEST PROCEDURES

EUT Function and Test Mode

The EUT has been tested under normal operating (TX) and standby (RX) condition.

The field strength of radiation emission was measured in the following position: EUT stand-up position (Y axis), lie-down position (X, Z axis).

The following data show only with the worst case setup.

The worst case of Y axis was reported.

Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report.

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4:2003, Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4:2003.

3.3 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

4. SETUP OF EQUIPMENT UNDER TEST**4.1 SUPPORT EQUIPMENT**

Device Type	Brand	Model	FCC ID	Series No.	Data Cable	Power Cord
---	---	---	---	---	---	---

Remark:

All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2 TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at Most for testing. The equipment conforms to the CISPR 16-1 / ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

No.	Equipment	Manufacturer	Model No.	S/N	Calibration date	Calibration due date
1	Test Receiver	Rohde & Schwarz	ESCI	100492	2010/03/14	2011/03/14
2	L.I.S.N.	Rohde & Schwarz	ENV216	100093	2010/03/14	2011/03/14
3	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2010/03/14	2011/03/14
4	Terminator	Hubersuhner	50Ω	No.1	2010/03/14	2011/03/14
5	RF Cable	SchwarzBeck	N/A	No.1	2010/03/14	2011/03/14
6	Test Receiver	Rohde & Schwarz	ESPI	101202	2010/03/14	2011/03/14
7	Bilog Antenna	Sunol	JB3	A121206	2010/03/14	2011/03/14
8	Test Antenna - Horn	Schwarzbeck	BBHA 9120C	--	2010/03/14	2011/03/14
9	Test Antenna - LOOP	Schwarzbeck	VULB 9163	--	2010/03/14	2011/03/14
10	Cable	Resenberger	N/A	NO.1	2010/03/14	2011/03/14
11	Cable	SchwarzBeck	N/A	NO.2	2010/03/14	2011/03/14
12	Cable	SchwarzBeck	N/A	NO.3	2010/03/14	2011/03/14
13	DC Power Filter	DuoJi	DL2×30B	N/A	2010/03/14	2011/03/14
14	Single Phase Power Line Filter	DuoJi	FNF 202B30	N/A	2010/03/14	2011/03/14
15	3 Phase Power Line Filter	DuoJi	FNF 402B30	N/A	2010/03/14	2011/03/14
16	Spectrum Analyzer	Agilent	4408B	MY41440460	2010/03/14	2011/03/14
17	Absorbing Clamp	Luthi	MDS21	3635	2010/03/14	2011/03/14
18	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2010/03/14	2011/03/14
19	AC Power Source	Kikusui	AC40MA	LM003232	2010/03/14	2011/03/14
20	Test Analyzer	Kikusui	KHA1000	LM003720	2010/03/14	2011/03/14
21	Line Impedence Network	Kikusui	LIN40MA-PCR-L	LM002352	2010/03/14	2011/03/14
22	ESD Tester	Kikusui	KES4021	LM003537	2010/03/14	2011/03/14
23	EMCPRO System	EM Test	UCS-500-M4	V0648102026	2010/03/14	2011/03/14
24	Signal Generator	IFR	2032	203002/100	2010/03/14	2011/03/14
25	Amplifier	A&R	150W1000	301584	2010/03/14	2011/03/14
26	CDN	FCC	FCC-801-M2-25	47	2010/03/14	2011/03/14
27	CDN	FCC	FCC-801-M3-25	107	2010/03/14	2011/03/14
28	EM Injection Clamp	FCC	F-203I-23mm	403	2010/03/14	2011/03/14
29	RF Cable	MIYAZAKI	N/A	No.1/No.2	2010/03/14	2011/03/14
30	Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	0304789	2010/03/14	2011/03/14
31	Telecommunication Antenna	European Antennas	PSA 75301R/170	0304213	2010/03/14	2011/03/14
32	Temperature Chamber	Guangzhou Gongwen	GDS-250	N/A	2010/03/14	2011/03/14

NOTE: Equipments listed above have been calibrated and are in the period of validation.

5. 47 CFR Part 15C 15.249 Requirements

5.1 Spurious Emission Test

5.1.1 Requirement

According to FCC section 15.249(a):

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (μV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


In the above emission table, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


5.1.2 Test Description


Test Setup:

Below 30MHz:



From 30MHz to 1000MHz:



Above 1GHz:**5.1.3 Test Description**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
 - Below 1GHz: RBW=100 kHz / VBW=300 kHz / Sweep=AUTO
 - Above 1GHz : (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

5.1.4 Test Result



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement



Site: site MOST 3M

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Part15 B 3M Radiation

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Baby Monitor

Distance:

M/N: PD160487

Mode: TX

Note: U060020D12

No.	Mk.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
		Level	Factor	ment						
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1	256.0100	11.18	17.44	28.62	46.00	-17.38	peak			
2 !	448.0700	21.31	20.14	41.45	46.00	-4.55	peak			
3 !	475.2300	21.29	21.41	42.70	46.00	-3.30	peak			
4	651.7700	10.23	24.14	34.37	46.00	-11.63	peak			
5	746.8300	9.55	25.80	35.35	46.00	-10.65	peak			

*:Maximum data x:Over limit !:over margin

Note: The overload point is the fundamental of the operating frequency, it may be ignored.



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement


File :PD160487

Data :#17

Date: 2010-10-29

Time: 23:51:49

70.0 dBuV/m



Site: site MOST 3M

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part15 B 3M Radiation

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Baby Monitor

Distance:

M/N: PD160487

Mode: TX

Note: U060020D12

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment				Height	Degree
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		179.3800	13.00	16.73	29.73	43.50	-13.77	peak		
2	!	458.7400	22.78	20.34	43.12	46.00	-2.88	peak		
3		682.8100	11.85	24.44	36.29	46.00	-9.71	peak		
4		715.7900	13.59	24.66	38.25	46.00	-7.75	peak		
5		746.8300	12.21	25.80	38.01	46.00	-7.99	peak		


*:Maximum data x:Over limit !:over margin

Note: The overload point is the fundamental of the operating frequency, it may be ignored.



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
 Guangdong, China
 Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement



Site site MOST 3M

Limit: FCC Part15 B 3M Radiation

Polarization: **Vertical**

Temperature: 26

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Baby Monitor

Distance:

M/N: PD160487

Mode: TX

Note: KA12D060020023U

No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height cm	Table Degree	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB	Detector	degree	
1 !	458.7400	22.01	20.34	42.35	46.00	-3.65	peak		
2 !	475.2300	18.60	21.41	40.01	46.00	-5.99	peak		
3	682.8099	11.30	24.44	35.74	46.00	-10.26	peak		
4	714.8200	14.90	24.65	39.55	46.00	-6.45	peak		
5	747.8000	13.75	25.80	39.55	46.00	-6.45	peak		

*:Maximum data x:Over limit !:over margin

Note: The overload point is the fundamental of the operating frequency, it may be ignored.



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement



Site site MOST 3M

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Part15 B 3M Radiation

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Baby Monitor

Distance:

M/N: PD160487

Mode: TX

Note: KA12D060020023U

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	Comment
			Level	Factor	ment			Height	Degree	
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	
1		256.0100	18.96	17.44	36.40	46.00	-9.60	peak		
2	!	458.7400	21.97	20.34	42.31	46.00	-3.69	peak		
3	!	480.0800	20.05	21.70	41.75	46.00	-4.25	peak		
4		715.7900	14.78	24.66	39.44	46.00	-6.56	peak		
5		747.8000	12.23	25.80	38.03	46.00	-7.97	peak		

*:Maximum data x:Over limit !:over margin

Note: The overload point is the fundamental of the operating frequency, it may be ignored.



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement

File : PD160487

Data : #20

Date: 2010-10-29

Time: 23:56:53



Site: site MOST 3M

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Part15 B 3M Radiation

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Baby Monitor

Distance:

M/N: PD160487

Mode: TX

Note: KA12D060020023U

No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
			dBuV	dB	dBuV/m			Detector	degree	
1		271.5300	13.36	18.99	32.35	46.00	-13.65	peak		
2		431.5800	15.87	20.32	36.19	46.00	-9.81	peak		
3	!	463.5900	22.97	20.80	43.77	46.00	-2.23	peak		
4		494.6300	15.40	21.51	36.91	46.00	-9.09	peak		
5		735.1900	14.04	25.16	39.20	46.00	-6.80	peak		

*:Maximum data x:Over limit !:over margin


Note: The overload point is the fundamental of the operating frequency, it may be ignored.



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement

File :PD160487 Data #:21 Date: 2010-10-29 Time: 23:57:29



Site: site MOST 3M

Limit: FCC Part15 B 3M Radiation

Polarization: **Vertical**

Temperature: 26

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Baby Monitor

Distance:

M/N: PD160487

Mode: TX

Note: KA12D060020023U

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					Comment
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	
1		130.8800	16.62	17.66	34.28	43.50	-9.22	peak		
2		256.0100	9.50	17.44	26.94	46.00	-19.06	peak		
3		463.5900	19.06	20.80	39.86	46.00	-6.14	peak		
4		703.1800	13.41	24.67	38.08	46.00	-7.92	peak		
5	!	735.1900	14.93	25.16	40.09	46.00	-5.91	peak		

*:Maximum data x:Over limit !:over margin

Note: The overload point is the fundamental of the operating frequency, it may be ignored.



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
 Guangdong, China
 Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement



Site site MOST 3M

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part15 B 3M Radiation

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Baby Monitor

Distance:

M/N: PD160487

Mode: TX

Note: U060020D12

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment				Height	Degree	Comment
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		268.6200	9.44	18.72	28.16	46.00	-17.84	peak			
2	!	463.5900	20.60	20.80	41.40	46.00	-4.60	peak			
3		480.0800	16.18	21.70	37.88	46.00	-8.12	peak			
4		703.1800	13.94	24.67	38.61	46.00	-7.39	peak			
5	!	735.1900	15.41	25.16	40.57	46.00	-5.43	peak			

*:Maximum data x:Over limit !:over margin

Note: The overload point is the fundamental of the operating frequency, it may be ignored.



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
 Guangdong, China
 Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement



Site site MOST 3M

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Part15 B 3M Radiation

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Baby Monitor

Distance:

M/N: PD160487

Mode: TX

Note: U060020D12

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					Comment
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	
1		256.0100	13.20	17.44	30.64	46.00	-15.36	peak		
2	!	462.6200	23.51	20.69	44.20	46.00	-1.80	peak		
3		495.6000	15.95	21.49	37.44	46.00	-8.56	peak		
4		703.1800	14.97	24.67	39.64	46.00	-6.36	peak		
5	!	735.1900	17.54	25.16	42.70	46.00	-3.30	peak		

*:Maximum data x:Over limit !:over margin

Note: The overload point is the fundamental of the operating frequency, it may be ignored.

Fundamental Emission:

Freq. (MHz)	Ant. Pol H/V	Peak	Ant. / CL	Actual Fs	Peak	AV	Detection
		Reading	CF		Limit	Margin	
		(dBuV)	(dB)		Peak	(dBuV/m)	
Low Channel							
907.002	H	65.15	27.56	92.71	94.00	-1.29	QP
907.002	V	60.62	27.56	88.18	94.00	-5.82	QP
Middle Channel							
919.001	H	63.90	27.50	91.40	94.00	-2.60	QP
919.001	V	60.02	27.50	87.52	94.00	-6.48	QP
High Channel							
927.001	H	64.86	27.43	92.29	94.00	-1.71	QP
927.001	V	60.23	27.43	87.66	94.00	-6.34	QP

Above 1 GHz

Operation Mode: CH Low **Test Date:** October. 29, 2010
Temperature: 20°C **Tested by:** Petter Ping
Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak	AV	Ant. / CL	Actual Fs	Peak	AV	AV	
		Reading	Reading	CF		Limit	Limit	Margin	
		(dBuV)	(dBuV)	(dB)		(dBuV/m)	(dBuV/m)	(dB)	
1812.50	H	56.90	40.89	7.83	64.73	48.72	74.00	54.00	-5.28
2412.50	H	49.62	36.14	9.11	58.73	45.25	74.00	54.00	-8.75
2725.00	H	44.56	40.23	10.13	54.69	50.36	74.00	54.00	-3.64
4537.50	H	44.49	34.75	15.42	59.91	50.17	74.00	54.00	-3.83
N/A									>20
1812.50	V	61.90	40.74	7.83	69.73	48.57	74.00	54.00	-5.43
2412.50	V	49.20	39.02	9.09	58.29	48.11	74.00	54.00	-5.89
2725.00	V	45.85	37.31	10.13	55.98	47.44	74.00	54.00	-6.56
4537.50	V	45.86	34.34	15.42	61.28	49.76	74.00	54.00	-4.24
N/A									>20

Operation Mode: CH Hlgh **Test Date:** October. 29, 2010
Temperature: 20°C **Tested by:** Petter Ping
Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak	AV	Ant. / CL CF	Actual Fs		Peak	AV	AV
		Reading (dBuV)	Reading (dBuV)	(dB)			Peak (dBuV/m)	AV (dBuV/m)	Limit (dBuV/m)
1850.00	H	63.59	42.67	8.06	71.65	50.73	74.00	54.00	-3.27
2775.00	H	57.64	36.85	10.48	68.12	47.33	74.00	54.00	-6.67
3850.00	H	54.56	35.23	13.44	68.00	48.67	74.00	54.00	-5.33
4637.50	H	50.47	34.56	16.16	66.63	50.72	74.00	54.00	-3.28
N/A									>20
1850.00	V	61.83	40.60	8.06	69.89	48.66	74.00	54.00	-5.34
2775.00	V	55.33	39.62	10.48	65.81	50.10	74.00	54.00	-3.90
3850.00	V	51.63	33.79	13.44	65.07	47.23	74.00	54.00	-6.77
4637.50	V	45.99	35.16	16.16	62.15	51.32	74.00	54.00	-2.68
N/A									>20

Notes:


1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
 - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

5.2 Band Edge

5.2.1 Requirement

According to FCC section 15.249(a), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.



5.2.2 Test Description



5.2.3 Test Result

The EUT operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.

Test Plot:



5.3 ANTENNA REQUIREMENT

5.3.1 DEFINITION

An analysis of the PD160487 was performed to determine compliance with FCC Section 15.203. This section requires specific handling and control of antennas used for devices subject to regulations.

5.3.2 EVALUATION PROCEDURE

The structure and application of the PD160487 was analyzed with respect to the rules. The antenna is an internal antenna, and is not accessible to the user. An auxiliary antenna port is not present.

5.3.3 EVALUATION CRITERIA

Section 15.203 of the rules states that the subject device must meet at least one of the following criteria:

- (a) Antenna must be permanently attached to the unit.
- (b) Antenna must use a unique type of connector to attach to the EUT.
- (c) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

5.3.4 EVALUATION RESULTS

The PD160487 meets the criteria of this rule by virtue of having an internal antenna inaccessible to the user.

The EUT is therefore compliant.

5.4 Power Line Conducted Emission Test


5.4.1 Limits of Line Conducted Emission Test

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz-500kHz	66-56	56-46
500kHz-5MHz	56	46
5MHz-30MHz	60	50

****Note:** 1. the lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

5.4.2 BLOCK DIAGRAM OF TEST SETUP



5.4.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per FCC Part 15 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per FCC Part 15.
- 3) All I/O cables were positioned to simulate typical actual usage as per FCC Part 15.
- 4) The EUT received DC 6V by adapter which through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5) All support equipments received power from a second LISN supplying power of AC 120V/60Hz, if any.
- 6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.
- 9) The following test mode(s) were scanned during the preliminary test:

Preliminary Conducted Emission Test				
Frequency Range Investigated		150KHz TO 30 MHz		
Mode of operation	Date	Report No.	Data#	Worst Mode
Normal Working	2010-10-19	MOST101005F2	PD160487_(L, N)	<input checked="" type="checkbox"/>

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

5.4.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

EUT and support equipment was set up on the test bench as per step 9 of the preliminary test.

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.


The test data of the worst case condition(s) was reported on the Summary Data page.

5.4.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Conducted Emission Measurement



Site: site #1

Phase: N

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Baby Monitor

M/N: PD160487

Mode: Normal Working

Note: U060020D12

No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Comment
		dBuV	dB	dBuV	dB	Detector	
1	0.1820	37.42	0.00	37.42	64.39	-26.97	peak
2	0.2420	36.96	0.00	36.96	62.03	-25.07	peak
3	0.3460	33.58	0.00	33.58	59.06	-25.48	peak
4	0.6980	30.99	0.00	30.99	56.00	-25.01	peak
5 *	0.9260	33.91	0.00	33.91	56.00	-22.09	peak
6	1.1580	28.04	0.00	28.04	56.00	-27.96	peak

*:Maximum data x:Over limit !:over margin



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax 0755-86170310

Conducted Emission Measurement


File : PD160487

Data #2

Date: 2010/10/19

Time: 17:29:47

80.0 dBmV



Site site #1

Phase: LF

Temperature: 26

Limit: FCC Part15 B Class B QP

Power: AC 120V/60Hz

Humidity: 60 %

EUT: Baby Monitor

M/N: PD160487

Mode: Normal Working

Note: U060020D12


No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Level	Factor	ment				
	MHz	dBmV	dB	dBmV	dBmV	dB		
1	0.2380	36.35	0.00	36.35	62.17	-25.82	peak	
2 *	0.4140	32.32	0.00	32.32	57.57	-25.25	peak	
3	0.9020	29.46	0.00	29.46	56.00	-26.54	peak	
4	1.5700	25.82	0.00	25.82	56.00	-30.18	peak	
5	2.4420	17.17	0.00	17.17	56.00	-38.83	peak	
6	4.7060	10.97	0.00	10.97	56.00	-45.03	peak	

*:Maximum data x:Over limit !:over margin



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax: 0755-86170310

Conducted Emission Measurement



Site site #1 Phase: L1 Temperature: 26
Limit: FCC Part15 B Class B QP Power: AC 120V/60Hz Humidity: 60 %
EUT: Baby Monitor
M/N: PD160487
Mode: Normal Working
Note: KA12D060020023U


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		0.2340	37.12	0.00	37.12	62.31	-25.19	peak	
2	*	0.3940	33.28	0.00	33.28	57.98	-24.70	peak	
3		0.6500	28.94	0.00	28.94	56.00	-27.06	peak	
4		1.1580	26.89	0.00	26.89	56.00	-29.11	peak	
5		1.5180	26.58	0.00	26.58	56.00	-29.42	peak	
6		5.8540	9.07	0.00	9.07	60.00	-50.93	peak	

*:Maximum data x:Over limit !:over margin



Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park
Guangdong, China
Tel: 0755-86170306 Fax 0755-86170310

Conducted Emission Measurement



No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
		Level	Factor	ment				
1 *	0.2540	37.02	0.00	37.02	61.63	-24.61	peak	
2	0.4340	32.09	0.00	32.09	57.18	-25.09	peak	
3	1.4780	25.55	0.00	25.55	56.00	-30.45	peak	
4	1.7060	23.62	0.00	23.62	56.00	-32.38	peak	
5	3.3140	12.55	0.00	12.55	56.00	-43.45	peak	
6	8.5620	6.74	0.00	6.74	60.00	-53.26	peak	


*:Maximum data x:Over limit !:over margin

APPENDIX 1
PHOTOGRAPHS OF TEST SETUP

CE TEST SETUP





(Model of adapter: KA12D060020023U)





(Model of adapter: U060020D12)

RE TEST SETUP



(Model of adapter: KA12D060020023U)



(Model of adapter: U060020D12)

APPENDIX 2
PHOTOGRAPHS OF EUT

FRONT VIEW OF SAMPLE



BACK VIEW OF SAMPLE



UP VIEW OF SAMPLE




LEFT VIEW OF SAMPLE



RIGHT VIEW OF SAMPLE



VIEW OF THE ADAPTER



(Model: KA12D060020023U)




(Model: U060020D12)


VIEW OF ENTIRE SAMPLE




INTERNAL PHOTO OF SAMPLE-1




INTERNAL PHOTO OF SAMPLE-2




INTERNAL PHOTO OF ANTENNA




INTERNAL PHOTO OF THE ADAPTER -1






(Model: KA12D060020023U)

INTERNAL PHOTO OF THE ADAPTER-2





(Model: U060020D12)

-----END OF REPORT-----