Company: Polycom Inc.

Evaluation of: Trio 8500

To: FCC CFR 47 Part 1.1310

Report No.: POLY35-U2_MPE FCC Rev A

MPE/RF EXPOSURE TEST REPORT



MPE/RF EXPOSURE EVALUATION



Evaluation of: Polycom Inc. Trio 8500

to

To: FCC CFR 47 Part 1.1310

Report Serial No.: POLY35-U2_MPE FCC Rev A

This report supersedes: NONE

Applicant: Polycom Inc.

6001 America Center Dr. San Jose, California 95002

USA

Product Function: Conference Phone/Video Conference

Issue Date: 19th July 2017

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.

575 Boulder Court Pleasanton California 94566 USA

Phone: +1 (925) 462-0304 Fax: +1 (925) 462-0306 www.micomlabs.com ACCREDITED
TESTING CERT #2381.01

MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



Title: Polycom Inc. Trio 8500
To: FCC CFR 47 Part 1.1310

Serial #: POLY35-U2_MPE FCC Rev A

Issue Date: 19th July 2017

Page: 3 of 4

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm²) = EIRP/($4*\pi*d^2$)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10 ^ (G (dBi)/10)$

The calculations in the table below use the highest conducted power value together with the highest antenna gain specified for the EUT. This calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density Limit (mW/cm²) @ 20cm	Min Calculated safe distance for Limit (cm)	Calculated Power Density (mW/cm²) @ 20cm
2400.0 - 2483.5	1.4	1.38	7.41	5.51	1.00	0.78	0.002

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com