

1/7/2023


HP, Inc.  
1501 Page Mill Road  
Palo Alto CA 94304

Dear Tony Griffiths,

Enclosed is the EMC test report for testing of the HP, Inc., P033 tested to the requirements of RSS-102 Issue 5, FCC Part 2.1091, and IEC62311: 2019

Thank you for using the services of Eurofins E&E North America. If you have any questions regarding these results or if MET can be of further service to you, please do feel free to contact me.

Sincerely,



Nancy LaBrecque  
Documentation Department  
Eurofins Electrical and Electronic Testing NA, Inc.

Reference: WIRA118717-MPE Rev 1



Certificates and reports shall not be reproduced except in full, without the written permission of Eurofins E&E North America. While use of the A2LA logo in this report reflects MET accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.

Eurofins MET Laboratories Inc. (Eurofins E&E North America) is part of the Eurofins Electrical & Electronics (E&E) global compliance network.

**RF Exposure Criteria  
Test Report  
Using Maximum Permissible Exposure (MPE) Calculations**

for the

**HP, Inc.**  
P033

Tested under

**RSS-102 Issue 5, FCC Part 2.1091, and IEC62311: 2019**

**Report: WIRA118717-MPE Rev 1**

1/7/2023



Bryan Taylor, Wireless Team Lead  
Electromagnetic Compatibility Lab



Nancy LaBrecque  
Documentation Department

**Engineering Statement:** The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Part 15.247 under normal use and maintenance.



Matthew Hinojosa  
EMC Manager, Austin Electromagnetic Compatibility Lab

## Report Status Sheet

Revision	Report Date	Reason for Revision
0	12/19/2022	Initial Issue.
1	1/7/2023	Technical Revisions Following TCB Review

## Table of Contents

<b>1.0 Requirements Summary.....</b>	<b>8</b>
<b>2.0 Equipment Configuration .....</b>	<b>9</b>
<b>2.1 Overview.....</b>	<b>9</b>
<b>2.2 Test Site .....</b>	<b>10</b>
<b>2.3 References.....</b>	<b>10</b>
<b>2.4 Description of Test Sample.....</b>	<b>11</b>
<b>2.5 Modifications.....</b>	<b>11</b>
<b>2.5.1 Modifications to EUT .....</b>	<b>11</b>
<b>2.5.2 Modifications to Test Standard.....</b>	<b>11</b>
<b>2.6 Disposition of EUT .....</b>	<b>11</b>
<b>3.0 Transmitter Requirements.....</b>	<b>12</b>

## **List of Tables**

Table 1. Summary of Test Results .....	8
Table 2. EUT Summary Table .....	9
Table 3. References .....	10

## List of Terms and Abbreviations

<b>AC</b>	Alternating Current
<b>ACF</b>	Antenna Correction Factor
<b>Cal</b>	Calibration
<i>d</i>	Measurement Distance
<b>dB</b>	Decibels
<b>dB<math>\mu</math>A</b>	Decibels above one <b>microamp</b>
<b>dB<math>\mu</math>V</b>	Decibels above one <b>microvolt</b>
<b>dB<math>\mu</math>A/m</b>	Decibels above one <b>microamp per meter</b>
<b>dB<math>\mu</math>V/m</b>	Decibels above one <b>microvolt per meter</b>
<b>DC</b>	Direct Current
<b>E</b>	Electric Field
<b>DSL</b>	Digital Subscriber Line
<b>ESD</b>	Electrostatic Discharge
<b>EUT</b>	Equipment Under Test
<i>f</i>	Frequency
<b>CISPR</b>	Comite International Special des Perturbations Radioelectriques (International Special Committee on Radio Interference)
<b>GRP</b>	Ground Reference Plane
<b>H</b>	Magnetic Field
<b>HCP</b>	Horizontal Coupling Plane
<b>Hz</b>	Hertz
<b>IEC</b>	International Electrotechnical Commission
<b>kHz</b>	kiloHertz
<b>kPa</b>	kiloPascal
<b>kV</b>	kilovolt
<b>LISN</b>	Line Impedance Stabilization Network
<b>MHz</b>	MegaHertz
<b><math>\mu</math>H</b>	microHenry
<b><math>\mu</math>F</b>	microFarad
<b><math>\mu</math>s</b>	microseconds
<b>PRF</b>	Pulse Repetition Frequency
<b>RF</b>	Radio Frequency
<b>RMS</b>	Root-Mean-Square
<b>V/m</b>	Volts per meter
<b>VCP</b>	Vertical Coupling Plane

## 1.0 Requirements Summary

Page Number	Test Name	Result
12	IEC62311: 2019 MPE Limits (For General Public Exposure)	Compliant
13	RSS-102 Issue 5 MPE Limits (For General Public Exposure)	Compliant
13	FCC Part 2.1091 MPE Limits (For General Public Exposure)	Compliant

**Table 1. Summary of Test Results**

## 2.0 Equipment Configuration

### 2.1 Overview

Eurofins MET Labs was contracted by HP, Inc. to perform testing on the P033, under HP, Inc.'s purchase order number 10000013761.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the HP, Inc. P033.

The results obtained relate only to the item(s) tested.

<b>Model(s) Tested:</b>	P033	
<b>Model(s) Covered:</b>	P033	
<b>EUT Specifications:</b>	Primary Power: 120VAC Antenna Gain <sup>1</sup> : <b>Bluetooth:</b> 4.09dBi <b>2.4GHz WiFi:</b> 4.07dBi (Antenna Path 1) 4.09dBi (Antenna Path 2) Directional Gain = $10\log[(10^{4.07/20} + 10^{4.09/20})^2 / 2] = 7.08\text{dBi}$ <b>5GHz WiFi Bands:</b> 3.64dBi (Antenna Path 1) 3.64dBi (Antenna Path 2) Directional Gain = $3.64 + 10\log(2) = 6.64\text{dBi}$ Note: the array gain was calculated per KDB 662911 D01 Section F.2.a.(i) for correlated signals with equal antenna gains.	
	EUT Frequency Ranges: U-NII-1: 5150 – 5250 MHz U-NII-2A: 5250 – 5350 MHz U-NII-2C: 5470 – 5725 MHz U-NII-3: 5725 – 5895 MHz 2.4GHz WiFi: 2412 – 2462MHz Bluetooth: 2402 – 2480MHz	
	Maximum Conducted Output Power: U-NII-1: 12.27dBm U-NII-2A: 12.72dBm U-NII-2C: 13.44dBm U-NII-3: 10.26dBm 2.4GHz WiFi: 14.75dBm Bluetooth: 7.04dBm	
<b>Analysis:</b>	The results obtained relate only to the item(s) tested.	
<b>Environmental Test Conditions:</b>	Temperature: 15-35° C Relative Humidity: 30-60% Barometric Pressure: 860-1060 mbar	
<b>Type of Filing:</b>	Original	
<b>Evaluated by:</b>	Bryan Taylor	
<b>Report Date(s):</b>	4/20/2022 through 5/27/2022	

**Table 2. EUT Summary Table**

<sup>1</sup> The antenna gain information was provided by HP, Inc. at the time of testing.

## 2.2 Test Site

All testing was performed at Eurofins E&E North America, Austin, TX. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

## 2.3 References

<b>IEC62311 Edition 2.0 (2019-04)</b>	Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz to 300 GHz)
<b>RSS-102: Issue 5</b>	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
<b>FCC Part 2.1091</b>	Radiofrequency radiation exposure evaluation: mobile devices.

**Table 3. References**

## **2.4 Description of Test Sample**

The HP, Inc. P033 (marketed as P033), is a video conferencing video bar designed to act as an audio / video endpoint codec over LAN networks. The device is powered by a AC/DC mains adapter and contains 2.4GHz / 5Ghz Wifi and Bluetooth radio interfaces.

## **2.5 Modifications**

### **2.5.1 Modifications to EUT**

No modifications were made to the EUT.

### **2.5.2 Modifications to Test Standard**

No modifications were made to the test standard.

## **2.6 Disposition of EUT**

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to HP, Inc. upon completion of testing.

### 3.0 Maximum Permissible Exposure Results

#### 3.1 IEC62311 (ICNIRP) RF Exposure Limits

**Table 7.** Reference levels for general public exposure to time-varying electric and magnetic fields (unperturbed rms values).<sup>a</sup>

Frequency range	E-field strength (V m <sup>-1</sup> )	H-field strength (A m <sup>-1</sup> )	B-field ( $\mu$ T)	Equivalent plane wave power density $S_{eq}$ (W m <sup>-2</sup> )
up to 1 Hz	—	$3.2 \times 10^4$	$4 \times 10^4$	—
1–8 Hz	10,000	$3.2 \times 10^4 f^2$	$4 \times 10^4 f^2$	—
8–25 Hz	10,000	$4,000/f$	$5,000/f$	—
0.025–0.8 kHz	$250/f$	$4/f$	$5/f$	—
0.8–3 kHz	$250/f$	5	6.25	—
3–150 kHz	87	5	6.25	—
0.15–1 MHz	87	$0.73/f$	$0.92/f$	—
1–10 MHz	$87f^{1/2}$	$0.73/f$	$0.92/f$	—
10–400 MHz	28	0.073	0.092	2
400–2,000 MHz	$1.375f^{1/2}$	$0.0037f^{1/2}$	$0.0046f^{1/2}$	$f/200$
2–300 GHz	61	0.16	0.20	10

<sup>a</sup> Note:

1.  $f$  as indicated in the frequency range column.
2. Provided that basic restrictions are met and adverse indirect effects can be excluded, field strength values can be exceeded.
3. For frequencies between 100 kHz and 10 GHz,  $S_{eq}$ ,  $E^2$ ,  $H^2$ , and  $B^2$  are to be averaged over any 6-min period.
4. For peak values at frequencies up to 100 kHz see Table 4, note 3.
5. For peak values at frequencies exceeding 100 kHz see Figs. 1 and 2. Between 100 kHz and 10 MHz, peak values for the field strengths are obtained by interpolation from the 1.5-fold peak at 100 kHz to the 32-fold peak at 10 MHz. For frequencies exceeding 10 MHz it is suggested that the peak equivalent plane wave power density, as averaged over the pulse width does not exceed 1,000 times the  $S_{eq}$  restrictions, or that the field strength does not exceed 32 times the field strength exposure levels given in the table.
6. For frequencies exceeding 10 GHz,  $S_{eq}$ ,  $E^2$ ,  $H^2$ , and  $B^2$  are to be averaged over any  $68/f^{1.05}$ -min period ( $f$  in GHz).
7. No E-field value is provided for frequencies <1 Hz, which are effectively static electric fields. Perception of surface electric charges will not occur at field strengths less than  $25 \text{ kVm}^{-1}$ . Spark discharges causing stress or annoyance should be avoided.

### 3.2 RSS-102 RF Exposure Limits

**Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)**

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10 <sup>21</sup>	83	90	-	Instantaneous*
0.1-10	-	0.73/ $f$	-	6**
1.1-10	87/ $f^{0.5}$	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ $f^{0.25}$	0.1540/ $f^{0.25}$	8.944/ $f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 $f^{0.3417}$	0.008335 $f^{0.3417}$	0.02619 $f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ $f^{1.2}$
150000-300000	0.158 $f^{0.5}$	4.21 x 10 <sup>-4</sup> $f^{0.5}$	6.67 x 10 <sup>-5</sup> $f$	616000/ $f^{1.2}$

**Note:**  $f$  is frequency in MHz.

\* Based on nerve stimulation (N5).

\*\* Based on specific absorption rate (SAR).

### 3.3 FCC Exposure Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	<6
3.0-30	3842/ $f$	4.89/ $f$	*(900/ $f^2$ )	<6
30-300	61.4	0.163	1.0	<6
300-1,500			1/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/ $f$	2.39/ $f$	*(180/ $f^2$ )	<30
30-300	27.3	0.073	0.2	<30
300-1,500			1/1500	<30
1,500-100,000			1.0	<30

$f$  = frequency in MHz. \* = Plane-wave equivalent power density.

### Test Procedure:

An MPE evaluation for was performed in order to show that the device was compliant with the general population exposure limits. The maximum power density was calculated for each transmitter band at a separation distance of 20cm using the maximum declared output power including tune up tolerance.

For each transmitter the maximum RF exposure at a 20 cm distance using the formula:

$$ConductedPower_{mW} = 10^{\frac{ConductedPower(dBm)}{10}}$$

$$PowerDensity = \frac{ConductedPower_{mW} \times Ant.Gain}{4\pi \times (20_{cm})^2}$$

For transmitters that could operate simultaneously, the MPE to limit ratio for each was calculated and then summed. If the sum of the MPE to limit ratios was less than 1, that specific combination of transmitters was deemed to comply.

### Test Results:

The P033 was **compliant** with RSS-102 Issue 5, FCC Part 2.1091, and IEC62311: 2019. The calculated maximum power density at 20cm distance was equal to or less than the required limits for general population exposure for RSS-102 Issue 5, FCC Part 2.1091, and IEC62311: 2019. Additionally, the sum of the worst case for each MPE to Limit ratio is less than 1 indicating that all radios may transmit simultaneously.

**Test Data:**

Duty Cycle	100 (%)							
Separation Dist.	20 (cm)							
Operating Mode	Frequency (MHz)	Declared Max Cond. Power (Inc. Tolerance) (dBm)	Duty Cycle Adjusted Cond. Output Power (dBm)	Antenna Gain (dB)	MPE Value (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Margin to Limit (mW/cm <sup>2</sup> )	MPE / Limit Ratio (for Co-Location)
2.4GHz WiFi	2412	14.75	14.75	7.09	0.0304	1.0000	0.9696	0.0304
Bluetooth	2402	7.04	7.04	4.09	0.0026	1.0000	0.9974	0.0026
U-NII Band WiFi	5180	13.44	13.44	6.64	0.0203	1.0000	0.9797	0.0203
							Sum:	0.0532

**FCC MPE Data**

Duty Cycle	100 (%)							
Separation Dist.	20 (cm)							
Operating Mode	Frequency (MHz)	Declared Max Cond. Power (Inc. Tolerance) (dBm)	Duty Cycle Adjusted Cond. Output Power (dBm)	Antenna Gain (dB)	MPE Value (W/m <sup>2</sup> )	MPE Limit (W/m <sup>2</sup> )	Margin to Limit (W/m <sup>2</sup> )	MPE / Limit Ratio (for Co-Location)
2.4GHz WiFi	2412	14.75	14.75	7.09	0.3039	5.3660	5.0621	0.0566
Bluetooth	2402	7.04	7.04	4.09	0.0258	5.3508	5.3250	0.0048
U-NII Band WiFi	5180	13.44	13.44	6.64	0.2026	9.0471	8.8444	0.0224
							Sum:	0.0839

**ISED MPE Data**

Duty Cycle	100 (%)							
Separation Dist.	20 (cm)							
Operating Mode	Frequency (MHz)	Declared Max Cond. Power (Inc. Tolerance) (dBm)	Duty Cycle Adjusted Cond. Output Power (dBm)	Antenna Gain (dB)	MPE Value (W/m <sup>2</sup> )	MPE Limit (W/m <sup>2</sup> )	Margin to Limit (W/m <sup>2</sup> )	MPE / Limit Ratio (for Co-Location)
2.4GHz WiFi	2412	14.75	14.75	7.09	0.3039	10.0000	9.6961	0.0304
Bluetooth	2402	7.04	7.04	4.09	0.0258	10.0000	9.9742	0.0026
U-NII Band WiFi	5180	13.44	13.44	6.64	0.2026	10.0000	9.7974	0.0203
							Sum:	0.0532

**IEC62311 MPE Data**
**Test Engineer(s):** Bryan Taylor

**Test Date(s):** 5/27/2022