

# TEST REPORT

## CERTIFICATE OF CONFORMITY

**Standard:** 47 CFR FCC Part 15, Subpart C (Section 15.247)

**Report No.:** RFCJDL-WTW-P23120588-1

**FCC ID:** M72-STG62R

**Product:** Studio G62

**Brand:** Poly

**Model No.:** PBJ-STG-62R

**Received Date:** 2024/1/16

**Test Date:** 2024/2/27 ~ 2024/3/15

**Issued Date:** 2024/4/23

**Applicant:** HP Inc.

**Address:** 1501 Page Mill Road, Palo Alto CA 94304 USA

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kewi Shan Dist., Taoyuan City 33383, Taiwan

**FCC Registration /**  
**Designation Number:** 788550 / TW0003

**Approved by:** Jeremy Lin , **Date:** 2024/4/23  
Jeremy Lin / Project Engineer

This test report consists of 66 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Pettie Chen / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us-our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

<b>Release Control Record</b> .....	<b>4</b>
<b>1 Certificate</b> .....	<b>5</b>
<b>2 Summary of Test Results</b> .....	<b>6</b>
2.1 Measurement Uncertainty .....	6
2.2 Supplementary Information .....	6
<b>3 General Information</b> .....	<b>7</b>
3.1 General Description .....	7
3.2 Antenna Description of EUT .....	8
3.3 Channel List .....	9
3.4 Test Mode Applicability and Tested Channel Detail .....	10
3.5 Duty Cycle of Test Signal .....	11
3.6 Test Program Used and Operation Descriptions .....	13
3.7 Connection Diagram of EUT and Peripheral Devices .....	13
3.8 Configuration of Peripheral Devices and Cable Connections .....	13
<b>4 Test Instruments</b> .....	<b>14</b>
4.1 RF Output Power .....	14
4.2 Power Spectral Density .....	14
4.3 6 dB Bandwidth .....	14
4.4 Conducted Out of Band Emissions .....	14
4.5 AC Power Conducted Emissions .....	15
4.6 Unwanted Emissions below 1 GHz .....	16
4.7 Unwanted Emissions above 1 GHz .....	17
<b>5 Limits of Test Items</b> .....	<b>18</b>
5.1 RF Output Power .....	18
5.2 Power Spectral Density .....	18
5.3 6 dB Bandwidth .....	18
5.4 Conducted Out of Band Emissions .....	18
5.5 AC Power Conducted Emissions .....	18
5.6 Unwanted Emissions below 1 GHz .....	19
5.7 Unwanted Emissions above 1 GHz .....	19
<b>6 Test Arrangements</b> .....	<b>20</b>
6.1 RF Output Power .....	20
6.1.1 Test Setup .....	20
6.1.2 Test Procedure .....	20
6.2 Power Spectral Density .....	20
6.2.1 Test Setup .....	20
6.2.2 Test Procedure .....	20
6.3 6 dB Bandwidth .....	21
6.3.1 Test Setup .....	21
6.3.2 Test Procedure .....	21
6.4 Conducted Out of Band Emissions .....	21
6.4.1 Test Setup .....	21
6.4.2 Test Procedure .....	21
6.5 AC Power Conducted Emissions .....	22
6.5.1 Test Setup .....	22
6.5.2 Test Procedure .....	22
6.6 Unwanted Emissions below 1 GHz .....	23
6.6.1 Test Setup .....	23
6.6.2 Test Procedure .....	24
6.7 Unwanted Emissions above 1 GHz .....	25
6.7.1 Test Setup .....	25
6.7.2 Test Procedure .....	25
<b>7 Test Results of Test Item</b> .....	<b>26</b>



7.1	RF Output Power.....	26
7.2	Power Spectral Density.....	29
7.3	6 dB Bandwidth.....	31
7.4	Conducted Out of Band Emissions.....	33
7.5	AC Power Conducted Emissions.....	41
7.6	Unwanted Emissions below 1 GHz.....	43
7.7	Unwanted Emissions above 1 GHz.....	45
<b>8</b>	<b>Pictures of Test Arrangements.....</b>	<b>65</b>
<b>9</b>	<b>Information of the Testing Laboratories.....</b>	<b>66</b>



## Release Control Record

Issue No.	Description	Date Issued
RFCJDL-WTW-P23120588-1	Original release.	2024/4/23

## 1 Certificate

**Product:** Studio G62

**Brand:** Poly

**Test Model:** PBJ-STG-62R

**Sample Status:** Engineering sample

**Applicant:** HP Inc.

**Test Date:** 2024/2/27 ~ 2024/3/15

**Standard:** 47 CFR FCC Part 15, Subpart C (Section 15.247)

**Measurement procedure:** ANSI C63.10-2013  
KDB 558074 D01 15.247 Meas Guidance v05r02  
KDB 662911 D01 Multiple Transmitter Output v02r01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -8.42 dB at 0.47000 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -6.2 dB at 43.58 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -4.4 dB at 2483.50 MHz
15.203	Antenna Requirement	Pass	Antenna connector is ipex(MHF) not a standard connector.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
RF Output Power	-	1.371 dB
Power Spectral Density	-	1.017 dB
6 dB Bandwidth	-	206.5 Hz
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.79 dB
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.88 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	2.44 dB
	30 MHz ~ 1 GHz	2.95 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
	18 GHz ~ 40 GHz	1.94 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

### 2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

### 3 General Information

#### 3.1 General Description

Product	Studio G62
Brand	Poly
Test Model	PBJ-STG-62R
Status of EUT	Engineering sample
Power Supply Rating	56Vdc from PoE
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in VHT mode 1024QAM for OFDMA in 11ax mode
Modulation Technology	DSSS, OFDM, OFDMA
Transfer Rate	Up to MCS11
Operating Frequency	2.412 GHz ~ 2.462 GHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20): 11 802.11n (HT40), VHT40, 802.11ax (HE40): 7
Output Power	31.625 mW (15 dBm)

Note:

1. The EUT uses following accessories.

POE Injector 2.5G (option)	
Brand	Model
Delta	ADH-45AR FBA
RJ-45 Cable (accessory)	
Model (P/N)	Specification
2457-06173-001	Signal Line : 3.6m
HDMI (accessory)	
Model (P/N)	Specification
2457-28808-006	Signal Line : 1.95m
Power cord (option)	
Specification	
Signal Line : 2.63m	
RJ-45 Cable (option) (provided with PoE kit box – cable for Zappa PoE Injector)	
Model (P/N)	Specification
2457-06174-001	Signal Line : 0.23m

2. The Bluetooth and WLAN cannot transmit simultaneously.

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna No.	Gain (dBi)									Antenna Type	Connector Type
	2400 MHz	2450 MHz	2500 MHz	5150 MHz	5350 MHz	5450 MHz	5550 MHz	5750 MHz	5850 MHz		
0	3.03	3.12	3.04	3.03	3.01	3.04	3.11	3.12	2.98	Dipole	ipex(MHF)
1	3.02	3.13	3.09	2.93	3.12	3.04	3.15	2.94	2.95	Dipole	ipex(MHF)

\* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. The EUT incorporates a MIMO function:

2.4 GHz Band		
Modulation Mode	TX & RX Configuration	
802.11b	2TX	2RX
802.11g	2TX	2RX
802.11n (HT20)	2TX	2RX
802.11n (HT40)	2TX	2RX
VHT20	2TX	2RX
VHT40	2TX	2RX
802.11ax (HE20)	2TX	2RX
802.11ax (HE40)	2TX	2RX

Note:

1. The modulation and bandwidth are similar for 802.11n mode for 20 MHz (40 MHz), VHT mode for 20 MHz (40 MHz), 802.11ax mode for 20 MHz (40 MHz), therefore the manufacturer will control the power for 802.11n/VHT mode is same as the 802.11ax mode or lower than it and investigated worst case to representative mode in test report.
2. The EUT device modulation technique OFDMA does not support partial RUs (resource units) and channel puncturing/bandwidth reduction mechanisms.



### 3.3 Channel List

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40), VHT40, 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

### 3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. EUT can be used in the following ways: X-axis/ Y-axis/ Z-axis. Pre-scan these ways and find the worst case as a representative test condition.
Worst Case:	1. X-axis/ Y-axis/ Z-axis Worst Condition: Z-axis

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Signal Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g	CDD	1, 6, 11	BPSK	6Mb/s
	802.11n (HT20)	CDD	1, 6, 11	BPSK	MCS0
	802.11n (HT40)	CDD	3, 6, 9	BPSK	MCS0
	VHT20	CDD	1, 6, 11	BPSK	MCS0
	VHT40	CDD	3, 6, 9	BPSK	MCS0
	802.11ax (HE20)	CDD	1, 6, 11	BPSK	MCS0
	802.11ax (HE40)	CDD	3, 6, 9	BPSK	MCS0
Power Spectral Density	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g	CDD	1, 6, 11	BPSK	6Mb/s
	802.11ax (HE20)	CDD	1, 6, 11	BPSK	MCS0
	802.11ax (HE40)	CDD	3, 6, 9	BPSK	MCS0
6 dB Bandwidth / Conducted Out of Band Emissions	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g	CDD	1, 6, 11	BPSK	6Mb/s
	802.11ax (HE20)	CDD	1, 6, 11	BPSK	MCS0
	802.11ax (HE40)	CDD	3, 6, 9	BPSK	MCS0
AC Power Conducted Emissions	802.11b	CDD	1	DBPSK	1Mb/s
Unwanted Emissions below 1 GHz	802.11b	CDD	1	DBPSK	1Mb/s
Unwanted Emissions above 1 GHz	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g	CDD	1, 6, 11	BPSK	6Mb/s
	802.11ax (HE20)	CDD	1, 6, 11	BPSK	MCS0
	802.11ax (HE40)	CDD	3, 6, 9	BPSK	MCS0


### 3.5 Duty Cycle of Test Signal

**802.11b:** Duty cycle =  $0.69 \text{ ms} / 0.695 \text{ ms} \times 100\% = 99.3\%$


**802.11g:** Duty cycle =  $1.98 \text{ ms} / 1.99 \text{ ms} \times 100\% = 99.5\%$

**802.11ax (HE20):** Duty cycle =  $100 \text{ ms} / 100 \text{ ms} \times 100\% = 100.0\%$

**802.11ax (HE40):** Duty cycle =  $100 \text{ ms} / 100 \text{ ms} \times 100\% = 100.0\%$




802.11b



802.11g




### Duty Cycle Analysis



802.11ax (HE20)

### Duty Cycle Analysis




802.11ax (HE40)

### 3.6 Test Program Used and Operation Descriptions

Controlling software WIFI\_BT\_DEBUG\_TOOL\_V0.0.1.5 has been activated to set the EUT under transmission condition continuously at specific channel frequency.

### 3.7 Connection Diagram of EUT and Peripheral Devices



### 3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Laptop	DELL	Inspiron 14R	8LRKKW1	NA	Provided by Lab
B	Monitor	DELL	A14S2421HSXmTW	CN-01KFWF-WSL00-24C-714B	NA	Provided by Lab
C	Monitor	DELL	A14S2421HSXmTW	CN-01KFWF-WSL00-24C-711B	NA	Provided by Lab
D	Keyboard	DELL	SK-8115	MY-OJ4635-71619-548-0467	DoC	Provided by Lab
E	Mouse	DELL	MS111-P	CN-011D3V-71581-1CJ-093C	DoC	Provided by Lab
F	Laptop	Lenovo	L470	PF11CSQA	NA	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	USB TYPE-C TO TYPE-A	1	1.5	Y	0	Provided by Lab
2	HDMI Cable	1	1.8	Y	0	Supplied by applicant
3	LAN Cable	1	0.2	Y	0	Supplied by applicant
4	LAN Cable	1	3	Y	0	Supplied by applicant
5	LAN Cable	1	10	N	0	Provided by Lab
6	Audio Cable	2	1.5	N	0	Provided by Lab
7	HDMI Cable	1	1.8	Y	0	Supplied by applicant
8	HDMI Cable	1	1.8	Y	0	Supplied by applicant
9	USB Cable	1	1.5	N	1	Provided by Lab
10	USB Cable	1	1.8	N	0	Provided by Lab

## 4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Peak Power Analyzer Keysight	8990B	MY51000485	2024/1/21	2025/1/20
Wideband Power Sensor Keysight	N1923A	MY58020002	2024/1/18	2025/1/17
		MY58140009	2024/1/18	2025/1/17

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2024/3/9

### 4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Signal & Spectrum Analyzer R&S	FSV3044	101504	2023/6/5	2024/6/4
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2024/3/9

### 4.3 6 dB Bandwidth

Refer to section 4.2 to get information of the instruments.

### 4.4 Conducted Out of Band Emissions

Refer to section 4.2 to get information of the instruments.

#### 4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance HUBER+SUHNER	E1-011315	13	2023/11/22	2024/11/21
50 ohm terminal resistance	E1-011279	04	2023/11/22	2024/11/21
	E1-011280	05	2023/11/22	2024/11/21
DC-LISN Schwarzbeck	NNBM 8126G	8126G-069	2023/11/7	2024/11/6
EMI Test Receiver R&S	ESCI	100613	2023/12/4	2024/12/3
Fixed Attenuator Mini-Circuits	HAT-10+	PAD-COND1-01	2024/1/6	2025/1/5
LISN R&S	ENV216	101826	2023/3/23	2024/3/22
	ESH3-Z5	100311	2023/9/6	2024/9/5
RF Coaxial Cable Woken	5D-FB	Cable-cond1-01	2024/1/6	2025/1/5
Software BVADT	BVADT_Cond_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2023/8/31	2024/8/30

Notes:

1. The test was performed in HY - Conduction 1.
2. Tested Date: 2024/3/15

#### 4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Max-Full	MFA-440H	AT93021705	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-472	2023/10/16	2024/10/15
EXA Signal Analyzer Agilent	N9010A	MY52220207	2023/12/28	2024/12/27
Loop Antenna Electro-Metrics	EM-6879	269	2023/9/23	2024/9/22
Loop Antenna TESEQ	HLA 6121	45745	2023/8/8	2024/8/7
MXE EMI Receiver Keysight	N9038A	MY55420137	2023/5/3	2024/5/2
Preamplifier EMCI	EMC 330H	980112	2023/9/27	2024/9/26
	EMC001340	980201	2023/9/27	2024/9/26
RF Coaxial Cable Woken	8D-FB	Cable-Ch10-01	2023/9/27	2024/9/26
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MG-7802	N/A	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 5.
2. Tested Date: 2024/3/15



#### 4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn Max-Full	MFA-440H	AT93021705	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	7	N/A	N/A
EXA Signal Analyzer Agilent	N9010A	MY52220207	2023/12/28	2024/12/27
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-969	2023/11/12	2024/11/11
	BBHA 9170	148	2023/11/12	2024/11/11
MXE EMI Receiver Keysight	N9038A	MY55420137	2023/5/3	2024/5/2
Preamplifier EMCI	EMC 012645	980115	2023/9/27	2024/9/26
	EMC 184045	980116	2023/9/27	2024/9/26
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	2023/7/8	2024/7/7
	EMC102-KM-KM-3000	150929	2023/7/8	2024/7/7
	EMC104-SM-SM- 8000+3000	171005	2023/9/27	2024/9/26
RF Coaxial Cable HUBER+SUHNER	SUCOFLEX 104	EMC104-SM-SM- 1000(140807)	2023/9/27	2024/9/26
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MG-7802	N/A	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 5.
2. Tested Date: 2024/2/27

## 5 Limits of Test Items

### 5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any  $N_{ANT}$ ;

Array Gain =  $5 \log(N_{ANT}/N_{SS})$  dB or 3 dB, whichever is less, for 20-MHz channel widths with  $N_{ANT} \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(N_{ANT}/N_{SS})$  dB.

### 5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

### 5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

### 5.4 Conducted Out of Band Emissions

Below 30 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

### 5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

## 5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**Notes:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

## 5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3


**Notes:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

## 6 Test Arrangements

### 6.1 RF Output Power

#### 6.1.1 Test Setup




#### 6.1.2 Test Procedure

Average Power:

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

### 6.2 Power Spectral Density

#### 6.2.1 Test Setup




#### 6.2.2 Test Procedure

- a. Measure the duty cycle (x).
- b. Set instrument center frequency to DTS channel center frequency.
- c. Set span to at least 1.5 times the OBW.
- d. Set RBW to: 3 kHz.
- e. Set VBW  $\geq 3 \times$  RBW.
- f. Detector = power averaging (RMS) or sample detector (when RMS not available).
- g. Ensure that the number of measurement points in the sweep  $\geq 2 \times$  span/RBW.
- h. Sweep time = auto couple.
- i. Do not use sweep triggering. Allow sweep to “free run”.
- j. Employ trace averaging (RMS) mode over a minimum of 100 traces.
- k. Use the peak marker function to determine the maximum amplitude level.

Note: If Duty cycle < 98%, Add  $10 \log (1/x)$ , where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

### 6.3 6 dB Bandwidth

#### 6.3.1 Test Setup




#### 6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.4 Conducted Out of Band Emissions

#### 6.4.1 Test Setup



#### 6.4.2 Test Procedure

##### MEASUREMENT PROCEDURE REF


- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

##### MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW  $\geq 300$  kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

## 6.5 AC Power Conducted Emissions

### 6.5.1 Test Setup



**Note: 1.Support units were connected to second LISN.**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.5.2 Test Procedure


- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


## 6.6 Unwanted Emissions below 1 GHz

### 6.6.1 Test Setup

#### For Radiated emission below 30 MHz



#### For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

## 6.6.2 Test Procedure

### For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

#### Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

### For Radiated emission above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.


#### Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.



## 6.7 Unwanted Emissions above 1 GHz

### 6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.7.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

#### Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or 10 Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

## 7 Test Results of Test Item

### 7.1 RF Output Power

Input Power:	56 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyong Wang
--------------	--------	---------------------------	--------------	------------	--------------

#### 802.11b

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
1	2412	11.97	12.01	31.625	15.00	30	Pass
6	2437	11.86	11.98	31.122	14.93	30	Pass
11	2462	11.58	11.88	29.805	14.74	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.13 dBi < 6 dBi, so the output power limit shall not be reduced.

#### 802.11g

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
1	2412	10.43	10.66	22.682	13.56	30	Pass
6	2437	10.22	10.37	21.409	13.31	30	Pass
11	2462	10.22	10.26	21.137	13.25	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.13 dBi < 6 dBi, so the output power limit shall not be reduced.

#### 802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
1	2412	10.23	10.40	21.509	13.33	30	Pass
6	2437	10.08	10.10	20.419	13.10	30	Pass
11	2462	10.16	10.21	20.871	13.20	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.13 dBi < 6 dBi, so the output power limit shall not be reduced.

### 802.11n (HT40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
3	2422	10.23	10.45	21.636	13.35	30	Pass
6	2437	9.98	10.02	20	13.01	30	Pass
9	2452	10.00	10.11	20.257	13.07	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.13 dBi < 6 dBi, so the output power limit shall not be reduced.

### VHT20

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
1	2412	10.28	10.42	21.681	13.36	30	Pass
6	2437	10.10	10.12	20.513	13.12	30	Pass
11	2462	10.18	10.23	20.967	13.22	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.13 dBi < 6 dBi, so the output power limit shall not be reduced.

### VHT40

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
3	2422	10.26	10.47	21.76	13.38	30	Pass
6	2437	10.00	10.03	20.069	13.03	30	Pass
9	2452	10.02	10.13	20.35	13.09	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.13 dBi < 6 dBi, so the output power limit shall not be reduced.

### 802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
1	2412	10.30	10.45	21.807	13.39	30	Pass
6	2437	10.11	10.14	20.584	13.14	30	Pass
11	2462	10.18	10.26	21.04	13.23	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.13 dBi < 6 dBi, so the output power limit shall not be reduced.

**802.11ax (HE40)**

Chan.	Chan. Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1				
3	2422	10.28	10.49	21.86	13.40	30	Pass
6	2437	10.01	10.06	20.162	13.05	30	Pass
9	2452	10.04	10.15	20.444	13.11	30	Pass

**Notes:**

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.13 dBi < 6 dBi, so the output power limit shall not be reduced.

## 7.2 Power Spectral Density

Input Power:	56 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyong Wang
--------------	--------	---------------------------	--------------	------------	--------------

### 802.11b

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1			
1	2412	-16.82	-13.74	-12.00	7.86	Pass
6	2437	-16.48	-16.03	-13.24	7.86	Pass
11	2462	-15.73	-16.94	-13.28	7.86	Pass

#### Notes:

1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain =  $10 \log[(10^{\text{Chain0}/20} + 10^{\text{Chain1}/20})^2 / 2]$
3. The directional gain is 6.14 dBi > 6 dBi, so the power density limit shall be reduced to  $8 - (6.14 - 6) = 7.86$  dBm/3kHz.

### 802.11g

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1			
1	2412	-24.08	-23.79	-20.92	7.86	Pass
6	2437	-24.56	-24.02	-21.27	7.86	Pass
11	2462	-24.59	-24.03	-21.29	7.86	Pass

#### Notes:

1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain =  $10 \log[(10^{\text{Chain0}/20} + 10^{\text{Chain1}/20})^2 / 2]$
3. The directional gain is 6.14 dBi > 6 dBi, so the power density limit shall be reduced to  $8 - (6.14 - 6) = 7.86$  dBm/3kHz.

### 802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1			
1	2412	-25.21	-24.99	-22.09	7.86	Pass
6	2437	-26.01	-25.10	-22.52	7.86	Pass
11	2462	-25.74	-25.27	-22.49	7.86	Pass

#### Notes:


1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain =  $10 \log[(10^{\text{Chain0}/20} + 10^{\text{Chain1}/20})^2 / 2]$
3. The directional gain is 6.14 dBi > 6 dBi, so the power density limit shall be reduced to  $8 - (6.14 - 6) = 7.86$  dBm/3kHz.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)		Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1			
3	2422	-27.48	-27.48	-24.47	7.86	Pass
6	2437	-28.10	-27.62	-24.84	7.86	Pass
9	2452	-28.08	-27.51	-24.78	7.86	Pass

Notes:

- Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
- Directional gain =  $10 \log[(10^{\text{Chain0}/20} + 10^{\text{Chain1}/20})^2 / 2]$
- The directional gain is 6.14 dBi > 6 dBi, so the power density limit shall be reduced to  $8 - (6.14 - 6) = 7.86$  dBm/3kHz.



### 7.3 6 dB Bandwidth

Input Power:	56 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyong Wang
--------------	--------	---------------------------	--------------	------------	--------------

#### 802.11b

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1		
1	2412	7.16	8.11	0.5	Pass
6	2437	7.61	8.09	0.5	Pass
11	2462	8.09	7.19	0.5	Pass

#### 802.11g

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1		
1	2412	16.34	16.35	0.5	Pass
6	2437	16.32	16.11	0.5	Pass
11	2462	16.35	16.35	0.5	Pass

#### 802.11ax (HE20)


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1		
1	2412	18.93	18.98	0.5	Pass
6	2437	18.71	18.77	0.5	Pass
11	2462	18.91	18.82	0.5	Pass

#### 802.11ax (HE40)


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)		Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1		
3	2422	37.68	37.72	0.5	Pass
6	2437	36.83	35.81	0.5	Pass
9	2452	37.71	37.85	0.5	Pass




### Spectrum Plot of Minimum Value




802.11b / Chain 0 : CH 1



802.11g / Chain 1 : CH 6



802.11ax (HE20) / Chain 0 : CH 6



802.11ax (HE40) / Chain 1 : CH 6







### 7.4 Conducted Out of Band Emissions


Input Power:	56 Vdc	Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyong Wang
--------------	--------	---------------------------	--------------	------------	--------------

#### 802.11b







Chain 1 : CH 1




Chain 1 : CH 1




Chain 1 : CH 6




Chain 1 : CH 6




Chain 1 : CH 11



Chain 1 : CH 11



















Chain 1 : CH 1 Band edge




Chain 1 : CH 11 Band edge


802.11g






802.11ax (HE20)







Chain 1 : CH 1




Chain 1 : CH 1




Chain 1 : CH 6




Chain 1 : CH 6




Chain 1 : CH 11



Chain 1 : CH 11




Chain 1 : CH 1 Band edge




Chain 1 : CH 11 Band edge

802.11ax (HE40)







Chain 1 : CH 3




Chain 1 : CH 3




Chain 1 : CH 6




Chain 1 : CH 6




Chain 1 : CH 9



Chain 1 : CH 9



Chain 1 : CH 3 Band edge



Chain 1 : CH 9 Band edge




## 7.5 AC Power Conducted Emissions

<b>RF Mode</b>	802.11b	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	150 kHz ~ 30 MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9 kHz
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 64% RH
<b>Tested By</b>	Vincent Chen		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15400	9.63	44.89	26.08	54.52	35.71	65.78	55.78	-11.26	-20.07
2	0.19000	9.64	40.14	21.66	49.78	31.30	64.04	54.04	-14.26	-22.74
3	0.22600	9.65	36.53	15.67	46.18	25.32	62.60	52.60	-16.42	-27.28
<b>4</b>	<b>0.47000</b>	<b>9.68</b>	<b>32.07</b>	<b>28.41</b>	<b>41.75</b>	<b>38.09</b>	<b>56.51</b>	<b>46.51</b>	<b>-14.76</b>	<b>-8.42</b>
5	3.56917	9.73	26.44	21.32	36.17	31.05	56.00	46.00	-19.83	-14.95
6	7.58200	9.77	25.29	19.23	35.06	29.00	60.00	50.00	-24.94	-21.00

### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>RF Mode</b>	802.11b	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	150 kHz ~ 30 MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9 kHz
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 64% RH
<b>Tested By</b>	Vincent Chen		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16932	9.63	42.62	23.81	52.25	33.44	64.99	54.99	-12.74	-21.55
2	0.19367	9.64	39.70	21.22	49.34	30.86	63.88	53.88	-14.54	-23.02
3	0.24200	9.65	34.81	16.83	44.46	26.48	62.03	52.03	-17.57	-25.55
4	0.47400	9.68	29.84	23.76	39.52	33.44	56.44	46.44	-16.92	-13.00
5	2.32600	9.74	25.16	18.07	34.90	27.81	56.00	46.00	-21.10	-18.19
6	7.66600	9.79	25.31	19.23	35.10	29.02	60.00	50.00	-24.90	-20.98

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




## 7.6 Unwanted Emissions below 1 GHz

RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	22°C, 69% RH
Tested By	Vincent Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	72.68	29.7 QP	40.0	-10.3	2.00 H	190	45.0	-15.3
2	167.74	36.6 QP	43.5	-6.9	1.00 H	210	49.7	-13.1
3	224.97	37.5 QP	46.0	-8.5	1.00 H	152	53.6	-16.1
4	296.75	38.2 QP	46.0	-7.8	1.50 H	229	50.3	-12.1
5	593.57	35.1 QP	46.0	-10.9	1.00 H	17	40.4	-5.3
6	793.39	36.5 QP	46.0	-9.5	2.00 H	187	37.5	-1.0

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




<b>RF Mode</b>	802.11b	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	30 MHz ~ 1 GHz	<b>Detector Function &amp; Bandwidth</b>	QP: RB=120kHz, DET=Quasi-Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 69% RH
<b>Tested By</b>	Vincent Chen		

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	43.58	33.8 QP	40.0	-6.2	1.00 V	77	46.4	-12.6
2	93.05	35.6 QP	43.5	-7.9	2.00 V	282	53.6	-18.0
3	296.75	34.0 QP	46.0	-12.0	1.00 V	281	46.1	-12.1
4	445.16	36.9 QP	46.0	-9.1	1.00 V	177	45.2	-8.3
5	593.57	36.0 QP	46.0	-10.0	1.50 V	318	41.3	-5.3
6	886.51	38.9 QP	46.0	-7.1	1.50 V	232	39.7	-0.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



## 7.7 Unwanted Emissions above 1 GHz

<b>RF Mode</b>	802.11b	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.6 PK	74.0	-14.4	1.27 H	353	24.8	34.8
2	2390.00	46.1 AV	54.0	-7.9	1.27 H	353	11.3	34.8
3	*2412.00	91.5 PK			1.27 H	353	56.7	34.8
4	*2412.00	88.9 AV			1.27 H	353	54.1	34.8
5	4824.00	53.9 PK	74.0	-20.1	1.86 H	227	46.1	7.8
6	4824.00	41.3 AV	54.0	-12.7	1.86 H	227	33.5	7.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.8 PK	74.0	-14.2	1.65 V	34	25.0	34.8
2	2390.00	46.2 AV	54.0	-7.8	1.65 V	34	11.4	34.8
3	*2412.00	106.5 PK			1.65 V	34	71.7	34.8
4	*2412.00	104.0 AV			1.65 V	34	69.2	34.8
5	4824.00	54.1 PK	74.0	-19.9	2.41 V	123	46.3	7.8
6	4824.00	41.5 AV	54.0	-12.5	2.41 V	123	33.7	7.8

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11b	<b>Channel</b>	CH 6 : 2437 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	92.2 PK			1.08 H	347	57.4	34.8
2	*2437.00	89.6 AV			1.08 H	347	54.8	34.8
3	4874.00	54.2 PK	74.0	-19.8	2.24 H	185	46.1	8.1
4	4874.00	41.5 AV	54.0	-12.5	2.24 H	185	33.4	8.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	106.3 PK			1.53 V	32	71.5	34.8
2	*2437.00	104.0 AV			1.53 V	32	69.2	34.8
3	4874.00	54.3 PK	74.0	-19.7	2.21 V	164	46.2	8.1
4	4874.00	41.7 AV	54.0	-12.3	2.21 V	164	33.6	8.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.

<b>RF Mode</b>	802.11b	<b>Channel</b>	CH 11 : 2462 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	92.6 PK			1.12 H	353	57.6	35.0
2	*2462.00	90.1 AV			1.12 H	353	55.1	35.0
3	2483.50	60.2 PK	74.0	-13.8	1.12 H	353	25.2	35.0
4	2483.50	47.0 AV	54.0	-7.0	1.12 H	353	12.0	35.0
5	4924.00	54.1 PK	74.0	-19.9	2.24 H	165	46.0	8.1
6	4924.00	41.3 AV	54.0	-12.7	2.24 H	165	33.2	8.1

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	106.4 PK			1.48 V	24	71.4	35.0
2	*2462.00	103.8 AV			1.48 V	24	68.8	35.0
3	2483.50	60.3 PK	74.0	-13.7	1.48 V	24	25.3	35.0
4	2483.50	47.1 AV	54.0	-6.9	1.48 V	24	12.1	35.0
5	4924.00	54.2 PK	74.0	-19.8	2.27 V	174	46.1	8.1
6	4924.00	41.5 AV	54.0	-12.5	2.27 V	174	33.4	8.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11g	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.8 PK	74.0	-14.2	2.93 H	311	25.0	34.8
2	2390.00	46.1 AV	54.0	-7.9	2.93 H	311	11.3	34.8
3	*2412.00	99.8 PK			2.93 H	311	65.0	34.8
4	*2412.00	89.1 AV			2.93 H	311	54.3	34.8
5	4824.00	54.6 PK	74.0	-19.4	1.52 H	198	46.8	7.8
6	4824.00	41.3 AV	54.0	-12.7	1.52 H	198	33.5	7.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.9 PK	74.0	-14.1	2.01 V	29	25.1	34.8
2	2390.00	46.2 AV	54.0	-7.8	2.01 V	29	11.4	34.8
3	*2412.00	107.8 PK			2.01 V	29	73.0	34.8
4	*2412.00	96.9 AV			2.01 V	29	62.1	34.8
5	4824.00	54.8 PK	74.0	-19.2	1.69 V	158	47.0	7.8
6	4824.00	41.5 AV	54.0	-12.5	1.69 V	158	33.7	7.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11g	<b>Channel</b>	CH 6 : 2437 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	99.0 PK			2.92 H	308	64.2	34.8
2	*2437.00	88.2 AV			2.92 H	308	53.4	34.8
3	4874.00	54.5 PK	74.0	-19.5	1.57 H	113	46.4	8.1
4	4874.00	41.3 AV	54.0	-12.7	1.57 H	113	33.2	8.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	108.2 PK			1.91 V	26	73.4	34.8
2	*2437.00	97.9 AV			1.91 V	26	63.1	34.8
3	4874.00	54.9 PK	74.0	-19.1	2.24 V	158	46.8	8.1
4	4874.00	41.6 AV	54.0	-12.4	2.24 V	158	33.5	8.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.

<b>RF Mode</b>	802.11g	<b>Channel</b>	CH 11 : 2462 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	98.0 PK			3.19 H	303	63.0	35.0
2	*2462.00	87.4 AV			3.19 H	303	52.4	35.0
3	2483.50	61.1 PK	74.0	-12.9	3.19 H	303	26.1	35.0
4	2483.50	47.0 AV	54.0	-7.0	3.19 H	303	12.0	35.0
5	4924.00	54.6 PK	74.0	-19.4	2.24 H	175	46.5	8.1
6	4924.00	41.2 AV	54.0	-12.8	2.24 H	175	33.1	8.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	108.1 PK			2.05 V	21	73.1	35.0
2	*2462.00	97.9 AV			2.05 V	21	62.9	35.0
3	2483.50	61.3 PK	74.0	-12.7	2.05 V	21	26.3	35.0
4	2483.50	47.8 AV	54.0	-6.2	2.05 V	21	12.8	35.0
5	4924.00	54.8 PK	74.0	-19.2	1.74 V	152	46.7	8.1
6	4924.00	41.4 AV	54.0	-12.6	1.74 V	152	33.3	8.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11ax (HE20)	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.3 PK	74.0	-14.7	3.06 H	301	24.5	34.8
2	2390.00	46.2 AV	54.0	-7.8	3.06 H	301	11.4	34.8
3	*2412.00	101.6 PK			3.06 H	301	66.8	34.8
4	*2412.00	88.6 AV			3.06 H	301	53.8	34.8
5	4824.00	55.0 PK	74.0	-19.0	1.87 H	256	47.2	7.8
6	4824.00	41.2 AV	54.0	-12.8	1.87 H	256	33.4	7.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.4 PK	74.0	-14.6	1.77 V	27	24.6	34.8
2	2390.00	46.4 AV	54.0	-7.6	1.77 V	27	11.6	34.8
3	*2412.00	110.8 PK			1.77 V	27	76.0	34.8
4	*2412.00	97.2 AV			1.77 V	27	62.4	34.8
5	4824.00	55.3 PK	74.0	-18.7	1.23 V	265	47.5	7.8
6	4824.00	41.6 AV	54.0	-12.4	1.23 V	265	33.8	7.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11ax (HE20)	<b>Channel</b>	CH 6 : 2437 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	100.7 PK			3.25 H	300	65.9	34.8
2	*2437.00	87.8 AV			3.25 H	300	53.0	34.8
3	4874.00	55.3 PK	74.0	-18.7	2.04 H	115	47.2	8.1
4	4874.00	41.5 AV	54.0	-12.5	2.04 H	115	33.4	8.1

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	110.7 PK			1.86 V	32	75.9	34.8
2	*2437.00	97.4 AV			1.86 V	32	62.6	34.8
3	4874.00	55.5 PK	74.0	-18.5	1.20 V	265	47.4	8.1
4	4874.00	41.8 AV	54.0	-12.2	1.20 V	265	33.7	8.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11ax (HE20)	<b>Channel</b>	CH 11 : 2462 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	100.7 PK			3.26 H	295	65.7	35.0
2	*2462.00	87.5 AV			3.26 H	295	52.5	35.0
3	2483.50	59.8 PK	74.0	-14.2	3.26 H	295	24.8	35.0
4	2483.50	47.1 AV	54.0	-6.9	3.26 H	295	12.1	35.0
5	4924.00	55.3 PK	74.0	-18.7	2.42 H	158	47.2	8.1
6	4924.00	41.5 AV	54.0	-12.5	2.42 H	158	33.4	8.1

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.7 PK			1.80 V	22	75.7	35.0
2	*2462.00	97.7 AV			1.80 V	22	62.7	35.0
3	2483.50	61.9 PK	74.0	-12.1	1.80 V	22	26.9	35.0
4	2483.50	48.5 AV	54.0	-5.5	1.80 V	22	13.5	35.0
5	4924.00	55.4 PK	74.0	-18.6	1.52 V	269	47.3	8.1
6	4924.00	41.7 AV	54.0	-12.3	1.52 V	269	33.6	8.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

<b>RF Mode</b>	802.11ax (HE40)	<b>Channel</b>	CH 3 : 2422 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.5 PK	74.0	-14.5	2.98 H	311	24.7	34.8
2	2390.00	46.3 AV	54.0	-7.7	2.98 H	311	11.5	34.8
3	*2422.00	98.9 PK			2.98 H	311	64.1	34.8
4	*2422.00	86.0 AV			2.98 H	311	51.2	34.8
5	4844.00	55.2 PK	74.0	-18.8	1.47 H	235	47.3	7.9
6	4844.00	41.1 AV	54.0	-12.9	1.47 H	235	33.2	7.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.7 PK	74.0	-14.3	1.72 V	24	24.9	34.8
2	2390.00	46.4 AV	54.0	-7.6	1.72 V	24	11.6	34.8
3	*2422.00	107.4 PK			1.72 V	24	72.6	34.8
4	*2422.00	95.0 AV			1.72 V	24	60.2	34.8
5	4844.00	55.4 PK	74.0	-18.6	1.52 V	235	47.5	7.9
6	4844.00	41.4 AV	54.0	-12.6	1.52 V	235	33.5	7.9

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11ax (HE40)	<b>Channel</b>	CH 6 : 2437 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	97.9 PK			2.90 H	302	63.1	34.8
2	*2437.00	85.1 AV			2.90 H	302	50.3	34.8
3	4874.00	55.2 PK	74.0	-18.8	1.69 H	253	47.1	8.1
4	4874.00	41.2 AV	54.0	-12.8	1.69 H	253	33.1	8.1

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	107.8 PK			1.88 V	31	73.0	34.8
2	*2437.00	94.9 AV			1.88 V	31	60.1	34.8
3	4874.00	55.4 PK	74.0	-18.6	2.63 V	118	47.3	8.1
4	4874.00	41.3 AV	54.0	-12.7	2.63 V	118	33.2	8.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.

<b>RF Mode</b>	802.11ax (HE40)	<b>Channel</b>	CH 9 : 2452 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	22°C, 67.7% RH
<b>Tested By</b>	Vincent Chen		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	97.7 PK			2.85 H	303	62.6	35.1
2	*2452.00	85.0 AV			2.85 H	303	49.9	35.1
3	2483.50	60.5 PK	74.0	-13.5	2.85 H	303	25.5	35.0
4	2483.50	47.2 AV	54.0	-6.8	2.85 H	303	12.2	35.0
5	4904.00	55.1 PK	74.0	-18.9	1.78 H	114	47.0	8.1
6	4904.00	40.9 AV	54.0	-13.1	1.78 H	114	32.8	8.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	108.5 PK			1.89 V	28	73.4	35.1
2	*2452.00	95.3 AV			1.89 V	28	60.2	35.1
3	2483.50	63.6 PK	74.0	-10.4	1.89 V	28	28.6	35.0
4	<b>2483.50</b>	<b>49.6 AV</b>	<b>54.0</b>	<b>-4.4</b>	<b>1.89 V</b>	<b>28</b>	<b>14.6</b>	<b>35.0</b>
5	4904.00	55.3 PK	74.0	-18.7	1.12 V	258	47.2	8.1
6	4904.00	41.2 AV	54.0	-12.8	1.12 V	258	33.1	8.1


**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.




### Plot of Band Edge

Frequency Range	2.31 GHz ~ 2.412 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	----------------------	-------------------------------	--




Frequency Range	2.462 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	---------------------	-------------------------------	--


### 802.11b Channel 11




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.31 GHz ~ 2.412 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	----------------------	-------------------------------	--


**802.11g Channel 1**




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--


### 802.11g Channel 11




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.31 GHz ~ 2.412 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	----------------------	-------------------------------	--


**802.11ax (HE20) Channel 1**




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.462 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	---------------------	-------------------------------	--


### 802.11ax (HE20) Channel 11




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.31 GHz ~ 2.412 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	----------------------	-------------------------------	--


**802.11ax (HE40) Channel 3**




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.462 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	---------------------	-------------------------------	--


### 802.11ax (HE40) Channel 9




Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)



## 8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)



## 9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@bureauveritas.com](mailto:service.adt@bureauveritas.com)

**Web Site:** <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---