

FCC PART 15.247

TEST REPORT

For

Hena Digital Technology (Shenzhen) Co., Ltd.

3F, South Tower, Jiuzhou Electric Building, Southern No, 12Rd High-tech Industrial Park, Nanshan District,
Shenzhen, China

FCC ID: M7C-PAD11641IWL

Report Type: Original Report	Product Type: Netbook
Test Engineer: Rocky Xiao	<i>Rocky Xiao</i>
Report Number: RDG160308003-00B	
Report Date: 2016-03-25	
Reviewed By: Dean Liu RF Engineer	<i>Dean Liu</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS.....	6
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	7
APPLICABLE STANDARD	7
FCC §15.203 - ANTENNA REQUIREMENT.....	8
APPLICABLE STANDARD	8
ANTENNA CONNECTOR CONSTRUCTION	8
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	9
APPLICABLE STANDARD	9
MEASUREMENT UNCERTAINTY.....	9
EUT SETUP	9
EMI TEST RECEIVER SETUP.....	10
TEST PROCEDURE	10
CORRECTED AMPLITUDE & MARGIN CALCULATION	10
TEST EQUIPMENT LIST AND DETAILS.....	11
TEST RESULTS SUMMARY	11
TEST DATA	11
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	14
APPLICABLE STANDARD	14
MEASUREMENT UNCERTAINTY.....	14
EUT SETUP	14
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	15
TEST PROCEDURE	15
TEST EQUIPMENT LIST AND DETAILS.....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST RESULTS SUMMARY	16
TEST DATA	17
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	26
APPLICABLE STANDARD	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST PROCEDURE	26
TEST DATA	26

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA	32
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST EQUIPMENT LIST AND DETAILS.....	38
TEST DATA	38
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST EQUIPMENT LIST AND DETAILS.....	42
TEST DATA	42
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	58
APPLICABLE STANDARD	58
TEST PROCEDURE	58
TEST EQUIPMENT LIST AND DETAILS.....	58
TEST DATA	58
FCC §15.247(d) - BAND EDGES TESTING	64
APPLICABLE STANDARD	64
TEST PROCEDURE	64
TEST EQUIPMENT LIST AND DETAILS.....	64
TEST DATA	65
DECLARATION LETTER.....	69

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Hena Digital Technology (Shenzhen) Co., Ltd.'s product, model number: PAD11641iWL (FCC ID: M7C-PAD11641IWL) (the "EUT") in this report was a *Netbook*, which was measured approximately: 24 cm (L) x 20cm (W) x 1.9 cm (H), rated input voltage: DC3.7V rechargeable Li-ion battery or DC5.0V charging from adapter.

Adapter information:

Model: TEKA018-0502500UK

Input: AC100-240V, 50/60 Hz, 0.5A

Output: DC5.0V, 2.5A

Note: The series product, models PAD11641iWL, CB116, VB116, GB116, DB116, QB116, SB116, KB116, EB116 are electrically identical, the differences between them is model name, we selected PAD11641iWL for fully testing, the details was explained in the attached declaration letter.

All measurement and test data in this report was gathered from production sample serial number: 1600308003 (Assigned by BACL, Dongguan). The EUT was received on 2016-03-08.

Objective

This report is prepared on behalf of Hena Digital Technology (Shenzhen) Co., Ltd. in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBC submissions with FCC ID: M7C-PAD11641IWL.

FCC Part 15.247 DTS submissions with FCC ID: M7C-PAD11641IWL.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in engineering mode.

EUT Exercise Software

Software: MPTool was used in test for switching test channel, the output power was configured as default value.

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	Earphone	/	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Power Cable	yes	no	0.85	Adater	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The tune-up conducted power is 3.3 dBm (2.14mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 2.14/5 \cdot (\sqrt{2.480}) = 0.67 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one Internal antenna arrangement for WiFi/BT, and the antenna gain is 3.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.12 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-12-10	2016-12-09
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-07-16	2016-07-15
N/A	Coaxial Cable	1.8m	N/A	2015-05-06	2016-05-06
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

13.9 dB at 17.599071 MHz in the Line conducted mode


Test Data**Environmental Conditions**

Temperature:	23°C
Relative Humidity:	46 %
ATM Pressure:	101.6 kPa

The testing was performed by Rocky Xiao on 2016-03-10.


Test Mode: Transmitting

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.429420	34.6	9.000	L1	9.8	22.7	57.3	Compliance
0.483938	39.1	9.000	L1	9.8	17.2	56.3	Compliance
0.563041	36.3	9.000	L1	9.8	19.7	56.0	Compliance
12.694276	40.8	9.000	L1	10.1	19.2	60.0	Compliance
16.122185	40.6	9.000	L1	10.1	19.4	60.0	Compliance
17.881783	42.2	9.000	L1	10.1	17.8	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.174519	23.9	9.000	L1	9.7	30.8	54.7	Compliance
0.491712	27.0	9.000	L1	9.8	19.1	46.1	Compliance
1.239175	21.8	9.000	L1	9.8	24.2	46.0	Compliance
1.385415	21.7	9.000	L1	9.8	24.3	46.0	Compliance
17.599071	36.1	9.000	L1	10.1	13.9	50.0	Compliance
17.739864	35.9	9.000	L1	10.1	14.1	50.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.422630	33.3	9.000	N	9.7	24.1	57.4	Compliance
0.476287	36.2	9.000	N	9.7	20.2	56.4	Compliance
0.499611	39.9	9.000	N	9.7	16.1	56.0	Compliance
12.296055	41.0	9.000	N	10.1	19.0	60.0	Compliance
17.459396	42.6	9.000	N	10.1	17.4	60.0	Compliance
17.739864	41.8	9.000	N	10.1	18.2	60.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.499611	23.7	9.000	N	9.7	22.3	46.0	Compliance
1.190776	23.6	9.000	N	9.8	22.4	46.0	Compliance
1.407671	23.4	9.000	N	9.8	22.6	46.0	Compliance
2.953456	14.2	9.000	N	9.8	31.8	46.0	Compliance
17.320829	35.3	9.000	N	10.1	14.7	50.0	Compliance
17.739864	33.7	9.000	N	10.1	16.3	50.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical; 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical; 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB


Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Av

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2015-09-06	2016-09-06
N/A	Coaxial Cable	14m	N/A	2015-05-06	2016-05-06
N/A	Coaxial Cable	8m	N/A	2015-05-06	2016-05-06
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

2.33 dB at 2400 MHZ in the **Horizontal** polarization for BDR Mode

Test Data**Environmental Conditions**

Temperature:	24.4°C
Relative Humidity:	64 %
ATM Pressure:	100.7 kPa

** The testing was performed by Rocky Xiao on 2016-03-22.*

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	61.36	PK	H	28.46	3.66	0.00	93.48	N/A	N/A
2402	60.71	AV	H	28.46	3.66	0.00	92.83	N/A	N/A
2402	60.18	PK	V	28.46	3.66	0.00	92.30	N/A	N/A
2402	59.47	AV	V	28.46	3.66	0.00	91.59	N/A	N/A
2400	25.79	PK	H	28.46	3.65	0.00	57.90	74.00	16.10
2400	15.36	AV	H	28.46	3.65	0.00	47.47	54.00	6.53
4804	32.55	PK	H	33.13	5.06	27.41	43.33	74.00	30.67
4804	18.87	AV	H	33.13	5.06	27.41	29.65	54.00	24.35
7206	31.95	PK	H	36.37	6.61	25.91	49.02	74.00	24.98
7206	18.66	AV	H	36.37	6.61	25.91	35.73	54.00	18.27
9608	29.24	PK	H	38.38	8.53	27.55	48.60	74.00	25.40
9608	16.46	AV	H	38.38	8.53	27.55	35.82	54.00	18.18
4000	36.35	PK	H	32.10	4.84	27.20	46.09	74.00	27.91
4000	23.83	AV	H	32.10	4.84	27.20	33.57	54.00	20.43
233.7	29.8	QP	V	12.07	1.85	21.48	22.24	46.00	23.76
Middle Channel: 2441 MHz									
2441	61.76	PK	H	28.56	3.76	0.00	94.08	N/A	N/A
2441	61.06	AV	H	28.56	3.76	0.00	93.38	N/A	N/A
2441	60.31	PK	V	28.56	3.76	0.00	92.63	N/A	N/A
2441	59.77	AV	V	28.56	3.76	0.00	92.09	N/A	N/A
4882	32.44	PK	H	33.40	5.19	27.42	43.61	74.00	30.39
4882	18.86	AV	H	33.40	5.19	27.42	30.03	54.00	23.97
7323	31.84	PK	H	36.58	6.75	25.88	49.29	74.00	24.71
7323	18.62	AV	H	36.58	6.75	25.88	36.07	54.00	17.93
9764	29.2	PK	H	38.35	8.62	27.20	48.97	74.00	25.03
9764	16.43	AV	H	38.35	8.62	27.20	36.20	54.00	17.80
4000	36.35	PK	H	32.10	4.84	27.20	46.09	74.00	27.91
4000	23.85	AV	H	32.10	4.84	27.20	33.59	54.00	20.41
3340	33.81	PK	H	32.09	4.86	27.25	43.51	74.00	30.49
3340	21.39	AV	H	32.09	4.86	27.25	31.09	54.00	22.91
233.7	30.2	QP	V	12.07	1.85	21.48	22.64	46.00	23.36
High Channel: 2480 MHz									
2480	61.98	PK	H	28.65	3.68	0.00	94.31	N/A	N/A
2480	61.44	AV	H	28.65	3.68	0.00	93.77	N/A	N/A
2480	60.74	PK	V	28.65	3.68	0.00	93.07	N/A	N/A
2480	60.23	AV	V	28.65	3.68	0.00	92.56	N/A	N/A
2483.5	25.33	PK	H	28.66	3.67	0.00	57.66	74.00	16.34
2483.5	13.93	AV	H	28.66	3.67	0.00	46.26	54.00	7.74
4960	32.25	PK	H	33.66	5.34	27.43	43.82	74.00	30.18
4960	18.77	AV	H	33.66	5.34	27.43	30.34	54.00	23.66
7440	31.93	PK	H	36.79	6.89	25.97	49.64	74.00	24.36
7440	18.74	AV	H	36.79	6.89	25.97	36.45	54.00	17.55
9920	29.09	PK	H	38.32	8.71	26.66	49.46	74.00	24.54
9920	16.41	AV	H	38.32	8.71	26.66	36.78	54.00	17.22
4000	36.37	PK	H	32.10	4.84	27.20	46.11	74.00	27.89
4000	23.79	AV	H	32.10	4.84	27.20	33.53	54.00	20.47
233.7	29.6	QP	V	12.07	1.85	21.48	22.04	46.00	23.96

EDR Mode ($\pi/4$ -DQPSK):

Frequency	Receiver		Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	(dB)	(dB)	(dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	62.25	PK	H	28.46	3.66	0.00	94.37	N/A	N/A
2402	58.79	AV	H	28.46	3.66	0.00	90.91	N/A	N/A
2402	61.29	PK	V	28.46	3.66	0.00	93.41	N/A	N/A
2402	57.91	AV	V	28.46	3.66	0.00	90.03	N/A	N/A
2400	29.56	PK	H	28.46	3.65	0.00	61.67	74.00	12.33
2400	19.56	AV	H	28.46	3.65	0.00	51.67	54.00	2.33
4804	32.48	PK	H	33.13	5.06	27.41	43.26	74.00	30.74
4804	18.91	AV	H	33.13	5.06	27.41	29.69	54.00	24.31
7206	31.88	PK	H	36.37	6.61	25.91	48.95	74.00	25.05
7206	18.73	AV	H	36.37	6.61	25.91	35.80	54.00	18.20
9608	29.23	PK	H	38.38	8.53	27.55	48.59	74.00	25.41
9608	16.53	AV	H	38.38	8.53	27.55	35.89	54.00	18.11
4000	36.38	PK	H	32.10	4.84	27.20	46.12	74.00	27.88
4000	23.7	AV	H	32.10	4.84	27.20	33.44	54.00	20.56
233.7	29.9	QP	V	12.07	1.85	21.48	22.34	46.00	23.66
Middle Channel: 2441 MHz									
2441	62.82	PK	H	28.56	3.76	0.00	95.14	N/A	N/A
2441	59.34	AV	H	28.56	3.76	0.00	91.66	N/A	N/A
2441	61.49	PK	V	28.56	3.76	0.00	93.81	N/A	N/A
2441	58.17	AV	V	28.56	3.76	0.00	90.49	N/A	N/A
4882	32.57	PK	H	33.40	5.19	27.42	43.74	74.00	30.26
4882	18.87	AV	H	33.40	5.19	27.42	30.04	54.00	23.96
7323	31.99	PK	H	36.58	6.75	25.88	49.44	74.00	24.56
7323	18.77	AV	H	36.58	6.75	25.88	36.22	54.00	17.78
9764	29.09	PK	H	38.35	8.62	27.20	48.86	74.00	25.14
9764	16.41	AV	H	38.35	8.62	27.20	36.18	54.00	17.82
4000	36.46	PK	H	32.10	4.84	27.20	46.20	74.00	27.80
4000	23.75	AV	H	32.10	4.84	27.20	33.49	54.00	20.51
3340	33.74	PK	H	32.09	4.86	27.25	43.44	74.00	30.56
3340	21.16	AV	H	32.09	4.86	27.25	30.86	54.00	23.14
233.7	30.1	QP	V	12.07	1.85	21.48	22.54	46.00	23.46
High Channel: 2480 MHz									
2480	62.98	PK	H	28.65	3.68	0.00	95.31	N/A	N/A
2480	59.75	AV	H	28.65	3.68	0.00	92.08	N/A	N/A
2480	61.88	PK	V	28.65	3.68	0.00	94.21	N/A	N/A
2480	58.62	AV	V	28.65	3.68	0.00	90.95	N/A	N/A
2483.5	25.52	PK	H	28.66	3.67	0.00	57.85	74.00	16.15
2483.5	13.93	AV	H	28.66	3.67	0.00	46.26	54.00	7.74
4960	32.6	PK	H	33.66	5.34	27.43	44.17	74.00	29.83
4960	18.84	AV	H	33.66	5.34	27.43	30.41	54.00	23.59
7440	31.89	PK	H	36.79	6.89	25.97	49.60	74.00	24.40
7440	18.76	AV	H	36.79	6.89	25.97	36.47	54.00	17.53
9920	29.11	PK	H	38.32	8.71	26.66	49.48	74.00	24.52
9920	16.45	AV	H	38.32	8.71	26.66	36.82	54.00	17.18
4000	36.51	PK	H	32.10	4.84	27.20	46.25	74.00	27.75
4000	23.87	AV	H	32.10	4.84	27.20	33.61	54.00	20.39
233.7	30.1	QP	V	12.07	1.85	21.48	22.54	46.00	23.46


EDR Mode (8-DPSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402 MHz									
2402	62.45	PK	H	28.46	3.66	0.00	94.57	N/A	N/A
2402	58.82	AV	H	28.46	3.66	0.00	90.94	N/A	N/A
2402	61.45	PK	V	28.46	3.66	0.00	93.57	N/A	N/A
2402	57.87	AV	V	28.46	3.66	0.00	89.99	N/A	N/A
2400	29.61	PK	H	28.46	3.65	0.00	61.72	74.00	12.28
2400	19.33	AV	H	28.46	3.65	0.00	51.44	54.00	2.56
4804	32.13	PK	H	33.13	5.06	27.41	42.91	74.00	31.09
4804	18.79	AV	H	33.13	5.06	27.41	29.57	54.00	24.43
7206	31.69	PK	H	36.37	6.61	25.91	48.76	74.00	25.24
7206	18.68	AV	H	36.37	6.61	25.91	35.75	54.00	18.25
9608	28.96	PK	H	38.38	8.53	27.55	48.32	74.00	25.68
9608	16.52	AV	H	38.38	8.53	27.55	35.88	54.00	18.12
4000	36.25	PK	H	32.10	4.84	27.20	45.99	74.00	28.01
4000	23.6	AV	H	32.10	4.84	27.20	33.34	54.00	20.66
233.7	30.2	QP	V	12.07	1.85	21.48	22.64	46.00	23.36
Middle Channel: 2441 MHz									
2441	62.98	PK	H	28.56	3.76	0.00	95.30	N/A	N/A
2441	59.29	AV	H	28.56	3.76	0.00	91.61	N/A	N/A
2441	61.79	PK	V	28.56	3.76	0.00	94.11	N/A	N/A
2441	58.12	AV	V	28.56	3.76	0.00	90.44	N/A	N/A
4882	32.2	PK	H	33.40	5.19	27.42	43.37	74.00	30.63
4882	18.87	AV	H	33.40	5.19	27.42	30.04	54.00	23.96
7323	31.62	PK	H	36.58	6.75	25.88	49.07	74.00	24.93
7323	18.73	AV	H	36.58	6.75	25.88	36.18	54.00	17.82
9764	29.04	PK	H	38.35	8.62	27.20	48.81	74.00	25.19
9764	16.58	AV	H	38.35	8.62	27.20	36.35	54.00	17.65
4000	36.28	PK	H	32.10	4.84	27.20	46.02	74.00	27.98
4000	23.56	AV	H	32.10	4.84	27.20	33.30	54.00	20.70
3340	33.62	PK	H	32.09	4.86	27.25	43.32	74.00	30.68
3340	21.23	AV	H	32.09	4.86	27.25	30.93	54.00	23.07
233.7	30	QP	V	12.07	1.85	21.48	22.44	46.00	23.56
High Channel: 2480 MHz									
2480	63.2	PK	H	28.65	3.68	0.00	95.53	N/A	N/A
2480	59.75	AV	H	28.65	3.68	0.00	92.08	N/A	N/A
2480	62.18	PK	V	28.65	3.68	0.00	94.51	N/A	N/A
2480	58.61	AV	V	28.65	3.68	0.00	90.94	N/A	N/A
2483.5	25.18	PK	H	28.66	3.67	0.00	57.51	74.00	16.49
2483.5	13.93	AV	H	28.66	3.67	0.00	46.26	54.00	7.74
4960	32.37	PK	H	33.66	5.34	27.43	43.94	74.00	30.06
4960	18.96	AV	H	33.66	5.34	27.43	30.53	54.00	23.47
7440	32.02	PK	H	36.79	6.89	25.97	49.73	74.00	24.27
7440	18.85	AV	H	36.79	6.89	25.97	36.56	54.00	17.44
9920	29.43	PK	H	38.32	8.71	26.66	49.80	74.00	24.20
9920	16.67	AV	H	38.32	8.71	26.66	37.04	54.00	16.96
4000	36.59	PK	H	32.10	4.84	27.20	46.33	74.00	27.67
4000	24.03	AV	H	32.10	4.84	27.20	33.77	54.00	20.23
233.7	30.2	OP	V	12.07	1.85	21.48	22.64	46.00	23.36


Conducted Spurious Emissions at Antenna Port

BDR Mode (GFSK):


Low Channel



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):


Low Channel



Middle Channel




High Channel




EDR Mode (8-DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	24.4°C
Relative Humidity:	64 %
ATM Pressure:	100.7 kPa

* The testing was performed by Rocky Xiao on 2016-03-22.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting


	Channel	Frequency	Channel Separation	Limit
		MHz	MHz	MHz
BDR (GFSK)	Low	2402	1.002	0.70
	Middle	2441	1.002	0.69
	High	2480	1.002	0.70
EDR ($\pi/4$ -DQPSK)	Low	2402	1.002	0.90
	Middle	2441	1.002	0.90
	High	2480	1.002	0.90
EDR (8DPSK)	Low	2402	1.002	0.92
	Middle	2441	1.002	0.92
	High	2480	1.002	0.92

Note: Limit = $(2/3) \times 20\text{dB bandwidth}$


BDR Mode (GFSK):



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):


Low Channel



Middle Channel




High Channel




EDR Mode (8-DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	24.4°C
Relative Humidity:	64 %
ATM Pressure:	100.7 kPa

* The testing was performed by Rocky Xiao on 2016-03-22.


Test Result: Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	1.05
	Middle	2441	1.04
	High	2480	1.05
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.35
	Middle	2441	1.35
	High	2480	1.35
EDR Mode (8-DPSK):	Low	2402	1.38
	Middle	2441	1.38
	High	2480	1.38


BDR Mode (GFSK):



Middle Channel




High Channel




EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 22.MAR.2016 05:54:25

Middle Channel




Date: 22.MAR.2016 05:57:05

High Channel




EDR Mode (8-DPSK):


Low Channel



Middle Channel



High Channel



FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	24.4°C
Relative Humidity:	64 %
ATM Pressure:	100.7 kPa

* The testing was performed by Rocky Xiao on 2016-03-22.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15




EDR Mode ($\pi/4$ -DQPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥15



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as $0.4 \times \text{channel no. (s)}$, the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time = time slot length $\times$ hope rate / number of hopping channels $\times 31.6\text{s}$
Hop rate = 1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	24.4°C
Relative Humidity:	64 %
ATM Pressure:	100.7 kPa

* The testing was performed by Rocky Xiao on 2016-03-22.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting


BDR Mode (GFSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.413	0.132	0.4	Compliance
	Middle	0.413	0.132	0.4	Compliance
	High	0.413	0.132	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/2/79) × 31.6 s				
DH3	Low	1.67	0.267	0.4	Compliance
	Middle	1.67	0.267	0.4	Compliance
	High	1.67	0.267	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/4/79) × 31.6 s				
DH5	Low	2.94	0.314	0.4	Compliance
	Middle	2.94	0.314	0.4	Compliance
	High	2.95	0.315	0.4	Compliance
	Note: Dwell time=Pulse time (ms) × (1600/6/79) × 31.6 s				

DH1: Low Channel




DH1: Middle Channel




Date: 22.MAR.2016 09:05:06

DH1: High Channel




Date: 22.MAR.2016 09:05:16

DH3: Low Channel




Date: 22.MAR.2016 09:08:45

DH3: Middle Channel




Date: 22.MAR.2016 09:08:57


DH3: High Channel




DH5: Low Channel



DH5: Middle Channel




DH5: High Channel




EDR Mode ($\pi/4$ -DQPSK):

Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
2DH1	Low	0.423	0.135	0.4	Compliance
	Middle	0.423	0.135	0.4	Compliance
	High	0.423	0.135	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
2DH3	Low	1.68	0.269	0.4	Compliance
	Middle	1.68	0.269	0.4	Compliance
	High	1.68	0.269	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
2DH5	Low	2.96	0.316	0.4	Compliance
	Middle	2.96	0.316	0.4	Compliance
	High	2.96	0.316	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				


2DH1: Low Channel




2DH1: Middle Channel




2DH1: High Channel



2DH3: Low Channel



2DH3: Middle Channel



Ref Lvl 20 dBm

Marker 1 [T1] -54.91 dBm

RBW 1 MHz RF Att 30 dB

VBW 1 MHz

SWT 3 ms Unit dBm

2 dB Offset

1MAX

TR

Center 2.48 GHz

300 μ s

1.679359 ms


0.58 dB

-9.418838 μ s


-54.91 dBm

[illegible]


2DH5: Middle Channel




2DH5: High Channel




Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
3DH1	Low	0.423	0.135	0.4	Compliance
	Middle	0.423	0.135	0.4	Compliance
	High	0.423	0.135	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/2/79) $\times$ 31.6 s				
3DH3	Low	1.68	0.269	0.4	Compliance
	Middle	1.68	0.269	0.4	Compliance
	High	1.68	0.269	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/4/79) $\times$ 31.6 s				
3DH5	Low	2.96	0.316	0.4	Compliance
	Middle	2.96	0.316	0.4	Compliance
	High	2.96	0.316	0.4	Compliance
	Note: Dwell time=Pulse time (ms) $\times$ (1600/6/79) $\times$ 31.6 s				




3DH1: Middle Channel



3DH1: High Channel




3DH3: Low Channel




Date: 22.MAR.2016 09:10:58

3DH3: Middle Channel




Date: 22.MAR.2016 09:11:06

3DH3: High Channel




Date: 22.MAR.2016 09:11:20

3DH5: Low Channel




Date: 22.MAR.2016 09:14:39

3DH5: Middle Channel



3DH5: High Channel



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	24.4°C
Relative Humidity:	64 %
ATM Pressure:	100.7 kPa

* The testing was performed by Rocky Xiao on 2016-03-22.


Test Result: Compliance.

Test Mode: Transmitting


Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	0.82	30
	Middle	2441	0.95	30
	High	2480	1.59	30
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	2.22	30
	Middle	2441	2.47	30
	High	2480	2.97	30
EDR Mode (8-DPSK)	Low	2402	2.47	30
	Middle	2441	2.59	30
	High	2480	3.22	30

Note: The data above was tested in conducted mode.


BDR Mode (GFSK):



Output Power, Middle Channel




Output Power, High Channel




EDR Mode ($\pi/4$ -DQPSK):

Output Power, Low Channel




Date: 22.MAR.2016 05:54:51

Output Power, Middle Channel




Date: 22.MAR.2016 05:57:32

Output Power, High Channel




EDR Mode (8-DPSK):


Output Power, Low Channel



Output Power, Middle Channel



Output Power, High Channel



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	24.4°C
Relative Humidity:	64 %
ATM Pressure:	100.7 kPa

** The testing was performed by Rocky Xiao on 2016-03-22.*

BDR Mode (GFSK):

Ref Lvl 20 dBm

Marker 2 [T1] -52.86 dBm

RBW 100 kHz RF Att 30 dB

VBW 300 kHz

SWT 5 ms Unit dBm

2 dB Offset

1MAX -19.96 dBm

2 [T1] -52.86 dBm

2.39986373 GHz

0.04 dBm

2.40196393 GHz

Center 2.4 GHz

800 kHz

Span 8 MHz

Date: 22.MAR.2016 05:49:30

Ref Lvl 20 dBm

Marker 2 [T1] -53.24 dBm

RBW 100 kHz RF Att 30 dB

VBW 300 kHz

SWT 5 ms Unit dBm

2 dB Offset

1MAX

1 [T1] -53.24 dBm 2.48755411 GHz

2 [T1] -19.54 dBm 2.47995090 GHz

Center 2.4835 GHz


1.4 MHz

Span 14 MHz


Date: 22.MAR.2016 05:53:35

EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side




Band Edge, Right Side




EDR Mode (8-DPSK):

Band Edge, Left Side



Band Edge, Right Side



DECLARATION LETTER

Hena Digital Technology (Shenzhen) Co., Ltd.
ADD: 3F, South Tower, Jiuzhou Electric Building, Southern No. 12Rd High-tech Industrial Park,
Nanshan District, Shenzhen, China
Tel: (86)0755-8287 7246 Fax: (86)0755-8287 9070
E-mail: zijian8548@yahoo.com.cn

DECLARATION OF SIMILARITY

FEDERAL COMMUNICATIONS COMMISSION
Authorization and Evaluation Division
7435 Oakland Mills Road
Columbia, MD 21046
Date: 2016-3-8

Dear Sir or Madam:


We, Hena Digital Technology (Shenzhen) Co., Ltd., hereby declare that product: Netbook, model number: CB116, VB116, GB116, DB116, QB116, SB116, KB116 and EB116 are electrically identical with the model number PAD11641iWL which was tested by BACL. They have the same electromagnetic emissions and electromagnetic compatibility characteristics. The results of which are featured in BACL project: RDG160308003, RDG160308003-20. the FCC ID: M7C-PAD11641iWL

A description of the difference among nine models and those that are declared similar are as follows:

They are the same product, and just have the different model name, the rest are the same.

Please contact me should there be need for any additional clarification or information.

Best Regards,



Chen Yong
Manager

*****END OF REPORT*****