

Prüfbericht-Nr.: <i>Test Report No.:</i>	50147916 001	Auftrags-Nr.: <i>Order No.:</i>	144181353	Seite 1 von 18 <i>Page 1 of 18</i>	
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	18.05.2018		
Auftraggeber: <i>Client:</i>	Remotec Technology Ltd. Workshop No. B2, 2/F., Block B, Tonic Industrial Centre, 19 Lam Hing Street, Kowloon Bay, HK				
Prüfgegenstand: <i>Test item:</i>	BT Remote Control				
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	BW7630UN, BW7640UN				
Auftrags-Inhalt: <i>Order content:</i>	US FCC Certification; ISED Canada Certification				
Prüfgrundlage: <i>Test specification:</i>	FCC Part 15 Subpart C RSS-247 Issue 2 ANSI C63.10-2013				
Wareneingangsdatum: <i>Date of receipt:</i>	24.10.2018				
	28.09.2018				
Prüfmuster-Nr.: <i>Test sample No.:</i>	A000791788-009~010				
	A000815028-001				
Prüfzeitraum: <i>Testing period:</i>	10.10.2018 - 31.10.2018				
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland Hong Kong Ltd.				
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland Hong Kong Ltd.				
Prüfergebnis*: <i>Test result*:</i>	Pass				
geprüft von / tested by:		kontrolliert von / reviewed by:			
					
09.11.2018	Benny Lau / Senior Project Manager	09.11.2018	Sharon Li / Unit Senior Manager		
Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>
Sonstiges / Other:		FCC ID: M7N-BW7630 IC: 7311A-BW7630			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>			Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
<p>* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(pass) = entspricht o.g. Prüfgrundlage(n) F(fail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet</p> <p>Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(pass) = passed a.m. test specification(s) F(fail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested</p>					
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</p> <p><i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>					

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information.....	4
Manufacturers declarations	4
Product function and intended use.....	4
Submitted documents.....	4
Independent Operation Modes	4
Related Submittal(s) Grants	4
Remark	5
Test Set-up and Operation Mode.....	6
Principle of Configuration Selection	6
Test Operation and Test Software.....	6
Special Accessories and Auxiliary Equipment.....	6
Countermeasures to achieve EMC Compliance.....	6
Test Methodology	7
Radiated Emission	7
Field Strength Calculation.....	7
Test Setup Diagram	8
Test Facility	10
Test Laboratory Information	10
List of Test and Measurement Instruments.....	11
Measurement Uncertainty	12
Results FCC Part 15 – Subpart C / RSS-247 Issue 2.....	13
FCC 15.203 – Antenna Requirement 1.....	Pass.....
FCC 15.204 – Antenna Requirement 2.....	N/A.....
RSS-Gen 6.3 – External Control.....	Pass.....
RSS-Gen 8.3 – Antenna Requirement	Pass.....
FCC 15.207/ RSS-Gen 8.8 – Conducted Emission on AC Mains.....	N/A.....
FCC 15.247 (a)(2) / RSS-247 5.2 – 6dB Bandwidth Measurement.....	Pass.....
RSS-Gen 6.6 – Occupied Bandwidth.....	Pass.....

FCC 15.247(b)(3) / RSS-247 5.4 – Maximum Peak Conducted Output Power.....	Pass.....	15
FCC 15.247(e) / RSS-247 5.2 – Power Spectral Density	Pass.....	15
FCC 15.247(d) / RSS-247 5.5 – Spurious Conducted Emissions	Pass.....	16
FCC 15.205/ RSS-Gen 8.9 – Radiated Emissions in Restricted Frequency Bands	Pass.....	17
Appendix 1 – Test protocols		17 pages
Appendix 2 – Test setup		2 pages
Appendix 3 – EUT External Photos		4 pages
Appendix 4 – EUT Internal Photos		3 pages
Appendix 5 – RF exposure information.....		2 pages

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	GFSK
Number of channels	40
Channel separation	2 MHz
Type of antenna	PCB Antenna
Antenna gain (dBi)	0 dBi
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	No
Nominal voltage	3 VDC
Independent Operation Modes	Transmitting

Product function and intended use

The equipment under test (EUT) is a Bluetooth low energy device.

The manufacturer declares that the model BW7630UN and BW7640UN are identical in PCB layout, components used, circuit design except the key layout of the plastic case and BW7640UN does not have the digital microphone in the non-RF portions. BW7630UN is selected for the full test. Both models are tested for Radiated Emission and the worst case is reported.

FCC ID: M7N-BW7630/ IC: 7311A-BW7630

Models	Product description
BW7630UN, BW7640UN	BT Remote Control

Submitted documents

Circuit Diagram
 Block Diagram
 Technical Description
 User manual
 Label

Independent Operation Modes

The basic operation modes are:

- Transmitting mode.

For further information refer to User Manual

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- A test mode sample is provided by the applicant to control the operating channel. The RF output power is fixed in the test mode sample. The setting of the RF output power used in the testing shall be fixed on the firmware of the final end product.

Special Accessories and Auxiliary Equipment

- None

Countermeasures to achieve EMC Compliance

- None

Test Methodology

Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013.

For measurement below 1GHz - the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz - the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:


$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.
R = Reading of Spectrum Analyzer in dBuV.
AF = Antenna Factor in dB.
CF = Cable Attenuation Factor in dB.
FA = Filter Attenuation Factor in dB.
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)





Diagram of Equipment Configuration for Antenna-port Conducted Measurement (if applicable)

Test Facility

Test Laboratory Information

TÜV Rheinland Hong Kong Ltd.

Address: 3-4, 11/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong

Tel.: +852 2192 1000

Fax: +852 2192 1001

Email service-gc@tuv.com

Web: www.tuv.com

The test facility is recognized or accredited by the following organizations:

FCC

Type	: Accredited Test Firm
Designation Number	: HK0013
Test Firm Registration Number	: 371735
Scope	: Intentional Radiators

ISED

The 10m Semi-anechoic chamber used by TÜV Rheinland Hong Kong Ltd at Hong Kong Productivity Council has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

Test Site Registration Number : 4780A-1

List of Test and Measurement Instruments

Radiated Emission

Equipment	Manufacturer	Type	Cal. Date	Due Date
Semi-anechoic Chamber	Frankonia	Nil	23-Apr-18	23-Apr-19
Test Receiver	R & S	ESU40	12-Jun-18	12-Jun-19
Active Loop Antenna	EMCO	6502	25-Oct-18	25-Oct-19
Bi-conical Antenna	R & S	HK116	21-Mar-18	21-Mar-20
Log Periodic Antenna	R & S	HL223	22-Mar-18	22-Mar-20
Standard Gain Horn	ETS-Lindgren	3160-07	4-Sep-18	4-Sep-20
Standard Gain Horn	ETS-Lindgren	3160-08	26-Sep-18	26-Sep-20
Standard Gain Horn	ETS-Lindgren	3160-10	3-Oct-18	3-Oct-20
Double-Ridged Waveguide Horn	EMCO	3116	5-Oct-18	5-Oct-20
Double-Ridged Waveguide Horn	EMCO	3117	30-Aug-18	30-Aug-20
Coaxial cable	Harbour	LL335	12-Jun-18	12-Jun-19
High Frequency Cable	Pasternack	PE3VNA4001-3M	11-Dec-17	11-Dec-19
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	25-Jun-18	25-Jun-19
Preamplifier 18GHz to 40GHz with cable (EMC656)	A.H. Systems, Inc.	PAM-1840VH	29-Jan-18	29-Jan-19
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	30-Oct-17	30-Oct-19

Radio Test

Equipment	Manufacturer	Type	Cal. Date	Due Date
Spectrum Analyzer	R & S	FSP30	3-May-18	2-May-19

Measurement Uncertainty

The estimated combined standard uncertainty for power-line conducted emissions measurements is $\pm 2.42\text{dB}$.

The estimated combined standard uncertainty for radiated emissions measurements is $\pm 4.81\text{dB}$ (9kHz to 30MHz) and $\pm 4.62\text{dB}$ (30MHz to 200MHz) and $\pm 5.67\text{dB}$ (200MHz to 1000MHz) and is $\pm 5.07\text{dB}$ (1GHz to 8.2GHz) and $\pm 4.58\text{dB}$ (8.2GHz to 12.4GHz) and $\pm 4.78\text{dB}$ (12.4GHz to 18GHz)

The estimated combined standard uncertainty for antenna conducted emission is $\pm 2.1\text{dB}$

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of $k=2$, which for the level of confidence is approximately 95%.

Results FCC Part 15 – Subpart C / RSS-247 Issue 2

FCC 15.203 – Antenna Requirement 1		Pass
FCC Requirement: No antenna other than that furnished by the responsible party shall be used with the device		
Results:	a) Antenna type: b) Manufacturer and model no: c) Peak Gain:	Integral PCB antenna N/A 0 dBi
Verdict:	Pass	
FCC 15.204 – Antenna Requirement 2		N/A
FCC Requirement: An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.		
Results:	Only one integral antenna can be used.	
Verdict:	N/A	
RSS-Gen 6.3 – External Control		Pass
IC Requirement: The device shall not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the limits prescribed in the applicable RSS.		
Results:	The device does not have any transmitter external controls accessible to the user that can be adjusted and operated in violation of the limits of this standard.	
Verdict:	Pass	
RSS-Gen 8.3 – Antenna Requirement		Pass
IC Requirement: When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer.		
Results:	a) Antenna type: b) Manufacturer c) model no d) Gain with reference to an isotropic radiator:	Fixed Integral PCB antenna N/A N/A 0 dBi
Verdict:	Pass	
FCC 15.207/ RSS-Gen 8.8 – Conducted Emission on AC Mains		N/A
There is no AC power input or output ports on the EUT.		

FCC 15.247 (a)(2) / RSS-247 5.2 – 6dB Bandwidth Measurement		Pass	
FCC/ IC Requirement: Systems using digital modulation techniques may operate in the 902 – 928 MHz, 2400 – 2483.5 MHz, and 5725 – 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.			
Test Specification : ANSI C63.10 – 2013 Test date : 31.10.2018 Tested Model : BW7630UN Mode of operation : Tx mode Port of testing : Temporary antenna port Supply voltage : 3VDC Temperature : 23°C Humidity : 50%			
Results: For test protocols please refer to Appendix 1			
Channel frequency (MHz)	6 dB left (MHz)	6 dB right (MHz)	6dB bandwidth (kHz)
2402	2401.620	2402.350	730
2440	2439.670	2440.300	630
2480	2479.610	2480.360	750

RSS-Gen 6.6 – Occupied Bandwidth		Pass	
FCC/ IC Requirement: N/A			
Test Specification : RSS-Gen Test date : 31.10.2018 Tested Model : BW7630UN Mode of operation : Tx mode Port of testing : Temporary antenna port Supply voltage : 3VDC Temperature : 23°C Humidity : 50%			
Results: Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types. For test protocols refer to Appendix 1.			
Frequency (MHz)	Left (MHz)	Right (MHz)	99% bandwidth (MHz)
2402	2401.450	2402.520	1.07
2440	2439.460	2440.510	1.05
2480	2479.450	2480.520	1.07

FCC 15.247(b)(3) / RSS-247 5.4 – Maximum Peak Conducted Output Power		Pass	
FCC/ IC Requirement: For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850MHz bands: 1 Watt (30dBm)			
Test Specification : ANSI C63.10 – 2013 Test date : 31.10.2018 Tested Model : BW7630UN Mode of operation : Tx mode Port of testing : Temporary antenna port Supply voltage : 3VDC Temperature : 23°C Humidity : 50%			
Results: For test protocols please refer to Appendix 1			
Frequency (MHz)	Measured Output Power (dBm)	Limit (W/dBm)	Verdict
2402	-5.19	30.0	Pass
2440	-6.49	30.0	Pass
2480	-7.88	30.0	Pass

FCC 15.247(e) / RSS-247 5.2 – Power Spectral Density		Pass	
FCC/ IC Requirement: For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.			
Test Specification : ANSI C63.10 – 2013 Test date : 31.10.2018 Tested Model : BW7630UN Mode of operation : Tx mode Port of testing : Temporary antenna port Supply voltage : 3VDC Temperature : 23°C Humidity : 50%			
Results: For test protocols please refer to Appendix 1.			
Operating frequency (MHz)	Power density (dBm)	Limit (dBm)	Verdict
2402	-5.41	8.0	Pass
2440	-6.82	8.0	Pass
2480	-8.25	8.0	Pass

FCC 15.247(d) / RSS-247 5.5 – Spurious Conducted Emissions		Pass			
Test Specification	: ANSI C63.10 – 2013				
FCC/ IC Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Results:		Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate.			
		Only the worst cases is shown below. For test protocols refer to Appendix 1			
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	2399.960	-53.74	-5.41	48.33	Pass
2440	7440.000	-52.06	-6.82	45.24	Pass
2480	7420.000	-51.60	-8.25	43.35	Pass

FCC 15.205/ RSS-Gen 8.9 – Radiated Emissions in Restricted Frequency Bands			Pass
Test Specification : ANSI C63.10 – 2013			
Test Date : 31.10.2018			
Tested Model : BW7630UN, BW7640UN			
Mode of operation : Tx mode			
Port of testing : Enclosure			
Frequency range : 9kHz – 25GHz			
Supply voltage : 3VDC			
Temperature : 23°C			
Humidity : 50%			
FCC/ IC Requirement: In any 100kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission general limits.			
Results:		Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate.	
		All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.	
Mode: 2402MHz TX		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2390.000	37.5	74.0 / PK	
2390.000	23.6	54.0 / AV	
No peak found	---	74.0 / PK	
No peak found	---	54.0 / AV	
Mode: 2402 MHz TX		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2390.000	40.8	74.0 / PK	
2390.000	26.8	54.0 / AV	
4803.482	54.1	74.0 / PK	
4803.482	46.6	54.0 / AV	
7206.525	49.6	74.0 / PK	
7206.525	38.8	54.0 / AV	
Mode: 2440 MHz TX		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
4879.471	47.0	74.0 / PK	
4879.471	37.6	54.0 / AV	
7319.198	48.6	74.0 / PK	
7319.198	37.8	54.0 / AV	
Mode: 2440 MHz TX		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
4880.474	52.2	74.0 / PK	
4879.471	44.4	54.0 / AV	
7319.310	50.8	74.0 / PK	
7319.310	41.1	54.0 / AV	

Mode: 2480MHz TX		
Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2483.500	37.5	74.0 / PK
2483.500	24.5	54.0 / AV
4959.464	46.4	74.0 / PK
4959.464	32.2	54.0 / AV
7438.477	37.5	74.0 / PK
7438.477	24.5	54.0 / AV

Mode: 2480 MHz TX		
Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2483.500	57.4	74.0 / PK
2483.500	38.3	54.0 / AV
4959.471	50.1	74.0 / PK
4959.471	41.8	54.0 / AV
7439.070	47.5	74.0 / PK
7439.070	34.7	54.0 / AV