

Prüfbericht - Nr.: 14029350 001
Test Report No.:
Seite 1 von 14
Page 1 of 14

Auftraggeber: **Remotec Technology Ltd.**
Client:
Room 2907 – 2908
Skyline Tower
39 Wang Kwong Road
Kowloon Bay, Kowloon, Hong Kong

Gegenstand der Prüfung: **Zwave Thermostat**
Test Item:

Bezeichnung: **BW8030US, BW8031US,** **BW8032US, BW8033US** **Serien-Nr.:** **Engineering sample**
Identification: **Serial No.:**

Wareneingangs-Nr.: **00120303003-002** **Eingangsdatum:** **03.03.2012**
Receipt No.: **Date of Receipt:**

Zustand des Prüfgegenstandes bei Anlieferung: **Test sample(s) is/are not damaged and suitable for testing.**
Condition of test item at delivery:

Prüfort: **TÜV Rheinland Hong Kong Ltd.**
Testing Location: **8/F., First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong**
Hong Kong Productivity Council
HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong

Prüfgrundlage: **FCC Part 15, Subpart C**
Test Specification:

Prüfergebnis: **Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n).**
Test Result: **The test item passed the test specification(s).**

Prüflaboratorium: **TÜV Rheinland Hong Kong Ltd.**
Testing Laboratory: **8-10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong**

geprüft / tested by: **kontrolliert / reviewed by:**

05.06.2012 **Joey Leung**
 Test Engineer



05.06.2012 **Sharon Li**
 Section Manager



Datum Name/Stellung
Date Name/Position

Unterschrift
Signature

Datum Name/Stellung
Date Name/Position

Unterschrift
Signature

Sonstiges / Other Aspects:
FCC ID: M7N-BW8030US

Abkürzungen: **P(pass)** = **entspricht Prüfgrundlage**
F(fail) = **entspricht nicht Prüfgrundlage**
N/A = **nicht anwendbar**
N/T = **nicht getestet**

Abbreviations: **P(pass)** = **passed**
F(fail) = **failed**
N/A = **not applicable**
N/T = **not tested**

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicate in extracts. This test report does not entitle to carry any safety mark on this or similar products.

Test Summary

Conducted Emission

Result: Pass

20dB bandwidth

Result: Pass

Radiated Emission of Carrier Frequency

Result: Pass

Spurious Radiated Emissions

Result: Pass

Contents

General Remarks	4
List of Test and Measurement Instruments.....	5
General Product Information	6
Product Function and Intended Use.....	6
Ratings and System Details.....	6
Independent Operation Modes.....	7
Submitted Documents	7
Related Submittal(s) Grants	7
Test Set-up and Operation Mode.....	8
Principle of Configuration Selection	8
Test Operation and Test Software.....	8
Special Accessories and Auxiliary Equipment.....	8
Countermeasures to achieve EMC Compliance	8
Test Methodology	9
Radiated Emission.....	9
Field Strength Calculation	9
Test Results	10
Conducted Emission Section 15.207.....	10
20dB Bandwidth Section 15.215(c).....	11
Radiated Emission of Carrier Frequency Section 15.249(a).....	12
Spurious Radiated Emissions Section 15.249(a, c, d, e)	13
Appendix 1: Test Results	
Appendix 2: Test Setup	
Appendix 3: EUT External Photo	
Appendix 4: EUT Internal Photo	
Appendix 5: Block Diagram, FCCID Label, Schematics and User manual.	

General Remarks

Nil.

List of Test and Measurement Instruments

Hong Kong Productivity Council (Registration number: 90656)

Equipment	Manufacturer	Type	S/N	Due Date
Semi-anechoic Chamber	Frankonia	Nil	Nil	25-May-13
Test Receiver	R & S	ESU40	100190	26-May-13
Bi-conical Antenna	R & S	HK116	100241	05-May-13
Log Periodic Antenna	R & S	HL223	841516/020	06-May-13
Coaxial cable 50ohm	Rosenberger	RTK081-05S-05S-10m	LA2-001-10M / 001	15-Nov-13
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	3950M00241	03-Oct-13
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	28-Oct-13
Horn Antenna	EMCO	3115	9002-3351	11-May-13
Active Loop Antenna	EMCO	6502	9107-2651	19-Apr-13
FSP 30 Spectrum Analyser	R & S	FSP 30	100007	16-Sep-12
RF Voltage Probe	Schwarzbeck	TK9416	None	10-Feb-13
LISN	R&S	ESH3-Z5	849876/026	06-Jan-13
Double Shield Cable	Radiall	RG142	Nil	23-Aug-12
Pulse Limiter	R&S	ESH3-Z2	Nil	03-Jun-13

General Product Information

Product Function and Intended Use

The equipment under test (EUT) is a remote control of home automation system. It is able to control the wireless enabled equipment at the home. It uses 908.4MHz as a communication channel. There is only one frequency channel in this product.

FCC ID: M7N-BW8030US

Model	Product description
BW8030US, BW8031US, BW8032US, BW8033US	Zwave Thermostat

The 4 models listed in the above table are identical in construction including schematics, PCB layouts and electronic components except a change in Cosmetic and Mechanical dimension are same.

Model BW8030US was selected as a representative for testing.

Ratings and System Details

	Transmitter
Operating Frequencies	: 908.4MHz
Number of channels	: 1
Type of antenna	: Integral antenna
Power supply	: 6.0VDC, 4 x AA size batteries; or 24VAC
Ports	: Yes

Independent Operation Modes

The basic operation modes are:

- Control of home electrical product
- Others, please refer to user manual for further details

Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- Bill(s) of material
- User manual
- FCC ID label

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- There is a multi-function button to exercise the device into different modulation frequencies.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- Testing board provided by the manufacturer
- AC/AC Power transformer
Model number: DE-30-24W
Input: 120VAC 60Hz 40VA
Output: 24VAC 30VA max.

Countermeasures to achieve EMC Compliance

- none

Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

System Factor = CF + FA - PA.

Where FS = Peak Value of Field Strength in dBuV/m at 3 meters.

R = Peak Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Average value of FS = FS - Average factor.

Average Factor = $20 \log \text{duty cycle}$.

Test Results

Conducted Emission

Section 15.207

RESULT:

Pass

Test Specification : FCC Part 15 Section 15.207
 Detector Function : Quasi-Peak and Average
 Supply Voltage : 120VAC 60Hz

Live measurement						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dB μ V	Average dB μ V	Limit QP (dB μ V)	Limit AV (dB μ V)	Verdict
0,15 – 0,5	No peak found	---	---	66 – 56*	56 – 46*	Pass
> 0,5 - 5	No peak found	---	---	56	46	Pass
> 5 - 30	No peak found	---	---	60	50	Pass
Neutral measurement						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dB μ V	Average dB μ V	Limit QP (dB μ V)	Limit AV (dB μ V)	Verdict
0,15 – 0,5	No peak found	---	---	66 – 56*	56 – 46*	Pass
> 0,5 - 5	No peak found	---	---	56	46	Pass
> 5 - 30	No peak found	---	---	60	50	Pass

*Decreases with the logarithm of the frequency.

For test results, please refer to Appendix 1.

20dB Bandwidth**Section 15.215(c)****RESULT:****Pass**

Test Specification : FCC Part 15 Section 15.215(c)
Detector Function : Peak
Measurement BW : 100kHz
Supply Voltage : 6.0V DC from batteries
Operating band : 908MHz

Frequency (MHz)	20dB Bandwidth (MHz)	Frequency at 20dB BW closest to Band Edge (MHz)	Delta to Band Edge (MHz)
908.400	0.412	908.248	-6.248

For test results, please refer to Appendix 1.

Limit	Section 15.215(c)
Frequency band (MHz)	
902 – 928	

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Radiated Emission of Carrier Frequency**Section 15.249(a)****RESULT:****Pass**

Test Specification : FCC Part 15 Section 15.249(a)
Test Method : ANSI 63.4-2003
Measurement Location : Semi Anechoic Chamber
Measurement Distance : 3m
Detector Function : Quasi-Peak
Measurement BW : 120kHz
Supply Voltage : 6.0V DC from batteries

Polarization: Vertical

Frequency (MHz)	Field strength at 3m (dB μ V/m)	Limit (dB μ V/m)	Delta to Limit (dB)
908.436	85.3	94.0	-8.7

Polarization: Horizontal

Frequency (MHz)	Field strength at 3m (dB μ V/m)	Limit (dB μ V/m)	Delta to Limit (dB)
908.398	83.1	94.0	-10.9

Limit**Section 15.249(a)**

Frequency band (MHz)	Peak Emission	
	(μ V/m)	(dB μ V/m)
902 – 928	50,000	94.0

As shown in Section 15.35(b), for frequencies above 1000 MHz, the above field strength limits of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

Spurious Radiated Emissions

Section 15.249(a, c, d, e)

RESULT:

Pass

Test Specification	:	FCC Part 15 Section 15.249(a, c, d and e)
Test Method	:	ANSI 63.4-2003
Measurement Location	:	Semi Anechoic Chamber
Measurement Distance	:	3m
Detector Function	:	<1000MHz, Quasi-Peak >=1000MHz, Peak and Average
Measurement BW	:	<1000MHz, 120kHz >=1000MHz, 1MHz
Supply Voltage	:	6.0V DC from batteries

Polarization: Vertical

Frequency (MHz)	Field strength at 3m (dB μ V/m)	Detector (PK / AV)	Limit at 3m (dB μ V/m)	Delta to Limit (dB)
1817.180	49.7	PK	74.0	-24.3
	47.1	AV	54.0	-6.9

Polarization: Horizontal

Frequency (MHz)	Field strength at 3m (dB μ V/m)	Detector (PK / AV)	Limit at 3m (dB μ V/m)	Delta to Limit (dB)
1817.270	44.4	PK	74.0	-29.6
	38.8	AV	54.0	-15.2

Remark: (1) '*' indicates the frequency of the emissions fall into the restricted band as defined in Section 15.205(a). They comply with the radiated emission limits specified in Section 15.209.
 (2) Emissions radiated outside the specified frequency bands, except for harmonics, were attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation
 (3) From the lowest oscillator frequency 8MHz to 30MHz, there is no spurious emission found.

Limit	Section 15.249(a)		
Fundamental Frequency (MHz)	Field strength (AV) (µV/m)	Field strength (AV) (dBµV/m)	Measurement distance (m)
902-928 MHz	500	20*log(500) = 53.98	3

The radiated spurious emission measurement results were well below the limit as stated in 15.209 and 15.205.

Limit	Section 15.249(d)
Emissions radiated outside of the specified frequency bands as listed in 15.249(a), except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.	

Limit	Section 15.209
Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.	

Limit for Radiated Emission under Section 15.209:

Frequency (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
30-88	100	20*log(100) = 40.00	3
88-216	150	20*log(150) = 43.52	3
216-960	200	20*log(200) = 46.02	3
960-2500	500	20*log(500) = 53.98	3

The emission limits shown in the above table below 1000MHz are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing average and peak detectors.