

FCC 47 CFR PART 15 SUBPART C AND ANSI C63.10:2013

TEST REPORT

For

Computer

Model: MIT-W101;MIT-W101XXXXXXXXXXXXXX
(where "X" may be any alphanumeric character , “-” or blank)

Trade Name: ADVANTECH

Issued for

Advantech Co. Ltd.

**No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114, Taiwan,
R.O.C.**

Issued by

**Compliance Certification Services Inc.
Hsinchu Lab.**

**No.989-1, Wenshan Rd., Shangshan Village,
Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)**

**TEL: +886-3-5921698
FAX: +886-3-5921108**

**<http://www.ccsrf.com>
E-Mail : service@ccsrf.com**

Issued Date: December 03, 2015



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	11/23/2015	Initial Issue	All Page 106	Michelle Chiu
01	12/03/2015	Added one adapter	P.5-6, P.86-87, All Page 108	Michelle Chiu

TABLE OF CONTENTS

TITLE	PAGE NO.
1. TEST REPORT CERTIFICATION	4
2. EUT DESCRIPTION	5
3. DESCRIPTION OF TEST MODES	6
4. TEST METHODOLOGY	8
5. FACILITIES AND ACCREDITATION	8
5.1 FACILITIES	8
5.2 ACCREDITATIONS.....	8
5.3 MEASUREMENT UNCERTAINTY	9
6. SETUP OF EQUIPMENT UNDER TEST.....	10
7. FCC PART 15.247 REQUIREMENTS.....	11
7.1 20dB BANDWIDTH FOR HOPPING	11
7.2 MAXIMUM PEAK OUTPUT POWER	17
7.3 AVERAGE POWER	19
7.4 HOPPING CHANNEL SEPARATION.....	21
7.5 NUMBER OF HOPPING FREQUENCY USED	27
7.6 DWELL TIME ON EACH CHANNEL	30
7.7 CONDUCTED SPURIOUS EMISSION	45
7.8 RADIATED EMISSION.....	53
7.9 CONDUCTED EMISSION	73
APPENDIX SETUP PHOTOS	78
EXTERNAL PHOTO.....	82
INTERNAL PHOTO	89

1. TEST REPORT CERTIFICATION

Applicant : Advantech Co. Ltd.
Address : No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114, Taiwan, R.O.C.
Equipment Under Test : Computer
Model : MIT-W101; MIT-W101XXXXXXXXXXXXXX (where "X" may be any alphanumeric character, "-" or blank)
Trade Name : ADVANTECH
Tested Date : July 23 ~ November 09, 2015

APPLICABLE STANDARD	
Standard	Test Result
FCC Part 15 Subpart C AND ANSI C63.10:2013	PASS


WE HEREBY CERTIFY THAT: The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Sb. Lu
Sr. Engineer

Reviewed by:



Gundam Lin
Sr. Engineer

2. EUT DESCRIPTION

Product Name	Computer
Model Number	MIT-W101; MIT-W101XXXXXXXXXXXXXX (where "X" may be any alphanumeric character , "-" or blank)
Identify Number	T150723L02
Received Date	July 23, 2015
Frequency Range	2402MHz to 2480MHz f = 2402 + nMHz, n = 0,78
Transmit Power	5.02 dBm (0.0032W)
Channel Spacing	1MHz
Channel Number	79 Channels
Transmit Data Rate	GFSK (1Mbps), $\pi/4$ -DQPSK (2Mbps), 8-DPSK (3Mbps)
Type of Modulation	Frequency Hopping Spread Spectrum
Antenna Type	PIFA Antenna x 1, Antenna 1(Main) / Chain 0, Antenna Gain : 3.96 dBi
Power Rating	11.1Vdc, 2860mAh, 31.75WH (For Battery) 19Vdc (For Charging)
Test Voltage	120Vac, 60Hz
AC Power Cord Type	Non-shielded cable, 1.8m (Detachable) (For Power Adapter 1, 2)
DC Power Cable Type	Non-shielded cable, 1.5m (Non-detachable), with a ferrite core (For Power Adapter 1, 2)
I/O Port	Micro HDMI Port x 1, USB Port x 2, Audio Port x 1, Power Port x 1, Docking Connector x 1, Connected pin for expansion module x 1

The difference of the series model :

Model Number	Difference
MIT-W101	1. For marketing purpose only. 2. where "X" may be any alphanumeric character , " - " or blank
MIT-W101XXXXXXXXXXXXXX	

Power Adapter:

No.	Manufacturer	Model No.	Power Input	Power Output
1	FSP	FSP065-REBN2	100-240Vac, 1.5A, 50-60Hz	19Vdc, 3.42A
2	SINPRO	HPU63A-107	100-240Vac, 1.62-0.72A, 47-63Hz	18Vdc, 3.5A max

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. For more details, please refer to the User's manual of the EUT.
3. The model MIT-W101 was considered the main model for testing.
4. This submittal(s) (test report) is intended for FCC ID: M82-MITW101 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.

3. DESCRIPTION OF TEST MODES

The EUT (MIT-W101) had been tested under operating condition.

For Bluetooth (1TX / 1RX) : Ant 1 (Chain 0) transmit/receive.

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	2402
Middle	2441
High	2480

Conducted Emission / Radiated Emission Test (Below 1 GHz)

1. The following test modes were scanned during the preliminary test:

No.	Pre-Test Mode
1	TX Mode / Power Adapter 1
2	TX Mode / Power Adapter 2

2. After the preliminary scan, the following test mode was found to produce the highest emission level.

Final Test Mode		
Emission	Radiated Emission	Mode 1
	Conducted Emission	Mode 1

Remark : Then, the above highest emission mode of the configuration of the EUT and cable was chosen for all final test items.

Radiated Emission Test (Above 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

Tested Channel	Modulation Technology	Modulation Type	Packet Type
Low, Mid, High	FHSS	GFSK	DH5
Low, Mid, High	FHSS	8-DPSK	3-DH5

Bandedge Measurement :

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

Tested Channel	Modulation Technology	Modulation Type	Packet Type
Low, High	FHSS	GFSK	DH5
Low, High	FHSS	8-DPSK	3-DH5

Antenna Port Conducted Measurement :

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

Tested Channel	Modulation Technology	Modulation Type	Packet Type
Low, Mid, High	FHSS	GFSK	DH5
Low, Mid, High	FHSS	8-DPSK	3-DH5

Remark : The field strength of spurious emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X, Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.

4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2013 and FCC CFR 47, 15.207, 15.209 and 15.247.

5. FACILITIES AND ACCREDITATION

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
No.989-1, Wenshan Rd., Shangshan Village,
Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)

The sites are constructed in conformance with the requirements of ANSI C63.10:2013 and CISPR 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4, CISPR 16-1-5.

5.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

Taiwan TAF

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	INDUSTRY CANADA
Japan	VCCI
Taiwan	BSMI
USA	FCC MRA

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

Remark: FCC Designation Number TW1027.

5.3 MEASUREMENT UNCERTAINTY

The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4-2.

PARAMETER	UNCERTAINTY
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 30 to 1000 MHz	+/- 3.97
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 1 to 18GHz	+/- 3.58
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 18 to 26 GHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 26 to 40 GHz	+/- 3.81
Conducted Emission (Mains Terminals), 9kHz to 30MHz	+/- 2.48

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than U_{CISPR} which is 3.6dB and 5.2dB respectively. CCS values (called U_{Lab} in CISPR 16-4-2) is less than U_{CISPR} as shown in the table above. Therefore, MU need not be considered for compliance.

6. SETUP OF EQUIPMENT UNDER TEST

SUPPORT EQUIPMENT

No.	Product	Manufacturer	Model No.	Serial No.
1	Notebook PC	HP	ProBook 4421s	CNF03242PJ

No.	Signal Cable Description
1	Non-shielded RJ-45 cable, 12m x 1

SETUP DIAGRAM FOR TESTS

EUT & peripherals setup diagram is shown in appendix setup photos.

EUT OPERATING CONDITION

1. EUT & peripherals setup diagram is shown in appendix setup photos.

2. TX Mode:

⇒ **Power control**

TX mode (GFSK)

Frequency: 2402, 2441, 2480

Power set: 7, 7, 7

Data Rate: 15/339 (DH5)

TX mode (8-DPSK)

Frequency: 2402, 2441, 2480

Power set: 7, 7, 7

Data Rate: 31/1021 (3-DH5)

3. All of the functions are under run.

4. Start test.

7. FCC PART 15.247 REQUIREMENTS

7.1 20dB BANDWIDTH FOR HOPPING

LIMITS

Limit : N/A

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

1. The 20dB band width was measured with a spectrum analyzer connected to RF antenna connector(conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer. Display Line and Marker Delta functions, the 20dB band width of the emission was determined.
2. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel.
3. RBW \geq 1% of the 20 dB bandwidth.
4. VBW \geq RBW.
5. Sweep = auto.

TEST RESULTS

Modulation Type: GFSK, CFG PKT Packet Type: 15 Packet Size: 339 (DH5)

Channel	Channel Frequency (MHz)	20dB Bandwidth (MHz)	Result
Low	2402	0.9293	N/A
Middle	2441	0.9290	N/A
High	2480	0.9295	N/A

Modulation Type: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021 (3-DH5)

Channel	Channel Frequency (MHz)	20dB Bandwidth (MHz)	Result
Low	2402	1.2937	N/A
Middle	2441	1.2887	N/A
High	2480	1.2881	N/A

20dB BANDWIDTH







7.2 MAXIMUM PEAK OUTPUT POWER

LIMITS

§15.247(b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/11/2015
Power Sensor	Anritsu	MA2411B	1126148	12/11/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to the power meter. The power meter is set to the peak power detection.

TEST RESULTS

Modulation Type: GFSK ,CFG PKT Packet Type: 15 Packet Size: 339 (DH5)

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Result
		(dBm)	(W)	(dBm)	(W)	
Low	2402	2.00	0.0016	20.97	0.125	PASS
Middle	2441	2.12	0.0016	20.97	0.125	PASS
High	2480	2.10	0.0016	20.97	0.125	PASS

Remark: The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

Modulation Type: 8-DPSK ,CFG PKT Packet Type: 31 Packet Size: 1021 (3-DH5)

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Result
		(dBm)	(W)	(dBm)	(W)	
Low	2402	4.90	0.0031	20.97	0.125	PASS
Middle	2441	5.02	0.0032	20.97	0.125	PASS
High	2480	5.00	0.0032	20.97	0.125	PASS

Remark: The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

7.3 AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/11/2015
Power Sensor	Anritsu	MA2411B	1126148	12/11/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to the power meter. The power meter is set to the average power detection.

TEST RESULTS

Modulation Type: GFSK ,CFG PKT Packet Type: 15 Packet Size: 339 (DH5)

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	1.77
Middle	2441	1.88
High	2480	1.85

Remark: The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

Modulation Type: 8-DPSK ,CFG PKT Packet Type: 31 Packet Size: 1021 (3-DH5)

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	2.01
Middle	2441	2.14
High	2480	2.10

Remark: The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

7.4 HOPPING CHANNEL SEPARATION

LIMITS

§15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of adjacent channels.
4. Measure the frequency difference of these two adjacent channels by spectrum analyzer MARK function. And then plot the result on spectrum analyzer screen.
5. Span = wide enough to capture the peaks of two adjacent channels.
6. Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span.
7. Video (or Average) Bandwidth (VBW) \geq RBW.
8. Sweep = auto.
9. Repeat above procedures until all frequencies measured were complete.

TEST RESULTS


Refer to section 7.1, 20dB bandwidth measurement, the measured channel separation should be greater than two-third of 20dB bandwidth or Minimum bandwidth.


Modulation Type: GFSK, CFG PKT Packet Type: 15 Packet Size: 339 (DH5)


Channel	Channel Frequency (MHz)	Adjacent Hopping Channel Separation (kHz)	Two –third of 20dB bandwidth (kHz)	Minimum Bandwidth	Result
Low	2402	1000	619.50	25 kHz	PASS
Middle	2441	1000	619.30	25 kHz	PASS
High	2480	1000	619.65	25 kHz	PASS


Modulation Type: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021 (3-DH5)

Channel	Channel Frequency (MHz)	Adjacent Hopping Channel Separation (kHz)	Two –third of 20dB bandwidth (kHz)	Minimum Bandwidth	Result
Low	2402	1000	862.45	25 kHz	PASS
Middle	2441	1000	859.10	25 kHz	PASS
High	2480	1000	858.70	25 kHz	PASS

HOPPING CHANNEL SEPARATION







7.5 NUMBER OF HOPPING FREQUENCY USED

LIMITS

§15.247(a)(1)(iii) For frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE


1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set the spectrum analyzer on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the spectrum analyzer on View mode and then plot the result on spectrum analyzer screen.
5. Span = the frequency band of operation.
6. RBW \geq 1% of the span.
7. VBW \geq RBW.
8. Sweep = auto.
9. Repeat above procedures until all frequencies measured were complete.

TEST RESULTS

Refer to the attached plot.

There are 79 hopping frequencies in a hopping sequence.

NUMBER OF HOPPING FREQUENCY USED



7.6 DWELL TIME ON EACH CHANNEL

LIMITS

§15.247(a)(1)(iii) For frequency hopping system operating in the 2400-2483.5MHz band, the average time of occupancy on any frequency shall not be greater than 0.4 second within a 31.6 second period.

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP



TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of spectrum analyzer on any frequency to be measured and set spectrum analyzer to zero span mode.
4. RBW = 1 MHz.
5. VBW \geq RBW.
6. Sweep = as necessary to capture the entire dwell time per hopping channel.
7. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
8. Repeat above procedures until all frequencies measured were complete.
9. The EUT has 3 type of payload, DH1, DH3, DH5. The hopping rate is 1600 per second. The longer the payload is, the slower the hopping rate is.

TEST RESULTS

Time of occupancy on the TX channel in 31.6sec = time domain slot length × hop rate ÷ number of hop per channel × 31.6

Refer to the attached graph.

The hopping rates of Bluetooth devices change with different types of payload. The longer the payload is, the slower the hopping rate. The hopping rate scenario is defined in Bluetooth core specification.

Modulation Type: GFSK

Channel	Channel Frequency (MHz)	Packet type	Dwell time (ms)	Time of occupancy on the TX channel in 31.6sec (ms)	Limit for Time of occupancy on the TX channel in 31.6sec (ms)	Results
Low	2402	DH1	0.392	125.44	400	PASS
	2402	DH3	1.650	264.00	400	PASS
	2402	DH5	2.890	308.27	400	PASS
Middle	2441	DH1	0.392	125.44	400	PASS
	2441	DH3	1.650	264.00	400	PASS
	2441	DH5	2.890	308.27	400	PASS
High	2480	DH1	0.392	125.44	400	PASS
	2480	DH3	1.650	264.00	400	PASS
	2480	DH5	2.890	308.27	400	PASS

Remark:

Ch Low

$DH1 : 0.392 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 125.44 \text{ (ms)}$

$DH3 : 1.650 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 264.00 \text{ (ms)}$

$DH5 : 2.890 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 308.27 \text{ (ms)}$

Ch Middle

$DH1 : 0.392 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 125.44 \text{ (ms)}$

$DH3 : 1.650 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 264.00 \text{ (ms)}$

$DH5 : 2.890 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 308.27 \text{ (ms)}$

Ch High

$DH1 : 0.392 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 125.44 \text{ (ms)}$

$DH3 : 1.650 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 264.00 \text{ (ms)}$

$DH5 : 2.890 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 308.27 \text{ (ms)}$

Modulation Type: 8-DPSK

Channel	Channel Frequency (MHz)	Packet type	Dwell time (ms)	Time of occupancy on the TX channel in 31.6sec (ms)	Limit for Time of occupancy on the TX channel in 31.6sec (ms)	Results
Low	2402	DH1	0.392	125.44	400	PASS
	2402	DH3	1.650	264.00	400	PASS
	2402	DH5	2.890	308.27	400	PASS
Middle	2441	DH1	0.392	125.44	400	PASS
	2441	DH3	1.650	264.00	400	PASS
	2441	DH5	2.890	308.27	400	PASS
High	2480	DH1	0.392	125.44	400	PASS
	2480	DH3	1.650	264.00	400	PASS
	2480	DH5	2.890	308.27	400	PASS

Remark:

Ch Low

 $DH1 : 0.392 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 125.44 \text{ (ms)}$ $DH3 : 1.650 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 264.00 \text{ (ms)}$ $DH5 : 2.890 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 308.27 \text{ (ms)}$


Ch Middle


 $DH1 : 0.392 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 125.44 \text{ (ms)}$ $DH3 : 1.650 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 264.00 \text{ (ms)}$ $DH5 : 2.890 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 308.27 \text{ (ms)}$


Ch High


 $DH1 : 0.392 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 125.44 \text{ (ms)}$ $DH3 : 1.650 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 264.00 \text{ (ms)}$ $DH5 : 2.890 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 308.27 \text{ (ms)}$


DWELL TIME ON EACH PAYLOAD

















DH1 CH Low (8-DPSK)**DH3 CH Low (8-DPSK)**



DH1 CH Middle (8-DPSK)**DH3 CH Middle (8-DPSK)**







7.7 CONDUCTED SPURIOUS EMISSION

LIMITS

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the and that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.


TEST SETUP




TEST PROCEDURE



The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


TEST RESULTS**OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT**





CH Low (2.38GHz ~ 2.5GHz / 8-DPSK)**CH Low (30MHz ~ 26.5GHz / 8-DPSK)**





CONDUCTED MEASUREMENT HOPPING BAND EDGES

7.8 RADIATED EMISSION

LIMITS

(1) According to § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

Remark:

1. ¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

2. ² Above 38.6

(2) According to § 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

(3) According to § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

Remark: **Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

(4) According to § 15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST EQUIPMENT**Radiated Emission / 966Chamber_B**


Name of Equipment	Manufacture	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY46180323	04/14/2016
EMI Test Receiver	Rohde & Schwarz	ESCI	100221	04/22/2016
Bi-log Antenna	TESEQ	CBL 6112D	35403	08/04/2016
Double-Ridged Waveguide Horn	ETS-LINDGREN	3117	00078733	12/02/2015
Horn Antenna	COM-POWER	AH-840	03077	12/17/2015
Pre-Amplifier	Agilent	8447D	2944A10052	07/14/2016
Pre-Amplifier	Agilent	8449B	3008A01916	07/14/2016
LOOP Antenna	COM-POWER	AL-130	121060	05/24/2016

Remark: Each piece of equipment is scheduled for calibration once a year.


TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission below 1GHz.


9kHz ~ 30MHz



30MHz ~ 1GHz



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



TEST PROCEDURE

1. The EUT was placed on the top of a rotating table 0.8 and 1.5 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
2. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Remark :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

TEST RESULTS**Below 1 GHz (9kHz ~ 30MHz)**

No emission found between lowest internal used/generated frequency to 30MHz.

Below 1 GHz (30MHz ~ 1GHz)

Product Name	Computer	Test By	Rex Chiu
Test Model	MIT-W101	Test Date	2015/09/03
Test Mode	Mode 1	Temp. & Humidity	25°C, 50%

966 Chamber_B at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
192.96	45.24	-16.19	29.05	43.50	-14.45	139	100	Peak
256.98	48.17	-12.04	36.13	46.00	-9.87	8	100	Peak
323.91	48.03	-10.90	37.13	46.00	-8.87	299	100	Peak
385.99	47.35	-9.42	37.93	46.00	-8.07	1	100	Peak
792.42	42.48	-4.32	38.16	46.00	-7.84	301	100	Peak
838.98	41.98	-3.66	38.32	46.00	-7.68	75	100	Peak
978.66	41.88	-2.06	39.82	54.00	-14.18	59	100	Peak

966 Chamber_B at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
40.67	46.85	-14.27	32.58	40.00	-7.42	196	100	Peak
128.94	43.73	-14.47	29.26	43.50	-14.24	187	100	Peak
256.98	43.39	-12.04	31.35	46.00	-14.65	152	100	Peak
290.93	44.47	-11.75	32.72	46.00	-13.28	33	100	Peak
323.91	42.79	-10.90	31.89	46.00	-14.11	260	100	Peak
792.42	34.08	-4.32	29.76	46.00	-16.24	246	100	Peak
978.66	38.41	-2.06	36.35	54.00	-17.65	348	100	Peak

Remark:

1. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit.
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – PreAmp.Gain (dB)
3. Result (dBuV/m) = Reading (dBuV) + Correction Factor (dB/m)
4. Margin (dB) = Remark result (dBuV/m) - Quasi-peak limit (dBuV/m)

Above 1 GHz

Product Name	Computer	Test By	Waternil Guan
Test Model	MIT-W101	Test Date	2015/08/28
Test Mode	GFSK TX / CH Low	Temp. & Humidity	25°C, 50%

966 Chamber_B at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
=====								
2322.00	47.16	2.57	49.73	74.00	-24.27	146	100	Peak
2482.00	47.59	2.97	50.56	74.00	-23.44	127	100	Peak
2500.00	45.95	3.01	48.96	74.00	-25.04	40	100	Peak
3435.00	40.06	4.90	44.96	74.00	-29.04	306	100	Peak
4800.00	38.50	7.98	46.48	74.00	-27.52	96	200	Peak
7170.00	37.63	11.92	49.55	74.00	-24.45	86	200	Peak

966 Chamber_B at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
=====								
1004.00	48.92	-3.39	45.53	74.00	-28.47	138	100	Peak
2322.00	43.83	2.57	46.40	74.00	-27.60	152	200	Peak
2500.00	46.08	3.01	49.09	74.00	-24.91	326	100	Peak
3810.00	41.41	5.61	47.02	74.00	-26.98	340	100	Peak
4800.00	38.30	7.98	46.28	74.00	-27.72	0	100	Peak
9630.00	36.48	14.12	50.60	74.00	-23.40	90	200	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)

Product Name	Computer	Test By	Waternal Guan
Test Model	MIT-W101	Test Date	2015/08/28
Test Mode	GFSK TX / CH Middle	Temp. & Humidity	25°C, 50%

966 Chamber_B at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
2360.00	48.48	2.67	51.15	74.00	-22.85	170	100	Peak
2500.00	45.56	3.01	48.57	74.00	-25.43	83	100	Peak
2522.00	48.84	3.05	51.89	74.00	-22.11	130	200	Peak
3990.00	40.31	5.95	46.26	74.00	-27.74	254	200	Peak
4875.00	38.29	8.04	46.33	74.00	-27.67	341	100	Peak
5475.00	38.34	9.99	48.33	74.00	-25.67	153	200	Peak

966 Chamber_B at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
2360.00	44.72	2.67	47.39	74.00	-26.61	126	200	Peak
2500.00	46.43	3.01	49.44	74.00	-24.56	348	100	Peak
2522.00	45.92	3.05	48.97	74.00	-25.03	97	100	Peak
3180.00	41.99	4.39	46.38	74.00	-27.62	231	100	Peak
4875.00	37.77	8.04	45.81	74.00	-28.19	16	200	Peak
6360.00	37.85	11.62	49.47	74.00	-24.53	349	200	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)

Product Name	Computer	Test By	Waternal Guan
Test Model	MIT-W101	Test Date	2015/08/28
Test Mode	GFSK TX / CH High	Temp. & Humidity	25°C, 50%

966 Chamber_B at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
2400.00	45.73	2.76	48.49	74.00	-25.51	107	100	Peak
2500.00	46.82	3.01	49.83	74.00	-24.17	291	100	Peak
2560.00	45.46	3.13	48.59	74.00	-25.41	120	200	Peak
4455.00	39.93	7.58	47.51	74.00	-26.49	154	100	Peak
4920.00	37.95	8.08	46.03	74.00	-27.97	71	100	Peak
6495.00	38.35	11.65	50.00	74.00	-24.00	212	200	Peak

966 Chamber_B at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
2400.00	43.41	2.76	46.17	74.00	-27.83	188	100	Peak
2500.00	46.76	3.01	49.77	74.00	-24.23	343	100	Peak
2560.00	42.52	3.13	45.65	74.00	-28.35	35	200	Peak
3180.00	41.36	4.39	45.75	74.00	-28.25	241	100	Peak
4920.00	37.94	8.08	46.02	74.00	-27.98	121	200	Peak
6390.00	37.47	11.63	49.10	74.00	-24.90	266	100	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)

Product Name	Computer	Test By	Waternal Guan
Test Model	MIT-W101	Test Date	2015/08/28
Test Mode	8-DPSK TX / CH Low	Temp. & Humidity	25°C, 50%

966 Chamber_B at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2322.00	46.45	2.57	49.02	74.00	-24.98	114	100	Peak
2482.00	48.61	2.97	51.58	74.00	-22.42	104	100	Peak
2500.00	46.96	3.01	49.97	74.00	-24.03	48	200	Peak
3180.00	41.92	4.39	46.31	74.00	-27.69	158	100	Peak
4815.00	37.56	7.99	45.55	74.00	-28.45	28	200	Peak
6555.00	37.23	11.72	48.95	74.00	-25.05	48	200	Peak

966 Chamber_B at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2322.00	45.22	2.57	47.79	74.00	-26.21	147	100	Peak
2500.00	46.55	3.01	49.56	74.00	-24.44	336	100	Peak
2692.00	43.12	3.40	46.52	74.00	-27.48	221	100	Peak
3180.00	42.13	4.39	46.52	74.00	-27.48	60	100	Peak
3945.00	40.07	5.87	45.94	74.00	-28.06	60	100	Peak
5460.00	38.10	9.93	48.03	74.00	-25.97	81	200	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)

Product Name	Computer	Test By	Waternal Guan
Test Model	MIT-W101	Test Date	2015/08/28
Test Mode	8-DPSK TX / CH Middle	Temp. & Humidity	25°C, 50%

966 Chamber_B at 3Meter / Horizontal

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2362.00	47.45	2.67	50.12	74.00	-23.88	139	100	Peak
2500.00	44.53	3.01	47.54	74.00	-26.46	50	200	Peak
2522.00	47.89	3.05	50.94	74.00	-23.06	132	100	Peak
4305.00	39.10	7.05	46.15	74.00	-27.85	186	200	Peak
5745.00	37.59	10.81	48.40	74.00	-25.60	313	200	Peak
9615.00	37.42	14.10	51.52	74.00	-22.48	107	100	Peak

966 Chamber_B at 3Meter / Vertical

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2362.00	45.77	2.67	48.44	74.00	-25.56	144	100	Peak
2500.00	46.30	3.01	49.31	74.00	-24.69	338	100	Peak
2520.00	45.02	3.05	48.07	74.00	-25.93	48	200	Peak
3180.00	44.31	4.39	48.70	74.00	-25.30	268	100	Peak
4875.00	38.03	8.04	46.07	74.00	-27.93	0	200	Peak
7170.00	37.81	11.92	49.73	74.00	-24.27	267	200	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)

Product Name	Computer	Test By	Waternal Guan
Test Model	MIT-W101	Test Date	2015/08/28
Test Mode	8-DPSK TX / CH High	Temp. & Humidity	25°C, 50%

966 Chamber_B at 3Meter / Horizontal



Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
=====								
2400.00	45.07	2.76	47.83	74.00	-26.17	148	100	Peak
2500.00	45.57	3.01	48.58	74.00	-25.42	85	100	Peak
2560.00	46.07	3.13	49.20	74.00	-24.80	127	200	Peak
4920.00	38.75	8.08	46.83	74.00	-27.17	325	100	Peak
5790.00	38.22	10.94	49.16	74.00	-24.84	172	200	Peak
7785.00	37.73	11.89	49.62	74.00	-24.38	188	200	Peak



966 Chamber_B at 3Meter / Vertical



Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
=====								
2400.00	44.93	2.76	47.69	74.00	-26.31	194	100	Peak
2500.00	47.90	3.01	50.91	74.00	-23.09	339	100	Peak
2560.00	43.78	3.13	46.91	74.00	-27.09	74	100	Peak
3180.00	43.80	4.39	48.19	74.00	-25.81	234	100	Peak
4980.00	38.03	8.12	46.15	74.00	-27.85	91	100	Peak
6885.00	36.98	12.16	49.14	74.00	-24.86	251	200	Peak



Remark:



1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Result = Reading + Correction Factor
Margin = Result - Limit
Remark Peak = Result(PK) - Limit(PK)
Remark AVG = Result(AV) - Limit(AV)

Restricted Band Edges**Detector Mode : Peak****Polarity : Horizontal****Detector Mode : Average****Polarity : Horizontal**

Detector Mode : Peak**Polarity : Vertical****Detector Mode : Average****Polarity : Vertical**

Detector Mode : Peak**Polarity : Horizontal****Detector Mode : Average****Polarity : Horizontal**


Detector Mode : Peak**Polarity : Vertical****Detector Mode : Average****Polarity : Vertical**

Detector Mode : Peak**Polarity : Horizontal****Detector Mode : Average****Polarity : Horizontal**

Detector Mode : Peak**Polarity : Vertical****CH Low (8-DPSK)**

Data: 98

Date: 2015-08-28 Time: 22:27:57


**Trace:**

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2322.00	45.34	2.57	47.91	74.00	-26.09			Peak
2390.00	39.88	2.74	42.62	74.00	-31.38			Peak

Detector Mode : Average**Polarity : Vertical****CH Low (8-DPSK)**

Data: 97

Date: 2015-08-28 Time: 22:27:30


**Trace:**

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2321.92	36.54	2.57	39.11	54.00	-14.89			Average
2390.00	28.72	2.74	31.46	54.00	-22.54			Average

Detector Mode : Peak**Polarity : Horizontal****CH High (8-DPSK)**

Data: 102

Date: 2015-08-28 Time: 22:31:12




Trace:

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2483.50	40.80	2.97	43.77	74.00	-30.23			Peak
2500.00	46.72	3.01	49.73	74.00	-24.27			Peak

Detector Mode : Average**Polarity : Horizontal****CH High (8-DPSK)**



Data: 101

Date: 2015-08-28 Time: 22:30:45



Trace:

Freq. MHz	Reading dBuV	C.F. dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Azimuth deg	Height cm	Remark
<hr/>								
2483.50	32.03	2.97	35.00	54.00	-19.00			Average
2500.00	36.52	3.01	39.53	54.00	-14.47			Average

Detector Mode : Peak**Polarity : Vertical****Detector Mode : Average****Polarity : Vertical**

7.9 CONDUCTED EMISSION

LIMITS



§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5.00	56	46
5.00 - 30.0	60	50

TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
L.I.S.N	Schwarzbeck	NSLK 8127	8127465	08/05/2016
L.I.S.N	Schwarzbeck	NSLK 8127	8127473	03/09/2016
EMI Test Receiver	Rohde & Schwarz	ESHS 30	838550/003	10/31/2016
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100111	06/28/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

TEST SETUP

TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.10:2013.

The test procedure is performed in a 4m x 3m x 2.4m (LxWxH) shielded room.


The EUT along with its peripherals were placed on a 1.0m (W) x 1.5m (L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.

The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.

The EUT was located so that the distance between the boundary of the EUT and the closest surface of the LISN is 0.8 m. Where a mains flexible cord was provided by the manufacturer shall be 1 m long, or if in excess of 1 m, the excess cable was folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.


TEST RESULTS

Product Name	Computer	Test By	Crystal Wu
Test Model	MIT-W101	Test Date	2015/11/05
Test Mode	Mode 1	Temp. & Humidity	28.9°C, 41%

LINE**Remark:**

1. Correction Factor = Insertion loss + Cable loss
2. Result level = Reading Value + Correction factor
3. Margin value = Result level – Limit value

Product Name	Computer	Test By	Crystal Wu
Test Model	MIT-W101	Test Date	2015/11/05
Test Mode	Mode 1	Temp. & Humidity	28.9°C, 41%

NEUTRAL**Remark:**

1. Correction Factor = Insertion loss + Cable loss
2. Result level = Reading Value + Correction factor
3. Margin value = Result level – Limit value