

ANSI/IEEE Std. C95.1-2005in accordance with the requirements of
FCC Report and Order: ET Docket 93-62**FCC TEST REPORT****For****Computer****Trade Name: ADVANTECH****Model:****MIT-W101;MIT-W101XXXXXXXXXXXXXX (where "X" may be any
alphanumeric character , “-” or blank)**

Issued to

Advantech Co. Ltd.**No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114, Taiwan, R.O.C.**

Issued by

Compliance Certification Services Inc.**No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891,
Taiwan. (R.O.C.)****<http://www.ccsrf.com>
service@ccsrf.com****Issued Date: 2015/11/02**

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2015/11/02	Initial Issue	ALL	Tony Liao

Table of Contents

1	Certificate of Compliance (SAR Evaluation)	5
2	Description of Equipment Under Test	6
2.1	Summary of Highest SAR Values.....	7
3	Requirements for Compliance Testing Defined.....	8
3.1	Requirements for Compliance Testing Defined by the FCC	8
4	Dosimetric Assessment System	9
4.1	Measurement System Diagram	10
4.2	System Components.....	11
5	Evaluation Procedures.....	14
6	SAR Measurement Procedures.....	16
6.1	Normal SAR Test Procedure	16
7	Measurement Uncertainty.....	18
8	Device Under Test	19
8.1	Wireless Technologies.....	19
8.2	Maximum Tune-up Power	20
8.3	Simultaneous Transmission.....	21
9	Summary of SAR Test Exclusion Configurations	22
9.1	Standalone SAR Test Exclusion Calculations	22
9.1.1	SAR Exclusion Calculations for Wi-Fi Antenna < 50mm from the User	23
9.1.2	SAR Exclusion Calculations for Wi-Fi Antenna > 50mm from the User	24
9.1.3	SAR Required Test Configuration	25
10	Exposure Limit	26
11	Tissue Dielectric Properties.....	27
11.1	Test Liquid Confirmation.....	27
11.2	Typical Composition of Ingredients for Liquid Tissue Phantoms.....	28
11.3	Simulating Liquids Parameter Check Results	29
12	System Performance Check.....	30
12.1	System Performance Check Results	31
13	RF Output Power Measurement.....	32
13.1	Wi-Fi (2.4GHz Band).....	33
13.2	Wi-Fi (5GHz Band).....	34
13.3	Bluetooth.....	36
14	SAR Measurements Results	37
15	Simultaneous Transmission SAR Analysis.....	39
15.1	Estimated SAR for Simultaneous Transmission SAR Analysis.....	40

15.1.1 Estimated SAR for Bluetooth.....	40
15.2 Sum of the SAR for Simultaneous Transmission Analysis	41
15.2.1 Sum of the SAR for Wi-Fi & Bluetooth.....	41
15.2.2 Sum of the SAR for Wi-Fi MIMO	41
16 Equipment List & Calibration Status	42
17 Facilities	43
18 Reference	43
19 Attachments.....	44

1 Certificate of Compliance (SAR Evaluation)

Applicant Advantech Co. Ltd.
No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114,
Taiwan, R.O.C.

Equipment Under Test: Computer

Trade Name: ADVANTECH

Model Number: MIT-W101;MIT-W101XXXXXXXXXXXXXX (where "X" may be any alphanumeric character, “-” or blank)

Date of Test: October 27 ~ 29, 2015

Device Category: PORTABLE DEVICES

Exposure Category: GENERAL POPULATION/UNCONTROLLED EXPOSURE

Applicable Standards	
FCC	<ul style="list-style-type: none">IEEE 1528 2013KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04KDB 447498 D01 General RF Exposure Guidance v06KDB 616217 D04 SAR for laptop and tablets v01r02KDB 248227 D01 SAR Measurement Guidance for 802.11 Transmitters v02r02
Limit	
1.6 W/kg	
Test Result	
Pass	


The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:



Scott Hsu
Section Manager
Compliance Certification Services Inc.

Tested by:



Tony Liao
SAR Engineer
Compliance Certification Services Inc.

2 Description of Equipment Under Test

Product	Computer		
Trade Name	ADVANTECH		
Model Number	MIT-W101;MIT-W101XXXXXXXXXXXXXX (where "X" may be any alphanumeric character , “-” or blank)		
RF Module	Atheros	Model:	AR5B22
Transmitters	Wi-Fi & Bluetooth		
Modulation Technique	Bluetooth:GFSK for 1Mbps;π/4-DQPSK for 2Mbps;8DPSK for 3Mbps		
	802.11a: Orthogonal Frequency Division Multiplexing (OFDM)		
	802.11b: Direct Sequence Spread Spectrum(DSSS)		
	802.11g: Orthogonal Frequency Division Multiplexing (OFDM)		
Antenna Specification	Main	Brand name	BJTEK NAVIGATION,INC.
		Parts Number	BJHEM851101830B00A-A
		Type	PIFA
	Aux	Brand name	INVAX System Technology Corp.
		Parts Number	IVX0035-C30BLF
		Type	PIFA
Rechargeable Li-polymer Battery—alternate	Brand: Formosan United Corporation Model: X54B Rating: 2860 mAh,11.1V,3.5A		

Remark:

1. The sample selected for test was prototype that representative to production product and was provided by manufacturer

2.1 Summary of Highest SAR Values

Results for highest reported SAR values for each frequency band and mode

Technology/Band	Test configuration	Mode	Highest Reported 1g-SAR (W/kg)
Wi-Fi 2.4 GHz	Rear	802.11g	0.808
Wi-Fi 5.3 GHz(U-NII 2A)	Rear	802.11n HT40	0.886
Wi-Fi 5.5 GHz(U-NII 2C)	Edge4	802.11n HT40	0.459
Wi-Fi 5.8 GHz(U-NII 3)	Edge4	802.11n HT40	1.193

3 Requirements for Compliance Testing Defined


3.1 Requirements for Compliance Testing Defined by the FCC

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 W/kg for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992 [6].

4 Dosimetric Assessment System

These measurements were performed with the automated near-field scanning system DASY4/DASY5 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m) which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe EX3DV4-SN: 3554 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure with accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated with the procedure and found to be better than ± 0.25 dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEEE 1528 2013.

4.1 Measurement System Diagram



The DASY4 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Staubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DASY4/DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.

4.2 System Components

DASY4/DASY5 Measurement Server

	<p>The DASY4/DASY5 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE3 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY4/DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.</p> <p>The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.</p>
	<p>The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.</p>

Data Acquisition Electronics (DAE)

	<p>The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.</p>
---	--

EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements

	Construction: Symmetrical design with triangular core Calibration: Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE) Calibration: Basic Broad Band Calibration in air: 10-3000 MHz. Conversion Factors (CF) for HSL 900 and HSL 1800 CF-Calibration for other liquids and frequencies upon request. Frequency: 10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz) Directivity: ± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in HSL (rotation normal to probe axis) Dynamic Range: 10 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μW/g) Dimensions: Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1 mm Application: High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
	

SAM Phantom (V4.0)

	Construction: The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 2013, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot. Shell Thickness: 2 ± 0.2 mm Filling Volume: Approx. 25 liters Dimensions: Height: 810mm; Length: 1000mm; Width: 500mm
---	---

SAM Phantom (ELI4)

	Construction: Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY4/DASY5 and higher and is compatible with all SPEAG dosimetric probes and dipoles Shell Thickness: 2.0 ± 0.2 mm (sagging: <1%) Filling Volume: Approx. 25 liters Dimensions: Major ellipse axis: 600 mm Minor axis: 400 mm 500mm
---	--

Device Holder for SAM Twin Phantom	
	<p>Construction: In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).</p>
System Validation Kits for SAM Phantom (V4.0)	
	<p>Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.</p> <p>Frequency: 2450, 5200, 5300, 5600, 5800 MHz</p> <p>Return loss: > 20 dB at specified validation position</p> <p>Power capability: > 100 W (f < 1GHz); > 40 W (f > 1GHz)</p> <p>Dimensions: D2450V2: dipole length: 51.5 mm; overall height: 290 mm D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm</p>
System Validation Kits for ELI4 phantom	
	<p>Construction: Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.</p> <p>Frequency: 2450, 5200, 5300, 5600, 5800 MHz</p> <p>Return loss: > 20 dB at specified validation position</p> <p>Power capability: > 100 W (f < 1GHz); > 40 W (f > 1GHz)</p> <p>Dimensions: D2450V2: dipole length: 51.5 mm; overall height: 290 mm D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm</p>

5 Evaluation Procedures

Data Evaluation

The DASY4/DASY5 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	dcp_i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with	V_i	= Compensated signal of channel i	$(i = x, y, z)$
	U_i	= Input signal of channel i	$(i = x, y, z)$
	cf	= Crest factor of exciting field	(DASY parameter)
	dcp_i	= Diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:
$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

H-field probes:
$$H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with	V_i	= Compensated signal of channel i	$(i = x, y, z)$
	$Norm_i$	= Sensor sensitivity of channel i	$(i = x, y, z)$

$\mu\text{V}/(\text{V}/\text{m})^2$ for E-field Probes

$ConvF$	= Sensitivity enhancement in solution
aij	= Sensor sensitivity factors for H-field probes
f	= Carrier frequency (GHz)
Ei	= Electric field strength of channel i in V/m
Hi	= Magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with

SAR = local specific absorption rate in W/kg

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ρ = equivalent tissue density in g/cm³

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{377} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with

P_{pwe} = Equivalent power density of a plane wave in mW/cm²

E_{tot} = total electric field strength in V/m

H_{tot} = total magnetic field strength in A/m

6 SAR Measurement Procedures

6.1 Normal SAR Test Procedure

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4/DASY5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, the grid resolution has to less than 15 mm by 15 mm at frequency $\leq 2\text{GHz}$; the grid resolution has to less than 12mm by 12 mm at frequency between 2GHz to 4GHz; grid resolution has to less than 10 mm by 10 mm at frequency between 4GHz to 6GHz.

According to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01

	$\leq 3\text{ GHz}$	$> 3\text{ GHz}$
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	$5 \pm 1\text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5\text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$	$\leq 2\text{ GHz}: \leq 15\text{ mm}$ $2 - 3\text{ GHz}: \leq 12\text{ mm}$	$3 - 4\text{ GHz}: \leq 12\text{ mm}$ $4 - 6\text{ GHz}: \leq 10\text{ mm}$
When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.		

- **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures points in accordance with the frequency can be divided into three parts. (1) The zoom scan volume was set to 5x5x7 points at frequency $\leq 2\text{GHz}$. (2) The zoom scan volume was set to 7x7x7 points at frequency between 2GHz to 4GHz (3) The zoom scan volume was set to 7x7x12 points at frequency between 4GHz to 6GHz. The measures points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more then one maximum, the number of Zoom Scans has to be enlarged accordingly.

According to KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01

		$\leq 3\text{ GHz}$	$> 3\text{ GHz}$
Maximum zoom scan spatial resolution: $\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$		$\leq 2\text{ GHz}: \leq 8\text{ mm}$ $2 - 3\text{ GHz}: \leq 5\text{ mm}$	$3 - 4\text{ GHz}: \leq 5\text{ mm}$ $4 - 6\text{ GHz}: \leq 4\text{ mm}$
	Uniform grid: $\Delta z_{\text{zoom}}(n)$	$\leq 5\text{ mm}$	$3 - 4\text{ GHz}: \leq 4\text{ mm}$ $4 - 5\text{ GHz}: \leq 3\text{ mm}$ $5 - 6\text{ GHz}: \leq 2\text{ mm}$
Maximum zoom scan spatial resolution, normal to phantom surface	graded grid	$\Delta z_{\text{zoom}}(1): \text{between 1st two points closest to phantom surface}$ $\leq 4\text{ mm}$	$3 - 4\text{ GHz}: \leq 3\text{ mm}$ $4 - 5\text{ GHz}: \leq 2.5\text{ mm}$ $5 - 6\text{ GHz}: \leq 2\text{ mm}$
		$\Delta z_{\text{zoom}}(n>1): \text{between subsequent points}$	$\leq 1.5 \cdot \Delta z_{\text{zoom}}(n-1)$
Maximum zoom scan volume	x, y, z	$\geq 30\text{ mm}$	$3 - 4\text{ GHz}: \geq 28\text{ mm}$ $4 - 5\text{ GHz}: \geq 25\text{ mm}$ $5 - 6\text{ GHz}: \geq 22\text{ mm}$

- **Power Drift Measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY4/DASY5 software stop the measurements if this limit is exceeded.

- **Z-Scan**

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.

7 Measurement Uncertainty

According to KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz section 2.8.2, SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is ≥ 1.5 W/kg for 1-g SAR, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

8 Device Under Test

8.1 Wireless Technologies

Wireless technologies	Tx Frequency Bands	Operating mode	Duty Cycle used for testing
Wi-Fi	2.4GHz Band	802.11b 802.11g 802.11n(HT20) 802.11n(HT40)	100%
	5GHz Band	802.11a 802.11n(HT20) 802.11n(HT40)	100%
Bluetooth	2.4GHz	2.1 4.0 LE	N/A

8.2 Maximum Tune-up Power

Tolerance (dB): ± 1.5		RF Output Power (dBm)	
Band (GHz)	Mode	Target	Max. tune-up power
2.4	802.11b	12.5	14.0
	802.11g	18.0	19.5
	802.11n HT20	16.5	18.0
	802.11n HT40	14.0	15.5
5.2 (UNII-1)	802.11a	13.0	14.5
	802.11n HT20	12.5	14.0
	802.11n HT40	13.5	15.0
5.3 (UNII-2A)	802.11a	13.0	15.0
	802.11n HT20	13.0	14.5
	802.11n HT40	13.0	14.5
5.5 (UNII-2C)	802.11a	12.5	14.0
	802.11n HT20	12.5	14.0
	802.11n HT40	12.5	14.0
5.8 (UNII-3)	802.11a	12.5	14.0
	802.11n HT20	12.5	14.0
	802.11n HT40	12.5	14.0
Bluetooth		1.0	2.5
Bluetooth LE		0.5	2.0

8.3 Simultaneous Transmission

RF Exposure Condition	Transmit Configurations
Wi-Fi	2.4GHz(Main + Aux) 5GHz(Main + Aux) Bluetooth(Main) 2.4GHz(Aux)+Bluetooth(Main) 5GHz(Aux) +Bluetooth(Main)

Note(s):

1. For WLAN mode can be used as transmitting/receiving on the Main and Aux Antenna.
2. WLAN and Bluetooth technology can transmit at same time.

9 Summary of SAR Test Exclusion Configurations

9.1 Standalone SAR Test Exclusion Calculations

Since the Dedicated Host Approach is applied, the standalone SAR test exclusion procedure in KDB 447498 section 4.3.1 is applied in conjunction with KDB 616217 section 4.3 to determine the minimum test separation distance:

1. According to KDB 447498 Section 4.1.5) if the antenna is at close proximity to user then the outer surface of the DUT should be treated as the radiating surface. The test separation distance is then determined by the smallest distance between the outer surface of the device and the user. For the purposes of this report close proximity has been defined as closer than 50 mm. For antennas <50 mm from the rear or edge the separation distance used for the estimated SAR calculations is 0 mm.
2. When the minimum test separation distance is < 5mm, a distance of 5mm is applied to determine SAR test exclusion.
3. When the separation distance from the antenna to an adjacent edge is > 5 mm, the actual antenna-to-edge separation distance is applied to determine SAR test exclusion.
4. If the antenna to DUT adjacent edge or bottom separation distance >50mm the actual antenna to user separation distance is used to determine SAR exclusion and estimated SAR value.

Refer to Appendix for the specific details on the antenna-to-antenna and antenna-to-edge distances used for test exclusion calculations.

9.1.1 SAR Exclusion Calculations for Wi-Fi Antenna < 50mm from the User

According to KDB 447498 v06, if the calculated **threshold value** is > 3 then SAR testing is required.

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main	2.4GHz	2437	19.5	89	5.5	157.2	258.0	13.2	26.0	25.3	>50mm	>200mm	10.5	5.3
	5.2GHz	5230	15.0	32	5.5	157.2	258.0	13.2	26.0	13.3	>50mm	>200mm	5.5	2.8
	5.3GHz	5260	15.0	32	5.5	157.2	258.0	13.2	26.0	13.3	>50mm	>200mm	5.5	2.8
	5.5GHz	5550	14.0	25	5.5	157.2	258.0	13.2	26.0	10.7	>50mm	>200mm	4.4	2.3
	5.8GHz	5795	14.0	25	5.5	157.2	258.0	13.2	26.0	10.9	>50mm	>200mm	4.5	2.3
	Bluetooth	2402	2.5	2	5.5	157.2	258.0	13.2	26.0	0.6	>50mm	>200mm	0.2	0.1

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Aux	2.4GHz	2437	19.5	89	14.5	10.7	282.7	164.3	6.6	9.6	13.0	>200mm	>50mm	21.0
	5.2GHz	5230	15.0	32	14.5	10.7	282.7	164.3	6.6	5.0	6.8	>200mm	>50mm	11.1
	5.3GHz	5260	15.0	32	14.5	10.7	282.7	164.3	6.6	5.1	6.9	>200mm	>50mm	11.1
	5.5GHz	5550	14.0	25	14.5	10.7	282.7	164.3	6.6	4.1	5.5	>200mm	>50mm	8.9
	5.8GHz	5795	14.0	25	14.5	10.7	282.7	164.3	6.6	4.2	5.6	>200mm	>50mm	9.1

9.1.2 SAR Exclusion Calculations for Wi-Fi Antenna > 50mm from the User

According to KDB 447498 v06, if the calculated Power threshold is less than the output power then SAR testing is required.

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main	2.4GHz	2437	20.0	100	5.5	157.2	258.0	13.2	26.0	<50mm	1168.5	>200mm	<50mm	<50mm
	5.2GHz	5180	15.0	32	5.5	157.2	258.0	13.2	26.0	<50mm	1138.3	>200mm	<50mm	<50mm
	5.3GHz	5260	15.0	32	5.5	157.2	258.0	13.2	26.0	<50mm	1137.8	>200mm	<50mm	<50mm
	5.5GHz	5500	15.0	32	5.5	157.2	258.0	13.2	26.0	<50mm	1136.4	>200mm	<50mm	<50mm
	5.8GHz	5745	14.5	28	5.5	157.2	258.0	13.2	26.0	<50mm	1135.0	>200mm	<50mm	<50mm
	Bluetooth	2402	2.5	2	5.5	157.2	258.0	13.2	26.0	<50mm	1169.2	>200mm	<50mm	<50mm

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)					Calculated Threshold Value				
			dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Axu	2.4GHz	2437	20.0	100	14.5	10.7	282.7	164.3	6.6	<50mm	<50mm	>200mm	1239.0	<50mm
	5.2GHz	5180	15.0	32	14.5	10.7	282.7	164.3	6.6	<50mm	<50mm	>200mm	1208.8	<50mm
	5.3GHz	5260	15.0	32	14.5	10.7	282.7	164.3	6.6	<50mm	<50mm	>200mm	1208.3	<50mm
	5.5GHz	5500	15.0	32	14.5	10.7	282.7	164.3	6.6	<50mm	<50mm	>200mm	1206.9	<50mm
	5.8GHz	5745	14.5	28	14.5	10.7	282.7	164.3	6.6	<50mm	<50mm	>200mm	1205.5	<50mm

9.1.3 SAR Required Test Configuration

For Wi-Fi and Bluetooth

Test Configurations	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Main 2.4GHz	YES	No	No	YES	YES
Wi-Fi Main 5.2GHz	YES	No	No	YES	No
Wi-Fi Main 5.3GHz	YES	No	No	YES	No
Wi-Fi Main 5.5GHz	YES	No	No	YES	No
Wi-Fi Main 5.8GHz	YES	No	No	YES	No
Bluetooth	No	No	No	No	No

Note(s):

1. Yes = SAR is required.
2. No = SAR is not required.

Test Configurations	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Aux 2.4GHz	YES	YES	No	No	YES
Wi-Fi Aux 5.2GHz	YES	YES	No	No	YES
Wi-Fi Aux 5.3GHz	YES	YES	No	No	YES
Wi-Fi Aux 5.5GHz	YES	YES	No	No	YES
Wi-Fi Aux 5.8GHz	YES	YES	No	No	YES
Bluetooth	No	No	No	No	No

Note(s):

1. Yes = SAR is required.
2. No = SAR is not required.

10 Exposure Limit

(A). Limits for Occupational/Controlled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.4	8.0	2.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

<u>Whole-Body</u>	<u>Partial-Body</u>	<u>Hands, Wrists, Feet and Ankles</u>
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE
GENERAL POPULATION/UNCONTROLLED EXPOSURE
PARTIAL BODY LIMIT
1.6 W/kg

11 Tissue Dielectric Properties

11.1 Test Liquid Confirmation

Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The relative permittivity and conductivity of the tissue material should be within $\pm 5\%$ of the values given in the table below. 5% may not be easily achieved at certain frequencies.

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in IEEE 1528 2013 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in IEEE 1528 2013 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in IEEE 1528 2013

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

11.2 Typical Composition of Ingredients for Liquid Tissue Phantoms

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

alt: 99⁺% Pure Sodium Chloride

Sugar: 98⁺% Pure Sucrose

Water: De-ionized, 16 MΩ⁺ resistivity

HEC: Hydroxyethyl Cellulose

DGBE: 99⁺% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra-pure): Polyethylene glycol mono [4-(1, 1, 3, 3-tetramethylbutyl)phenyl]ether

Simulating Liquids for 5 GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2

11.3 Simulating Liquids Parameter Check Results

Date	Band	Freq(MHz)	Measured			Standard		Δ		Limit(%)
			ϵ' (εr)	ϵ''	σ	ϵ' (εr)	σ	ϵ' (εr)	σ	
2015/10/28	Body 5000	5180	51.20	18.81	5.41	49.02	5.28	4.45%	2.62%	±5
		5200	51.18	18.85	5.45	49.00	5.30	4.44%	2.75%	±5
		5220	51.15	18.86	5.47	48.98	5.32	4.44%	2.75%	±5
		5240	51.10	18.87	5.49	48.96	5.35	4.37%	2.69%	±5
		5260	51.04	18.89	5.52	48.94	5.37	4.29%	2.74%	±5
		5280	50.99	18.92	5.55	48.92	5.40	4.23%	2.85%	±5
		5300	50.96	18.95	5.58	48.90	5.42	4.21%	2.94%	±5
		5320	50.95	18.99	5.61	48.86	5.44	4.27%	3.15%	±5
		5500	50.59	19.15	5.85	48.60	5.65	4.10%	3.55%	±5
		5520	50.53	19.17	5.88	48.58	5.67	4.02%	3.61%	±5
		5540	50.51	19.22	5.92	48.56	5.70	4.01%	3.83%	±5
		5560	50.50	19.25	5.94	48.54	5.72	4.03%	3.90%	±5
		5580	50.48	19.27	5.97	48.52	5.75	4.04%	3.98%	±5
		5600	50.44	19.28	6.00	48.50	5.77	4.00%	3.98%	±5
		5620	50.39	19.27	6.02	48.46	5.79	3.98%	3.90%	±5
		5640	50.33	19.31	6.05	48.42	5.81	3.94%	4.05%	±5
		5660	50.31	19.35	6.08	48.38	5.84	3.98%	4.24%	±5
		5680	50.28	19.38	6.12	48.34	5.86	4.02%	4.40%	±5
		5700	50.27	19.41	6.15	48.30	5.88	4.07%	4.55%	±5
		5745	50.16	19.42	6.20	48.26	5.93	3.95%	4.46%	±5
		5765	50.12	19.45	6.23	48.24	5.96	3.91%	4.57%	±5
		5785	50.08	19.49	6.26	48.22	5.98	3.88%	4.69%	±5
		5805	50.06	19.53	6.30	48.19	6.01	3.89%	4.86%	±5
		5825	50.05	19.54	6.32	48.15	6.03	3.94%	4.87%	±5
2015/10/29	Body 2450	2412	52.36	13.62	1.82	52.75	1.91	-0.75%	-4.64%	±5
		2437	52.29	13.73	1.86	52.72	1.94	-0.80%	-4.09%	±5
		2442	52.28	13.73	1.86	52.71	1.94	-0.83%	-4.08%	±5
		2450	52.26	13.77	1.87	52.70	1.95	-0.84%	-3.87%	±5
		2462	52.19	13.81	1.89	52.68	1.97	-0.95%	-3.94%	±5
		2472	52.15	13.87	1.90	52.67	1.98	-0.99%	-3.88%	±5

12 System Performance Check

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the SAM twin phantom filled with Body simulating liquid of the following parameters.
- The DASY4/DASY5 system with an E-field probe EX3DV4 SN: 3554 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration ($dx=dy=5$ mm, $dz=5$ mm).
- Distance between probe sensors and phantom surface was set to 3.0 mm.
- The dipole input power (forward power) was $100\text{ mW}\pm3\%$.
- The results are normalized to 1 W input power.

Reference SAR Values for System Performance Check

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (W/kg)		
				1g/10g	Head	Body
D2450V2	728	2015/5/28	2450	1g	52.6	50.2
				10g	24.5	23.4
D5GHzV2	1004	2015/11/19	5200	1g	80.5	74.7
				10g	22.9	20.7
D5GHzV2	1004	2015/11/19	5300	1g	85.7	77.7
				10g	24.4	21.6
D5GHzV2	1004	2015/11/19	5600	1g	84.1	81.2
				10g	23.9	22.4
D5GHzV2	1004	2015/11/19	5800	1g	80.3	74.2
				10g	22.8	20.3

12.1 System Performance Check Results

Date	System Dipole			Parameters	Target	Measured	Deviation[%]	Limited[%]
	Type	Serial No.	Liquid					
2015/10/28	D5GHzV2 (5.2GHz)	1004	Body	1g SAR:	74.7	76.2	2.01	± 5
				10g SAR:	20.7	21.2	2.42	± 5
2015/10/28	D5GHzV2 (5.3GHz)	1004	Body	1g SAR:	77.7	79.0	1.67	± 5
				10g SAR:	21.6	22.4	3.70	± 5
2015/10/28	D5GHzV2 (5.6GHz)	1004	Body	1g SAR:	81.2	81.8	0.74	± 5
				10g SAR:	22.4	22.7	1.34	± 5
2015/10/28	D5GHzV2 (5.8GHz)	1004	Body	1g SAR:	74.2	74.9	0.94	± 5
				10g SAR:	20.3	21.1	3.94	± 5
2015/10/29	D2450V2	728	Body	1g SAR:	50.2	50.1	-0.20	± 5
				10g SAR:	23.4	23.6	0.85	± 5

13 RF Output Power Measurement

According to KDB248227D01 802.11 Wi-Fi SAR V02 section 4, the default power measurement procedures are:

- 1) Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.
- 2) Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.
 - a) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
 - b) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.
- 3) For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.

13.1 Wi-Fi (2.4GHz Band)

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)			Maximum Tune-up Pwr (dBm)	SAR Test (Yes/No)	Note
					Main	Aux	Total			
2.4	802.11b	1	1	2412	12.7	12.7	15.7	17.0	Yes	
			6	2437	12.9	12.4	15.6	17.0		
			11	2462	12.9	12.8	15.9	17.0		
	802.11g	6	1	2412	11.8	11.2	14.5	16.0	Yes	
			6	2437	18.3	17.6	21.0	22.5		
			11	2462	9.5	9.3	12.4	14.0		
	802.11n HT20	MCS8	1	2412	9.9	9.6	12.7	14.5	Yes	1
			6	2437	17.0	16.2	19.6	21.0		
			11	2462	9.3	8.8	12.1	13.5		
	802.11n HT40	MCS8	3	2422	No Required			13.5	No	1
			6	2437				18.5		
			9	2452				13.0		

Note(s):

1. Output Power and SAR is not required for 802.11n HT40 channels when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

13.2 Wi-Fi (5GHz Band)

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)			Maximum Tune-up Pwr (dBm)	SAR Test (Yes/No)	Note
					Main	Aux	Total			
5.2 (U-NII 1)	802.11a	6	36-48	5180-5240	No Required			17.5	No	3
	802.11n (HT20)	MCS8	36-48	5180-5240				18.0	No	3
	802.11n (HT40)	MCS8	38	5190	10.7	10.1	13.4	15.0	No	3
			46	5230	13.4	13.1	16.3	18.0		
5.3 (U-NII 2A)	802.11a	6	52	5260	13.5	13.0	16.3	18.0	Yes	
			56	5280	13.5	13.0	16.3	18.0	Yes	
			60	5300	13.5	13.0	16.2	18.0	Yes	
			64	5320	13.5	13.0	16.3	18.0	Yes	
	802.11n (HT20)	MCS8	52-64	5260-5320	No Required			17.5	No	1
	802.11n (HT40)	MCS8	52-64	5260-5320				17.5	No	1
5.5 (U-NII-2C)	802.11a	6	100-140	5500-5700	No Required			17.0	No	2
	802.11n (HT20)	MCS8	100-140	5500-5700				17.0	No	2
	802.11n (HT40)	MCS8	102	5510	13.4	12.0	15.8	17.0	Yes	
			110	5550	13.5	12.8	16.2	17.0	Yes	
			118	5590	13.4	12.6	16.0	17.0	Yes	
			126	5630	13.4	12.6	16.0	17.0	Yes	
			134	5670	13.5	12.7	16.1	17.0	Yes	

Note(s):

1. Output Power and SAR measurement is not required for 802.11n HT20/n HT40 channels when the specified maximum tune-up powers are the same in 802.11a and the measured SAR is $\leq 1.2 \text{ W/Kg}$.
2. Output Power and SAR measurement is not required for 802.11a/n HT20 channels when the specified maximum tune-up powers are the same in 802.11n HT40 and the measured SAR is $\leq 1.2 \text{ W/Kg}$.
3. When the specified maximum output power is the same for both UNII band 1 and UNII band 2A, begin SAR measurement in UNII band 2A; and if the highest reported SAR for UNII band 2A is
 - 2.1. $\leq 1.2 \text{ W/kg}$, SAR is not required for UNII band 1.
 - 2.2. $> 1.2 \text{ W/kg}$, both bands should be tested independently for SAR.

Band (GHz)	Mode	Data rate (Mbps)	Ch #	Freq. (MHz)	Avg. Pwr (dBm)			Maximum Tune-up Pwr (dBm)	SAR Test (Yes/No)	Note
					Main	Aux	Total			
5.8 (U-NII-3)	802.11a	6	149-165	5745-5825	No Required			17.0	No	1
	802.11n (HT20)	MCS8	149-165	5745-5825				17.0	No	1
	802.11n (HT40)	MCS8	151	5755	10.6	9.3	13.0	14.0	Yes	
			159	5795	12.9	12.4	15.7	17.0	Yes	

Note(s):

1. Output Power and SAR measurement is not required for 802.11a/n HT20 channels when the specified maximum tune-up powers are the same in 802.11n HT40 and the measured SAR is ≤ 1.2 W/Kg.

13.3 Bluetooth

Refer section 9, the Bluetooth maximum tune-up power is 2.5 dBm .This power level qualifies not required for SAR testing.

14 SAR Measurements Results

Wi-Fi (2.4GHz Band):

Band (GHz)	Mode	Dist. (mm)	Test Position	Ch#	Freq. (MHz)	Chain	Power (dBm)		Area Scan Max. SAR (W/kg)	Meas. 1g SAR (W/kg)	Reported SAR (W/kg)	Note	Plot No.
							Tune up limit	Meas.					
2.4GHz	802.11b	0	Rear	6	2437	Main	14.0	12.9	0.181	0.125	0.161		
			Aux			Aux	14.0	12.4	0.189	0.147	0.214		
		0	Edge 1	6	2437	Aux	14.0	12.4	0.125				
		0	Edge 3	6	2437	Main	14.0	12.9	0.143				
	802.11g	0	Edge 4	6	2437	Main	14.0	12.9	0.136	0.096	0.124		
			Aux			Aux	14.0	12.4	0.137	0.086	0.124		
		0	Rear	6	2437	Main	19.5	18.3	0.775	0.518	0.683		1
		0	Rear	1	2412	Aux	13.0	11.2	0.146	0.102	0.154	3	
	802.11n	0	Edge 1	6	2437	Aux	19.5	17.6	0.362	0.247	0.383		
			Edge 3	6	2437	Main	19.5	18.3	0.041				
		0	Edge 4	6	2437	Main	19.5	18.3	0.382	0.266	0.351		
			Aux			Aux	19.5	17.6	0.642	0.406	0.629		
HT20	802.11n	0	Rear	6	2437	Main	18.0	17.0	0.322	0.215	0.271		
			Aux			Aux	18.0	16.2	0.302				
		0	Edge 1	6	2437	Aux	18.0	16.2	0.176				
		0	Edge 3	6	2437	Main	18.0	17.0	0.141				
		0	Edge 4	6	2437	Main	18.0	17.0	0.164	0.113	0.142		
		0	Edge 4	6	2437	Aux	18.0	16.2	0.309	0.190	0.288		

Note(s):

1. Highest reported SAR is ≤ 0.4 W/kg. Therefore, SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band.
2. Highest reported SAR is > 0.4 W/kg. Due to the highest reported SAR for this test position, other test positions in this exposure condition were evaluated until a SAR ≤ 0.8 W/kg was reported.
3. Highest reported SAR is > 0.8 W/kg. Added second highest power channel for this test position.

Wi-Fi (5 GHz Band):

Band (GHz)	Mode	Dist. (mm)	Test Position	Ch#	Freq. (MHz)	Chain	Power (dBm)		Area Scan Max. SAR (W/Kg)	Meas. 1g SAR (W/kg)	Reported SAR (W/kg)	Note	Plot No.
							Tune up limit	Meas.					
802.11a	5.3 (U-NII-2A)	0	Rear	52	5260	Main	15.0	13.5	1.200	0.604	0.853		
						Aux	15.0	13.0	0.176			3	
		0	Rear	56	5280	Main	15.0	13.5	1.280	0.627	0.886		2
						Aux	15.0	13.0	0.359			3	
		0	Edge 1	52	5260	Aux	15.0	13.0	0.298			3	
802.11n HT40	5.5 (U-NII-2C)	0	Edge 3	52	5260	Main	15.0	13.5	0.123	0.080	0.113		
		0	Edge 4	52	5260	Aux	15.0	13.0	0.450	0.237	0.376		
		0	Rear	110	5550	Main	14.0	13.5	0.618	0.304	0.343		
						Aux	14.0	12.8	0.180			3	
	5.8 (U-NII-3)	0	Edge 1	110	5550	Aux	14.0	12.8	0.325	0.145	0.191		
		0	Edge 3	110	5550	Main	14.0	13.5	0.166			3	
		0	Edge 4	110	5550	Aux	14.0	12.8	0.587	0.348	0.459		3
		0	Rear	159	5795	Main	14.0	12.9	0.979	0.533	0.683		
						Aux	14.0	12.4	0.356	0.209	0.304		
		0	Edge 1	159	5795	Aux	14.0	12.4	0.309				
		0	Edge 3	159	5795	Main	14.0	12.9	0.191	0.131	0.168		
		0	Edge 4	159	5795	Aux	14.0	12.4	1.480	0.820	1.193		4
		0	Edge 4	151	5755	Aux	11.0	9.3	0.888	0.287	0.425	2	
		0	Edge 4	159	5795	Aux	14.0	12.4	1.580	0.721	1.049	4	

Note(s):

1. Highest reported SAR is > 0.4 W/kg. Due to the highest reported SAR for this test position, other test positions in this exposure condition were evaluated until a SAR ≤ 0.8 W/kg was reported.
2. Highest reported SAR is > 0.8 W/kg. Added second highest power channel for this test position.
3. Highest reported SAR is ≤ 0.4 W/kg. Therefore, SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band.
4. Repeated measurements are required only when the measured SAR is ≥ 0.80 W/kg. If the measured SAR values are < 1.45 W/kg with $\leq 20\%$ variation, only one repeated measurement is required to reaffirm that the results are not expected to have substantial variations, which may introduce significant compliance concerns. (Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01)
 - 4.1 Original SAR = 0.820 W/kg, therefore two times repeat SAR is required.
 - 4.2 Repeat SAR = 0.721 < 1.45 W/kg
 - 4.3 SAR variation = 12.0 % $< 20\%$

15 Simultaneous Transmission SAR Analysis

KDB 447498 D01 General RF Exposure Guidance v05, introduces a new formula for calculating the SAR to Peak Location Ratio (SPLSR) between pairs of simultaneously transmitting antennas:

$$SPLSR = (SAR_1 + SAR_2)^{1.5} / R_i$$

Where:

SAR₁ is the highest Reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition

SAR₂ is the highest Reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first

R_i is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured, for both antennas in the pair, it is determined by the actual x, y and z coordinates in the 1-g SAR for each SAR peak location, based on the extrapolated and interpolated result in the zoom scan measurement, using the formula of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$

A new threshold of 0.04 is also introduced in the draft KDB. Thus, in order for a pair of simultaneous transmitting antennas with the sum of 1-g SAR > 1.6 W/kg to qualify for exemption from Simultaneous Transmission SAR measurements, it has to satisfy the condition of:

$$(SAR_1 + SAR_2)^{1.5} / R_i < 0.04$$

15.1 Estimated SAR for Simultaneous Transmission SAR Analysis

Considerations for SAR estimation

- When standalone SAR test exclusion applies, standalone SAR must also be estimated to determine simultaneous transmission SAR test exclusion.
- Dedicated Host Approach criteria for SAR test exclusion is likewise applied to SAR estimation, with certain distinctions between test exclusion and SAR estimation:
 - When the separation distance from the antenna to an adjacent edge is ≤ 5 mm, a distance of 5 mm is applied for SAR estimation; this is the same between test exclusion and SAR estimation calculations.
 - When the separation distance from the antenna to an adjacent edge is > 5 mm but ≤ 50 mm, the actual antenna-to-edge separation distance is applied for SAR estimation.
 - When the minimum test separation distance is > 50 mm, the estimated SAR value is 0.4 W/kg

15.1.1 Estimated SAR for Bluetooth

According to section 9, the Bluetooth must be estimated according to following to determine simultaneous transmission SAR test exclusion:

- $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f_{GHz}}/x]$ W/kg for test separation distances ≤ 50 mm; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
- 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Antenna	Band	Frequency (MHz)	Output Power		Separation Distances(mm)				Estimated 1-g SAR (W/Kg)					
			dBm	mW	Rear	Edge1	Edge2	Edge3	Edge4	Rear	Edge1	Edge2	Edge3	Edge4
Wi-Fi Aux	2.4GHz	2437	19.5	89	14.5	10.7	282.7	164.3	6.6	Measure	Measure	0.400	0.400	Measure
Wi-Fi Aux	5.2GHz	5230	15.0	32	14.5	10.7	282.7	164.3	6.6	Measure	Measure	0.400	0.400	Measure
Wi-Fi Aux	5.3GHz	5260	15.0	32	14.5	10.7	282.7	164.3	6.6	Measure	Measure	0.400	0.400	Measure
Wi-Fi Aux	5.5GHz	5550	14.0	25	14.5	10.7	282.7	164.3	6.6	Measure	Measure	0.400	0.400	Measure
Wi-Fi Aux	5.8GHz	5795	14.0	25	14.5	10.7	282.7	164.3	6.6	Measure	Measure	0.400	0.400	Measure
Wi-Fi Main	2.4GHz	2437	19.5	89	5.5	157.2	258.0	13.2	26.0	Measure	0.400	0.400	Measure	Measure
Wi-Fi Main	5.2GHz	5230	15.0	32	5.5	157.2	258.0	13.2	26.0	Measure	0.400	0.400	Measure	0.375
Wi-Fi Main	5.3GHz	5260	15.0	32	5.5	157.2	258.0	13.2	26.0	Measure	0.400	0.400	Measure	0.376
Wi-Fi Main	5.5GHz	5550	14.0	25	5.5	157.2	258.0	13.2	26.0	Measure	0.400	0.400	Measure	0.302
Wi-Fi Main	5.8GHz	5795	14.0	25	5.5	157.2	258.0	13.2	26.0	Measure	0.400	0.400	Measure	0.309
Wi-Fi Main	Bluetooth	2402	2.50	2	5.5	157.2	258.0	13.2	26.0	0.075	0.400	0.400	0.031	0.016

15.2 Sum of the SAR for Simultaneous Transmission Analysis

15.2.1 Sum of the SAR for Wi-Fi & Bluetooth

Band	Test Position	Simultaneous Transmission Scenario		\sum 1-g SAR (W/kg)	SPLSR (Yes/No)
		Wi-Fi Aux	Bluetooth		
2.4GHz	Rear	0.808	0.075	0.883	No
	Edge 4	0.629	0.016	0.645	No

Note(s):

As the Sum of the SAR is not greater than 1.6W/Kg, so SPLSR is not required.

Band	Test Position	Simultaneous Transmission Scenario		\sum 1-g SAR (W/kg)	SPLSR (Yes/No)
		Wi-Fi Aux	Bluetooth		
5GHz	Rear	0.304	0.075	0.379	No
	Edge 4	1.193	0.016	1.209	No

Note(s):

As the Sum of the SAR is not greater than 1.6W/Kg, so SPLSR is not required.

15.2.2 Sum of the SAR for Wi-Fi MIMO

Band	Test Position	Simultaneous Transmission Scenario		\sum 1-g SAR (W/kg)	SPLSR (Yes/No)
		Wi-Fi Main	Wi-Fi Aux		
2.4GHz	Rear	0.683	0.808	1.491	No
	Edge 4	0.351	0.629	0.980	No

Note(s):

As the Sum of the SAR is not greater than 1.6W/Kg, so SPLSR is not required.

Band	Test Position	Simultaneous Transmission Scenario		\sum 1-g SAR (W/kg)	SPLSR (Yes/No)
		Wi-Fi Main	Wi-Fi Aux		
5GHz	Rear	0.853	0.304	1.157	No
	Edge 4	0.376	1.193	1.569	No

Note(s):

As the Sum of the SAR is not greater than 1.6W/Kg, so SPLSR is not required.

16 Equipment List & Calibration Status

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Cycle(year)	Calibration Due
S-Parameter Network Analyzer	Agilent	E5071C	MY46213916	1	2016/06/25
Electronic Probe kit	Hewlett Packard	85070D	N/A	N/A	N/A
Power Meter	Agilent	4416	GB41291611	1	2016/09/06
Power Sensor	Agilent	8481H	MY41091956	1	2016/09/06
Data Acquisition Electronics (DAE)	SPEAG	DAE4	558	1	2016/06/15
Dosimetric E-Field Probe	SPEAG	EX3DV4	3554	1	2016/10/01
2450 MHz System Validation Dipole	SPEAG	D2450V2	728	1	2016/05/27
5GHz System Validation Dipole	SPEAG	D5GHzV2	1004	1	2015/11/19
Robot	Staubli	RX90L	F02/5T69A1/A/01	N/A	N/A
Amplifier	Mini-Circuit	ZVE-8G	665500309	N/A	N/A
Amplifier	Mini-Circuit	ZHL-1724HLN	D072602#2	N/A	N/A

17 Facilities

All measurement facilities used to collect the measurement data are located at

- No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.
- No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)
- No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

18 Reference

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commision, O_ce of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEICE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies", in ICECOM _ 97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions onMicrowave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992..Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10

19 Attachments

Exhibit	Content
1	System Performance Check Plots
2	SAR Test Data Plots
3	Calibration Data Report
4	T150723L02-SF PHOTOS

END OF REPORT