

**IEEE C95.1 2005
KDB 447498 D01 V06
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091**

RF EXPOSURE REPORT

For

Computer

**Model: UTC-520F, UTC-520FXXXXXXXXXXXXXXXXXX (where "X"
may be any alphanumeric character , "-" or blank)**

Trade Name: ADVANTECH

Issued to

Advantech Co.Ltd.

No.1, Alley 20, Lane 26, Rueiguang Road, Neihu District, Taipei 114, Taiwan, R.O.C.

Issued by

Compliance Certification Services Inc.

**No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)**

<http://www.ccsrf.com>

service@ccsrf.com

Issued Date: February 8, 2018



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	February 8, 2018	Initial Issue	ALL	Allison Chen
01	March 28, 2018	1. Modify frequency band of UNII-2C and UNII-3.	P.5	Allison Chen

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION..... 4

2. LIMIT 5

3. EUT SPECIFICATION 5

4. TEST RESULTS..... 7

5. MAXIMUM PERMISSIBLE EXPOSURE 8

1. TEST RESULT CERTIFICATION

We hereby certify that:


The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
IEEE C95.1 2005 KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091	No non-compliance noted

Approved by:


Sam Chuang
 Manager
 Compliance Certification Services Inc.

Tested by:


Allison Chen
 Report coordinator
 Compliance Certification Services Inc.

2. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

3. EUT SPECIFICATION

EUT	Computer
Model	UTC-520F, UTC-520FXXXXXXXXXXXXXXXXXX (where "X" may be any alphanumeric character, "-" or blank)
Trade Name	ADVANTECH
Model Discrepancy	All the above models are identical except for the designation of model numbers. The suffix of (X= a-z / 0-9 or blank) on model number is just for marketing purpose only.
Frequency band (Operating)	<input checked="" type="checkbox"/> 802.11b/g/n 20: 2412MHz ~ 2462MHz 802.11n 40: 2422MHz ~ 2452MHz 802.11a/n 20: 5180MHz ~ 5240MHz / 5260MHz ~ 5320MHz / 5500MHz ~ 5700MHz / 5745MHz ~ 5825MHz 802.11n 40: 5190MHz ~ 5230MHz / 5270MHz ~ 5310MHz / 5510MHz ~ 5670MHz / 5755MHz ~ 5795MHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)

Antenna Specification	2.4G			
		Description	Type	Peak Gain
	Ant 1	WIFI black	PIFA	3.03dBi
	Ant 2	WIFI white	PIFA	2.67dBi
	Power Directional Gain		2.85dBi	
Antenna Specification	5G			
		Description	Type	Peak Gain
	Ant 1	WIFI black	PIFA	6.42dBi
	Ant 2	WIFI white	PIFA	5.50dBi
	Power Directional Gain		5.98dBi	
	<p>2.4GHz: Directional Gain : 2.85 dBi (Numeric gain: 1.93) Worst</p> <p>5GHz: Directional Gain : 5.98 dBi (Numeric gain: 3.96) Worst</p>			
	<p>Notes:</p> <p>1. Power Directional Gain: $10\text{LOG}(((10^{\text{Ant1}/10})+10^{\text{Ant2}/10}))/2)$</p>			
Max tune up Power	IEEE 802.11b :	14.50 dBm	(28.184 mW)	
	IEEE 802.11g :	17.50 dBm	(56.234 mW)	
	IEEE 802.11n 20 :	19.50 dBm	(89.125 mW)	
	IEEE 802.11n 40 :	19.50 dBm	(89.125 mW)	
	IEEE 802.11a :	19.00 dBm	(79.433 mW)	
	IEEE 802.11n 20 :	22.50 dBm	(177.828 mW)	
	IEEE 802.11n 40 :	18.00 dBm	(63.096 mW)	
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A			

4. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where $E =$ Field strength in Volts / meter

$P =$ Power in Watts

$G =$ Numeric antenna gain

$d =$ Distance in meters

$S =$ Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where $d =$ Distance in cm

$P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where $P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

IEEE 802.11b:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	28.184	1.93	20	0.0108	1

IEEE 802.11g:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	56.234	1.93	20	0.0216	1

IEEE 802.11n 20:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	89.125	1.97	20	0.0349	1

IEEE 802.11n 40:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	89.125	1.97	20	0.0349	1

IEEE 802.11a:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
52	5260	79.433	3.96	20	0.0626	1

IEEE 802.11n 20:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
48	5240	177.828	3.96	20	0.1401	1

IEEE 802.11n 40:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
46	5230	63.096	3.96	20	0.0497	1