

RF Exposure Report

Report No.: SA140707C54I

FCC ID: M82-UTX-3115

Test Model: UTX-3115

Series Model: UTX-3115XXXXXXXXXXXXXXXXXX, UTX3115XXXXXXXXXXXXXXXXXX ("X" can be 0-9 or A-Z or blank or any alphanumeric character), HPE Edgeline EL10

Received Date: Jun. 18, 2014

Issued Date: Aug. 30, 2016

Applicant: ADVANTECH CO., LTD

Address: No. 1, Alley 20, Lane 26, Rueiguang Rd, Neihu District, Taipei, Taiwan 114

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Tune up Power	6

Release Control Record

Issue No.	Description	Date Issued
SA140707C54I	Original release	Aug. 30, 2016

1 Certificate of Conformity

Product: COMPUTER

Brand: Advantech, Hewlett Packard Enterprise

Test Model: UTX-3115

Series Model: UTX-3115XXXXXXXXXXXXXXXXXX, UTX3115XXXXXXXXXXXXXXXXXX ("X" can be 0-9 or A-Z or blank or any alphanumeric character), HPE Edgeline EL10

Sample Status: Engineering sample

Applicant: ADVANTECH CO., LTD

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 (October 23, 2015)
IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** Aug. 30, 2016
Celine Chou / Specialist

Approved by : Ken Liu , **Date:** Aug. 30, 2016
Ken Liu / Senior Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Tune up Power

Frequency Band (MHz)	Modulation Mode	Max Power (dBm)	Chain	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	802.11b	19.17	A	2.98	20	0.033	1
		17.84	B	2.98	20	0.024	1
	802.11g	25.66	A	2.98	20	0.145	1
		24.59	B	2.98	20	0.114	1
	802.11n (20MHz)	26.01	A	2.98	20	0.158	1
		24.83	B	2.98	20	0.120	1
		25.98	A + B	5.99	20	0.313	1
	802.11n (40MHz)	26.78	A	2.98	20	0.188	1
		23.95	B	2.98	20	0.098	1
		26.19	A + B	5.99	20	0.329	1
5180-5240	802.11a	14.91	A	1.40	20	0.009	1
		15.07	B	1.40	20	0.009	1
	802.11n (20MHz)	15.10	A	1.40	20	0.009	1
		15.06	B	1.40	20	0.009	1
		15.17	A + B	4.41	20	0.018	1
	802.11n (40MHz)	15.65	A	1.40	20	0.010	1
		15.01	B	1.40	20	0.009	1
		14.94	A + B	4.41	20	0.017	1
	802.11ac (80MHz)	6.89	A	1.40	20	0.001	1
		7.79	B	1.40	20	0.002	1
		8.56	A + B	4.41	20	0.004	1

Frequency Band (MHz)	Modulation Mode	Max Power (dBm)	Chain	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5260-5320	802.11a	14.71	A	1.40	20	0.008	1
		16.18	B	1.40	20	0.011	1
	802.11n (20MHz)	14.70	A	1.40	20	0.008	1
		15.01	B	1.40	20	0.009	1
		15.18	A + B	4.41	20	0.018	1
	802.11n (40MHz)	9.97	A	1.40	20	0.003	1
		10.19	B	1.40	20	0.003	1
		10.84	A + B	4.41	20	0.007	1
	802.11ac (80MHz)	9.87	A	1.40	20	0.003	1
		10.28	B	1.40	20	0.003	1
		10.05	A + B	4.41	20	0.006	1
5500-5720	802.11a	17.21	A	1.40	20	0.014	1
		17.01	B	1.40	20	0.014	1
	802.11n (20MHz)	17.13	A	1.40	20	0.014	1
		16.23	B	1.40	20	0.012	1
		17.20	A + B	4.41	20	0.029	1
	802.11n (40MHz)	16.76	A	1.40	20	0.013	1
		16.57	B	1.40	20	0.012	1
		16.62	A + B	4.41	20	0.025	1
	802.11ac (80MHz)	14.23	A	1.40	20	0.007	1
		14.23	B	1.40	20	0.007	1
		16.69	A + B	4.41	20	0.026	1

Frequency Band (MHz)	Modulation Mode	Max Power (dBm)	Chain	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5745-5825	802.11a	18.79	A	1.40	20	0.021	1
		19.53	B	1.40	20	0.025	1
	802.11n (20MHz)	17.84	A	1.40	20	0.017	1
		19.23	B	1.40	20	0.023	1
		18.38	A + B	4.41	20	0.038	1
	802.11n (40MHz)	17.47	A	1.40	20	0.015	1
		19.31	B	1.40	20	0.023	1
		16.51	A + B	4.41	20	0.025	1
	802.11ac (80MHz)	16.58	A	1.40	20	0.012	1
		13.23	B	1.40	20	0.006	1
		12.49	A + B	4.41	20	0.010	1

Note:

2.4GHz Band:

802.11b / g: gain = 2.98dBi

802.11n: Directional gain = 2.98dBi + 10log(2) = 5.99dBi

5.0GHz Band:

802.11a: gain = 1.4dBi

802.11n: Directional gain = 1.4dBi + 10log(2) = 4.41dBi

Mode	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
BT LE	2402~2480	4.54	2.98	20	0.001	1
BT EDR	2402~2480	4.87	2.98	20	0.001	1

Frequency Band (MHz)	ERP (dBm)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
GPRS 824.2 ~ 848.8MHz	28.59	30.74	20	0.236	0.549
EDGE 824.2 ~ 848.8MHz	28.10	30.25	20	0.211	0.549
WCDMA 826.4 ~ 846.6MHz	19.86	22.01	20	0.032	0.551

Note: EIRP = ERP + 2.15dBi.

Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
GPRS 1850.2 ~ 1909.8MHz	28.22	20	0.132	1
EDGE 1850.2 ~ 1909.8MHz	27.70	20	0.117	1
WCDMA 1852.4 ~ 1907.6MHz	21.06	20	0.025	1
WCDMA 1712.4 ~ 1752.6MHz	20.71	20	0.023	1

* The WLAN 2.4GHz, 5GHz, BT EDR, BT LE and WWAN cannot transmit simultaneously.

---END---