

A

B

C

D

E

F

94.5mm

R5*3

PMS Yellow C

INPUT: 19V = 4.74A

MODEL: P470

CAUTION: For use with approved ac adapters only



FCC ID : MAU470

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions:
 (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



CAUTION:
 This surface is hot. avoid contous body contact and do not place this notebook on your lap while it is operating.

S/N: _____

REF: _____



MADE IN CHINA MMC

69.5mm

C5*1

NOTE:

1. MATERIAL:PC(FR65),t 0.254,防火係數94-0, IT MUST BE APPROVED BY UL & CSA STANDARD
2. LABEL SHOULD HAVE PRESSURE SENSITIVEADHESIVE WITH PROTECTIVE RELEASE LINER ON THEBACL SIDE
3. COLORS:TEXT FOREGROUND:PANTONE COOL GRAY 5C ; BACKGROUND:TAC-11A19
4. LABEL MANUFACTURER MUST USE A PROCESS & MATERIALS THOSE WHICH HAVE BEEN APPROVED BY US & CSA
5. ADHESIVE:3M467
6. 依RD承認為準
7. 成品需符合GP要求

ITEM	CONTENTS OF CHANGE	RVS	CHK	APV	M/D/Y	TOL [±] RANGE	Pla	Met	Ins	Por	Cab	Pac	Gas	PCB	DATE	MAR-27-07	MATERIAL	SEE NOTES	TREATMENT	REMARK					
							0.1	0.1	0.1	0.2	0.5	1	0.5	0.1	UNIT	MM	SCALE	--	DRAWING NAME	TF041-LABEL;RATING,P470					
						6~30	0.1	0.1	0.15	.25	1	1	0.5	0.1	DRAWN	DESIGNED	CHECKED	APPROVED	MATERIAL NO.	MF	242	1270	00003	R00	
						30~80	0.1	0.15	0.2	0.3	2	1.5	1	0.1											
						80~180	.15	.15	.25	0.3	2	2	1	.15											
						180~315	.15	0.2	0.3	0.4	2.5	2	1	.15											
						315~800	0.2	0.3	0.4	0.5	3	3	2	.15											

MITAC Technology Corp.

A

B

C

D

E

SHEET No. 1 of 1