

Nemko Korea Co., Ltd.

155 & 159, Osan-Ro, Mohyeon-Eup, Cheoin-Gu, Yongin-Si, Gyeonggi-Do 16885 KOREA, REPUBLIC OF
TEL:+82 31 330-1700 FAX:+82 31 322 2332

FCC and IC EVALUATION REPORT FOR CERTIFICATION

Applicant :

Anam Electronics Co., Ltd.
27, Digital-ro 27ga-gil, Guro-gu, Seoul,
08375, Republic of Korea.
Attn. : Byeong-Seob, Lee

Dates of Issue : July 25, 2019
Test Report No. : NK-19-R-052
Test Site : Nemko Korea Co., Ltd.

FCC ID
IC

MBBVOP13082E
11657A-VOP13082E

Brand Name

ANAM

Contact Person

Anam Electronics Co., Ltd.
27, Digital-ro 27ga-gil, Guro-gu, Seoul, 08375,
Republic of Korea.
Byeong-Seob, Lee
Telephone No. : +82-2-6424-4881

Applied Standard: FCC 47 CFR Part 15.247
IC RSS-247 Issue 2 and IC RSS-GEN Issue 5
Classification: Digital Transmission System (DTS)
EUT Type: DMA WiFi/BT Platform Module

The device bearing the brand name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Jul. 25. 2019

Tested By : Wonjae Song
Engineer



July. 25. 2019

Reviewed By : Seungyong Shin
Technical Manager

TABLE OF CONTENTS

1. Scope	4
2. Introduction (Site Description)	5
2.1 Test facility	5
2.2 Accreditation and listing	6
3. Test Conditions & EUT Information	7
3.1 Operation During Test	7
3.1.1 Table of test power setting	7
3.1.2 Table of test channels	8
3.1.3 Antenna information	8
3.1.4 Additional Information Related to Testing	9
3.1.5 Table of test modes	9
3.2 Support Equipment	10
3.3 Setup Drawing	10
3.4 EUT Information	11
4. Summary of Test Results	12
5. Recommendation / Conclusion	13
6. Antenna Requirements	13
7. Description of Test	14
7.1 Conducted Emissions	14
7.2 Radiated Emissions	15
7.3 6 dB Bandwidth	16
7.4 Maximum Conducted Output Power (average)	17
7.5 Maximum Power Spectral Density (average)	18
7.6 Conducted Spurious Emissions	19
7.7 Duty Cycle	20

8. Test Data	21
8.1 Radiated Emissions	21
8.2 6 dB Bandwidth	23
8.3 Maximum Conducted Output Power (average) and E.I.R.P	31
8.4 Maximum Power Spectral Density (average)	34
8.5 Conducted Spurious Emissions	46
8.6 Radiated Spurious Emissions	72
8.7 Radiated Band Edge	76
9. Test Equipment	78
10. Accuracy of Measurement	79

1. SCOPE

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission under FCC part 15 and IC RSS-247 Issue2.

Responsible Party :	Anam Electronics Co., Ltd. 27, Digital-ro 27ga-gil, Guro-gu, Seoul, 08375, Republic of Korea
Contact Person :	Byeong Seob, Lee
Manufacturer :	Anam Electronics Co., Ltd. 27, Digital-ro 27ga-gil, Guro-gu, Seoul, 08375, Republic of Korea

- FCC ID: MBBVOP13082E
- IC: 11657A-VOP13082E
- Model: VOP13082E
- Variant Models: VOP13082B, VOP13802C, VOP13082D
- HVIN: VOP13082E
- Brand Name: ANAM
- EUT Type: DMA WiFi/BT Platform Module
- Classification: Digital Transmission System (DTS)
- Applied Standard: FCC 47 CFR Part 15.247
IC RSS-247 Issue 2 and IC RSS-GEN Issue 5
- Test Procedure(s): ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05
- Dates of Test: May 30, 2019 ~ July 25, 2019
- Place of Test: Nemko Korea Co., Ltd.

2. INTRODUCTION

2.1 Test facility

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2014), the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013) was used in determining radiated and conducted emissions emanating from **Anam Electronics Co., Ltd. FCC ID : MBB VOP13082E** and **IC : 11657A- VOP13082E**.

These measurement tests were conducted at **Nemko Korea Co., Ltd. EMC Laboratory**.

The site address 155 & 159, Osan-Ro, Mohyeon-Eup, Cheoin-Gu, Yongin-Si, Gyeonggi-Do 16885 KOREA, REPUBLIC OF.

The area of Nemko Korea Corporation Ltd. EMC Test Site is located in a mountain area at 80 km (48 miles) southeast and Incheon International Airport (Incheon Airport), 30 km (18miles) south-southeast from central Seoul.

It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures.

The detailed description of the measurement facility was found to be in compliance with the requirements of ANSI C63.4-2014 according to §2.948.



Nemko Korea Co., Ltd.
EMC Lab.
155 & 159, Osan-Ro, Mohyeon-Eup,
Cheoin-Gu, Yongin-Si, Gyeonggi-Do
16885 KOREA, REPUBLIC OF
Tel)+82-31-330-1700
Fax)+82-31-322-2332

Fig. 1. The map above shows the Seoul in Korea vicinity area.

The map also shows Nemko Korea Corporation Ltd. EMC Lab. and Incheon Airport.

2.2 Accreditation and listing

Accreditation type		Accreditation number
	CAB Accreditation for DOC	Designation No. KR0026
	KOLAS Accredited Lab. (Korea Laboratory Accreditation Scheme)	Registration No. 155
	Canada IC Registered site	Site No. 2040E
	VCCI registration site(RE/CE/Telecom CE)	Member No. 2118
	EMC CBTL	-
	KCC(RRL)Designated Lab.	Registration No. KR0026

3. TEST CONDITIONS & EUT INFORMATION

3.1 Operation During Test

The EUT is the SISO, CDD, MIMO transceiver which is module supporting the 802.11a/b/g/n/ac mode (802.11a/b/g/n(20,40MHz)/ac(20,40,80MHz) : 1TX/1RX, 2TX/2RX).

The Laptop was used to control the EUT to transmit the wanted TX channel continuously (duty cycle< 98%) by the testing program (TeraTerm) supported by manufacturer.

The operating voltage of EUT was 5.0 Vdc supplied from jig board connected to USB port on Laptop PC.

The EUT was tested at the lowest, middle and the highest channels with the maximum output power in accordance with the manufacturer's specifications. The worst data were recorded in the report.

3.1.1 Table of test power setting

Frequency	Mode	Power setting Level (1TX)	Power setting Level (2TX)
2412 MHz	802.11b	14	-
	802.11g	12	-
	802.11n (20 MHz)	12	9
2437 MHz	802.11b	14	-
	802.11g	12	-
	802.11n (20 MHz)	12	9
2462 MHz	802.11b	14	-
	802.11g	12	-
	802.11n (20 MHz)	12	9
2422MHz	802.11n (40 MHz)	11	11
2437 MHz		11	11
2452 MHz		11	11

3.1.2 Table of test channels

Frequency band	Mode	Test Channel (CH)	Frequency (MHz)
2.4 GHz	802.11b,g,n (20 MHz)	1	2412
		6	2437
		11	2462
	802.11n (40 MHz)	3	2422
		6	2437
		9	2452

3.1.3 Antenna information

Frequency band	Mode	Data rate	Antenna TX mode	Support CDD	Support MIMO
2.4 GHz	802.11b,g	All	■ 1TX, □ 2TX	□ Yes, ■ No	□ Yes, ■ No
	802.11n (20MHz)	MCS 0~7	■ 1TX, ■ 2TX	■ Yes, □ No	□ Yes, ■ No
		MCS 8~15	□ 1TX, ■ 2TX	□ Yes, ■ No	■ Yes, □ No
	802.11n (40MHz)	MCS 0~7	■ 1TX, ■ 2TX	■ Yes, □ No	□ Yes, ■ No
		MCS 8~15	□ 1TX, ■ 2TX	□ Yes, ■ No	■ Yes, □ No

Note:

1. CDD mode is Cyclic Delay Diversity mode.
2. For 802.11b,g,EUT support SISO,CDD mode for All.
3. For 802.11n(20 MHz),EUT support SISO,CDD mode for MCS0~7 and MIMO mode for MCS8~15.
4. For 802.11n(40 MHz),EUT support SISO,CDD mode for MCS0~7 and MIMO mode for MCS8~15.
5. CDD mode, $N_{ss}=1$, MIMO mode, $N_{ss}=2$, where N_{ss} = number of spatial streams.
6. MIMO mode means SM-MIMO transmission.

3.1.4 Additional Information Related to Testing

The cable and attenuator loss from 30MHz to 26.5GHz was reflected in spectrum analyzer with correction factor for all conducted testing.

3.1.5 Table of test modes


Test Items	Mode	*Data rate (Mbps)	Test Channel (CH)	Antenna
Conducted Emissions	802.11b	N/A	N/A	N/A
Radiated Emissions	802.11b	1	6	Ant 1
6 dB Bandwidth	802.11b	1	1/6/11	Ant 1
	802.11g	6	1/6/11	Ant 1
	802.11n (20 MHz)	MCS0	1/6/11	Ant 1
	802.11n (40 MHz)	MCS0	3/6/9	Ant 1
Maximum Conducted Output Power	802.11b	1	1/6/11	Ant 0, Ant 1
	802.11g	6	1/6/11	Ant 0, Ant 1
	802.11n (20 MHz)	MCS0	1/6/11	Ant 0, Ant1
	802.11n (40 MHz)	MCS0	3/6/9	Ant 0, Ant1
Power Spectral Density	802.11b	1	1/6/11	Ant 1
	802.11g	6	1/6/11	Ant 1
	802.11n (20 MHz)	MCS0	1/6/11	Ant 1
	802.11n (40 MHz)	MCS0	3/6/9	Ant 1
Conducted Spurious Emission, Radiated Spurious Emission, Band edge Emission	802.11b	1	1/6/11	Ant 1
	802.11g	6	1/6/11	Ant 1
	802.11n (20 MHz)	MCS0	1/6/11	Ant 1
	802.11n (40 MHz)	MCS0	3/6/9	Ant 1

*The worst data rate was determined by the conducted output power that generates the highest emission performing pre-scan testing in all data rates of each mode.

3.2 Support Equipment

EUT	Anam Electronics Co., Ltd. Model : VOP13082E	S/N: N/A
Laptop Computer	HP Model : G62-355TU	FCC DOC S/N : CNF0489WDT
AC/DC Adapter	HP Model : PPP009D 1.5 m unshielded power cable	FCC DOC S/N : WBGSV0ACXZH162

3.3 Setup Drawing



3.4 EUT Information

The EUT is the **Anam Electronics Co., Ltd. DMA WiFi/BT Platform Module FCC ID: MBB VOP13082E, IC: 11657A- VOP13082E.**

Specifications:

EUT Type	DMA WiFi/BT Platform Module
Model Name	VOP13082E
Variant Model Name	VOP13082B, VOP13802C, VOP13082D
Brand Name	ANAM
Frequency of Operation	802.11b,g,n (20 MHz) : 2412 MHz ~ 2462 MHz 802.11n (40 MHz) : 2422 MHz ~ 2452 MHz
Maximum Conducted Output Power	802.11b : 18.06 dBm 802.11g : 14.25 dBm 802.11n (20 MHz) : 13.07 dBm 802.11n (40 MHz) : 13.73 dBm
FCC Classification	Digital Transmission System (DTS)
Number of Channels	802.11b,g,n (20 MHz): 11 CH 802.11n (40 MHz): 7 CH
Modulations	DSSS(BPSK,QPSK,CCK) for 802.11b OFDM(BPSK,QPSK,16QAM,64QAM) for 802.11g/n
Antenna Gain (peak)	Ant : 4.0 dBi
Antenna Setup	802.11b/g/n (20, 40MHz) : 1TX / 1RX, 2TX / 2RX
Voltage	5.0 Vdc
Temperature Range	-10 °C ~ +70 °C
Size (W x H x D)	About 74 mm x 87 mm x 16.4 mm
Weight	About 44 g
HVIN (Hardware Version Number)	VOP13082E
FVIN (Firmware Version Identification Number)	SUN_NAND_0613
Remarks	-

4. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specification:

Name of Test	FCC Paragraph No.	IC Paragraph No.	Result	Remark
Conducted Emission	15.207	RSS-GEN Issue 5 8.8	NA	
Radiated Emission	15.209	RSS-GEN Issue 5 8.9	Complies	
6 dB Bandwidth	15.247(a)(2)	RSS-247 Issue 2 5.2	Complies	
Maximum Conducted Output Power	15.247(b)(3)	RSS-247 Issue 2 5.4	Complies	
Power Spectral Density	15.247(e)	RSS-247 Issue 2 5.2	Complies	
Conducted Spurious Emission	15.247(d)	RSS-247 Issue 2 5.5	Complies	
Radiated Spurious Emission	15.247(d)	RSS-247 Issue 2 5.5	Complies	
Maximum Permissible Exposure	1.1307(b)	RSS-102 Issue 5	Complies	

5. RECOMMENDATION/CONCLUSION

The data collected shows that the **Anam Electronics Co., Ltd. DMA WiFi/BT Platform Module FCC ID: MBB VOP13082E, IC: 11657A- VOP13082E** is in compliance with Part 15.247 of the FCC Rule and RSS-247 Issue 2 of the IC Specification.

6. ANTENNA REQUIREMENTS

§15.203 of the FCC Rules part 15 Subpart C

: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The antenna of the **Anam Electronics Co., Ltd. DMA WiFi/BT Platform Module FCC ID: MBB VOP13082E, IC: 11657A- VOP13082E** is **permanently attached** and there are no provisions for connection to an external antenna. It complies with the requirement of §15.203.

Directional gain was be calculated according to “**662911 D01 Multiple Transmitter Output v02r01**” and would be found at end of average output power and PSD results in this report.

Model name	Max. gain (dBi)		Type	External or Internal
	2.4GHz	5GHz		
N2420DG3-T2L-PK1-G520U	3.1	2.8	PIFA	Internal
503021-0113-0BC ¹⁾	2.0	2.0	Dipole	External
120300055600J	2.0	2.0	Dipole	External
120700034000J	2.0	2.0	Dipole	External
120300055601J	2.0	2.0	Dipole	External
KH-WFDI-AN001 ²⁾	4.0	2.8	PIFA	Internal
KH-WFDI-AN002	4.0	2.8	PIFA	Internal
KH-WFDI-AN003	3.6	2.1	PIFA	Internal
KH-WFDI-AN004	3.6	2.1	PIFA	Internal
KH-WFDI-AN005	3.5	2.1	PIFA	Internal
KH-WFDI-AN006	3.5	2.1	PIFA	Internal

Note:

1. Pre-radiated testing was performed to determine worst antenna type of two antenna type (Dipole and PIFA).
2. Pre-radiated testing was performed to determine worst antenna type of two antenna type (Dipole and PIFA).
As a result, this antenna was determined as worst antenna type for final radiated testing.

7. DESCRIPTION OF TESTS

7.1 Conducted Emissions

The Line conducted emission test facility is located inside a 4 x 7 x 2.5 meter shielded enclosure. It is manufactured by EM engineering. The shielding effectiveness of the shielded room is in accordance with MIL-STD-285 or NSA 65-6. A 1 m x 1.5 m wooden table 0.8 m height is placed 0.4 m away from the vertical wall and 1.5 m away from the side of wall of the shielded room. Rohde & Schwarz (ESH3-Z5) and (ESH2-Z5) of the 50 ohm/50 μ H Line Impedance Stabilization Network (LISN) are bonded to the shielded room. The EUT is powered from the Rohde & Schwarz LISN (ESH3-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH2-Z5). Power to the LISNs are filtered by high-current high insertion loss Power line filters. The purpose of filter is to attenuate ambient signal interference and this filter is also bonded to shielded enclosure. All electrical cables are shielded by tinned copper zipper tubing with inner diameter of 1 / 2 ". If DC power device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the LISNs, All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1 meter length. Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 150 kHz to 30 MHz with 200 msec sweep time. The frequency producing the maximum level was re-examined using the EMI test receiver. (Rohde & Schwarz ESCS30). The detector functions were set to CISPR quasi-peak mode & average mode. The bandwidth of receiver was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by; switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; whichever determined the worst case emission. Each EME reported was calibrated using the R&S signal generator.




Fig. 2. LISN Schematic Diagram

7.2 Radiated Emissions

The measurement was performed at the test site that is specified in accordance with ANSI C63.10-2013.

The spurious emission was scanned from 9 kHz to 30 MHz using Loop Antenna(Rohde&Schwarz, HFH2-Z2) and 30 to 1000 MHz using Trilog broadband test antenna(Schwarzbeck, VULB 9163). Above 1 GHz, Horn antenna (Schwarzbeck BBHA 9120D: up to 18 GHz, Q-par Angus QSH20S20 : 18 to 26.5 GHz) was used.

For emissions testing at below 1GHz, The test equipment was placed on turntable with 0.8 m above ground. For emission measurements above 1 GHz, The test equipment was placed on turntable with 1.5 m above ground. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The EUT, cable, wire arrangement and mode of operation that has the highest amplitude relative to the limit was selected. Then, the turn table was rotated from 0° to 360° and an antenna mast was moved from 1 m to 4 m height to maximize the suspected highest amplitude signal. The final maximized level was recorded.


At frequencies below 1000 MHz, measurements performed using the CISPR quasi-peak detection. At frequencies above 1000 MHz, measurements performed using the peak and average measurement procedures described in ANSI 63.10-2013 section 11.12. Peak emission levels were measured by setting the analyzer RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Trace mode = max hold. Average emission levels were measured by setting the analyzer RBW = 1 MHz, VBW = 10kHz, Detector = Peak, Trace mode = max hold. Allow max hold to run for at least 50 times (1/duty cycle) traces.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100	3
88–216	150	3
216–960	200	3
Above 960	500	3

Radiated Emissions Limits per 47 CFR 15.209(a) and RSS-GEN Issue 5 8.9

7.3 6 dB Bandwidth

Test Setup



Test Procedure

EUTs 6 dB bandwidth is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

RBW = 100 kHz

VBW > 3 x RBW

Detector = Peak


Trace mode = max hold

Sweep = auto couple

The bandwidth measurement function on the spectrum analyzer is used to measure the 6 dB bandwidth.

7.4 Maximum Conducted Output Power (average)

Test Setup




Test Procedure

EUTs Maximum Conducted Output Power (average) is measured at low, middle, high channels with a Power meter connected to the antenna terminal while the EUTs operating at its maximum power control level.

Add $10 \log (1/x)$, where x is the duty cycle

7.5 Maximum Power Spectral Density (average)

Test Setup



Test Procedure

EUTs Maximum Power Spectral Density (average) is measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level.

The spectrum analyzer setting is as follows.

Center frequency = DTS channel center frequency

Span = at least 1.5 times the DTS bandwidth

RBW : 3 kHz ≤ RBW ≤ 100 kHz

VBW ≥ 3 x RBW

Detector = power averaging (RMS)

Ensure that the number of measurement points = sweep ≥ 2 x span / RBW

Sweep time = auto couple

Employ trace averaging (RMS) = minimum of 100 traces


Add 10 log (1/x), where x is the duty cycle

Use the peak marker function to determine the maximum amplitude level.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.6 Conducted Spurious Emissions

Test Setup



Test Procedure

EUTs Conducted spurious emissions are measured at low, middle, high channels with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

1) Reference Level

Center frequency = DTS channel center frequency

Span $\geq 1.5 \times$ DTS bandwidth

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

2) Unwanted Emissions

Set the center frequency and span to encompass frequency range to be measured.

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Detector = peak

Sweep time = auto couple


Trace mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

7.7 Duty Cycle

Test Setup



Test Procedure

EUTs duty cycle are measured at middle channel with a spectrum analyzer connected to the antenna terminal while the EUTs operating at its maximum power control level. The spectrum analyzer setting is as follows.

Center frequency = Center frequency of the transmission

Span = zero

RBW = 8 MHz

VBW = 8 MHz

Detector = peak

Sweep time = at least 3 ms

Sweep mode = Single

The marker function on the spectrum analyzer is used to determine the duty cycle.

The results of the duty cycle measurement according to the above test procedure.

	Data rate	On time (ms)	On + Off time (ms)	Duty Cycle (%)	Duty Factor (dB)
b mode	1Mbps	8.379	8.440	99.3	0.032
g mode	6Mbps	1.392	1.455	95.7	0.192
n(20MHz)mode	MCS0	1.300	1.363	95.4	0.206
n(40MHz)mode	MCS0	0.647	0.711	91.0	0.410

8. TEST DATA

8.1 Radiated Emissions

FCC §15.209, IC RSS-Gen Issue 5 8.9

Result

Frequency	Reading	Pol*	Antenna Heights	Turntable	AF+CL+Amp	Result	Limit	Margin
(MHz)	(dBμV/m)	(H/V)	(cm)	Angles (°)	(dB)**	(dBμV/m)	(dBμV/m)	(dB)
32.53	41.75	V	100	146	-25.2	16.6	40.0	23.5
180.62	63.84	V	100	76	-26.5	37.3	43.5	6.2
225.78	65.89	V	100	125	-24.1	41.8	46.0	4.2
316.10	60.93	H	100	223	-21.3	39.6	46.0	6.4
792.96	44.64	H	100	216	-12.3	32.3	46.0	13.7

Radiated Measurements at 3meters


Notes:

1. All modes were measured and the worst-case emission was reported.
2. *Pol. H = Horizontal, V = Vertical
3. **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
4. Measurements using CISPR quasi-peak mode below 1 GHz.
5. The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization. The worst data was recorded.
6. 11 channel (2462MHz) in n(20) mode is the worst case.
7. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).
8. The limit is on the FCC §15.209 and RSS-Gen Issue 5 8.9.

PLOTS OF EMISSIONS

Worst Case

Radiated emission below 1GHz_ n(20) mode 2462 MHz



TEST DATA

8.2 6 dB Bandwidth

FCC §15.247(a)(2), IC RSS-247 Issue 2 5.2

Test Mode : Set to Lowest channel, Middle channel and Highest channel,

802.11b mode

Channel	Frequency (MHz)	6 dB modulated bandwidth (MHz)	Limit (MHz)	Margin (MHz)	99% emission bandwidth (MHz)
Lowest	2412	9.05	0.50	8.55	14.09
Middle	2437	9.10	0.50	8.60	14.26
Highest	2462	9.07	0.50	8.57	14.27

802.11g mode

Channel	Frequency (MHz)	6 dB modulated bandwidth (MHz)	Limit (MHz)	Margin (MHz)	99% emission bandwidth (MHz)
Lowest	2412	15.13	0.50	14.63	16.38
Middle	2437	15.12	0.50	14.62	16.39
Highest	2462	15.07	0.50	14.57	16.38

802.11n (20 MHz) mode

Channel	Frequency (MHz)	6 dB modulated bandwidth (MHz)	Limit (MHz)	Margin (MHz)	99% emission bandwidth (MHz)
Lowest	2412	15.12	0.50	14.62	17.52
Middle	2437	15.11	0.50	14.61	17.52
Highest	2462	15.12	0.50	14.62	17.52

TEST DATA


802.11n (40 MHz) mode

Channel	Frequency (MHz)	6 dB modulated bandwidth (MHz)	Limit (MHz)	Margin (MHz)	99% emission bandwidth (MHz)
Lowest	2422	35.13	0.50	34.63	35.92
Middle	2437	35.13	0.50	34.63	35.94
Highest	2452	35.13	0.50	34.63	35.94


PLOTS OF EMISSIONS

802.11b mode

6 dB Bandwidth, 1 Channel (2412 MHz)




6 dB Bandwidth, 6 Channel (2437 MHz)




PLOTS OF EMISSIONS

6 dB Bandwidth, 11 Channel (2462 MHz)




802.11g mode

6 dB Bandwidth, 1 Channel (2412 MHz)




PLOTS OF EMISSIONS

6 dB Bandwidth, 6 Channel (2437 MHz)




6 dB Bandwidth, 11 Channel (2462 MHz)




PLOTS OF EMISSIONS

802.11n (20 MHz) mode

6 dB Bandwidth, 1 Channel (2412 MHz)




6 dB Bandwidth, 6 Channel (2437 MHz)




PLOTS OF EMISSIONS

6 dB Bandwidth, 11 Channel (2462 MHz)




802.11n (40 MHz) mode

6 dB Bandwidth, 3 Channel (2422 MHz)




PLOTS OF EMISSIONS

6 dB Bandwidth, 6 Channel (2437 MHz)



802.11n (40 MHz) mode

6 dB Bandwidth, 9 Channel (2452 MHz)



TEST DATA

8.3 Maximum Conducted Output Power (average) and E.I.R.P

FCC §15.247(b)(3), IC RSS-247 Issue 2 5.4

Test Mode : Set to Lowest channel, Middle channel and Highest channel,

802.11b mode

Channel	Frequency (MHz)	Measured conducted power (dBm)	Duty Factor (dB)	*Maximum Conducted Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	E.I.R.P Limit (dBm)
1	2412	17.94	0.03	17.97	30.00	21.97	36.00
6	2437	17.83	0.03	17.86	30.00	21.86	36.00
11	2462	18.03	0.03	18.06	30.00	22.06	36.00

802.11g mode

Channel	Frequency (MHz)	Measured conducted power (dBm)	Duty Factor (dB)	*Maximum Conducted Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	E.I.R.P Limit (dBm)
1	2412	14.06	0.19	14.25	30.00	18.25	36.00
6	2437	14.01	0.19	14.20	30.00	18.20	36.00
11	2462	14.01	0.19	14.20	30.00	18.20	36.00

TEST DATA

802.11n (20MHz) mode_1Tx

Channel	Frequency (MHz)	Measured conducted power (dBm)	Duty Factor (dB)	*Maximum Conducted Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	E.I.R.P Limit (dBm)
1	2412	12.86	0.21	13.07	30.00	17.07	36.00
6	2437	12.85	0.21	13.06	30.00	17.06	36.00
11	2462	12.84	0.21	13.05	30.00	17.05	36.00

802.11n (20MHz) mode_2Tx

Channel	Frequency (MHz)	Measured conducted power (dBm)		Duty Factor (dB)	*Maximum Conducted Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	E.I.R.P Limit (dBm)
		Ant 0	Ant 1		Total output power			
1	2412	9.35	10.03	0.21	12.92	30.00	16.92	36.00
6	2437	9.38	10.13	0.21	12.99	30.00	16.99	36.00
11	2462	9.01	10.15	0.21	12.83	30.00	16.83	36.00

802.11n (40MHz) mode_1Tx

Channel	Frequency (MHz)	Measured conducted power (dBm)	Duty Factor (dB)	*Maximum Conducted Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	E.I.R.P Limit (dBm)
3	2422	10.87	0.41	11.28	30.00	15.28	36.00
6	2437	10.71	0.41	11.12	30.00	15.12	36.00
9	2452	10.69	0.41	11.10	30.00	15.10	36.00

TEST DATA

802.11n (40MHz) mode_2Tx

Channel	Frequency (MHz)	Measured conducted power (dBm)		Duty Factor (dB)	*Maximum Conducted Power (dBm)	Limit (dBm)	E.I.R.P (dBm)	E.I.R.P Limit (dBm)
		Ant 0	Ant 1		Total output power			
3	2422	10.17	10.24	0.41	13.63	30.00	17.63	36.00
6	2437	10.20	10.16	0.41	13.60	30.00	17.60	36.00
9	2452	10.24	10.26	0.41	13.67	30.00	17.67	36.00

Note:

- *Maximum Conducted (average) Power = Measured conducted power + Duty Factor
- Total output power = $10 \log [10^{\{(Chain\ 0\ Power + duty\ factor)/10\}} + 10^{\{(Chain\ 1\ Power + duty\ factor)/10\}} + 10^{\{(Chain\ 2\ Power + duty\ factor)/10\}} + 10^{\{(Chain\ 3\ Power + duty\ factor)/10\}}]$
- For CDD transmission, directional gain is. **4.0 dBi**.
For MIMO transmission, directional gain is **4.0 dBi**.
Directional gain was calculated according to KDB662911 D01 Multiple Transmitter Output v02r01.
For power measurements on IEEE 802.11 devices employing CDD, directional gain is as follows,
Directional gain = $G_{ANT} + Array\ Gain = 4.0\ dBi + 0\ dB = 4.0\ dBi$.
Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;
Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;
Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{ANT} \geq 5$.
For power measurements on all devices employing MIMO, directional gain is as follows,
Directional gain = $G_{ANT} + 10 \log(N_{ANT}/N_{SS})\ dBi = 4.0\ dBi + 10 \log(2/2)\ dB = 4.0\ dBi$.
where N_{SS} = the number of independent spatial streams of data and G_{ANT} is the antenna gain in dBi
For this device, MIMO mode means SM-MIMO(Spatial Multiplexing) transmission and $N_{SS}=2$.
- E.I.R.P was calculated by following equation according to KDB412172 D01 Determining ERP and EIRP v01
 $E.I.R.P = P_T + G_T - L_C$
 P_T = Transmitter outputpower (dBm)
 G_T = Gain of the transmitting antenna in dBi, Directional antenna gain is **4.0 dBi**.
 L_C = Signal attenuation in the connecting cable between the transmitter and antenna in dB. This factor of an integral antenna is negligible.
- The following equation was used for spectrum offset:
Spectrum offset (dB) = Attenuator (dB) + Cable Loss (dB) + SMA Type Connector Loss (dB)

TEST DATA

8.4 Maximum Power Spectral Density (average)

FCC §15.247(e), IC RSS-247 Issue 2 5.2

Test Mode : Set to Lowest channel, Middle channel and Highest channel,

802.11b mode

Channel	Frequency (MHz)	Measured PSD (dBm/100kHz)	Duty Factor (dB)	*Maximum PSD (dBm/100kHz)	Limit (dBm/3kHz)
1	2412	1.01	0.03	1.04	8.00
6	2437	1.01	0.03	1.04	8.00
11	2462	1.08	0.03	1.11	8.00

802.11g mode

Channel	Frequency (MHz)	Measured PSD (dBm/100kHz)	Duty Factor (dB)	*Maximum PSD (dBm/100kHz)	Limit (dBm/3kHz)
1	2412	-4.83	0.19	-4.64	8.00
6	2437	-4.69	0.19	-4.50	8.00
11	2462	-4.44	0.19	-4.25	8.00

TEST DATA

802.11n (20 MHz) mode_1Tx

Channel	Frequency (MHz)	Measured PSD (dBm/100kHz)	Duty Factor (dB)	*Maximum PSD (dBm/100kHz)	Limit (dBm/3kHz)
1	2412	-6.03	0.21	-5.82	8.00
6	2437	-6.01	0.21	-5.80	8.00
11	2462	-5.89	0.21	-5.68	8.00

802.11n (20 MHz) mode_2Tx

Channel	Frequency (MHz)	Measured PSD (dBm/100kHz)	Duty Factor (dB)	*Maximum PSD (dBm/100kHz)	Limit (dBm/3kHz)
1	2412	-8.06	0.21	-4.84	8.00
6	2437	-8.06	0.21	-4.84	8.00
11	2462	-8.26	0.21	-5.04	8.00

802.11n (40 MHz) mode_1Tx

Channel	Frequency (MHz)	Measured PSD (dBm/100kHz)	Duty Factor (dB)	*Maximum PSD (dBm/100kHz)	Limit (dBm/3kHz)
3	2422	-10.96	0.41	-10.55	8.00
6	2437	-11.28	0.41	-10.87	8.00
9	2452	-11.61	0.41	-11.20	8.00

TEST DATA

802.11n (40 MHz) mode_2TX

Channel	Frequency (MHz)	Measured PSD (dBm/100kHz)	Duty Factor (dB)	*Maximum PSD (dBm/100kHz)	Limit (dBm/3kHz)
3	2422	-11.87	0.41	-8.45	8.00
6	2437	-11.93	0.41	-8.51	8.00
9	2452	-11.5	0.41	-8.08	8.00


Note:

- *Maximum PSD = Measured PSD + Duty Factor
- "Measure and add $10 \log(N_{ANT})$ dB, where N_{ANT} is the number of outputs" was used for measuring in-band Total PSD.
Total PSD = Measured PSD + duty factor + $10 \log(N_{ANT})$
- For CDD transmission, directional gain is. **7.01 dBi**. For MIMO transmission, directional gain is **4.0 dBi**.
Directional gain was calculated according to KDB662911 D01 Multiple Transmitter Output v02r01.
For PSD measurements on all devices employing CDD, directional gain is as follows,
Directional gain = G_{ANT} + Array Gain = 4.0 dBi + 3.01 dB = 7.01 dBi
Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB = $10 \log(2/1)$ = 3.01 dB.
where N_{SS} = the number of independent spatial streams of data and G_{ANT} is the antenna gain in dBi.
For CDD mode of this device, $N_{SS}=1$.
For PSD measurements on all devices employing MIMO, directional gain is as follows,
Directional gain = G_{ANT} + $10 \log(N_{ANT}/N_{SS})$ dBi = 4.0 dBi + $10 \log(2/2)$ dB = 4.0 dBi.
where N_{SS} = the number of independent spatial streams of data and G_{ANT} is the antenna gain in dBi
For this device, MIMO mode means SM-MIMO(Spatial Multiplexing) transmission and $N_{SS}=2$.
- The following equation was used for spectrum offset:
Spectrum offset (dB) = Attenuator (dB) + Cable Loss (dB) + SMA Type Connector Loss (dB)


PLOTS OF EMISSIONS

802.11b mode

Maximum Power Spectral Density, 1 Channel (2412 MHz)




Maximum Power Spectral Density, 6 Channel (2437 MHz)




PLOTS OF EMISSIONS

Maximum Power Spectral Density, 11 Channel (2462 MHz)




802.11g mode

Maximum Power Spectral Density, 1 Channel (2412 MHz)




PLOTS OF EMISSIONS

Maximum Power Spectral Density, 6 Channel (2437 MHz)




Maximum Power Spectral Density, 11 Channel (2462 MHz)




PLOTS OF EMISSIONS

802.11n (20 MHz) mode

Maximum Power Spectral Density, 1 Channel (2412 MHz)




Maximum Power Spectral Density, 6 Channel (2437 MHz)




PLOT OF TEST DATA

Maximum Power Spectral Density, 11 Channel (2462 MHz)




802.11n (20 MHz) mode 2TX

Maximum Power Spectral Density, 1 Channel (2412 MHz)




PLOT OF TEST DATA

Maximum Power Spectral Density, 6 Channel (2437 MHz)




Maximum Power Spectral Density, 11 Channel (2462 MHz)




PLOT OF TEST DATA

802.11n (40 MHz) mode

Maximum Power Spectral Density, 3 Channel (2422 MHz)




Maximum Power Spectral Density, 6 Channel (2437 MHz)




PLOT OF TEST DATA

Maximum Power Spectral Density, 9 Channel (2452 MHz)




802.11n (40 MHz) mode 2TX

Maximum Power Spectral Density, 3 Channel (2422 MHz)




PLOT OF TEST DATA

Maximum Power Spectral Density, 6 Channel (2437 MHz)



Maximum Power Spectral Density, 9 Channel (2452 MHz)



TEST DATA

8.5 Conducted Spurious Emissions

FCC §15.247(d), IC RSS-247 Issue 2 5.5

Test Mode : Set to Lowest channel, Middle channel and Highest channel,

802.11b mode

Channel	Frequency (MHz)	Reference Level (dBm/100kHz)	Conducted Spurious Emissions (dBc)	Limit (dBc)
1	2412	8.55	More than 30 dBc	30
6	2437	8.41	More than 30 dBc	30
11	2462	8.65	More than 30 dBc	30

802.11g mode

Channel	Frequency (MHz)	Reference Level (dBm/100kHz)	Conducted Spurious Emissions (dBc)	Limit (dBc)
1	2412	4.46	More than 30 dBc	30
6	2437	4.29	More than 30 dBc	30
11	2462	4.52	More than 30 dBc	30

802.11n (20 MHz) mode

Channel	Frequency (MHz)	Reference Level (dBm/100kHz)	Conducted Spurious Emissions (dBc)	Limit (dBc)
1	2412	3.38	More than 30 dBc	30
6	2437	3.36	More than 30 dBc	30
11	2462	3.40	More than 30 dBc	30

TEST DATA

802.11n (40 MHz) mode

Channel	Frequency (MHz)	Reference Level (dBm/100kHz)	Conducted Spurious Emissions (dBc)	Limit (dBc)
3	2422	3.01	More than 30 dBc	30
6	2437	3.03	More than 30 dBc	30
9	2452	2.73	More than 30 dBc	30

802.11n (20 MHz) mode 2TX

Channel	Frequency (MHz)	Reference Level (dBm/100kHz)	Conducted Spurious Emissions (dBc)	Limit (dBc)
1	2412	0.09	More than 30 dBc	30
6	2437	0.19	More than 30 dBc	30
11	2462	0.01	More than 30 dBc	30

802.11n (40 MHz) mode 2TX

Channel	Frequency (MHz)	Reference Level (dBm/100kHz)	Conducted Spurious Emissions (dBc)	Limit (dBc)
3	2422	-2.51	More than 30 dBc	30
6	2437	-2.56	More than 30 dBc	30
9	2462	-2.43	More than 30 dBc	30


Notes:

The cable and attenuator loss from 30 MHz to 26.5 GHz was reflected in spectrum analyzer with correction factor for the spurious emissions test.


PLOTS OF EMISSIONS

802.11b mode

Reference Power Spectral Density, 1 Channel (2412 MHz)




Band Edge, 1 Channel (2412 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2412 MHz)




Reference Power Spectral Density, 6 Channel (2437 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2437 MHz)




Reference Power Spectral Density, 11 Channel (2462 MHz)




PLOTS OF EMISSIONS

Band Edge, 11 Channel (2462 MHz)




Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2462 MHz)




PLOTS OF EMISSIONS

802.11g mode

Reference Power Spectral Density, 1 Channel (2412 MHz)




Band Edge, 1 Channel (2412 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2412 MHz)




Reference Power Spectral Density, 6 Channel (2437 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2437 MHz)




Reference Power Spectral Density, 11 Channel (2462 MHz)




PLOTS OF EMISSIONS

Band Edge, 11 Channel (2462 MHz)




Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2462 MHz)




PLOTS OF EMISSIONS

802.11n (20MHz) mode

Reference Power Spectral Density, 1 Channel (2412 MHz)




Band Edge, 1 Channel (2412 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2412 MHz)




Reference Power Spectral Density, 6 Channel (2437 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2437 MHz)




Reference Power Spectral Density, 11 Channel (2462 MHz)




PLOTS OF EMISSIONS

Band Edge, 11 Channel (2462 MHz)




Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2462 MHz)




PLOTS OF EMISSIONS

802.11n (40MHz) mode

Reference Power Spectral Density, 3 Channel (2422 MHz)




Band Edge, 3 Channel (2422 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2422 MHz)




Reference Power Spectral Density, 6 Channel (2437 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2437 MHz)




Reference Power Spectral Density, 9 Channel (2452 MHz)




PLOTS OF EMISSIONS

Band Edge, 9 Channel (2452 MHz)




Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2452 MHz)




PLOTS OF EMISSIONS

802.11n (20MHz) mode 2TX

Reference Power Spectral Density, 1 Channel (2412 MHz)




Band Edge, 1 Channel (2412 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2412 MHz)




Reference Power Spectral Density, 6 Channel (2437 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2437 MHz)




Reference Power Spectral Density, 11 Channel (2462 MHz)




PLOTS OF EMISSIONS

Band Edge, 11 Channel (2462 MHz)




Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2462 MHz)




PLOTS OF EMISSIONS

802.11n (40MHz) mode 2TX

Reference Power Spectral Density, 3 Channel (2422 MHz)




Band Edge, 3 Channel (2422 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2422 MHz)




Reference Power Spectral Density, 6 Channel (2437 MHz)




PLOTS OF EMISSIONS

Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2437 MHz)




Reference Power Spectral Density, 9 Channel (2452 MHz)




PLOTS OF EMISSIONS

Band Edge, 9 Channel (2452 MHz)



Conducted Spurious Emissions, 30 MHz ~ 26.5 GHz (2452 MHz)



TEST DATA

8.6 Radiated Spurious Emissions

FCC §15.247(d), IC RSS-247 Issue 2 5.5

Test Mode : Set to Lowest channel, Middle channel and Highest channel,

802.11n(20) mode

1 Channel

Frequency (M Hz)	Reading (dBμV)	Polar (H/V)	mode	AF+CL+Am p (dB)**	Result (dBμV/m)	Lim it (dBμV/m)	M arg in (dB)
4849.17	44.1	H	peak	12	45.3	74.0	28.7

6 Channel

Frequency (M Hz)	Reading (dBμV)	Polar (H/V)	mode	AF+CL+Am p (dB)**	Result (dBμV/m)	Lim it (dBμV/m)	M arg in (dB)
7582.33	43.2	V	peak	8.8	52.0	74.0	22.0

11 Channel

Frequency (M Hz)	Reading (dBμV)	Polar (H/V)	mode	AF+CL+Am p (dB)**	Result (dBμV/m)	Lim it (dBμV/m)	M arg in (dB)
2774.80	60.9	V	peak	-7.2	53.7	74.0	20.4

TEST DATA

Note:


1. *Pol. H = Horizontal V = Vertical
2. **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
3. Average measurement was not performed when peak-detected emission complies with the average limit.
4. Other spurious was under 30 dB below Fundamental.
5. 11 channel (2462MHz) in n(20) mode was the worst condition. For other modes, peak-detected emissions have enough margin more than 20dBc, therefore the results were not recorded in this report
6. The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization. The worst data was recorded.
7. Peak emissions were measured using RBW = 1 MHz, VBW = 3 MHz, Detector = Peak.
8. Average emissions were measured using RBW = 1 MHz, VBW = 10 kHz, Detector = Peak.
9. The spectrum was measured from 9 kHz to 10th harmonic and the worst-case emissions were reported. No significant emissions were found beyond the 3rd harmonic for this device.

PLOTS OF EMISSIONS


Worst Case

802.11n(20) mode

11 channel : 1 GHz to 8 GHz_Peak




11 channel : 8 GHz to 18 GHz_Peak




PLOTS OF EMISSIONS

11 channel : 8 GHz to 18 GHz_Average



11 channel : 18 GHz to 26.5 GHz_Peak



TEST DATA

8.7 Radiated Band Edge

FCC §15.247(d), IC RSS-247 Issue 2 5.5

Test Mode : Set to Lowest channel and Highest channel

802.11n(20MHz) mode

1 Channel

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	mode	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2389.76	75.7	H	peak	-7.8	67.9	74.0	6.1
2389.76	59.3	H	average	-7.8	51.5	54.0	2.5
2390.00	70.6	H	peak	-7.8	62.8	74.0	11.2
2390.00	60.1	H	average	-7.8	52.3	54.0	1.7

11 Channel

Frequency (MHz)	Reading (dBμV)	Pol* (H/V)	mode	AF+CL+Amp (dB)**	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2383.50	72.1	H	peak	-7.6	64.5	74.0	9.5
2383.50	57.6	H	average	-7.6	50.0	54.0	4.0
2483.99	73.4	H	peak	-7.6	65.8	74.0	8.2
2483.99	57.6	H	average	-7.6	50.0	54.0	4.0

Note:


- *Pol. H = Horizontal V = Vertical
- **AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.
- Other spurious was under 30 dB below Fundamental.
- Lowest channel (2412MHz) in n(20MHz) mode was the worst condition.
- The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization. The worst data was recorded.
- Peak emissions were measured using RBW = 1 MHz, VBW = 3 MHz, Detector = Peak.
- Average emissions were measured using RBW = 1 MHz, VBW = 10 kHz, Detector = Peak.

PLOT OF TEST DATA


Worst Case

802.11n (20 MHz) mode

1 channel_Peak



1 channel_Average



9. TEST EQUIPMENT

No.	Instrument	Manufacturer	Model	Serial No.	Calibration Date	Calibration Interval
1	*Test Receiver	R & S	ESU 40	100202	Apr. 02 2019	1 year
2	Test Receiver	R & S	ESCS30	100302	Oct. 11 2018	1 year
3	*Attenuator	PASTERNAK	PE7395-10	1441-1	Jul. 11 2019	1 year
4	*Attenuator	FAIRVIEW	SA3N5W-06	N/A	Apr. 03 2019	1 year
5	*Attenuator	FAIRVIEW	SA3N5W-10	N/A	Apr. 03 2019	1 year
6	Attenuator	WEINSCHL	56-10	58765	Oct. 12 2018	1 year
7	*Amplifier	R & S	SCU 01	10029	Apr. 02 2019	1 year
8	*Amplifier	R & S	SCU18F	180025	Apr. 02 2019	1 year
9	*Amplifier	R & S	SCU26	10011	Jul. 15 2019	1 year
10	Amplifier	R & S	SCU40	100380	Jul. 15 2019	1 year
11	Spectrum Analyzer	R & S	FSW43	100732	Apr. 02 2019	1 year
12	*Spectrum Analyzer	Agilent	E4440A	MY44022567	Oct. 11 2018	1 year
13	*Spectrum Analyzer	R & S	FSW43	104084	Apr. 02 2019	1 year
14	*Loop Antenna	R & S	HFH2-Z2	100279	Feb. 13 2019	2 year
15	*Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-474	Jun. 28 2019	2 year
16	*Horn Antenna	Q-par Angus	QSH20S20	8179	Aug. 01 2017	2 year
17	Horn Antenna	Q-par Angus	QSH22K20	8180	Aug. 02 2017	2 year
18	*Trilog-Broadband Antenna	SCHWARZBECK	VULB 9163	946	May. 18 2019	2 year
19	LISN	R & S	ESH3-Z5	833874/006	Oct. 12 2018	1 year
20	*Position Controller	INNCO	CO2000	12480406/L	N/A	N/A
21	*Controller	INNCO	CO3000	CO3000/937/38330516/L	N/A	N/A
22	*Turn Table	INNCO	DS1200S	N/A	N/A	N/A
23	*Turn Table	INNCO	DT2000-2t	N/A	N/A	N/A
24	*Antenna Mast	INNCO	MA4000	N/A	N/A	N/A
25	*TILT Antenna Mast	INNCO	MA4640-XP-EP	N/A	N/A	N/A
26	*Open Switch And Control Unit	R & S	OSP-120	100081	N/A	N/A
27	*Open Switch And Control Unit	R & S	OSP-120	101766	N/A	N/A
28	*Shielded Room	Seo-Young EMC	N/A	N/A	N/A	N/A
29	*Anechoic Chamber	Seo-Young EMC	N/A	N/A	N/A	N/A
30	*WiFi Filter Bank	R & S	U083	N/A	N/A	N/A
31	*WiFi Filter Bank	R & S	U082	N/A	N/A	N/A

*) Test equipment used during the test

10. ACCURACY OF MEASUREMENT

The Measurement Uncertainties stated were calculated in accordance with the requirements of measurement uncertainty contained in CISPR 16-4-2 with the confidence level of 95%

1. Conducted Uncertainty Calculation

Source of Uncertainty	X_i	Uncertainty of X_i		Coverage factor k	$u(X_i)$ (dB)	C_i	$C_i u(X_i)$ (dB)
		Value (dB)	Probability Distribution				
Receiver reading	RI	± 0.1	normal 1	1.000	0.1	1	0.1
Attenuation AMN-Receiver	LC	± 0.08	normal 2	2.000	0.04	1	0.04
AMN Voltage division factor	LAMN	± 0.8	normal 2	2.000	0.4	1	0.4
Sine wave voltage	dVSW	± 2.00	normal 2	2.000	1.00	1	1.00
Pulse amplitude response	dVPA	± 1.50	rectangular	1.732	0.87	1	0.87
Pulse repetition rate response	dVPR	± 1.50	rectangular	1.732	0.87	1	0.87
Noise floor proximity	dVNF	± 0.00	-	-	0.00	1	0.00
AMN Impedance	dZ	± 1.80	triangular	2.449	0.73	1	0.73
Ⓐ Mismatch	M	+ 0.70	U-Shaped	1.414	0.49	1	0.49
Ⓑ Mismatch	M	- 0.80	U-Shaped	1.414	- 0.56	1	- 0.56
Measurement System Repeatability	RS	0.05	normal 1	1.000	0.05	1	0.05
Remark	Ⓐ: AMN-Receiver Mismatch : + Ⓑ: AMN-Receiver Mismatch : -						
Combined Standard Uncertainty	Normal			± 1.88			
Expanded Uncertainty U	Normal ($k = 2$)			± 3.76			

2. Radiation Uncertainty Calculation

Source of Uncertainty	X_i	Uncertainty of X_i		Coverage factor k	$u(X_i)$ (dB)	C_i	$C_i u(X_i)$ (dB)
		Value (dB)	Probability Distribution				
Measurement System Repeatability	RS	0.34	normal 1	1.00	0.34	1	0.34
Receiver reading	Ri	± 0.02	normal 2	2.00	0.01	1	0.01
Sine wave voltage	dVsw	± 0.17	normal 2	2.00	0.09	1	0.09
Pulse amplitude response	dVpa	± 0.92	normal 2	2.00	0.46	1	0.46
Pulse repetition rate response	dVpr	± 0.35	normal 2	2.00	0.18	1	0.18
Noise floor proximity	dVnf	± 0.50	normal 2	2.00	0.25	1	0.25
Antenna Factor Calibration	AF	± 2.00	rectangular	$\sqrt{3}$	1.15	1	1.15
Cable Loss	CL	± 1.00	normal 2	2.00	0.50	1	0.50
Antenna Directivity	AD	± 0.00	rectangular	$\sqrt{3}$	0.00	1	0.00
Antenna Factor Height Dependence	AH	± 2.00	rectangular	$\sqrt{3}$	1.15	1	1.15
Antenna Phase Centre Variation	AP	± 0.20	rectangular	$\sqrt{3}$	0.12	1	0.12
Antenna Factor Frequency Interpolation	Ai	± 0.25	rectangular	$\sqrt{3}$	0.14	1	0.14
Site Imperfections	Si	± 4.00	triangular	$\sqrt{6}$	1.63	1	1.63
Measurement Distance Variation	DV	± 0.60	rectangular	$\sqrt{3}$	0.35	1	0.35
Antenna Balance	Dbal	± 0.90	rectangular	$\sqrt{3}$	0.52	1	0.52
Cross Polarisation	DCross	± 0.00	rectangular	$\sqrt{3}$	0.00	1	0.18
Mismatch	M	+ 0.98 - 1.11	U-Shaped	$\sqrt{2}$	0.74	1	0.74
EUT Volume Diameter	Vd	0.33	normal 1	1.00	0.33	1	0.11
Remark							
Combined Standard Uncertainty	Normal						
Expanded Uncertainty U	Normal ($k = 2$)						