



FINAL
PRODUCT SPECIFICATION
& PERFORMANCE TEST
2016-1
RETRACTABLE SNAP-IN ANTENNA

This AVANTEGO retractable snap-in antenna is developed to be used as a mobile phone antenna. The performance is optimised for the **Standard Telecom, NXC-3200, CDMA/AMPS handset.**

Document No: 2016-1 issue 5

21 July 2000

Mechanical Development

21 July 2000

RF Development

Jan Sjöholm
Manager Mechanical development

Approved 21 July 2000
AVANTEGO AB

Pär Berglund
Manager RF development & Technical support

Approved _____
R &D Center
STANDARD TELECOM

Anders Sandgren
Manager Project & Sales Manager

Approved _____
Inspection Quality Control
STANDARD TELECOM

1: ELECTRICAL SPECIFICATION	PAGE
1:1 Frequency range	3
1:2 Handset	3
1:3 Matching circuit	3
1:4 VSWR	4
1:5 Gain	4
1:6 Power rating	4
 2: MECHANICAL SPECIFICATION	
2:1 Appearance	5
2:2 Helical deformation	5
2:3 Torque	5
2:4 Force on Contact Spring	5
2:5 Drop	6
2:6 Tension Load	6
2:7 Extension and Retraction Forces	6
2:8 Operating temperature	6
2:9 Temperature cycling	7
2:10 Humidity	7
 3: PERFORMANCE TEST	
3:1 VSWR	8
3:2 Radiation	8
3:3 Power Rating	9
3:4 Helix deformation	10
3:5 Torque	10
3:6 Force on Contact Spring	11
3:7 Drop	11
3:8 Tension Load	11
3:9 Extension and Retraction Forces	11
3:10 Operating temperature	11
3:11 Temperature cycling	12
3:12 Humidity	12
 4: LOG OF CHANGES	13
5: SPECIFICATION DRAWING	14



ELECTRICAL SPECIFICATION

1:1 FREQUENCY RANGE

Frequency range:
824-894 MHz

1:2 HANDSET

Handset number:
AVANTEGO No: AL101
Received at AVANTEGO: 000302

Note: This specification is only valid with the handset and PCB above.

1:3 MATCHING CIRCUIT

Feed-12nH shunt-2.2nH series-1pF shunt-antenna

Note: This specification is only valid with matching circuit above.

1:4 VSWR

Typical values in free space for retracted antenna:

824-894 MHz VSWR < 1.8:1

Maximum values in free space for retracted antenna:

824-894 MHz VSWR < 2.5:1

Typical values in talk position for retracted antenna:

824-894 MHz VSWR < 2:1

Typical values in free space for extended antenna:

824-894 MHz VSWR < 1.4:1

Maximum values in free space for extended antenna:

824-894 MHz VSWR < 1.8:1

Typical values in talk position for extended antenna:

824-894 MHz VSWR < 1.8:1

1:5 GAIN

Typical values in maximum direction for retracted antenna:

824-894 MHz -2.2 dBd

Minimum values in maximum direction for retracted antenna:

824-894 MHz -3.5 dBd

Typical values in maximum direction for extended antenna:

824-894 MHz -1 dBd

Minimum values in maximum direction for extended antenna:

824-894 MHz -1.5 dBd

1:6 POWER RATING

Maximum input power:

824-894 MHz 2W

Demands:

No visual deformation is allowed, and the antenna must meet the electrical specification after the test.

MECHANICAL SPECIFICATION

2:1 APPEARANCE

Demands

The appearance shall be according to the product specification drawing [2016-1](#) issue 7 on page 14.

2:2 HELICAL DEFORMATION

Demands

Angle (α): [30°](#)
Bending Force (F) [30N](#)

The antenna must meet the electrical specification and remain mechanically bounded after the test.
Only minor non reversible deformations is allowed.

2:3 TORQUE

Typical value

T=[10](#) Ncm

The antenna must meet the electrical specification and remain mechanically bounded after the test. Only minor non reversible deformations is allowed.

2:4 Force on Contact Spring

Demands

F=[5](#) N

The antenna must meet the electrical specification and remain mechanically bounded after the test.

2:5 DROP

Demands

Drop Height	150cm
Handset weight	160g
Angle	0°

The antenna must meet the electrical specification and remain mechanically bounded after the test.

Only minor non reversible deformations is allowed.

2:6 TENSION LOAD

Demands

Between cover and frame	50N
Between whip and helix	50N

The antenna must meet the electrical specification and remain mechanically bounded after the test.

Only minor non reversible deformations is allowed.

2:7 EXTENSION AND RETRACTION FORCES

Demands

Extension from retracted position	0,2-5,0N
Retraction from extended position	0,2-5,0N

The demands is valid up to 10 000 cycles.

2:8 OPERATING TEMPERATURE

Demands

-20°C to 70°C

No visual deformation is allowed, and the antenna must operate properly during the test.

2:9 TEMPERATURE CYCLING

Demands

Low cycling temperature	-40°C
High cycling temperature	70°C

No visual deformation is allowed, and the antenna must meet the specification after the test.

2:10 HUMIDITY

Demands

Relative humidity	95%
Temperature	55°C

No visual deformation is allowed, and the antenna must satisfy the electrical specification after the test.

PERFORMANCE TEST


3:1 VSWR



The VSWR is measured with a network analyser or other equipment with same or better accuracy as HP 8753D network analysers.

Free space means that the antenna and mobile phone is placed on a non absorbing non reflecting material in an environment suitable for measurements on antennas. *Talk position* means that the phone is measured in user position. The talk position VSWR measurements is performed when a person is holding the phone in a typical user position.

3:2 RADIATION

The radiation measurements are performed in an anechoic chamber. Three different planes are measured. E1-plane (*picture 3:2A*), E2-plane (*picture 3:2B*) and H-plane (*picture 3:2C*).





3:3 POWER RATING

A 2W cw signal from a signal generator/amplifier is connected, through a power meter to the antenna for 10 minutes at room temperature.


3:4 HELIX DEFORMATION

The test object is placed in a test jig.

A force (F) is applied perpendicular to the antenna, 10mm from the top until the specified force (F) or angle (α) is reached. (picture 3:4A)

3:5 TORQUE

The test object is placed in a test jig. A torque measurement instrument is attached to the test object. The test object is exposed to the specified torque. (picture 3:5A)



3:6 FORCE ON CONTACT SPRING

The test object is placed in a test jig.

A force (F) is applied on the contact spring in axial direction. The force (F) is increased until the contact spring releases from the antenna.

3:7 DROP

The retracted antenna is attached to a test fixture with a specified weight, and is after that dropped from a specified height and with specified angle. This is repeated with the same antenna in extended position.

3:8 TENSION LOAD

The antenna is placed in a test jig. A force measurement instrument is attached to the cover. The cover is exposed to the specified force. Then the whip is exposed to the specified force.

3:9 EXTENSION AND RETRACTION FORCES

The antenna is placed in a test jig. A force measurement instrument is attached to the whip. The antenna is extended from retracted position.

The whip is locked in extended position. The antenna is pushed down from extended position using a force measurement instrument.

3:10 OPERATING TEMPERATURE

The test is performed in a climatic chamber.

VSWR is measured at lowest and highest specified temperature

3:11 TEMPERATURE CYCLING

The test is performed in a climatic chamber.

The temperature is cycled between “Low cycling temperature” and “High cycling temperature” 10 times. Between every cycling the temperature is kept constantly at “Low cycling temperature” and “High cycling temperature” for one hour. Start and end temperature is room temperature (approximately 20°C)

Room temperature ↻ 10 times (Low cycling temperature for one hour ↻ High cycling temperature for one hour) ↻ Room temperature


3:12 HUMIDITY

The test object is placed in a and climatic chamber with specified humidity for 24 hours. After that it's kept in room temperature for 24 hours.

The antenna must satisfy the electrical demands after the test.

4 LOG OF CHANGES

Issue	Item	From	To
4	Page 1	CDMA	CDMA/AMPS
5	Page 1	AirLinx	Standard Telecom



5	PVC	Colour acc. to NCS: S-6500N
4	Stainless steel	Gold plated
3	Zytel	Surface acc. to Charmilles VDI 3400 No. 30. Colour acc. to NCS: S-6500N
2	Delrin	Surface acc. to Charmilles VDI 3400 No. 30. Colour Black
1	Santoprene 103-40	Surface acc. to Charmilles VDI 3400 No. 33. Colour acc. to NCS: S-6500N
Item	Material	Note