

RF Exposure Report

Report No.: SA130523E10B

FCC ID: MCLJ20H076

Test Model: J20H076

Received Date: Sep. 14, 2015

Test Date: Oct. 05, 2015

Issued Date: Oct. 21, 2015

Applicant: HON HAI PRECISION IND. CO., LTD.

Address: 5F-1,5 Hsin-An Road Hsinchu, Science-Based Industrial Park Taiwan,
R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

Test Location (3): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	5
3 Calculation Result of Maximum Conducted Power	6



A D T

Release Control Record

Issue No.	Description	Date Issued
SA130523E10B	Original release.	Oct. 21, 2015

1 Certificate of Conformity

Product: 802.11abgn wireless module

Brand: FOXCONN

Test Model: J20H076

Sample Status: ENGINEERING SAMPLE

Applicant: HON HAI PRECISION IND. CO., LTD.

Test Date: Oct. 05, 2015

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** Oct. 21, 2015
Elsie Hsu / Specialist

Approved by :  , **Date:** Oct. 21, 2015
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

1. The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Brand	Model	Antenna Type	Antenna Gain (dBi)	Connector	Frequency range (MHz to MHz)
Chain (0)	NA	NA	PCB	3.10	Murata	2400~2483.5
				4.51		5150~5350
				4.75		5470~5725
				4.80		5725~5845
Chain (1)	NA	NA	PCB	3.18	Murata	2400~2483.5
				4.54		5150~5350
				4.78		5470~5725
				4.98		5725~5845

3 Calculation Result of Maximum Conducted Power

The Max power (except U-NII-3 band) was refer to the original test report.

For 15.247(2.4GHz):

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	657.863	6.15	20	0.53934	1

NOTE:

$$2.4\text{GHz: Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 6.15\text{dBi}$$

For 15.407(5GHz):

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
5180-5240 5260-5320 5500-5580 & 5660-5700	235.624	7.78	20	0.28116	1
5745 ~ 5825	87.007	7.9	20	0.10673	1

NOTE:

$$5150\sim 5350\text{MHz: Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 7.52\text{dBi}$$

$$5470\sim 5725\text{MHz: Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 7.78\text{dBi}$$

$$5725\sim 5845\text{MHz: Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 7.9\text{dBi}$$

--- END ---