VHF 136-174 MHz

MODEL FREQUENCY (MHz)
LM150B 144 - 174

SPECIFICATIONS

Black coil and field tunable black whip for LM mounts, 144 - 174 MHz.

Black coil and field tun-

Black coil and field tun-

able unplated stainless

whip for LM mounts,

144 - 174 MHz.

able chrome whip for LM mounts, 144 - 174 MHz.

GAIN 3 dBd / 5.2 dBi
TYPE 5/8 wave
VSWR (see bandwidth) 1.5:1 or less

BANDWIDTH @ 1.5 3%
BANDWIDTH @ 2.0 6%
POWER RATING 200 Watts
COLOR Black

WHIP W490B, .100 tapered COAX Order separately

MAX HEIGHT 51 3/4"



LM150C 144 - 174

SPECIFICATIONS

GAIN 3 dBd / 5.2 dBi
TYPE 5/8 wave
VSWR (see bandwidth) 1.5:1 or less
RANDWIDTH @ 1.5

BANDWIDTH @ 1.5 3%
BANDWIDTH @ 2.0 6%
POWER RATING 200 Watts
COLOR Black/Chrome
WHIP W490, .100 tapered
COAX Order separately

MAX HEIGHT 51 3/4"



 MODEL
 FREQUENCY (MHz)

 LM150U
 144 - 174

SPECIFICATIONS

GAIN 3 dBd / 5.2 dBi
TYPE 5/8 wave
VSWR (see bandwidth) 1.5:1 or less

BANDWIDTH @ 1.5 3% BANDWIDTH @ 2.0 6%

POWER RATING 200 Watts
COLOR Black/Chrome

WHIP W490U, .100 tapered COAX Order separately

MAX HEIGHT 51 3/4"



66