

From: Eva Kao [eva\_kao@cclab.com.tw]  
Sent: Tuesday, October 15, 2002 2:32 AM  
To: Mike Kuo  
Subject: Re: Win Far Technology Co., Ltd., FCC ID:MDXRF1012, AN02T2316

Hi Mike,

Please find the attached is new version of operation description for your reference.

Thanks!  
Eva

----- Original Message -----

From: "Mike Kuo" <MKUO@CCSEMC.com>  
To: "'Eva Kao'" <eva\_kao@cclab.com.tw>  
Sent: Tuesday, October 15, 2002 1:35 PM  
Subject: RE: Win Far Technology Co., Ltd., FCC ID:MDXRF1012, AN02T2316

> Hi Eva:  
>  
> Take a look the operational description. Why it mention pulse code ?  
>  
> M.Kuo  
>  
> -----Original Message-----  
> From: Eva Kao [mailto:eva\_kao@cclab.com.tw]  
> Sent: Monday, October 14, 2002 8:15 PM  
> To: Mike Kuo  
> Subject: Re: Win Far Technology Co., Ltd., FCC ID:MDXRF1012, AN02T2316  
>  
>  
> Dear Mike  
>  
> Yes, I know your means. But we had discussed this question with the  
> manufacturer.  
> This Device is not pulse modulation. It is Frequency Modulation . So the  
> average value  
> was measured by average detector.  
>  
>  
>  
>  
> ----- Original Message -----  
> From: "Mike Kuo" <MKUO@CCSEMC.com>  
> To: "Eva Kao (E-mail)" <eva\_kao@cclab.com.tw>; <steven@cclab.com.tw>  
> Sent: Tuesday, October 15, 2002 10:04 AM  
> Subject: FW: Win Far Technology Co., Ltd., FCC ID:MDXRF1012, AN02T2316  
>  
>  
> >  
> >  
> > -----Original Message-----  
> > From: CERTADM  
> > Sent: Monday, October 14, 2002 7:04 PM

> > To: 'mkuo@ccsemc.com'  
> > Subject: Win Far Technology Co., Ltd., FCC ID:MDXRF1012, AN02T2316  
> >  
> >  
> > Notice\_content  
> > -----  
> > Question #1: In accordance with 15.35( c ), when the radiated emission  
> > limits are expressed in terms of the average value of the emission, and  
> > the  
> > pulsed operation is employed, the measurement field strength shall be  
> > determined by averaging over one complete pulse train, including  
blanking  
> > intervals...". For pulsed operation, once the duty cycle is determined  
by  
> > following 15.35( c ) procedures, the average readings are equal to peak  
> > readings minus duty cycle. Average detector can not be used for pulsed  
> > operation. Since the peak readings are over the average limits, please  
> > provide duty cycle measurements and calculate the average readings.  
> >  
> > Best Regards  
> >  
> > Mike Kuo / TCB Certifier  
> > The items indicated above must be submitted before processing can  
continue  
> > on the above referenced application. Failure to provide the requested  
> > information within 60 days of the original e-mail date may result in  
> > application dismissal and forfeiture of the filing fee. Also, please  
note  
> > that partial responses increase processing time and should not be  
submitted.  
> > Any questions about the content of this correspondence should be  
directed  
> to  
> > the e-mail address listed below the name of the sender.