



FCC RADIO TEST REPORT

FCC ID : MG3-R37024B
Equipment : Tivo Creek Lite MSO Backlit
Brand Name : Universal Electronics
Model Name : Tivo Creek Lite MSO Backlit
Applicant : Universal Electronics
15147 N Scottsdale Rd Ste H300, Scottsdale, AZ 85254
Manufacturer : Universal Electronics
15147 N Scottsdale Rd Ste H300, Scottsdale, AZ 85254
Standard : FCC Part 15 Subpart C §15.247

The product was received on Mar. 05, 2025 and testing was performed from Mar. 20, 2025 to Mar. 25, 2025. We, Sporton International (USA) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International (USA) Inc., the test report shall not be reproduced except in full.

Approved by: Neil Kao

Sporton International (USA) Inc.
1175 Montague Expressway, Milpitas, CA 95035



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	5
2 Test Configuration of Equipment Under Test	6
2.1 Carrier Frequency Channel	6
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System.....	8
2.4 Support Unit used in test configuration and system	8
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	9
3 Test Result.....	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement.....	11
3.3 Power Spectral Density Measurement	12
3.4 Conducted Band Edges and Spurious Emission Measurement	13
3.5 Radiated Band Edges and Spurious Emission Measurement	14
3.6 Antenna Requirements	18
4 List of Measuring Equipment	19
5 Measurement Uncertainty	20
Appendix A. Conducted Test Results	
Appendix B. Radiated Spurious Emission Test Data	
Appendix C. Duty Cycle Plots	
Appendix D. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR241202001	01	Initial issue of report	May 29, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	-
-	15.207	AC Conducted Emission	Not Required	See Note
3.6	15.203	Antenna Requirement	Pass	-

Note:

- Not required means after assessing, test items are not necessary to carry out.
- The power source method of the EUT is to use battery (DC power source), and there is no other AC power port, after assessing, AC Conduction Emission test is not required.

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Sample 1	PMN 1
Sample 2	PMN 2
Sample 3	PMN 3
General Specs	Bluetooth-LE
Antenna Type	PCB trace

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	-0.82

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International (USA) Inc.
Test Site Location	1175 Montague Expressway, Milpitas, CA 95035 TEL : 408 9043300
Test Site No.	Sporton Site No. 03CH01-CA, TH01-CA

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: US1250

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2020

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Remark: 1. For Radiated Test Cases, the tests were performed with Sample 2. 2. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. 3. The detailed Radiated test modes are shown in Appendix B.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Laptop	acer	N18Q13	PD9AX201NG	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.5 EUT Operation Test Setup

The RF test items, utility “RadioControlConsole 4.0.0.0” was installed in laptop which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	6111D	50392	30MHz~1GHz	Aug. 13, 2024	Mar. 21, 2025~ Mar. 25, 2025	Aug. 12, 2025	Radiation (03CH01-CA)
Loop Antenna	R&S	HFH2-Z2E	100840	9kHz~30MHz	May 02, 2024	Mar. 21, 2025~ Mar. 25, 2025	May 01, 2025	Radiation (03CH01-CA)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	02113	1GHz~18GHz	Apr. 26, 2024	Mar. 21, 2025~ Mar. 25, 2025	Apr. 25, 2025	Radiation (03CH01-CA)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA9170	00841	18GHz~40GHz	Aug. 07, 2024	Mar. 21, 2025~ Mar. 25, 2025	Aug. 06, 2025	Radiation (03CH01-CA)
Preamplifier	SONOMA	310N	372241	9kHz~1GHz	Apr. 24, 2024	Mar. 21, 2025~ Mar. 25, 2025	Apr. 23, 2025	Radiation (03CH01-CA)
Preamplifier	E-instrument	ERA-100M-18 G-56-01-A70	EC1900252	1GHz~18GHz	Apr. 25, 2024	Mar. 21, 2025~ Mar. 25, 2025	Apr. 24, 2025	Radiation (03CH01-CA)
Preamplifier	Keysight	83017A	MY53270321	1GHz~26.5GHz	Apr. 25, 2024	Mar. 21, 2025~ Mar. 25, 2025	Apr. 24, 2025	Radiation (03CH01-CA)
Preamplifier	EMEC	EMC18G40G	060726	18G-40G	Apr. 04, 2024	Mar. 21, 2025~ Mar. 25, 2025	Apr. 03, 2025	Radiation (03CH01-CA)
Filter	Wainwright	WLK12-1200-1 272-11000-40 SS	SN1	1.2GHz Low Pass Filter	Jun. 04, 2024	Mar. 21, 2025~ Mar. 25, 2025	Jun. 03, 2025	Radiation (03CH01-CA)
Filter	Wainwright	WHKX12-2700 -3000-18000-6 OST	SN9	3GHz High Pass Filter	Jun. 04, 2024	Mar. 21, 2025~ Mar. 25, 2025	Jun. 03, 2025	Radiation (03CH01-CA)
EMI Test Receiver	Rohde & Schwarz	ESU26	100049	20Hz~26.5GHz	Apr. 25, 2024	Mar. 21, 2025~ Mar. 25, 2025	Apr. 24, 2025	Radiation (03CH01-CA)
Spectrum Analyzer	Keysight	N9010B	MY63440343	MY63440343	Jan. 16, 2024	Mar. 21, 2025~ Mar. 25, 2025	Jan. 15, 2025	Radiation (03CH01-CA)
RF Cable	HUBER+SUH NER	SUCOFLEX 102	8015932/2,80 15762/2, 804938/2	NA	Mar. 04, 2025	Mar. 21, 2025~ Mar. 25, 2025	Mar. 03, 2026	Radiation (03CH01-CA)
Hygrometer	TESTO	608-H1	45142559	NA	Aug. 14, 2024	Mar. 21, 2025~ Mar. 25, 2025	Aug. 13, 2025	Radiation (03CH01-CA)
Controller	Chaintek	EM-1000	060881	Control Turn Table & Antenna Mast	N/A	Mar. 21, 2025~ Mar. 25, 2025	N/A	Radiation (03CH01-CA)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Mar. 21, 2025~ Mar. 25, 2025	N/A	Radiation (03CH01-CA)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Mar. 21, 2025~ Mar. 25, 2025	N/A	Radiation (03CH01-CA)
Test Software	Audix E3	E6.2009-8-24d	PK-002093	N/A	N/A	Mar. 21, 2025~ Mar. 25, 2025	N/A	Radiation (03CH01-CA)
Hygrometer	Testo	608-H1	45141354	N/A	Aug. 14, 2024	Mar. 20, 2025	Aug. 13, 2025	Conducted (TH01-CA)
Power Sensor	DARE!!	RPR3008W	RPR6W-2301 003	10MHz-8GHz	Apr. 25, 2024	Mar. 20, 2025	Apr. 24, 2025	Conducted (TH01-CA)
Switch Box	EM Electronics	EMSW18	SW1070901- DDTB6SW5A 4	N/A	Jul. 16, 2024	Mar. 20, 2025	Jul. 15, 2025	Conducted (TH01-CA)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101545	10Hz-40GHz	Apr. 25, 2024	Mar. 20, 2025	Apr. 24, 2025	Conducted (TH01-CA)

5 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.5 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5 dB
--	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Venkata Kondepudi	Temperature:	22.6	°C
Test Date:	2025/3/20	Relative Humidity:	40	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.048	0.695	0.50	Pass
BLE	1Mbps	1	19	2440	1.057	0.705	0.50	Pass
BLE	1Mbps	1	39	2480	1.052	0.694	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	6.13	30.00	-0.82	5.31	36.00	Pass
BLE	1Mbps	1	19	2440	6.60	30.00	-0.82	5.78	36.00	Pass
BLE	1Mbps	1	39	2480	6.98	30.00	-0.82	6.16	36.00	Pass




TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	5.82	-4.88	-0.82	8.00	Pass
BLE	1Mbps	1	19	2440	6.26	-3.90	-0.82	8.00	Pass
BLE	1Mbps	1	39	2480	6.71	-4.18	-0.82	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




**6dB Bandwidth**

<1M>

6 dB Bandwidth Plot on Channel 00**6 dB Bandwidth Plot on Channel 19****6 dB Bandwidth Plot on Channel 39**




**99% Occupied Bandwidth**


<1M>

99% Occupied Bandwidth Plot on Channel 00**99% Occupied Bandwidth Plot on Channel 19****99% Occupied Bandwidth Plot on Channel 39**

**Power Spectral Density (dBm/3kHz)**


<1M>

Power Density (dBm/3kHz) Plot Channel 00**Power Density (dBm/3kHz) Plot Channel 19****Power Density (dBm/3kHz) Plot Channel 39**

Band Edge and Conducted Spurious Emission
<1M>



Channel 19

100kHz PSD reference Level Plot




Mid Channel Plot

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 39


100kHz PSD reference Level Plot




High Channel Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot





Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	Jesse Fan and Ken Kuo	Temperature :	18.3~21.9°C
		Relative Humidity :	42.3~47.3%

Note symbol

-L	Low channel location
-R	High channel location





C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	2 Tx	Bluetooth-LE_GFSK	0	2402	1Mbps	-	-
Mode 2	2400-2483.5	2 Tx	Bluetooth-LE_GFSK	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	2 Tx	Bluetooth-LE_GFSK	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	2 Tx	Bluetooth-LE_GFSK	39	2480	1Mbps	-	LF
Mode 5	2400-2483.5	2 Tx	Bluetooth-LE_GFSK	39	2480	1Mbps	-	SHF





C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	Bluetooth-LE_GFSK	0	2369.98	49.76	54.00	-4.24	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	0	4804.00	49.54	54.00	-4.46	H	Avg.	Pass	-	Harmonic
2	Bluetooth-LE_GFSK	19	2375.91	47.95	54.00	-6.05	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	19	4880.00	49.49	54.00	-4.51	H	Avg.	Pass	-	Harmonic
3	Bluetooth-LE_GFSK	39	2483.82	47.59	54.00	-6.41	H	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GFSK	39	4960.00	51.54	54.00	-2.46	H	Avg.	Pass	-	Harmonic
4	LF	39	33.88	29.21	40.00	-10.79	V	QP	Pass	-	LF
5	SHF	39	23201.00	41.04	74.00	-32.96	H	Peak	Pass	-	SHF





Mode	1																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_Bluetooth-LE_GFSK_CH0_2402MHz																																																																																																		
ANT	2 Tx																																																																																																		
Pol.	Horizontal						Fundamental																																																																																												
Peak																																																																																																			
	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																												
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2341.10</td><td>58.08</td><td>74.00</td><td>-15.92</td><td>42.73</td><td>27.28</td><td>8.70</td><td>30.61</td><td>9.98</td><td>110</td><td>304</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2341.10	58.08	74.00	-15.92	42.73	27.28	8.70	30.61	9.98	110	304	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>104.73</td><td>-----</td><td>-----</td><td>88.96</td><td>27.47</td><td>8.89</td><td>30.57</td><td>9.98</td><td>110</td><td>304</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	104.73	-----	-----	88.96	27.47	8.89	30.57	9.98	110	304
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2341.10	58.08	74.00	-15.92	42.73	27.28	8.70	30.61	9.98	110	304	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	104.73	-----	-----	88.96	27.47	8.89	30.57	9.98	110	304	PEAK																																																																																							
Avg																																																																																																			
	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto						Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto																																																																																												
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2369.98</td><td>49.76</td><td>54.00</td><td>-4.24</td><td>34.23</td><td>27.35</td><td>8.79</td><td>30.59</td><td>9.98</td><td>110</td><td>304</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2369.98	49.76	54.00	-4.24	34.23	27.35	8.79	30.59	9.98	110	304	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>104.84</td><td>-----</td><td>-----</td><td>89.07</td><td>27.47</td><td>8.89</td><td>30.57</td><td>9.98</td><td>110</td><td>304</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	104.84	-----	-----	89.07	27.47	8.89	30.57	9.98	110	304
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2369.98	49.76	54.00	-4.24	34.23	27.35	8.79	30.59	9.98	110	304	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	104.84	-----	-----	89.07	27.47	8.89	30.57	9.98	110	304	AVERAGE																																																																																							





Mode	1																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_Bluetooth-LE_GFSK_CH0_2402MHz																																																																																																		
ANT	2 Tx																																																																																																		
Pol.	Vertical						Fundamental																																																																																												
Peak																																																																																																			
	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2346.00</td><td>57.89</td><td>74.00</td><td>-16.11</td><td>42.43</td><td>27.37</td><td>8.72</td><td>30.61</td><td>9.98</td><td>400</td><td>12</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2346.00	57.89	74.00	-16.11	42.43	27.37	8.72	30.61	9.98	400	12	PEAK	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>98.51</td><td>-----</td><td>-----</td><td>82.67</td><td>27.54</td><td>8.89</td><td>30.57</td><td>9.98</td><td>400</td><td>12</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	98.51	-----	-----	82.67	27.54	8.89	30.57	9.98	400	12
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2346.00	57.89	74.00	-16.11	42.43	27.37	8.72	30.61	9.98	400	12	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	98.51	-----	-----	82.67	27.54	8.89	30.57	9.98	400	12	PEAK																																																																																							
Avg																																																																																																			
	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2369.98</td><td>47.12</td><td>54.00</td><td>-6.88</td><td>31.51</td><td>27.43</td><td>8.79</td><td>30.59</td><td>9.98</td><td>400</td><td>12</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2369.98	47.12	54.00	-6.88	31.51	27.43	8.79	30.59	9.98	400	12	AVERAGE	Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>98.59</td><td>-----</td><td>-----</td><td>82.75</td><td>27.54</td><td>8.89</td><td>30.57</td><td>9.98</td><td>400</td><td>12</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	98.59	-----	-----	82.75	27.54	8.89	30.57	9.98	400	12
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2369.98	47.12	54.00	-6.88	31.51	27.43	8.79	30.59	9.98	400	12	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2402.00	98.59	-----	-----	82.75	27.54	8.89	30.57	9.98	400	12	AVERAGE																																																																																							







Mode	1																																																																																																																																																							
	Harmonic																																																																																																																																																							
	2400-2483.5_Bluetooth-LE_GFSK_CH0_2402MHz																																																																																																																																																							
ANT	2 Tx																																																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																																																	
Peak																																																																																																																																																								
	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 HORIZONTAL						Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 VERTICAL																																																																																																																																																	
Avg	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4804.00</td><td>53.21</td><td>74.00</td><td>-20.79</td><td>76.42</td><td>32.56</td><td>11.36</td><td>67.60</td><td>0.47</td><td>100</td><td>68</td><td>PEAK</td></tr><tr><td>2</td><td>4804.00</td><td>49.54</td><td>54.00</td><td>-4.46</td><td>72.75</td><td>32.56</td><td>11.36</td><td>67.60</td><td>0.47</td><td>100</td><td>68</td><td>Average</td></tr><tr><td>3</td><td>9608.00</td><td>55.13</td><td>-----</td><td>-----</td><td>69.33</td><td>38.43</td><td>16.08</td><td>69.06</td><td>0.35</td><td>100</td><td>34</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	53.21	74.00	-20.79	76.42	32.56	11.36	67.60	0.47	100	68	PEAK	2	4804.00	49.54	54.00	-4.46	72.75	32.56	11.36	67.60	0.47	100	68	Average	3	9608.00	55.13	-----	-----	69.33	38.43	16.08	69.06	0.35	100	34	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4804.00</td><td>51.77</td><td>74.00</td><td>-22.23</td><td>74.91</td><td>32.63</td><td>11.36</td><td>67.60</td><td>0.47</td><td>312</td><td>360</td><td>PEAK</td></tr><tr><td>2</td><td>4804.00</td><td>47.06</td><td>54.00</td><td>-6.14</td><td>71.00</td><td>32.63</td><td>11.36</td><td>67.60</td><td>0.47</td><td>312</td><td>360</td><td>Average</td></tr><tr><td>3</td><td>9608.00</td><td>53.82</td><td>-----</td><td>-----</td><td>68.05</td><td>38.40</td><td>16.08</td><td>69.06</td><td>0.35</td><td>100</td><td>117</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	51.77	74.00	-22.23	74.91	32.63	11.36	67.60	0.47	312	360	PEAK	2	4804.00	47.06	54.00	-6.14	71.00	32.63	11.36	67.60	0.47	312	360	Average	3	9608.00	53.82	-----	-----	68.05	38.40	16.08	69.06	0.35	100	117	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																														
1	4804.00	53.21	74.00	-20.79	76.42	32.56	11.36	67.60	0.47	100	68	PEAK																																																																																																																																												
2	4804.00	49.54	54.00	-4.46	72.75	32.56	11.36	67.60	0.47	100	68	Average																																																																																																																																												
3	9608.00	55.13	-----	-----	69.33	38.43	16.08	69.06	0.35	100	34	Peak																																																																																																																																												
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																														
1	4804.00	51.77	74.00	-22.23	74.91	32.63	11.36	67.60	0.47	312	360	PEAK																																																																																																																																												
2	4804.00	47.06	54.00	-6.14	71.00	32.63	11.36	67.60	0.47	312	360	Average																																																																																																																																												
3	9608.00	53.82	-----	-----	68.05	38.40	16.08	69.06	0.35	100	117	Peak																																																																																																																																												

Remark: The unwanted signal 9608.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).



Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_CH0_2402MHz	
ANT	2 Tx	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 HORIZONTAL	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 VERTICAL



Mode	2																																																																																																		
	Band Edge - L																																																																																																		
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																																																																		
ANT	2 Tx																																																																																																		
Pol.	Horizontal						Fundamental																																																																																												
Peak																																																																																																			
	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																												
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2369.67</td><td>58.62</td><td>74.00</td><td>-15.38</td><td>43.09</td><td>27.35</td><td>8.79</td><td>30.59</td><td>9.98</td><td>100</td><td>309</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2369.67	58.62	74.00	-15.38	43.09	27.35	8.79	30.59	9.98	100	309	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>106.04</td><td>-----</td><td>-----</td><td>90.00</td><td>27.60</td><td>9.04</td><td>30.58</td><td>9.98</td><td>100</td><td>309</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	106.04	-----	-----	90.00	27.60	9.04	30.58	9.98	100	309
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2369.67	58.62	74.00	-15.38	43.09	27.35	8.79	30.59	9.98	100	309	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2440.00	106.04	-----	-----	90.00	27.60	9.04	30.58	9.98	100	309	PEAK																																																																																							
Avg																																																																																																			
	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto						Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto																																																																																												
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2375.91</td><td>47.95</td><td>54.00</td><td>-6.05</td><td>32.38</td><td>27.37</td><td>8.81</td><td>30.59</td><td>9.98</td><td>100</td><td>309</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2375.91	47.95	54.00	-6.05	32.38	27.37	8.81	30.59	9.98	100	309	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>106.20</td><td>-----</td><td>-----</td><td>90.16</td><td>27.60</td><td>9.04</td><td>30.58</td><td>9.98</td><td>100</td><td>309</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	106.20	-----	-----	90.16	27.60	9.04	30.58	9.98	100	309
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2375.91	47.95	54.00	-6.05	32.38	27.37	8.81	30.59	9.98	100	309	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2440.00	106.20	-----	-----	90.16	27.60	9.04	30.58	9.98	100	309	AVERAGE																																																																																							





Mode	2																																																							
	Band Edge - R																																																							
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																							
ANT	2 Tx																																																							
Pol.	Horizontal						Fundamental																																																	
Peak	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.94</td><td>50.34</td><td>74.00</td><td>-15.66</td><td>41.00</td><td>27.04</td><td>9.26</td><td>30.54</td><td>9.98</td><td>100</td><td>309</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2487.94	50.34	74.00	-15.66	41.00	27.04	9.26	30.54	9.98	100	309	PEAK	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2487.94	50.34	74.00	-15.66	41.00	27.04	9.26	30.54	9.98	100	309	PEAK																																												
Avg	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.94</td><td>47.78</td><td>54.00</td><td>-6.22</td><td>31.30</td><td>27.81</td><td>9.24</td><td>30.55</td><td>9.98</td><td>100</td><td>309</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2487.94	47.78	54.00	-6.22	31.30	27.81	9.24	30.55	9.98	100	309	AVERAGE	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2487.94	47.78	54.00	-6.22	31.30	27.81	9.24	30.55	9.98	100	309	AVERAGE																																												







Mode	2																																																																																															
	Band Edge - L																																																																																															
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																																																															
ANT	2 Tx																																																																																															
Pol.	Vertical					Fundamental																																																																																										
Peak	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.13</td><td>56.83</td><td>74.00</td><td>-17.17</td><td>41.10</td><td>27.49</td><td>8.84</td><td>30.58</td><td>9.98</td><td>375</td><td>0 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2388.13	56.83	74.00	-17.17	41.10	27.49	8.84	30.58	9.98	375	0 PEAK	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>99.16</td><td>-----</td><td>-----</td><td>83.05</td><td>27.67</td><td>9.04</td><td>30.58</td><td>9.98</td><td>375</td><td>0 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	99.16	-----	-----	83.05	27.67	9.04	30.58	9.98	375	0 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2388.13	56.83	74.00	-17.17	41.10	27.49	8.84	30.58	9.98	375	0 PEAK																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2440.00	99.16	-----	-----	83.05	27.67	9.04	30.58	9.98	375	0 PEAK																																																																																					
Avg	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2387.74</td><td>45.52</td><td>54.00</td><td>-8.48</td><td>29.79</td><td>27.49</td><td>8.84</td><td>30.58</td><td>9.98</td><td>375</td><td>0 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2387.74	45.52	54.00	-8.48	29.79	27.49	8.84	30.58	9.98	375	0 AVERAGE	Level (dBuV/m) Frequency (MHz) Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>99.27</td><td>-----</td><td>-----</td><td>83.16</td><td>27.67</td><td>9.04</td><td>30.58</td><td>9.98</td><td>375</td><td>0 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	99.27	-----	-----	83.16	27.67	9.04	30.58	9.98	375	0 AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2387.74	45.52	54.00	-8.48	29.79	27.49	8.84	30.58	9.98	375	0 AVERAGE																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																						
1	2440.00	99.27	-----	-----	83.16	27.67	9.04	30.58	9.98	375	0 AVERAGE																																																																																					





Mode	2																																																							
	Band Edge - R																																																							
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																							
ANT	2 Tx																																																							
Pol.	Vertical						Fundamental																																																	
Peak	 Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2497.00</td><td>58.03</td><td>74.00</td><td>-15.97</td><td>41.41</td><td>27.91</td><td>9.27</td><td>30.54</td><td>9.98</td><td>375</td><td>0</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2497.00	58.03	74.00	-15.97	41.41	27.91	9.27	30.54	9.98	375	0	PEAK	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2497.00	58.03	74.00	-15.97	41.41	27.91	9.27	30.54	9.98	375	0	PEAK																																												
Avg	 Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2499.46</td><td>46.43</td><td>54.00</td><td>-7.57</td><td>29.79</td><td>27.92</td><td>9.28</td><td>30.54</td><td>9.98</td><td>375</td><td>0</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2499.46	46.43	54.00	-7.57	29.79	27.92	9.28	30.54	9.98	375	0	AVERAGE	Blank					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																														
1	2499.46	46.43	54.00	-7.57	29.79	27.92	9.28	30.54	9.98	375	0	AVERAGE																																												







Mode	2																																																																																																																																																																																																
	Harmonic																																																																																																																																																																																																
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz																																																																																																																																																																																																
ANT	2 Tx																																																																																																																																																																																																
Pol.	Horizontal	Vertical																																																																																																																																																																																															
Peak																																																																																																																																																																																																	
	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 HORIZONTAL	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 VERTICAL																																																																																																																																																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>52.96</td><td>74.00</td><td>-21.04</td><td>75.66</td><td>32.92</td><td>11.42</td><td>67.51</td><td>0.47</td><td>100</td><td>142</td><td>PEAK</td></tr><tr><td>2</td><td>4880.00</td><td>49.49</td><td>54.00</td><td>-4.51</td><td>72.19</td><td>32.92</td><td>11.42</td><td>67.51</td><td>0.47</td><td>100</td><td>142</td><td>Average</td></tr><tr><td>3</td><td>7320.00</td><td>50.50</td><td>74.00</td><td>-23.50</td><td>66.35</td><td>36.88</td><td>14.00</td><td>67.06</td><td>0.33</td><td>100</td><td>171</td><td>PEAK</td></tr><tr><td>4</td><td>7320.00</td><td>43.27</td><td>54.00</td><td>-10.73</td><td>59.12</td><td>36.88</td><td>14.00</td><td>67.06</td><td>0.33</td><td>100</td><td>171</td><td>Average</td></tr><tr><td>5</td><td>9760.00</td><td>57.02</td><td>-----</td><td>-----</td><td>70.96</td><td>38.33</td><td>16.33</td><td>68.94</td><td>0.34</td><td>100</td><td>34</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4880.00	52.96	74.00	-21.04	75.66	32.92	11.42	67.51	0.47	100	142	PEAK	2	4880.00	49.49	54.00	-4.51	72.19	32.92	11.42	67.51	0.47	100	142	Average	3	7320.00	50.50	74.00	-23.50	66.35	36.88	14.00	67.06	0.33	100	171	PEAK	4	7320.00	43.27	54.00	-10.73	59.12	36.88	14.00	67.06	0.33	100	171	Average	5	9760.00	57.02	-----	-----	70.96	38.33	16.33	68.94	0.34	100	34	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>48.91</td><td>74.00</td><td>-25.09</td><td>71.55</td><td>32.98</td><td>11.42</td><td>67.51</td><td>0.47</td><td>302</td><td>350</td><td>PEAK</td></tr><tr><td>2</td><td>4880.00</td><td>44.53</td><td>54.00</td><td>-9.47</td><td>67.17</td><td>32.98</td><td>11.42</td><td>67.51</td><td>0.47</td><td>302</td><td>350</td><td>Average</td></tr><tr><td>3</td><td>7320.00</td><td>49.22</td><td>74.00</td><td>-24.78</td><td>64.98</td><td>36.97</td><td>14.00</td><td>67.06</td><td>0.33</td><td>103</td><td>180</td><td>PEAK</td></tr><tr><td>4</td><td>7320.00</td><td>40.62</td><td>54.00</td><td>-13.38</td><td>56.38</td><td>36.97</td><td>14.00</td><td>67.06</td><td>0.33</td><td>103</td><td>180</td><td>Average</td></tr><tr><td>5</td><td>9760.00</td><td>56.47</td><td>-----</td><td>-----</td><td>70.42</td><td>38.32</td><td>16.33</td><td>68.94</td><td>0.34</td><td>100</td><td>118</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4880.00	48.91	74.00	-25.09	71.55	32.98	11.42	67.51	0.47	302	350	PEAK	2	4880.00	44.53	54.00	-9.47	67.17	32.98	11.42	67.51	0.47	302	350	Average	3	7320.00	49.22	74.00	-24.78	64.98	36.97	14.00	67.06	0.33	103	180	PEAK	4	7320.00	40.62	54.00	-13.38	56.38	36.97	14.00	67.06	0.33	103	180	Average	5	9760.00	56.47	-----	-----	70.42	38.32	16.33	68.94	0.34	100	118
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																							
1	4880.00	52.96	74.00	-21.04	75.66	32.92	11.42	67.51	0.47	100	142	PEAK																																																																																																																																																																																					
2	4880.00	49.49	54.00	-4.51	72.19	32.92	11.42	67.51	0.47	100	142	Average																																																																																																																																																																																					
3	7320.00	50.50	74.00	-23.50	66.35	36.88	14.00	67.06	0.33	100	171	PEAK																																																																																																																																																																																					
4	7320.00	43.27	54.00	-10.73	59.12	36.88	14.00	67.06	0.33	100	171	Average																																																																																																																																																																																					
5	9760.00	57.02	-----	-----	70.96	38.33	16.33	68.94	0.34	100	34	Peak																																																																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																							
1	4880.00	48.91	74.00	-25.09	71.55	32.98	11.42	67.51	0.47	302	350	PEAK																																																																																																																																																																																					
2	4880.00	44.53	54.00	-9.47	67.17	32.98	11.42	67.51	0.47	302	350	Average																																																																																																																																																																																					
3	7320.00	49.22	74.00	-24.78	64.98	36.97	14.00	67.06	0.33	103	180	PEAK																																																																																																																																																																																					
4	7320.00	40.62	54.00	-13.38	56.38	36.97	14.00	67.06	0.33	103	180	Average																																																																																																																																																																																					
5	9760.00	56.47	-----	-----	70.42	38.32	16.33	68.94	0.34	100	118	Peak																																																																																																																																																																																					
Avg																																																																																																																																																																																																	

Remark: The unwanted signal 9760.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).







Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_CH19_2440MHz	
ANT	2 Tx	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 HORIZONTAL	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 VERTICAL





Mode	3																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																		
ANT	2 Tx																																																																																																		
Pol.	Horizontal						Fundamental																																																																																												
Peak																																																																																																			
	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.36</td><td>59.07</td><td>74.00</td><td>-14.93</td><td>42.61</td><td>27.00</td><td>9.23</td><td>30.55</td><td>9.98</td><td>100</td><td>307</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.36	59.07	74.00	-14.93	42.61	27.00	9.23	30.55	9.98	100	307	PEAK	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>105.21</td><td>-----</td><td>-----</td><td>88.82</td><td>27.77</td><td>9.20</td><td>30.56</td><td>9.98</td><td>100</td><td>307</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	105.21	-----	-----	88.82	27.77	9.20	30.56	9.98	100	307
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.36	59.07	74.00	-14.93	42.61	27.00	9.23	30.55	9.98	100	307	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	105.21	-----	-----	88.82	27.77	9.20	30.56	9.98	100	307	PEAK																																																																																							
Avg																																																																																																			
	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.82</td><td>47.59</td><td>54.00</td><td>-6.41</td><td>31.15</td><td>27.79</td><td>9.22</td><td>30.55</td><td>9.98</td><td>100</td><td>307</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.82	47.59	54.00	-6.41	31.15	27.79	9.22	30.55	9.98	100	307	AVERAGE	Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2480.00</td><td>105.33</td><td>-----</td><td>-----</td><td>88.94</td><td>27.77</td><td>9.20</td><td>30.56</td><td>9.98</td><td>100</td><td>307</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	105.33	-----	-----	88.94	27.77	9.20	30.56	9.98	100	307
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.82	47.59	54.00	-6.41	31.15	27.79	9.22	30.55	9.98	100	307	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	105.33	-----	-----	88.94	27.77	9.20	30.56	9.98	100	307	AVERAGE																																																																																							





Mode	3																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																		
ANT	2 Tx																																																																																																		
Pol.	Vertical						Fundamental																																																																																												
Peak																																																																																																			
	Site : 03CH01-CA Condition: PEAK_BE_74 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																																		
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.30</td><td>58.95</td><td>74.00</td><td>-15.05</td><td>42.45</td><td>27.85</td><td>9.22</td><td>30.55</td><td>9.98</td><td>400</td><td>15</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2484.30	58.95	74.00	-15.05	42.45	27.85	9.22	30.55	9.98	400	15	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>100.42</td><td>-----</td><td>-----</td><td>83.96</td><td>27.84</td><td>9.20</td><td>30.56</td><td>9.98</td><td>400</td><td>15</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	100.42	-----	-----	83.96	27.84	9.20	30.56	9.98	400	15
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2484.30	58.95	74.00	-15.05	42.45	27.85	9.22	30.55	9.98	400	15	PEAK																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	100.42	-----	-----	83.96	27.84	9.20	30.56	9.98	400	15	PEAK																																																																																							
Avg																																																																																																			
	Site : 03CH01-CA Condition: AVG_BE_54 3m HORN_02113_240426 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto																																																																																																		
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.68</td><td>46.73</td><td>54.00</td><td>-7.27</td><td>30.23</td><td>27.85</td><td>9.22</td><td>30.55</td><td>9.98</td><td>400</td><td>15</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.68	46.73	54.00	-7.27	30.23	27.85	9.22	30.55	9.98	400	15	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>100.52</td><td>-----</td><td>-----</td><td>84.06</td><td>27.84</td><td>9.20</td><td>30.56</td><td>9.98</td><td>400</td><td>15</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2480.00	100.52	-----	-----	84.06	27.84	9.20	30.56	9.98	400	15
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2483.68	46.73	54.00	-7.27	30.23	27.85	9.22	30.55	9.98	400	15	AVERAGE																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2480.00	100.52	-----	-----	84.06	27.84	9.20	30.56	9.98	400	15	AVERAGE																																																																																							





Mode	3																																																																																																																																																																	
	Harmonic																																																																																																																																																																	
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																																																																																	
ANT	2 Tx																																																																																																																																																																	
Pol.	Horizontal	Vertical																																																																																																																																																																
Peak																																																																																																																																																																		
	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 HORIZONTAL	Site : 03CH01-CA Condition: PEAK_74 3m HORN_02113_240426 VERTICAL																																																																																																																																																																
Avg	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th></tr><tr><td>1 4960.00</td><td>54.00</td><td>74.00</td><td>-19.20</td><td>77.39</td><td>33.15</td><td>11.47</td><td>67.68</td><td>0.47</td><td>100</td></tr><tr><td>2 4968.00</td><td>51.54</td><td>54.00</td><td>-2.46</td><td>74.13</td><td>33.15</td><td>11.47</td><td>67.68</td><td>0.47</td><td>100</td></tr><tr><td>3 7440.00</td><td>50.50</td><td>74.00</td><td>-23.50</td><td>66.64</td><td>36.57</td><td>14.08</td><td>67.13</td><td>0.34</td><td>100</td></tr><tr><td>4 7448.00</td><td>43.80</td><td>54.00</td><td>-10.20</td><td>59.94</td><td>36.57</td><td>14.08</td><td>67.13</td><td>0.34</td><td>100</td></tr><tr><td>5 9920.00</td><td>56.47</td><td>-----</td><td>-----</td><td>70.29</td><td>38.45</td><td>16.35</td><td>68.98</td><td>0.36</td><td>100</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	1 4960.00	54.00	74.00	-19.20	77.39	33.15	11.47	67.68	0.47	100	2 4968.00	51.54	54.00	-2.46	74.13	33.15	11.47	67.68	0.47	100	3 7440.00	50.50	74.00	-23.50	66.64	36.57	14.08	67.13	0.34	100	4 7448.00	43.80	54.00	-10.20	59.94	36.57	14.08	67.13	0.34	100	5 9920.00	56.47	-----	-----	70.29	38.45	16.35	68.98	0.36	100	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th></tr><tr><td>1 4960.00</td><td>52.51</td><td>74.00</td><td>-21.49</td><td>75.07</td><td>33.18</td><td>11.47</td><td>67.68</td><td>0.47</td><td>373</td></tr><tr><td>2 4968.00</td><td>49.11</td><td>54.00</td><td>-4.89</td><td>71.67</td><td>33.18</td><td>11.47</td><td>67.68</td><td>0.47</td><td>373</td></tr><tr><td>3 7440.00</td><td>49.00</td><td>74.00</td><td>-25.00</td><td>65.07</td><td>36.64</td><td>14.08</td><td>67.13</td><td>0.34</td><td>100</td></tr><tr><td>4 7448.00</td><td>40.79</td><td>54.00</td><td>-13.21</td><td>56.86</td><td>36.64</td><td>14.08</td><td>67.13</td><td>0.34</td><td>100</td></tr><tr><td>5 9920.00</td><td>54.90</td><td>-----</td><td>-----</td><td>68.73</td><td>38.44</td><td>16.35</td><td>68.98</td><td>0.36</td><td>100</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	1 4960.00	52.51	74.00	-21.49	75.07	33.18	11.47	67.68	0.47	373	2 4968.00	49.11	54.00	-4.89	71.67	33.18	11.47	67.68	0.47	373	3 7440.00	49.00	74.00	-25.00	65.07	36.64	14.08	67.13	0.34	100	4 7448.00	40.79	54.00	-13.21	56.86	36.64	14.08	67.13	0.34	100	5 9920.00	54.90	-----	-----	68.73	38.44	16.35	68.98	0.36	100
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm																																																																																																																																																									
1 4960.00	54.00	74.00	-19.20	77.39	33.15	11.47	67.68	0.47	100																																																																																																																																																									
2 4968.00	51.54	54.00	-2.46	74.13	33.15	11.47	67.68	0.47	100																																																																																																																																																									
3 7440.00	50.50	74.00	-23.50	66.64	36.57	14.08	67.13	0.34	100																																																																																																																																																									
4 7448.00	43.80	54.00	-10.20	59.94	36.57	14.08	67.13	0.34	100																																																																																																																																																									
5 9920.00	56.47	-----	-----	70.29	38.45	16.35	68.98	0.36	100																																																																																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm																																																																																																																																																									
1 4960.00	52.51	74.00	-21.49	75.07	33.18	11.47	67.68	0.47	373																																																																																																																																																									
2 4968.00	49.11	54.00	-4.89	71.67	33.18	11.47	67.68	0.47	373																																																																																																																																																									
3 7440.00	49.00	74.00	-25.00	65.07	36.64	14.08	67.13	0.34	100																																																																																																																																																									
4 7448.00	40.79	54.00	-13.21	56.86	36.64	14.08	67.13	0.34	100																																																																																																																																																									
5 9920.00	54.90	-----	-----	68.73	38.44	16.35	68.98	0.36	100																																																																																																																																																									

Remark: The unwanted signal 9920.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).





Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz	
ANT	2 Tx	
Pol.	Horizontal	Vertical
10.6G -18G Avg	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 HORIZONTAL	 Site : 03CH01-CA Condition: AVG_54 3m HORN_02113_240426 VERTICAL



Mode	4																																																																																																																																																																																																												
	LF																																																																																																																																																																																																												
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																																																																																																																												
ANT	2 Tx																																																																																																																																																																																																												
Pol.	Horizontal						Vertical																																																																																																																																																																																																						
QP/ Peak																																																																																																																																																																																																													
	Site : 03CH01-CA Condition: QP 3m B1LOG_54683_241115 HORIZONTAL						Site : 03CH01-CA Condition: QP 3m B1LOG_54683_241115 VERTICAL																																																																																																																																																																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>33.88</td><td>25.36</td><td>40.00</td><td>-14.64</td><td>33.65</td><td>23.07</td><td>1.01</td><td>32.46</td><td>0.09</td><td>-- Peak</td></tr><tr><td>2</td><td>191.99</td><td>25.50</td><td>43.50</td><td>-18.00</td><td>40.61</td><td>14.93</td><td>2.31</td><td>32.44</td><td>0.09</td><td>-- Peak</td></tr><tr><td>3</td><td>270.56</td><td>24.75</td><td>46.00</td><td>-21.25</td><td>35.15</td><td>19.12</td><td>2.79</td><td>32.45</td><td>0.14</td><td>-- Peak</td></tr><tr><td>4</td><td>288.02</td><td>25.14</td><td>46.00</td><td>-20.86</td><td>35.35</td><td>19.22</td><td>2.90</td><td>32.48</td><td>0.15</td><td>-- Peak</td></tr><tr><td>5</td><td>747.80</td><td>29.27</td><td>46.00</td><td>-16.73</td><td>28.77</td><td>28.05</td><td>4.67</td><td>32.44</td><td>0.22</td><td>-- Peak</td></tr><tr><td>6</td><td>955.38</td><td>32.93</td><td>46.00</td><td>-13.07</td><td>27.48</td><td>31.08</td><td>5.23</td><td>31.22</td><td>0.36</td><td>-- Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	33.88	25.36	40.00	-14.64	33.65	23.07	1.01	32.46	0.09	-- Peak	2	191.99	25.50	43.50	-18.00	40.61	14.93	2.31	32.44	0.09	-- Peak	3	270.56	24.75	46.00	-21.25	35.15	19.12	2.79	32.45	0.14	-- Peak	4	288.02	25.14	46.00	-20.86	35.35	19.22	2.90	32.48	0.15	-- Peak	5	747.80	29.27	46.00	-16.73	28.77	28.05	4.67	32.44	0.22	-- Peak	6	955.38	32.93	46.00	-13.07	27.48	31.08	5.23	31.22	0.36	-- Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>33.88</td><td>29.21</td><td>40.00</td><td>-10.79</td><td>37.50</td><td>23.07</td><td>1.01</td><td>32.46</td><td>0.09</td><td>100 360 QP</td></tr><tr><td>2</td><td>154.16</td><td>28.39</td><td>43.50</td><td>-15.11</td><td>41.74</td><td>16.89</td><td>2.13</td><td>32.45</td><td>0.08</td><td>-- Peak</td></tr><tr><td>3</td><td>254.07</td><td>22.08</td><td>46.00</td><td>-23.92</td><td>32.38</td><td>19.31</td><td>2.69</td><td>32.43</td><td>0.13</td><td>-- Peak</td></tr><tr><td>4</td><td>508.21</td><td>25.25</td><td>46.00</td><td>-20.75</td><td>29.76</td><td>24.13</td><td>3.80</td><td>32.62</td><td>0.18</td><td>-- Peak</td></tr><tr><td>5</td><td>753.62</td><td>29.97</td><td>46.00</td><td>-16.03</td><td>29.41</td><td>28.07</td><td>4.69</td><td>32.42</td><td>0.22</td><td>-- Peak</td></tr><tr><td>6</td><td>945.68</td><td>33.69</td><td>46.00</td><td>-12.31</td><td>28.66</td><td>30.78</td><td>5.21</td><td>31.30</td><td>0.34</td><td>-- Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	33.88	29.21	40.00	-10.79	37.50	23.07	1.01	32.46	0.09	100 360 QP	2	154.16	28.39	43.50	-15.11	41.74	16.89	2.13	32.45	0.08	-- Peak	3	254.07	22.08	46.00	-23.92	32.38	19.31	2.69	32.43	0.13	-- Peak	4	508.21	25.25	46.00	-20.75	29.76	24.13	3.80	32.62	0.18	-- Peak	5	753.62	29.97	46.00	-16.03	29.41	28.07	4.69	32.42	0.22	-- Peak	6	945.68	33.69	46.00	-12.31	28.66	30.78	5.21	31.30	0.34
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																				
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																			
1	33.88	25.36	40.00	-14.64	33.65	23.07	1.01	32.46	0.09	-- Peak																																																																																																																																																																																																			
2	191.99	25.50	43.50	-18.00	40.61	14.93	2.31	32.44	0.09	-- Peak																																																																																																																																																																																																			
3	270.56	24.75	46.00	-21.25	35.15	19.12	2.79	32.45	0.14	-- Peak																																																																																																																																																																																																			
4	288.02	25.14	46.00	-20.86	35.35	19.22	2.90	32.48	0.15	-- Peak																																																																																																																																																																																																			
5	747.80	29.27	46.00	-16.73	28.77	28.05	4.67	32.44	0.22	-- Peak																																																																																																																																																																																																			
6	955.38	32.93	46.00	-13.07	27.48	31.08	5.23	31.22	0.36	-- Peak																																																																																																																																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																				
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																			
1	33.88	29.21	40.00	-10.79	37.50	23.07	1.01	32.46	0.09	100 360 QP																																																																																																																																																																																																			
2	154.16	28.39	43.50	-15.11	41.74	16.89	2.13	32.45	0.08	-- Peak																																																																																																																																																																																																			
3	254.07	22.08	46.00	-23.92	32.38	19.31	2.69	32.43	0.13	-- Peak																																																																																																																																																																																																			
4	508.21	25.25	46.00	-20.75	29.76	24.13	3.80	32.62	0.18	-- Peak																																																																																																																																																																																																			
5	753.62	29.97	46.00	-16.03	29.41	28.07	4.69	32.42	0.22	-- Peak																																																																																																																																																																																																			
6	945.68	33.69	46.00	-12.31	28.66	30.78	5.21	31.30	0.34	-- Peak																																																																																																																																																																																																			



Mode	5																																																																																																				
	SHF																																																																																																				
	2400-2483.5_Bluetooth-LE_GFSK_CH39_2480MHz																																																																																																				
ANT	2 Tx																																																																																																				
Pol.	Horizontal						Vertical																																																																																														
Peak																																																																																																					
	Site : 03CH01-CA Condition: PEAK_74 1m SHF_HORN_841_240807 HORIZONTAL						Site : 03CH01-CA Condition: PEAK_74 1m SHF_HORN_841_240807 VERTICAL																																																																																														
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>23201.00</td><td>41.04</td><td>74.00</td><td>-32.96</td><td>63.92</td><td>39.12</td><td>0.00</td><td>52.46</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	23201.00	41.04	74.00	-32.96	63.92	39.12	0.00	52.46	-9.54	--	--	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>23523.00</td><td>41.04</td><td>74.00</td><td>-32.96</td><td>63.74</td><td>39.16</td><td>0.00</td><td>52.32</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	23523.00	41.04	74.00	-32.96	63.74	39.16	0.00	52.32	-9.54	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																										
1	23201.00	41.04	74.00	-32.96	63.92	39.12	0.00	52.46	-9.54	--	--	Peak																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																										
1	23523.00	41.04	74.00	-32.96	63.74	39.16	0.00	52.32	-9.54	--	--	Peak																																																																																									



Appendix C. Duty Cycle Plots

Antenna	Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting
2 Tx	Bluetooth - LE for 1Mbps	100.00	-	-	10Hz

Ant. <2 Tx>

