

## RF EXPOSURE STATEMENT

### Notice in Installation Manual:

### FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment, when installed as directed. This equipment should be installed and operated with fix-mounted antennas that are installed with a minimum of 2 meters of separation distance between the antenna and all persons' body during normal operation.

### RF Exposure Calculations:

The following information provides the **minimum** separation distance for the highest gain antenna provided with the the **Model: RFM-2400 Transceiver**, as calculated from **FCC OET 65 Appendix B, Table 1B** Guidelines for General Population/Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0 mW/cm<sup>2</sup> uncontrolled exposure limit. The Friss formula used was:

$$S = (Po \cdot G) / (4 \cdot \pi \cdot r^2) \quad \text{or} \quad r = \sqrt{(Po \cdot G) / (4 \cdot \pi \cdot S)}$$

Where **S** = 1.0 mW/cm<sup>2</sup> for 2400 MHz

Where **Po** = 10 mW (Peak RF)

Where **G** = Isotropic antenna gain (2.0 numeric)

Where **r** = Minimum Safe Distance from antenna (cm)

For: 3 dBi Omni Antenna ..... r = 1.3 cm