

TEST REPORT

For

RFID READER/WRITER

In conformity with

FCC CFR 47 Part15 Subpart C

Model : TR3XM-SN02

FCC ID : MK4TR3XM-SX01

Test Item : RFID READER/WRITER

Report No. : ERY1406P23R9

Issue Date : 23 Jun. 2014

Prepared for

TAKAYA Corporation
661-1, Ibara-cho, Ibara-city, Okayama, 715-8503 Japan

Prepared by

SGS RF Technologies Inc.
472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan
Telephone: +81+(0)45- 534-0645
FAX: +81+(0)45- 534-0646

**This report shall not be reproduced, except in full, without the written permission of
SGS RF Technologies Inc. The test results in this report apply only to the sample tested.
SGS RF Technologies Inc. is managed to ISO17025 and has the necessary knowledge and test
facilities for testing according to the referenced standards.**

Table of contents

1 General information.....	3
1.1 Product description	3
1.2 Test(s) performed/ Summary of test result	3
1.3 Test facility	4
1.4 Measurement uncertainty.....	4
1.5 Summary of test results.....	5
1.6 Setup of equipment under test (EUT)	5
1.6.1 Test configuration of EUT	5
1.6.2 Operating condition:	5
1.6.3 Setup diagram of tested system.....	6
1.7 Equipment modifications.....	6
1.8 Deviation from the standard	6
2 Test procedure and test data	7
2.1 Occupied bandwidth	7
2.2 Transmitter radiated spurious emissions between 9 KHz to 30 MHz.....	8
2.3 Transmitter radiated spurious emissions between 30MHz to 1000MHz	11
2.4 Frequency stability.....	15
2.5 Transmitter AC power line conducted emissions	16
3 Test setup photographs.....	19
3.1 Radiated spurious emissions.....	19
3.2 AC power line conducted emissions.....	19
3.3 Frequency Stability	19
4 List of utilized test equipment / calibration	20

History

Report No.	Date	Revisions	Issued By
ERY1405P19R2	19 May. 2014	Initial Issue	T.Kato
ERY1406P23R9	23 Jun. 2014	Correct the FCC ID (Top page)	T.Kato

1 General information

1.1 Product description

Test item	: RFID READER/WRITER
Manufacturer	: TAKAYA Corporation
Address	: 661-1, Ibara-cho, Ibara-city, Okayama, 715-8503 Japan
Model	: TR3XM-SN02
FCC ID	: MK4TR3XM-SX01
Serial number	: 14000001
Software version	: 1.04
Hardware version	: V10
Operating frequency	: 13.56 MHz
Type of modulation	: ASK
Operating temperature range	: 0 to +55 degC
Receipt date of EUT	: 15 May. 2014
Nominal power source voltages	: DC 5.0 V

1.2 Test(s) performed/ Summary of test result

Test specification(s)	: FCC CFR 47 Part 15 Subpart B (01 Oct. 2010)
Test method(s)	: ANSI C63.4: 2003
Test(s) started	: 16 May. 2014
Test(s) completed	: 16 May. 2014
Purpose of test(s)	: Certification
Summary of test result	: <u>Complied</u>

Note: The above judgment is only based on the measurement data and it does not include the measurement uncertainty. Accordingly, the statement below is applied to the test result.

The EUT complies with the limit required in the standard in case that the margin is not less than the measurement uncertainty in the Laboratory.

Compliance of the EUT is more probable than non-compliance in case that the margin is less than the measurement uncertainty in the Laboratory.

Test engineer : T. Kato
T. Kato
EMC testing Department

Reviewer : K. Ohnishi
K. Ohnishi
Manager
EMC testing Department

1.3 Test facility

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at SGS RF Technologies Inc., located in 472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per October 1, 2010.

The description of the test facilities has been filed under registration number 319924 at the Office of the Federal Communications Commission. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at <http://www.fcc.gov>.

Registered by Industry Canada (IC): The registered facility number is as follows;
Test site No. 1 (Semi-Anechoic chamber 3m): 6974A-1

Accredited by **National Voluntary Laboratory Accreditation Program** (NVLAP) for the emission tests stated in the scope of the certificate under Certificate Number 200780-0

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB CODE 200780-0

1.4 Measurement uncertainty

The treatment of uncertainty is based on the general matters on the definition of uncertainty in "Guide to the expression of uncertainty in measurement (GUM)" published by ISO. The Lab's uncertainty is determined by referring UKAS Publication LAB34: 2002 "The Expression of Uncertainty in EMC Testing" and CISPR16-4-2: 2011 "Uncertainty in EMC Measurements".

The uncertainty of the measurement result in the level of confidence of approximately 95% (k=2) is as follows;

Conducted emission: ± 3.4 dB (10 kHz - 30 MHz)
Radiated emission (9 kHz - 30 MHz): ± 3.3 dB
Radiated emission (30 MHz - 200 MHz): ± 5.0 dB
Radiated emission (200 MHz - 1000 MHz): ± 6.2 dB

1.5 Summary of test results

Requirement	Section in specification	Result	Section in this report
Occupied bandwidth	-	N/A (*)	2.1
Radiated emissions (9 kHz to 30 MHz)	15.225 (a),(b),(c),(d)	Complied	2.2
Radiated emissions (30 to 1000 MHz)	15.225 (d)	Complied	2.3
Carrier frequency stability	15.225 (e)	N/A (*)	2.4
AC power line conducted emissions	15.207	Complied	2.5

* The difference point between original and this model is the change of I/F circuit (LAN port). Since there change of RF circuit, spurious emission test only was applied in this report.

1.6 Setup of equipment under test (EUT)

1.6.1 Test configuration of EUT

Equipment(s) under test

No.	Item	Manufacture	Model No.	Serial No.
A	RFID READER/WRITER	TAKAYA Corporation	TR3XM-SN02	14000001
B	AC adaptor	UNIFIVE	US300520	B09-0396290

Support Equipment(s)

No.	Item	Manufacture	Model No.	Serial No.
C	PC	DELL	VOSTRO	JX189A00
D	HUB	corega	HUB-8PM	0053170010901922
E	AC adaptor (for HUB)	corega	-	-

Connected cable(s)


No.	Item	Identification (Manu.etc.)	Cable Shielded	Ferrite Core	Length [m]
1	DC cable (AC adaptor for EUT)	UNIFIVE	No	No	1.9
2	LAN cable 1	-	Yes	No	1.1
3	LAN canle 2	-	Yes	No	2.1
4	DC cable (AC adaptor for HUB)	corega	No	No	1.9

1.6.2 Operating condition:

Continuous transmission the test mode (ISO/IEC 18092 Felica)

Note: The EUT have six operating modes. But the EUT do not change RF circuit from original model, so the test was applied only with worst mode in previous test result.

1.6.3 Setup diagram of tested system



1.7 Equipment modifications

No modifications have been made to the equipment in order to achieve compliance with the applicable standards described in clause 1.2.

1.8 Deviation from the standard

No deviations from the standards described in clause 1.2.

2 Test procedure and test data

2.1 Occupied bandwidth

Test setup

Test setup was implemented according to the method of ANSI C63.4: 2003 13.1.7 “Occupied bandwidth measurements” and Annex H.6 “Occupied bandwidth measurements”.

Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 13.1.7 “Occupied bandwidth measurements” and Annex H.6 “Occupied bandwidth measurements”.

The spectrum analyzer RBW was set as follows and VBW the video bandwidth shall be set to a value at least three times greater than the RBW.

Fundamental frequency being measured	Minimum instrument bandwidth
9 kHz to 30 MHz	1 kHz
30 MHz to 1000 MHz	10 kHz
1000 MHz to 40 GHz	100 kHz

Limitation

There are no limitations. The measurement value is used to calculate the emission designator.

Test equipment used (refer to List of utilized test equipment)

--	--	--	--	--	--


Test results - This item was not tested.

Test Data

2.2 Transmitter radiated spurious emissions between 9 KHz to 30 MHz

Test setup

Test setup was implemented according to the method of ANSI C63.4: 2003 clause 6 “General requirements for EUT equipment arrangements and operation”, clause 8.2 and Annex H.3 “Radiated emission measurements setup”.



Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 clauses 8.2. The EUT is placed on a non-conducted table which is 0.8m height from a ground plane and the measurement antenna to EUT distance is 3 meters. The turn table is rotated for 360 degrees to determine the maximum emission level.

In the frequency range of 9 kHz to 30 MHz, a calibrated loop antenna was positioned with its plane vertical at the distance 3m from the EUT with an extrapolation of corrected distance factor and rotated about its vertical axis for maximum response at each azimuth about the EUT. For certain applications, the loop antenna also needs to be positioned horizontally. The center of the loop shall be 1 m above the ground. EUT is placed at three different orientations (X, Y and Z axis) in order to find the worst orientation. The spectrum analyzer and receiver are set to the followings;

Below 30 MHz:

RBW=10 kHz, VBW= 30 kHz, final measurement is carried out with a receiver RBW of 9 kHz (QP)

Applicable rule and limitation

§15.205 restricted bands of operation

Except as shown in paragraph 15.205 (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.490 - 0.510	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(1)

15.205(b) except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 general requirements

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency [MHz]	Field Strength [μ V/m]	Measurement Distance [m]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30.0	30	30

In the emission table above, the tighter limit applies at the band edges.

The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz.

Radiated emission limits in the above bands are based on measurements employing an average detector.

§15.225 Operation within the band 13.110 – 14.010 MHz

Frequency [MHz]	Field strength @30m [μ V/m]	Field strength @30m [dB μ V/m]	Field strength @3m [dB μ V/m]
13.110 - 13.410	106	40.5	80.5
13.410 - 13.553	334	50.5	90.5
13.553 - 13.567	15,848	84.0	124.0
13.567 - 13.710	334	50.5	90.5
13.710 - 14.010	106	40.5	80.5

$\text{dB}\mu\text{V/m} = 20 \times \log (\mu\text{V/m})$, Corrected distance factor = 40dB / decade (15.31(f))

The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the above radiated emission limits in § 15.209.

Test equipment used (refer to List of utilized test equipment)

AC01	LP01	CL11	TR06
------	------	------	------

Test software used

EMI Ver. 5.5

Calculation method

The Correction Factor and Result are calculated as followings.

$$\text{Correction Factor [dB/m]} = \text{Ant. Factor [dB/m]} + \text{Loss [dB]}$$
$$\text{Result [dB}\mu\text{V/m]} = \text{Reading [dB}\mu\text{V]} + \text{Correction Factor [dB/m]}$$

Test results - Complied with requirement

Test Data

Measurement distance: 3 m


[Emission level]

Freq. [MHz]	Reading at 3m [dB μ V]	Corr. Factor [dB]	Result [dB μ V/m]	Limit at 3m [dB μ V/m]	Margin [dB]
-	-	-	-	-	-

There were no spurious emissions greater than 20dB below the limit.

[Chart]

Axis: Z-plane (Worst)




Tested Date: 16 May. 2014
Humidity: 60 %

Temperature: 21 degC
Atmos. Press: 1000 hPa

2.3 Transmitter radiated spurious emissions between 30MHz to 1000MHz

Test setup

Test setup was implemented according to the method of ANSI C63.4: 2003 clause 6 “General requirements for EUT equipment arrangements and operation”, clause 8.2.3 and Annex H.4 “Radiated emission measurements setup”.



Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 clauses 8.2.3. Exploratory radiated measurements were performed at the measurement distance of 3 meters using broadband antennas and a spectrum analyzer. The EUT was set up in its typical configuration and arrangement, and operated in its various modes.

For each mode of operation required to be tested, the frequency spectrum were monitored. Variations in antenna height between 1 and 4 m, antenna polarization, EUT azimuth, and cable or wire placement (each variable within bounds specified elsewhere) were explored to produce the emission that has the highest amplitude relative to the limit.

Based on the exploratory measurement results, the one EUT, cable and wire arrangement, and mode of operation that produces the emission that has the highest amplitude relative to the limit is selected for the final measurement

This investigation was performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. EUT was placed at three different orientations (X, Y and Z axis) in order to find the worst orientation.

Applicable rule and limitation

§15.209 general requirements

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency [MHz]	Measurement Distance [m]	Field Strength [μ V/m]	Field Strength [dB μ V/m]
30 - 88	3	100	40.0
88 - 216	3	150	43.5
216 - 960	3	200	46.0
Above 960	3	500	53.9

In the emission table above, the tighter limit applies at the band edges.

The level of any unwanted emissions from an intentional radiator operating under these general provisions shall not exceed the level of the fundamental emission.

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector.

Test equipment used (refer to List of utilized test equipment)

AC01	BA10	CL11	PR03	TR06
------	------	------	------	------

Test software used

EMI Ver. 5.5

Calculation method

The Correction Factor and Result are calculated as followings.

$$\text{Correction Factor [dB/m]} = \text{Ant. Factor [dB/m]} + \text{Loss [dB]} - \text{Gain [dB]}$$
$$\text{Result [dB}\mu\text{V/m]} = \text{Reading [dB}\mu\text{V]} + \text{Correction Factor [dB/m]}$$

Test results - Complied with requirement


Test Data

Test condition: X-plane

[Emission level]

No.	Frequency [MHz]	Reading [dB μ V]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Ant.
1	100.001	50.7	10.0	7.6	30.1	38.2	43.5	5.3	Hori.
2	320.006	44.2	13.7	9.2	29.9	37.2	46.0	8.8	Hori.
3	340.007	44.9	14.3	9.4	29.9	38.7	46.0	7.3	Hori.
4	30.575	33.8	18.7	6.8	30.3	29.0	40.0	11.0	Vert.
5	40.680	38.9	13.0	7.0	30.3	28.6	40.0	11.4	Vert.
6	49.390	43.3	8.8	7.1	30.2	29.0	40.0	11.0	Vert.
7	100.000	47.2	10.0	7.6	30.1	34.7	43.5	8.8	Vert.

[Chart]




Test condition: Y-plane

[Emission level]

No.	Frequency [MHz]	Reading [dB μ V]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Ant.
1	100.002	47.1	10.0	7.6	30.1	34.6	43.5	8.9	Hori.
2	320.007	42.1	13.7	9.2	29.9	35.1	46.0	10.9	Hori.
3	340.000	44.5	14.3	9.4	29.9	38.3	46.0	7.7	Hori.
4	30.575	34.0	18.7	6.8	30.3	29.2	40.0	10.8	Vert.
5	40.680	39.7	13.0	7.0	30.3	29.4	40.0	10.6	Vert.
6	49.391	43.1	8.8	7.1	30.2	28.8	40.0	11.2	Vert.
7	100.002	42.6	10.0	7.6	30.1	30.1	43.5	13.4	Vert.

[Chart]




Test condition: Z-plane

[Emission level]

No.	Frequency [MHz]	Reading [dB μ V]	Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Ant.
1	100.001	45.3	10.0	7.6	30.1	32.8	43.5	10.7	Hori.
2	280.006	43.6	12.8	9.0	29.9	35.5	46.0	10.5	Hori.
3	320.008	42.9	13.7	9.2	29.9	35.9	46.0	10.1	Hori.
4	340.008	41.8	14.3	9.4	29.9	35.6	46.0	10.4	Hori.
5	384.011	43.7	15.4	9.6	29.9	38.8	46.0	7.2	Hori.
6	40.680	39.0	13.0	7.0	30.3	28.7	40.0	11.3	Vert.
7	49.392	46.4	8.8	7.1	30.2	32.1	40.0	7.9	Vert.
8	50.112	40.7	8.5	7.1	30.2	26.1	40.0	13.9	Vert.
9	100.002	41.8	10.0	7.6	30.1	29.3	43.5	14.2	Vert.

[Chart]



Tested Date: 16 May. 2014
Humidity: 60 %

Temperature: 21 degC
Atmos. Press: 1000 hPa

2.4 Frequency stability

Test setup

Test setup was implemented according to the method of ANSI C63.4: 2003 clauses 13.1.6.1 “Frequency stability measurements”, and Annex H.5 “Frequency measurements”.

Test procedure

Measurement procedures were implemented according to the test method of ANSI C63.4: 2003 Annex H5. Place the de-energized EUT in the temperature test chamber. Supply the EUT with nominal ac voltage, or install a new or fully charged battery in the EUT. An antenna was connected to the antenna output connector of the EUT if possible.

The frequency counter was connected to the measurement antenna with a suitable length of coaxial cable.

The environmental chamber set to the highest temperature specified in applicable regulation.

Allow sufficient time (approximately 30 minutes) for the temperature of the chamber to stabilize.

Turn the EUT on and measure the EUT operating frequency at startup, and two, five, and ten minutes after startup.

The measurements were performed that the temperature chamber set to reduce the lowest temperature specified in applicable regulation.

Applicable rule and limitation

§15.225(e): Frequency tolerance

Test items	Variation ranges		Limit
Temperature variations	-	-	+/-0.01%

Test equipment used (refer to List of utilized test equipment)

--	--	--	--

Test results - This item was not tested.

Test Data

Temp. [degC]	Voltages [V]	Measured Frequency [MHz]				Worst Deviation [%]	Limit [%]
		Start-up	2 min.	5 min.	10 min.		
							+/- 0.01
							+/- 0.01
							+/- 0.01
							+/- 0.01

Tested Date: -
Humidity: - %

Temperature: - degC
Atmos. Press: - hPa

2.5 Transmitter AC power line conducted emissions

Test setup

Test setup was implemented according to the method of ANSI C63.4: 2003 clause 6 “General requirements for EUT equipment arrangements and operation” and Annex H.1 “AC power line conducted emission measurements setup”.

Test procedure

Measurement procedures were implemented according to the method of ANSI C63.4: 2003 clauses 7, clause 13.1.3 and Annex H.2 “AC power line conducted emission measurements”.

Exploratory measurements were used the spectrum analyzer to identify the frequency of the emission that has the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable positions, and with a typical system equipment configuration and arrangement.

Final ac power line conducted emission measurements were performed based on the exploratory tests.

The EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit are selected for the final measurement.

When the measurement value is grater than average limitation the average detection measurements were performed.

Applicable rule and limitation

§15.207 (a) AC power line conducted limits

Frequency of Emission [MHz]	Conducted emissions Limit [dB μ V]	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50

* Decreases with the logarithm of the frequency. The lower limit applies at the band edges.

Test equipment used (refer to List of utilized test equipment)

TR09	LN05	CL18
------	------	------

Test software used

EMI Ver. 5.5

Calculation method

The Correction Factor and Result are calculated as followings.

$$\begin{aligned}\text{Correction Factor [dB]} &= \text{ISN Factor [dB]} + \text{Loss [dB]} \\ \text{Result [dB}\mu\text{V]} &= \text{Reading [dB}\mu\text{V]} + \text{Correction Factor [dB]}\end{aligned}$$

Test Data


[Emission level]

No.	Frequency [MHz]	Reading		C.F. [dB]	Result		Limit		Phase	Pass /Fail
		QP [dB μ V]	AV [dB μ V]		QP [dB μ V]	AV [dB μ V]	QP [dB μ V]	AV [dB μ V]		
1	0.16147	36.3	8.5	10.2	46.5	18.7	65.4	55.4	Va	Pass
2	0.17294	36.9	13.3	10.1	47.0	23.4	64.8	54.8	Va	Pass
3	0.18736	47.1	28.5	10.1	57.2	38.6	64.2	54.2	Va	Pass
4	0.22177	28.4	2.6	10.1	38.5	12.7	62.8	52.8	Va	Pass
5	0.24248	39.6	19.8	10.0	49.6	29.8	62.0	52.0	Va	Pass
6	0.25617	38.4	18.6	10.0	48.4	28.6	61.6	51.6	Va	Pass
7	13.5600	30.6	22.8	10.1	40.7	32.9	60.0	50.0	Va	Pass
8	27.1200	28.2	12.1	10.5	38.7	22.6	60.0	50.0	Va	Pass
9	0.15666	36.3	7.9	10.4	46.7	18.3	65.6	55.6	Vb	Pass
10	0.17848	45.9	24.9	10.3	56.2	35.2	64.6	54.6	Vb	Pass
11	0.25765	38.2	18.8	10.2	48.4	29.0	61.5	51.5	Vb	Pass
12	0.30574	34.8	17.7	10.2	45.0	27.9	60.1	50.1	Vb	Pass
13	13.5600	29.4	21.4	10.4	39.8	31.8	60.0	50.0	Vb	Pass
14	27.1200	28.6	12.5	10.8	39.4	23.3	60.0	50.0	Vb	Pass


Note: 13.56 MHz is Tx carrier frequency, so only this frequency was tested with antenna terminated condition.

[Chart]

Normal test (with Antenna)



Antenna terminated



Tested Date: 16 May. 2014
Humidity: 49 %

Temperature: 24 degC
Atmos. Press: 1000 hPa

4 List of utilized test equipment / calibration

RFT ID No.	Kind of Equipment and Precision	Manufacturer	Model No.	Serial Number	Calibration Date	Calibrated until
AC01(EM)	Anechoic Chamber (1st test room)	JSE	203397C	-	2014/4/26	2015/4/30
BA10	Biological Antenna	TESEQ	CBL6111D	32342	2013/6/14	2014/6/30
CL11	Antenna Cable for RE	RFT	-	-	2014/3/31	2015/3/31
CL18	Antenna Cable for CE	RFT	-	-	2014/4/18	2015/4/30
LN05	LISN	Kyoritsu	KNW-407F	8-1773-2	2013/5/20	2014/5/31
LP05	Loop Antenna	ETS-Lindgren	6502	00143302	2014/2/4	2015/2/28
PR15	Pre. Amplifier	Anritsu	MH648A	6201156141	2013/6/11	2014/6/30
TR06	Test Receiver (F/W : 3.93 SP2)	Rohde & Schwarz	ESU26	100002	2013/9/10	2014/9/30
TR09	Test Receiver (F/W : 4.43 SP3)	Rohde & Schwarz	ESU8	100386	2014/2/4	2015/2/28

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.