

A. INTRODUCTION

The following certification data are submitted in connection with this request for type certification of the G-220 transceiver in accordance with Section 2, of FCC Rules.

The G-220 is a hand-held, battery operated, UHF, frequency modulated, transceiver intended for voice communications applications under Part 95 GMRS (channels 1-7 or 15-22)* or Part 95 FRS (channels 8-14)*.

*See Appendix A for frequency assignment.

1. The unit's antenna meets 95.647, (i.e. is integral to the transmitter).
2. Except for power, the technical parameters for operating on all the channels (both FRS and GMRS) are the same as those for FRS, (i.e. 12.5 kHz bandwidth, 2.5 ppm frequency tolerance, maximum 2.5 kHz deviation, etc).
3. A notice is included in the user instructions that clearly informs the consumer (buyer/owner) when the radio is transmitting on GMRS frequencies, that operation on GMRS frequencies requires an FCC license and such operation is subject to additional rules specified in 47 CFR Part 95.

B. GENERAL INFORMATION REQUIRED FOR TYPE CERTIFICATION (Section 2.1033 of the Rules)

1. Name of applicant: Midland Consumer Radio
2. Identification of equipment: FCC ID: MMAG220
 - a. The equipment identification label is submitted as a separate exhibit.
 - b. Photographs of the equipment are submitted as separate exhibits.
3. Quantity production is planned.
4. Technical description:
 - a. 11k0F3E emission (FRS and GMRS)
 - b. Frequency range: 462.5500-467.7125 MHz.
 - c. Operating power ERP(d):

FRS 0.41 W

GMRS 1.3 W

1

B. GENERAL INFORMATION (Cont.)

- d. Maximum power permitted under FCC Part 95 (interstitial) is 5 watts ERP. The G-220

- fully complied with that power limitation.
- e. The dc voltage and dc currents at final amplifier:

	GMRS	FRS
Collector voltage:	5.8	5.9 Vdc
Collector current:	0.61	0.43 A
 - f. Function of each active semiconductor device:
See Appendix 1.
 - g. Complete circuit diagram is submitted as a separate exhibit.
 - h. A draft instruction book is submitted as a separate exhibit.
 - i. The transmitter tune-up procedure is submitted as a separate exhibit.
 - j. A description of circuits for stabilizing frequency is included in Appendix 2.
 - k. A description of circuits and devices employed for suppression of spurious radiation and for limiting modulation is included in Appendix 3.
 - l. Not applicable.

5. Data for 2.1046 through 2.1057 follow this section.

C. RF POWER OUTPUT (Section 2.1046 of the Rules)

ERP(d) by substitution: FRS 0.41 W
 GMRS 1.3 W

D. MODULATION CHARACTERISTICS (Section 2.1047)

1. A curve showing frequency response of the transmitter is shown in Figure 1. Reference level was audio signal output from a Boonton 8220 modulation meter with one kHz deviation. Audio output was measured with an Audio Precision System One TRMS voltmeter and tracking generator.

2. Modulation limiting curves are shown in Figure 2, using a Boonton 8220 modulation meter. Signal level was established with an Audio Precision System One. The curves show compliance with Section 2.1047 and 95.633(b).

2

D. MODULATION CHARACTERISTICS (Cont.)

3. Figure 3 is a graph of the post-limiter low pass filter which meets the requirements of paragraph 95.633(b) in providing a roll-off of $60\log f/3$ dB where f is audio frequency in kHz. Measurements were made following EIA RS-152B with an Audio Precision System One on the Boonton 8220 modulation meter audio output.

4. Occupied Bandwidth (Section 2.1047 and 95.629(a) of the Rules)


Figure 4a is a plot of the sideband envelope of the transmitter output taken with a Tektronix 494P spectrum analyzer on GMRS Channel 1. Modulation corresponded to conditions of 2.1049(c)(1) and consisted of a 2500 Hz tone at an input level 16 dB greater than that necessary to produce 50% modulation at 2317 Hz, the frequency of maximum response.

Figure 4b is a plot under the same conditions for FRS Channel 8.

The plots are within the limits imposed by Section 2.1049 and 95.635(b)(1)(3)(7) for frequency modulation. The horizontal scale (frequency) is 10 kHz per division and the vertical scale (amplitude) is a logarithmic presentation equal to 10 dB per division.

5. Emission Designator Calculation:

$$(2D + 2F) \quad 2 \times 2.5 + 2 \times 3.0 = 11k0F3E$$




MODULATION FREQUENCY RESPONSE
FCC ID: MMAG220

FIGURE 1

4

FIGURE 2

AUDIO LIMITER CHARACTERISTICS




AUDIO LIMITER CHARACTERISTICS
FCC ID: MMAG220

FIGURE 2

5

FIGURE 3

AUDIO LOW PASS FILTER RESPONSE




AUDIO LOW PASS FILTER RESPONSE
FCC ID: MMAG220

FIGURE 3

6

FIGURE 4a

OCCUPIED BANDWIDTH



ATTENUATION IN dB BELOW MEAN OUTPUT POWER Required

On any frequency more than 50%
up to and including 100% of the
authorized bandwidth, 20 kHz
(10-20 kHz)

25

On any frequency more than 100%,
up to and including 250% of the
authorized bandwidth (20-50 kHz)

35

On any frequency removed from
the assigned frequency by more
than 250% of the authorized
bandwidth (over 50 kHz)

$$43 + 10 \log P = 44$$


(P = 1.3 W)

OCCUPIED BANDWIDTH
FCC ID: MMAG220

FIGURE 4a, (GMRS)

7
FIGURE 4b

OCCUPIED BANDWIDTH



ATTENUATION IN dB BELOW
MEAN OUTPUT POWER
Required

On any frequency more than 50%
up to and including 100% of the
authorized bandwidth, 20 kHz
(10-20 kHz)

25

On any frequency more than 100%,
up to and including 250% of the
authorized bandwidth (20-50 kHz)

35

On any frequency removed from
the assigned frequency by more
than 250% of the authorized
bandwidth (over 50 kHz)

$$43 + 10 \log P = 39$$

(P = 0.41 W)

OCCUPIED BANDWIDTH
FCC ID: MMAG220

FIGURE 4b, (FRS)

8

E. SPURIOUS EMISSIONS AT THE ANTENNA TERMINALS

Not Applicable, integral antenna.

F. MEASUREMENTS OF SPURIOUS RADIATION
(Section 2.1053, 95.635(b)(7) of the Rules)

Measurement of radiated spurious emissions from the G-220 were made by substitution with a Tektronix 494P spectrum analyzer using Singer DM-105A calibrated test antennae for the measurements to 1 GHz, Polarad CA-L, CA-S, CA-M and/or EMC0 3115. The transmitter was located in an OATS 3 meters from the test antenna. Supply voltage was a power supply with a terminal voltage under load of 6.0 Vdc. The transmitter and test antennae were arranged to maximize pickup. Both vertical and horizontal test antenna polarization were employed.

TABLE 1a

TRANSMITTER RADIATED SPURIOUS
462.5625 MHz, 6.0 Vdc, GMRS, Channel 1

<u>Frequency</u> <u>MHz</u>	<u>dB Below</u> <u>Carrier</u> <u>Reference</u> ¹
462.563	0
925.126	46H
1387.689	49V
1850.252	45V
2312.815	52V

Required: $43 + 10\log(1.3) = 44$

¹Worst-case polarization, H-Horizontal, V-Vertical.

All other spurious from 21.5 MHz to 4.7 GHz were 20 dB or more below FCC limit.

9

F. MEASUREMENTS OF SPURIOUS RADIATION (Cont.)

TABLE 1b

TRANSMITTER RADIATED SPURIOUS
467.5625 MHz, 6.0 Vdc, FRS, Channel 8

dB Below

<u>Frequency</u> <u>MHz</u>	<u>Carrier</u> <u>Reference</u> ¹
467.563	0
935.125	47H
1402.688	52V
1870.250	40V
2337.813	59V

$$\text{Required: } 43 + \text{Log}(0.41) = 39$$

¹Worst-case polarization, H-Horizontal, V-Vertical.

All other spurious from 12.5 MHz to 4.7 GHz were 20 dB or more below FCC limit.

G. FREQUENCY STABILITY
(Section 2.1055 and 95.621(b) of the Rules)

Measurement of frequency stability versus temperature was made at temperatures from -30°C to +50°C. At each temperature, the unit was exposed to test chamber ambient a minimum of 60 minutes after indicated chamber temperature ambient had stabilized to within $\pm 2^\circ$ of the desired test temperature. Following the 1 hour soak at each temperature, the unit was turned on, keyed and frequency measured within 2 minutes. Test temperature was sequenced in the order shown in Table 2, starting with -30°C.

A Thermotron S1.2 temperature chamber was used. Temperature was monitored with a Keithley 871 digital temperature probe. Primary supply was 6.0 volts. Frequency was measured with a HP 5385A digital frequency counter. Measurements were made at 462.5625 MHz. No transient keying effects were observed.

10

G. FREQUENCY STABILITY (Cont.)

TABLE 2

462.5625 MHz, 6.0 V Nominal

<u>Temperature, °C</u>	<u>Output_Frequency, _MHz</u>	<u>p.p.m.</u>
-30.3	463.562368	-0.3

-20.1	462.562439	-0.1
- 9.9	462.562602	0.2
1.1	462.562522	0.0
10.4	462.562442	-0.1
20.0	462.562381	-0.3
31.2	462.562306	-0.4
40.3	462.562311	-0.4
49.9	462.562752	0.5

Maximum frequency error: 462.562752
462.562500
+ .000252 MHz

FCC Part 95 specifies .00025% or a maximum of $\pm$.001156 MHz, which corresponds to:

High Limit 462.563656 MHz
Low Limit 462.561344 MHz

H. FREQUENCY STABILITY AS A FUNCTION OF SUPPLY VOLTAGE (Section 2.1055 and 95.621(b) of the Rules)

Oscillator frequency as a function of power supply voltage was measured with a HP 5385A digital frequency counter as supply voltage provided by an HP 6264B variable dc power supply was varied from $\pm 15\%$ above the nominal 6.0 volt rating to below the battery end point. A Keithley 197 digital voltmeter was used to measure supply voltage at transmitter primary input terminals. Measurements were made at 20 °C ambient.

11
TABLE 3

462.5625 MHz, 20°C, 6.0 V Nominal

<u>%</u>	<u>Supply_Voltage</u>	<u>Output_Frequency,_MHz</u>	<u>p.p.m.</u>
115	6.9	462.562467	-0.1
110	6.6	462.562439	-0.1

105	6.3	462.562408	-0.2
100	6.0	462.562381	-0.3
95	5.7	462.562364	-0.3
90	5.4	462.562358	-0.3
85	5.1	462.562359	-0.3
*	4.8	462.562368	-0.3

Maximum frequency error:	462.562358
	<u>462.562500</u>

*MFR rated battery endpoint. - .000142 MHz

FCC Part 95 specifies .00025% or a maximum of $\pm .001156$ MHz,
corresponding to:

High Limit	462.563656 MHz
Low Limit	462.561344 MHz

APPENDIX A

CHANNEL ASSIGNMENT

GMRS Channels:

CH1:	462.5625 MHz
CH2:	462.5875 MHz
CH3:	462.6125 MHz

CH4: 462.6375 MHz
CH5: 462.6625 MHz
CH6: 462.6875 MHz
CH7: 462.7125 MHz

CH15: 462.5500 MHz
CH16: 462.5750 MHz
CH17: 462.6000 MHz
CH18: 462.6250 MHz
CH19: 462.6500 MHz
CH20: 462.6750 MHz
CH21: 462.7000 MHz
CH22: 462.7250 MHz

FRS Channels:

CH8: 467.5625 MHz
CH9: 467.5875 MHz
CH10: 467.6125 MHz
CH11: 467.6375 MHz
CH12: 467.6625 MHz
CH13: 467.6875 MHz
CH14: 467.7125 MHz

APPENDIX 1

ΣΕΜΙΧΟΝΔΥΧΤΟΡΣ ΑΝΔ ΦΥΝΧΤΙ

ΤΡΑΝΣΙΣΤΟΡ

ΘΡ1	2ΣΧ4226	N.E.X	ΡΕ ΡΦ ΑΜΠ.
ΘΡ2	2ΣΧ4226	N.E.X	1ᾲΣΤ ΜΙΞΕΡ.
ΘΡ3	KTX3880Σ	K.E.X	1ᾲΣΤ ΙΦ ΑΜΠ.

ΘΡ5	KPX104Σ	K.E.X	TONE ΔΕΤ.
ΘΡ6	KTA1504Σ	K.E.X	ΣΘΥΕΛΑΧΗ ΜΥΤΕ.
ΘΤ1	2ΣΧ4226	N.E.X	ΤΞ ΒΥΦΦΕΡ.
ΘΤ2	2ΣΧ4226	N.E.X	ΤΞ ΠΟΩΕΡ ΔΡΙΞΕ ΑΜΠ.
ΘΤ3	NE5510279A	N.E.X	ΤΞ ΠΟΩΕΡ ΦΙΝΑΛ ΑΜΠ.
ΘΦ1	2ΣΧ4226	N.E.X	ΒΥΦΦΕΡ.
ΘΦ2	KPX110Σ	K.E.X	ΡΞ Β+ ΣΩΙΤΧΗΙΝΓ ΑΤ ΤΞ.
ΘΣ1	KPA105Σ	K.E.X	ΡΞ Β+ ΣΩΙΤΧΗΙΝΓ.
ΘΣ2	KPA105Σ	K.E.X	ΠΟΩΕΡ ΣΑΞΕ ΧΟΝΤΡΟΛ.
ΘΣ3	KPA105Σ	K.E.X	ΤΞ Β+ ΣΩΙΤΧΗΙΝΓ.
ΘΣ4	KPX104Σ	K.E.X	ΤΞ Β+ ΣΩΙΤΧΗΙΝΓ.
ΘΣ5	KPA110Σ	K.E.X	ΒΑΧΚ ΛΙΓΗΤ ΛΕΔ ΣΩΙΤΧΗΙΝΓ.
ΘΣ7	KPA101Σ	K.E.X	ΠΤΤ Σ/Ω
ΘΣ9	KPX110Σ	K.E.X	ΧΑΛΛ ΜΥΤΕ
Θ1	2ΣΧ4226	N.E.X	ΡΞ ΒΥΦΦΕΡ.
Θς1	KPX104Σ	K.E.X	ΡΞ/ΤΞ ςΧΟ ΣΩΙΤΧΗΙΝΓ.
Θς2	2ΣΧ4226	N.E.X	Ο.Σ.Χ
ΘΒ1	KTX3875Σ	K.E.X	ΛΟΩ ΒΑΤΤ. ΔΕΤ.
ΘΒ1	KTX3875Σ	K.E.X	ΠΟΩΕΡ Η/Λ ΧΟΝΤΡΟΛ

ΙΝΤΕΓΡΑΤΕΔ ΧΙΡΧΥΙΤ

ΙΧ1	KA3361	ΣΑΜΣΥΝΓ	2ΝΔ ΜΙΞΕΡ ΙΦ ΑΝΔ ΦΜ ΔΕΤΕΧΤ
ΙΧ2	ΤΜΠ87Χ807Υ	ΤΟΣΗΒΑ	ΧΠΥ
ΙΧ3	NΘM2070	Θ.P.X	ΑΥΔΙΟ ΠΟΩΕΡ ΑΜΠ.
ΙΧ4	TB31202ΦΝ	ΤΟΣΗΒΑ	ΠΑΛ ΦΡΕΘΥΕΝΧΨ ΣΨΝΤΗΕΣΙΖΕΡ
ΙΧ5	TK71530	TOKO	ΡΕΓΥΛΑΤΟΡ
ΙΧ6	ΛΜ324	NATIONΑΛ	ΠΡΕ-ΕΜΠΑΣΙΣ ΛΙΜΙΤΤΕΡ ΑΝΔ ΜΙΧ
ΙΧ8	ΛΜ324	NATIONΑΛ	ΧΤΧΣΣ ΤΟΝΕ ΔΕΤ.
ΙΧ10	ΛΜ324	NATIONΑΛ	ΔΕ-ΕΜΠΑΣΙΣ ΤΟΝΕ ΦΙΛΤΕΡ

APPENDIX 2

CIRCUITS AND DEVICES TO STABILIZE FREQUENCY

The PLL synthesizer of the G-220 (GMRS) consists of the signal loop PLL circuit with the reference of 6.25 kHz. The IC4 PLL IC includes all the functions such as the reference oscillator, the driver, the phase detector, the lock detector and the programmable divider.

At the reference oscillator, the 21.25 MHz TCXO of the CTX1 is connected to the pin 11 of the IC4 to oscillate the frequency of 21.25 MHz. The TCXO (21.25 MHz) is the temperature compensation circuit to maintain the frequency within the allowable error range even under a low temperature of -30.

The phase detectors send out the output power to the loop filter through 3 pin of the IC4. If the oscillation frequency of the VCO is low compared to the reference frequency, the phase detector sends out the output power in positive pulse. If the oscillation frequency of the VCO is high, phase detector sends out the output power in negative pulse. Therefore, the VCO can maintain the frequency set.

CIRCUITS AND DEVICES TO
STABILIZE FREQUENCY, etc.
FCC ID: MMAG220

APPENDIX 2
APPENDIX 3

CIRCUITS AND DEVICES TO
SUPPRESS SPURIOUS EMISSIONS, ETC.

The transmitted signal of approximately 7 mW, combined at the PLL module is supplied to the base of the QT3 amplifier. The transmitted signal amplified to 2 watts here passes the TX LPF of the 2nd characteristic of the LT4 and the LT5, and RX/TX switching takes place by the DT2. After this, the signal is provided to the antenna the TX LPF of the 1st characteristics, consisted of the LT7.

CIRCUITS AND DEVICES TO
SUPPRESS SPURIOUS EMISSIONS, etc.
FCC ID: MMAG220

APPENDIX 3