



APPENDIX B – EUT TEST SETUP PHOTOGRAPHS











[Tissue Liquid Depth : 15cm]




Battery Type: Energizer (Alkaline)

GMRS	
Time	Power Out
0	4.240
2	4.100
4	4.000
6	3.900
8	3.800
10	3.700
12	3.500
14	3.300
16	3.008
18	2.770
20	2.400
22	2.100
24	1.800
26	1.550
28	1.382
30	1.285
32	1.263
34	1.210
36	1.163
38	1.134
40	1.115



FRS	
Time	Power Out
0	0.538
2	0.513
4	0.492
6	0.473
8	0.459
10	0.447
12	0.434
14	0.416
16	0.402
18	0.385
20	0.376
22	0.364
24	0.355
26	0.347
28	0.339
30	0.331
32	0.327
34	0.320
36	0.315
38	0.311
40	0.307



Date: January 05, 2005

Federal Communications Commission
Authorization and Evaluation Division
7435 Oakland Mills Road
Columbia, MD21046

Subject: GXT-500 Model Battery Type

To whom it may concern

Here we would like to confirm that the 'AA' type batteries only should be used
For this subject model GXT-500. (FCC ID: MMAGXT500)

Sincerely Yours,
Global Link Corporation Limited.

Signed by

President



Feb' 4 '2005