

RADIO TEST REPORT

Test Report No. 15627086H-R2

Customer	Tokai Rika Co Ltd
Description of EUT	RKE Transmitter
Model Number of EUT	B4A2F2R
FCC ID	MOZB4A2F2R
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied
Issue Date	March 24, 2025
Remarks	-

Representative test engineer

Shousei Hamaguchi
Engineer

Approved by

Akihiko Maeda
Leader

CERTIFICATE 5107.02

The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
 There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 24.0

ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.
It does not cover administrative issues such as Manual or non-Radio test related Requirements.
(if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided by the customer for this report is identified in SECTION 1.
- The laboratory is not responsible for information provided by the customer which can impact the validity of the results.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

REVISION HISTORY

Original Test Report No. 15627086H

This report is a revised version of 15627086H-R1. 15627086H-R1 is replaced with this report.

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	15627086H	January 28, 2025	-
1	15627086H-R1	March 13, 2025	Addition of the variant models in Clause 2.2.
1	15627086H-R1	March 13, 2025	Correction of Mode for Plot data.
2	15627086H-R2	March 24, 2025	Addition and revision of the following information due to additional measurements: - Clause 2.2 Test Date - APPENDIX 1 Test Data (Page18) - APPENDIX 2 Test Equipment
2	15627086H-R2	March 24, 2025	Addition of the following sentence in Clause 4.1; “*Transmitting duty was 100 % on Transmitting mode tests.”
2	15627086H-R2	March 24, 2025	Correction of the Test Location in Test data (Page 13, 14, and 19);

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	IEC	International Electrotechnical Commission
AFH	Adaptive Frequency Hopping	IEEE	Institute of Electrical and Electronics Engineers
AM	Amplitude Modulation	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISO	International Organization for Standardization
AP	Access Point	JAB	Japan Accreditation Board
ASK	Amplitude Shift Keying	LAN	Local Area Network
Atten., ATT	Attenuator	LIMS	Laboratory Information Management System
AV	Average	MCS	Modulation and Coding Scheme
BPSK	Binary Phase-Shift Keying	MRA	Mutual Recognition Arrangement
BR	Bluetooth Basic Rate	N/A	Not Applicable
BT	Bluetooth	NIST	National Institute of Standards and Technology
BT LE	Bluetooth Low Energy	NS	No signal detect.
BW	BandWidth	NSA	Normalized Site Attenuation
Cal Int	Calibration Interval	NVLAP	National Voluntary Laboratory Accreditation Program
CCK	Complementary Code Keying	OBW	Occupied Band Width
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PRBS	Pseudo-Random Bit Sequence
DSSS	Direct Sequence Spread Spectrum	PSD	Power Spectral Density
EDR	Enhanced Data Rate	QAM	Quadrature Amplitude Modulation
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QP	Quasi-Peak
EMC	ElectroMagnetic Compatibility	QPSK	Quadri-Phase Shift Keying
EMI	ElectroMagnetic Interference	RBW	Resolution Band Width
EN	European Norm	RDS	Radio Data System
ERP, e.r.p.	Effective Radiated Power	RE	Radio Equipment
EU	European Union	RF	Radio Frequency
EUT	Equipment Under Test	RMS	Root Mean Square
Fac.	Factor	RSS	Radio Standards Specifications
FCC	Federal Communications Commission	Rx	Receiving
FHSS	Frequency Hopping Spread Spectrum	SA, S/A	Spectrum Analyzer
FM	Frequency Modulation	SG	Signal Generator
Freq.	Frequency	SVSWR	Site-Voltage Standing Wave Ratio
FSK	Frequency Shift Keying	TR	Test Receiver
GFSK	Gaussian Frequency-Shift Keying	Tx	Transmitting
GNSS	Global Navigation Satellite System	VBW	Video BandWidth
GPS	Global Positioning System	Vert.	Vertical
Hori.	Horizontal	WLAN	Wireless LAN

CONTENTS	PAGE
SECTION 1: Customer Information	5
SECTION 2: Equipment Under Test (EUT).....	5
SECTION 3: Test Specification, Procedures & Results	6
SECTION 4: Operation of EUT during testing	9
SECTION 5: Radiated Spurious Emission.....	10
SECTION 6: Automatically deactivate	12
SECTION 7: -20 dB Bandwidth and 99% emission bandwidth	12
APPENDIX 1: Test Data.....	13
Automatically deactivate	13
Radiated Emission (Fundamental and Spurious Emission).....	15
-20 dB Bandwidth / 99% emission bandwidth	19
APPENDIX 2: Test Instruments	20
APPENDIX 3: Photographs of Test Setup	21
Radiated Spurious Emission.....	21
Worst Case Position	23

SECTION 1: Customer Information

Company Name	Tokai Rika Co Ltd
Address	3-260 Toyota, Oguchi-cho, Niwa-gun, Aichi 480-0195, Japan
Telephone Number	+81-70-2244-4738
Contact Person	Tetsuhiro Okuoka

The information provided by the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

SECTION 2: Equipment Under Test (EUT)

2.1 Identification of EUT

Description	RKE Transmitter
Model Number	B4A2F2R
Serial Number	Refer to SECTION 4.2
Condition	Engineering prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	December 23, 2024 and January 14, 2025
Test Date	December 25, 2024 to March 24, 2025

2.2 Product Description

General Specification

Rating	DC 3.0 V (battery (DC 2.5 V to 3.2 V))
Operating temperature	-20 deg. C to +60 deg. C

Radio Specification

Equipment Type	Transmitter
Frequency of Operation	Channel 1(CH 1): 433.58 MHz Channel 2(CH 2): 434.42 MHz
Type of Modulation	FSK

*Tested model has variation models: Variation 1 (4 switches), Variation 2 (2 switches) and Variation 3 (3 switches).

The differences of these variations are appearance and the number of switches.
Therefore the test was performed with original model (Variation 1) as representative.

SECTION 3: Test Specification, Procedures & Results

3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators Section 15.231 Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.

3.2 Procedures and Results

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted emission	FCC: ANSI C63.10:2013 6 Standard test methods ISED: RSS-Gen 8.8	FCC: Section 15.207 ISED: RSS-Gen 8.8	N/A	N/A	*1)
Automatically deactivate	FCC: ANSI C63.10:2013 6 Standard test methods ISED: -	FCC: Section 15.231(a)(1) ISED: RSS-210 A1.2	N/A	Complied	Radiated
Electric Field Strength of Fundamental Emission	FCC: ANSI C63.10:2013 6 Standard test methods ISED: RSS-Gen 6.12	FCC: Section 15.231(b) ISED: RSS-210 A1.3	4.9 dB 434.420 MHz Vertical, AV	Complied	Radiated
Electric Field Strength of Spurious Emission	FCC: ANSI C63.10:2013 6 Standard test methods ISED: RSS-Gen 6.13	FCC: Section 15.205 Section 15.209 Section 15.231(b) ISED: RSS-210 A1.3 RSS-Gen 8.9	3.2 dB 3909.780 MHz Horizontal, AV	Complied	Radiated
-20 dB Bandwidth	FCC: ANSI C63.10:2013 6 Standard test methods ISED: -	FCC: Section 15.231(c) ISED: Reference data	N/A	Complied	Radiated

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

*1) The test is not applicable since the EUT does not have AC Mains.

FCC Part 15.31 (e)

The test was performed with the New Battery during the tests.
Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT.
Therefore, the equipment complies with the antenna requirement of Section 15.203.

3.3 Addition to Standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% emission bandwidth	ANSI C63.10:2013 6 Standard test methods	Reference data	N/A	-	Radiated

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement. Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Radiated emission

Measurement distance	Frequency range		Unit	Calculated Uncertainty (+/-)
3 m	9 kHz to 30 MHz		dB	3.3
10 m			dB	3.1
3 m	30 MHz to 200 MHz	Horizontal	dB	5.0
		Vertical	dB	5.0
	200 MHz to 1000 MHz	Horizontal	dB	5.2
		Vertical	dB	6.2
10 m	30 MHz to 200 MHz	Horizontal	dB	5.5
		Vertical	dB	5.4
	200 MHz to 1000 MHz	Horizontal	dB	5.5
		Vertical	dB	5.5
3 m	1 GHz to 6 GHz		dB	5.1
	6 GHz to 18 GHz		dB	5.4
1 m	10 GHz to 18 GHz		dB	5.4
	18 GHz to 26.5 GHz		dB	5.3
	26.5 GHz to 40 GHz		dB	4.8
0.5 m	26.5 GHz to 40 GHz		dB	5.0

Automatically deactivate, -20 dB Bandwidth and 99% Occupied Bandwidth

Item	Unit	Calculated Uncertainty (+/-)
Bandwidth (OBW)	%	0.96
Time readout (time span upto 100 msec)	%	0.11
Time readout (time span upto 1000 msec)	%	0.11
Time readout (time span upto 60 sec)	%	0.02

3.5 Test Location

UL Japan, Inc. Ise EMC Lab.
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan
Telephone: +81-596-24-8999

*A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919
ISED Lab Company Number: 2973C / CAB identifier: JP0002

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

3.6 Test Data, Test Instruments, and Test Set Up

Refer to APPENDIX.

SECTION 4: Operation of EUT during testing

4.1 Operating Mode(s)

Test mode	Remarks
1) Transmitting mode (Tx 433.58 MHz) *1)	Used for other than Automatically deactivate test
2) Transmitting mode (Tx 434.42 MHz) *1)	Used for other than Automatically deactivate test
3) Normal use mode (Tx 433.58 MHz)	Used for Automatically deactivate test only
4) Normal use mode (Tx 434.42 MHz)	Used for Automatically deactivate test only


*The system was configured in typical fashion (as a user would normally use it) for testing.
*Transmitting duty was 100 % on Transmitting mode tests.
*Power of the EUT was set by the software as follows;
Software: Transmitter Version: 120
(Date: 2024.08.20, Storage location: EUT memory)

*This setting of software is the worst case.
Any conditions under the normal use do not exceed the condition of setting.
In addition, end users cannot change the settings of the output power of the product.
Justification: The system was configured in typical fashion (as a user would normally use it) for testing.

*1) The software of this mode is the same as one of normal product, except that EUT continues to transmit (For Normal use mode, EUT stops to transmit in a given time, even if transceiver button is being pressed.).

This EUT has two modes which mechanical key is folded in or not. The worst case was confirmed on the mechanical key folded-in and folded-out, as a result, the test on mechanical key folded-in was the worst case. Therefore, the test on mechanical key folded-in was performed only.

4.2 Configuration and Peripherals



* Setup was taken into consideration and test data was taken under worse case conditions.

Description of EUT

No.	Item	Model number	Serial Number	Manufacturer	Remark
A	RKE Transmitter	B4A2F2R	No.2 *1) No.3 *2)	Tokai Rika Co Ltd	EUT

*1) Used for other tests except for Automatically deactivate test

*2) Used for Automatically deactivate test only

SECTION 5: Radiated Spurious Emission

Test Procedure

[For below 30 MHz]

The noise level was checked by moving a search-coil (Loop Antenna) close to the EUT.

[For 30 MHz to 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 1.0 m, raised 0.8 m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane.

The measuring antenna height was varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The measurements were performed for both vertical and horizontal antenna polarization.


The radiated emission measurements were made with the following detector function of the test receiver / spectrum analyzer.

Test Antennas are used as below:

Frequency	Below 30 MHz	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Loop	Biconical	Logperiodic	Horn

Frequency	From 9 kHz to 90 kHz and From 110 kHz to 150 kHz	From 90 kHz to 110 kHz	From 150 kHz to 490 kHz	From 490 kHz to 30 MHz	From 30 MHz to 1 GHz	Above 1 GHz
Detector Type	Peak	Peak	Peak	Peak	Peak and Peak with Duty factor	Peak and Peak with Duty factor and AV
IF Bandwidth	200 Hz	200 Hz	9.1 kHz	9.1 kHz	120 kHz	PK: S/A: RBW: 1 MHz, VBW: 3 MHz AV: S/A: RBW 1 MHz, VBW: 10 Hz


[Test Setup]
Below 1 GHz



* : Center of turn table

Test Distance: 3 m

1 GHz to 4.5 GHz



r : Radius of an outer periphery of EUT
x : Center of turn table

Distance Factor: $20 \times \log (3.75 \text{ m}^* / 3.0 \text{ m}) = 1.94 \text{ dB}$
*(Test Distance + SVSWR Volume / 2) - r = 3.75 m

Test Distance: 3 m
SVSWR Volume: 1.5 m
(SVSWR Volume has been calibrated based on CISPR 16-1-4.)
r: 0.0 m

(The test was performed with r = 0.0 m since EUT is small and it was the rather conservative condition.)

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range	: 9 kHz to 4.5 GHz
Test data	: APPENDIX
Test result	: Pass

SECTION 6: Automatically deactivate

Test Procedure

The measurement was performed with Electric field strength using a spectrum analyzer.

Test data : APPENDIX
Test result : Pass

SECTION 7: -20 dB Bandwidth and 99% emission bandwidth

Test Procedure

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
-20 dB Bandwidth / 99% emission bandwidth	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak *1)	Max Hold *1)	Spectrum Analyzer

*1) Peak hold was applied as Worst-case measurement.


Test data : APPENDIX
Test result : Pass

APPENDIX 1: Test Data

Automatically deactivate

Test place Ise EMC Lab.
Semi Anechoic Chamber No.2
Date January 15, 2025
Temperature / Humidity 24 deg. C / 33 % RH
Engineer Shousei Hamaguchi
Mode Mode 3


Time of Transmitting [s]	Limit [s]	Result
0.7572	5.00	Pass



Automatically deactivate

Test place Ise EMC Lab.
Semi Anechoic Chamber No.2
Date January 15, 2025
Temperature / Humidity 24 deg. C / 33 % RH
Engineer Shousei Hamaguchi
Mode Mode 4

Time of Transmitting [s]	Limit [s]	Result
0.7572	5.00	Pass



Radiated Emission (Fundamental and Spurious Emission)

Test place Semi Anechoic Chamber	Ise EMC Lab. No.2	No.2	No.2
Date	December 25, 2024	December 26, 2024	December 27, 2024
Temperature / Humidity	21 deg. C / 55 % RH	20 deg. C / 53 % RH	19 deg. C / 47 % RH
Engineer	Kiyoshiro Okazaki	Kiyoshiro Okazaki	Ken Fujita
Mode	Mode 1		

Polarity [Hori/Vert]	Frequency [MHz]	Reading [dBuV]AV	Reading [dBuV]PK	Ant Factor	Loss [dB]	Gain [dB]	Duty Factor	Result (PK) [dBuV/m]	Result (PK with Duty Factor or AV) [dBuV/m]	Limit (PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (PK) [dB]	Margin (AV) [dB]	Inside or Outside of Restricted Bands	Remarks
Hori.	433.580	-	76.2	16.3	9.7	28.7	0.0	73.5	73.5	100.8	80.8	27.3	7.3	Carrier	*1)
Hori.	867.160	-	32.4	21.9	11.3	28.9	0.0	36.7	36.7	80.8	60.8	44.1	24.1	Outside	*1)
Hori.	1300.740	-	47.7	26.0	5.1	34.1	0.0	44.7	44.7	73.9	53.9	29.2	9.2	Inside	*1)
Hori.	1734.320	-	47.9	25.0	4.6	33.6	0.0	43.9	43.9	80.8	60.8	36.9	16.9	Outside	*1)
Hori.	2167.900	-	49.0	28.0	4.7	33.2	0.0	48.5	48.5	80.8	60.8	32.3	12.3	Outside	*1)
Hori.	2601.480	-	46.0	27.5	4.9	33.2	-	45.2	45.2	80.8	60.8	35.6	15.6	Outside	Floor noise
Hori.	3035.060	-	46.3	28.4	5.1	33.3	-	46.5	46.5	80.8	60.8	34.3	14.3	Outside	Floor noise
Hori.	3468.640	-	46.6	28.6	5.6	33.1	0.0	47.7	47.7	80.8	60.8	33.1	13.1	Outside	*1)
Hori.	3902.220	47.2	54.0	29.7	6.1	32.9	-	56.9	50.1	73.9	53.9	17.0	3.8	Inside	
Hori.	4335.800	-	44.7	30.5	6.8	32.8	-	49.2	49.2	73.9	53.9	24.7	4.7	Inside	Floor noise
Vert.	433.580	-	78.2	16.3	9.7	28.7	0.0	75.5	75.5	100.8	80.8	25.3	5.3	Carrier	*1)
Vert.	867.160	-	35.2	21.9	11.3	28.9	0.0	39.5	39.5	80.8	60.8	41.3	21.3	Outside	*1)
Vert.	1300.740	-	46.5	26.0	5.1	34.1	-	43.5	43.5	73.9	53.9	30.4	10.4	Inside	Floor noise
Vert.	1734.320	-	46.4	25.0	4.6	33.6	-	42.4	42.4	80.8	60.8	38.4	18.4	Outside	Floor noise
Vert.	2167.900	-	45.9	28.0	4.7	33.2	-	45.4	45.4	80.8	60.8	35.4	15.4	Outside	Floor noise
Vert.	2601.480	-	45.5	27.5	4.9	33.2	-	44.7	44.7	80.8	60.8	36.1	16.1	Outside	Floor noise
Vert.	3035.060	-	45.5	28.4	5.1	33.3	-	45.7	45.7	80.8	60.8	35.1	15.1	Outside	Floor noise
Vert.	3468.640	-	46.6	28.6	5.6	33.1	0.0	47.7	47.7	80.8	60.8	33.1	13.1	Outside	*1)
Vert.	3902.220	47.6	53.9	29.7	6.1	32.9	-	56.8	50.5	73.9	53.9	17.1	3.4	Inside	
Vert.	4335.800	-	44.2	30.5	6.8	32.8	-	48.7	48.7	73.9	53.9	25.2	5.2	Inside	Floor noise

Sample calculation:

Result of PK = Reading + Ant Factor + Loss (Cable + Attenuator + Filter (above 1 GHz) + Distance factor (above 1 GHz)) - Gain (Amplifier)

Result of PK with Duty factor (PK / W) = Reading + Ant Factor + Loss (Cable + Attenuator + Filter (above 1 GHz) + Distance factor (above 1 GHz)) - Gain (Amplifier) + Duty factor

Result of AV= Reading + Ant Factor + Loss {Cable + Attenuator+ Filter +Distance factor (above 1 GHz)} - Gain (Amplifier)

For above 1 GHz: Distance Factor: $20 \times \log (3.75 \text{ m}/3.0 \text{ m}) = 1.94 \text{ dB}$

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

*1) Since the peak emission result satisfied the average limit, duty factor was omitted.

If Gain 0.0 dB shown in the above table, pre-amplifier was not used to avoid the influence of carrier power. The pre-amplifier used for carrier frequency measurement was not saturated.

Radiated Emission (Fundamental and Spurious Emission)

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.2	No.2	No.2
Date	December 25, 2024	December 26, 2024	December 27, 2024
Temperature / Humidity	21 deg. C / 55 % RH	20 deg. C / 53 % RH	19 deg. C / 47 % RH
Engineer	Kiyoshiro Okazaki	Kiyoshiro Okazaki	Ken Fujita
Mode	Mode 2		

Polarity [Hor/Vert]	Frequency [MHz]	Reading [dBuV]AV	Reading [dBuV]PK	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (PK) [dBuV/m]	Result (PK with Duty Factor or AV) [dBuV/m]	Limit (PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (PK) [dB]	Margin (AV) [dB]	Inside or Outside of Restricted Bands	Remarks
Hori.	434.420	-	76.4	16.3	9.7	28.7	0.0	73.7	73.7	100.8	80.8	27.1	7.1	Carrier	*1)
Hori.	868.840	-	34.8	21.9	11.3	28.9	0.0	39.1	39.1	80.8	60.8	41.7	21.7	Outside	*1)
Hori.	1303.260	-	48.5	26.0	5.0	34.1	0.0	45.4	45.4	73.9	53.9	28.5	8.5	Inside	*1)
Hori.	1737.680	-	47.6	25.0	4.6	33.6	0.0	43.6	43.6	80.8	60.8	37.2	17.2	Outside	*1)
Hori.	2172.100	-	49.4	28.1	4.7	33.2	0.0	49.0	49.0	80.8	60.8	31.8	11.8	Outside	*1)
Hori.	2606.520	-	45.0	27.5	4.9	33.2	-	44.2	44.2	80.8	60.8	36.6	16.6	Outside	Floor noise
Hori.	3040.940	-	45.9	28.5	5.1	33.3	-	46.2	46.2	80.8	60.8	34.6	14.6	Outside	Floor noise
Hori.	3475.360	-	47.4	28.6	5.6	33.1	0.0	48.5	48.5	80.8	60.8	32.3	12.3	Outside	*1)
Hori.	3909.780	47.8	53.3	29.7	6.1	32.9	-	56.2	50.7	73.9	53.9	17.7	3.2	Inside	
Hori.	4344.200	-	44.9	30.5	6.8	32.8	-	49.4	49.4	73.9	53.9	24.5	4.5	Inside	Floor noise
Vert.	434.420	-	78.6	16.3	9.7	28.7	0.0	75.9	75.9	100.8	80.8	24.9	4.9	Carrier	*1)
Vert.	868.840	-	34.9	21.9	11.3	28.9	0.0	39.2	39.2	80.8	60.8	41.6	21.6	Outside	*1)
Vert.	1303.260	-	46.2	26.0	5.0	34.1	-	43.1	43.1	73.9	53.9	30.8	10.8	Inside	Floor noise
Vert.	1737.680	-	46.5	25.0	4.6	33.6	-	42.5	42.5	80.8	60.8	38.3	18.3	Outside	Floor noise
Vert.	2172.100	-	46.6	28.1	4.7	33.2	0.0	46.2	46.2	80.8	60.8	34.6	14.6	Outside	*1)
Vert.	2606.520	-	45.3	27.5	4.9	33.2	-	44.5	44.5	80.8	60.8	36.3	16.3	Outside	Floor noise
Vert.	3040.940	-	46.3	28.5	5.1	33.3	-	46.6	46.6	80.8	60.8	34.2	14.2	Outside	Floor noise
Vert.	3475.360	-	47.4	28.6	5.6	33.1	0.0	48.5	48.5	80.8	60.8	32.3	12.3	Outside	*1)
Vert.	3909.780	46.7	53.1	29.7	6.1	32.9	-	56.0	49.6	73.9	53.9	17.9	4.3	Inside	
Vert.	4344.200	-	44.7	30.5	6.8	32.8	-	49.2	49.2	73.9	53.9	24.7	4.7	Inside	Floor noise

Sample calculation:

Result of PK = Reading + Ant Factor + Loss (Cable + Attenuator + Filter (above 1 GHz) + Distance factor (above 1 GHz)) - Gain (Amplifier)

Result of PK with Duty factor (PK / W) = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1 GHz) + Distance factor (above 1 GHz)} - Gain (Amplifier) + Duty factor

Result of AV= Reading + Ant Factor + Loss {Cable + Attenuator + Filter + Distance factor (above 1 GHz)} - Gain (Amplifier)

For above 1 GHz: Distance Factor: $20 \times \log (3.75 \text{ m}/3.0 \text{ m}) = 1.94 \text{ dB}$


*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

*1) Since the peak emission result satisfied the average limit, duty factor was omitted.

If Gain 0.0 dB shown in the above table, pre-amplifier was not used to avoid the influence of carrier power. The pre-amplifier used for carrier frequency measurement was not saturated.


Radiated Spurious Emission
(Plot data, Worst case for Spurious Emission)

Test place	Ise EMC Lab.	No.2	No.2
Semi Anechoic Chamber			
Date	December 25, 2024	December 26, 2024	December 27, 2024
Temperature / Humidity	21 deg. C / 55 % RH	20 deg. C / 53 % RH	19 deg. C / 47 % RH
Engineer	Kiyoshiro Okazaki	Kiyoshiro Okazaki	Ken Fujita
Mode	Mode 2		



9th harmonics duty consideration

Test place Ise EMC Lab.
Semi Anechoic Chamber No.2
Date March 24, 2025
Temperature / Humidity 22 deg. C / 35 % RH
Engineer Shousei Hamaguchi
Mode Mode 1, 2 (9th harmonics)



-20 dB Bandwidth / 99% emission bandwidth

Test place Ise EMC Lab.
Semi Anechoic Chamber No.2
Date January 15, 2025
Temperature / Humidity 24 deg. C / 33 % RH
Engineer Shousei Hamaguchi
Mode Tx

Bandwidth Limit : Fundamental Frequency $433.58 \text{ MHz} \times 0.25 \% = 1083.950 \text{ kHz}$

* The above limit was calculated from more stringent nominal frequency.

* Method of KDB 926416 for systems employing non sweeping frequencies was referred.

433.58 MHz

-20 dB Bandwidth [kHz]
65.388

434.42 MHz

-20 dB Bandwidth [kHz]
65.460

-20 dB Bandwidth [kHz]	Bandwidth Limit [kHz]	Result
130.848	1083.950	Pass


Bandwidth Limit : Fundamental Frequency $433.58 \text{ MHz} \times 0.25 \% = 1083.950 \text{ kHz}$

99% emission bandwidth [kHz]	Bandwidth Limit [kHz]	Result
68.4644	1083.950	Pass


Bandwidth Limit : Fundamental Frequency $434.42 \text{ MHz} \times 0.25 \% = 1086.050 \text{ kHz}$

99% emission bandwidth [kHz]	Bandwidth Limit [kHz]	Result
68.4114	1086.050	Pass

433.58 MHz



434.42 MHz



APPENDIX 2: Test Instruments

Test Equipment

Test Item	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	141265	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	9111B-190	07/10/2024	12
RE	141317	Coaxial Cable	UL-ISE	-	-	09/11/2024	12
RE	141331	Attenuator(6dB)	TME	UFA-01	-	02/19/2025	12
RE	141403	High Pass Filter 1.22-4.60GHz	Mini-Circuits	VHF-1200	10435	07/04/2024	12
RE	141427	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103B+BBA9106	08031	07/30/2024	12
RE	141512	Horn Antenna 1-18GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	254	10/17/2024	12
RE	141542	Digital Tester	Fluke Corporation	FLUKE 26-3	78030611	08/06/2024	12
RE	141594	Pre Amplifier	Keysight Technologies Inc	8447D	2944A10150	02/19/2025	12
RE	141900	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY46185823	11/13/2024	12
RE	141902	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY46187105	05/30/2024	12
RE	141950	EMI Test Receiver	Rohde & Schwarz	ESU26	100412	11/28/2024	12
RE	142004	AC2_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-06902	12/12/2023	24
RE	142006	AC2_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-06902	04/17/2023	24
RE	142228	Measure, Tape, Steel	KOMELON	KMC-36	-	-	-
RE	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	202511	Loop Antenna	UL-ISE	-	-	-	-
RE	244707	Thermo-Hygrometer	HIOKI E.E. CORPORATION	LR5001	231202102	01/19/2025	12
RE	244712	Thermo-Hygrometer	HIOKI E.E. CORPORATION	LR5001	231202106	01/19/2025	12
RE	252663	Microwave Cable	Huber+Suhner	SF126E/11PC35/11PC35/1000MM,5000MM	616276/126E / 616275/126E	09/10/2024	12
RE	253739	Pre Amplifier	Keysight Technologies Inc	8449B	3008A01919	10/23/2024	12

***Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.**

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

RE: Radiated Emission