

EMI TEST REPORT

Test Report No. 15865647H-A-R1

Customer	Tokai Rika Co Ltd
Description of EUT	Receiver (SMART tuner and TPMS Receiver)
Model Number of EUT	BM2KV
FCC ID	MOZBM2KV
Test Regulation	FCC Part 15 Subpart B
Test Result	Complied
Issue Date	August 28, 2025
Remarks	-

Representative test engineerMasaya Minami
Engineer**Approved by**Akihiko Maeda
Leader

CERTIFICATE 5107.02

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
- ☒ There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 24.0

ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers EMC technical requirements. It does not cover administrative issues such as Manual or non-EMC test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided by the customer for this report is identified in SECTION 1.
- The laboratory is not responsible for information provided by the customer which can impact the validity of the results.
- For any test report referred in this report, the latest version (including any revisions) is always referred to.
- If the latest version is a revision, it replaces the previous version. See the table below for revisions and versions.

REVISION HISTORY

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	15865647H-A	August 25, 2025	-
1	15865647H-A-R1	August 28, 2025	Change "*2)" in the Remarks from Item E to Item C.

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	Hori.	Horizontal
AAN	Asymmetric Artificial Network	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	I/O	Input/Output
AE	Auxiliary equipment	IEC	International Electrotechnical Commission
AM	Amplitude Modulation	IEEE	Institute of Electrical and Electronics Engineers
AMN	Artificial Mains Network	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISN	Impedance Stabilization Network
AP	Access Point	ISO	International Organization for Standardization
ASK	Amplitude Shift Keying	JAB	Japan Accreditation Board
Atten., ATT	Attenuator	LAN	Local Area Network
AV	Average	LCL	Longitudinal Conversion Loss
BPSK	Binary Phase-Shift Keying	LIMS	Laboratory Information Management System
BR	Bluetooth Basic Rate	LISN	Line Impedance Stabilization Network
BT	Bluetooth	MRA	Mutual Recognition Arrangement
BT LE	Bluetooth Low Energy	N/A	Not Applicable
BW	BandWidth	NIST	National Institute of Standards and Technology
C.F	Correction Factor	NS	No signal detect.
Cal Int	Calibration Interval	NSA	Normalized Site Attenuation
CAV	CISPR AV	OBW	Occupied BandWidth
CCK	Complementary Code Keying	OFDM	Orthogonal Frequency Division Multiplexing
CDN	Coupling Decoupling Network	PER	Packet Error Rate
Ch., CH	Channel	PK	Peak
CISPR	Comite International Special des Perturbations Radioelectriques	P _{LT}	long-term flicker severity
Corr.	Correction	POHC(A)	Partial Odd Harmonic Current
CPE	Customer premise equipment	Pol., Pola.	Polarization
CW	Continuous Wave	PR-ASK	Phase Reversal ASK
DBPSK	Differential BPSK	P _{ST}	short-term flicker severity
DC	Direct Current	QAM	Quadrature Amplitude Modulation
DET	Detector	QP	Quasi-Peak
D-factor, D.fac.	Distance factor	QPSK	Quadrature Phase Shift Keying
Dmax	maximum absolute voltage change during an observation period	r.m.s., RMS	Root Mean Square
DQPSK	Differential QPSK	RBW	Resolution BandWidth
DSSS	Direct Sequence Spread Spectrum	RE	Radio Equipment
DUT	Device Under Test	REV	Reverse
EDR	Enhanced Data Rate	RF	Radio Frequency
e.i.r.p., EIRP	Equivalent Isotropically Radiated Power	RFID	Radio Frequency Identifier
EM clamp	Electromagnetic clamp	RNSS	Radio Navigation Satellite Service
EMC	ElectroMagnetic Compatibility	RSS	Radio Standards Specifications
EMI	ElectroMagnetic Interference	Rx	Receiving
EMS	ElectroMagnetic Susceptibility	S.fac.	Site factor
EN	European Norm	SINAD	Ratio of (Signal + Noise + Distortion) to (Noise + Distortion)
e.r.p., ERP	Effective Radiated Power	S/N	Signal to Noise ratio
ETSI	European Telecommunications Standards Institute	SA, S/A	Spectrum Analyzer
EU	European Union	SABS	South African Bureau of Standards
EUT	Equipment Under Test	SANS	South African National Standards
Fac.	Factor	SG	Signal Generator
FCC	Federal Communications Commission	SVSWR	Site-Voltage Standing Wave Ratio
FHSS	Frequency Hopping Spread Spectrum	THC(A)	Total Harmonic Current
FM	Frequency Modulation	THD(%)	Total Harmonic Distortion
Freq.	Frequency	TR, T/R	Test Receiver
FSK	Frequency Shift Keying	Tx	Transmitting
Fund	Fundamental	UFA	Uniform field area
FWD	Forward	VBW	Video BandWidth
GFSK	Gaussian Frequency-Shift Keying	Vert.	Vertical
GNSS	Global Navigation Satellite System	WLAN	Wireless LAN
GPS	Global Positioning System	xDSL	Generic term for all types of DSL technology (DSL: Digital Subscriber Line)

CONTENTS	PAGE
SECTION 1: Customer information	5
SECTION 2: Equipment under test (EUT)	5
SECTION 3: Test Summary	6
SECTION 4: Operation of EUT during testing	9
SECTION 5: Radiated Emission	11
APPENDIX 1: Test data	13
Radiated Emission	13
APPENDIX 2: Test instruments	19
APPENDIX 3: Photographs of test setup.....	20
Radiated Emission	20
Worst Case Position	22

SECTION 1: Customer information

Company Name	Tokai Rika Co Ltd
Address	3-260 Toyota, Oguchi-cho, Niwa-gun, Aichi 480-0195, Japan
Telephone Number	+81-70-2244-3504
Contact Person	Tomoki Kuwabara

The information provided by the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

SECTION 2: Equipment under test (EUT)

2.1 Identification of EUT

Description	Receiver (SMART tuner and TPMS Receiver)
Model Number	BM2KV
Serial Number	Refer to SECTION 4.2
Condition	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	July 25, 2025
Test Date	July 25 and 27, 2025

2.2 Product Description

General Specification

Rating	DC 12.0 V
Clock frequency (ies) in the system	RF-IC: 27.6 MHz CPU: 20.03 MHz

Radio Specification

Radio Type	Receiver
Frequency of Operation *	SMART (CH1): 433.58 MHz SMART (CH2): 434.42 MHz TPMS: 433.90 MHz
Operating Channel Width (OCW)	SMART (CH1): 433.58 MHz $\pm$ 0.1 MHz SMART (CH2): 434.42 MHz $\pm$ 0.1 MHz TPMS: 433.90 MHz $\pm$ 0.1 MHz
Local Oscillalized Frequency	SMART (CH1): 433.38 MHz SMART (CH2): 434.22 MHz TPMS: 433.70 MHz
Type of receiving system	Super Heterodyne
Receiving Band	200 kHz

* NOTE

These channels do not work together at a time. When one channel receives a signal, the other two receive no signals.

SECTION 3: Test Summary

3.1 Test Specification

Test Specification	FCC Part 15 Subpart B The latest version on the first day of the testing period
Title	FCC 47CFR Part15 Radio Frequency Device Subpart B Unintentional Radiators

3.2 Reference Standards

ANSI/USEMCSC C63.2-2023
ANSI C63.4-2014+C63.4a-2017
ANSI C63.5-2017
ANSI C63.25.1-2018

3.3 Summary of Test Results

Item	Limits	Result	Remarks
Conducted emission	FCC:Part 15 Subpart B 15.107(a) ISED: RSS-Gen 7.2	N/A	*1)
Radiated emission	FCC: Part 15 Subpart B 15.109(a) ISED: RSS-Gen 7.3	Complied	-
Antenna Terminal	FCC: Part 15 Subpart B 15.111(a) ISED: RSS-Gen 7.4	N/A	*2)
* Note: UL Japan, Inc.'s EMI Work Procedure: Work Instructions-ULID-003591. *1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line. *2) The receiving antenna (of this EUT) is installed inside the EUT and cannot be removed (permanently attached). Therefore, Radiated emission test was performed.			

3.4 Addition to standard

No addition, exclusion nor deviation has been made from the standard.

3.5 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.
Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Radiated emission

Measurement distance	Frequency range		Unit	Calculated Uncertainty (+/-)
3 m	9 kHz to 30 MHz		dB	3.3
10 m			dB	3.1
3 m	30 MHz to 200 MHz	Horizontal	dB	5.0
		Vertical	dB	5.0
	200 MHz to 1000 MHz	Horizontal	dB	5.2
		Vertical	dB	6.2
10 m	30 MHz to 200 MHz	Horizontal	dB	5.5
		Vertical	dB	5.4
	200 MHz to 1000 MHz	Horizontal	dB	5.5
		Vertical	dB	5.5
3 m	1 GHz to 6 GHz		dB	5.1
	6 GHz to 18 GHz		dB	5.4
1 m	10 GHz to 18 GHz		dB	5.4
	18 GHz to 26.5 GHz		dB	5.3
	26.5 GHz to 40 GHz		dB	4.8
0.5 m	26.5 GHz to 40 GHz		dB	5.0

3.6 Test Location

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan

Telephone: +81-596-24-8999

A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919

ISED Lab Company Number: 2973C / CAB identifier: JP0002

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber (SAC1)	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber (SAC2)	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber (SAC3)	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room (PR3)	3 m
No.3 shielded room (SR3)	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber (SAC4)	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room (PR4)	3 m
No.4 shielded room (SR4)	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber (SAC5)	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room (MR5)	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room (SR6)	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room (MR6)	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room (SR7)	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room (MR8)	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room (MR9)	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room (SR10)	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room (MR11)	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room (MR12)	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

3.7 Test data, Test instruments, and Test set up

Refer to APPENDIX.

SECTION 4: Operation of EUT during testing

4.1 Operating Mode(s)


Mode	1. SMART Receiving mode (433.58 MHz) ^{*1)}
	2. SMART Receiving mode (434.42 MHz) ^{*1)}
	3. TPMS Receiving mode (433.90 MHz)
Software(s)	TY_310D_TPMSSMT_01_320.run

^{*1)} The EUT alternately receives two frequencies (433.58 MHz and 434.42 MHz) by time sharing.

^{*}The test signal level was confirmed to be sufficient to stabilize the local oscillator of the EUT.

^{*} It was confirmed by using checker that the EUT receives the signal from the transmitter (pair of EUT).

4.2 Configuration and peripherals



^{*1)} Mode 1 and 2 only

^{*2)} Mode 3 only

^{*} Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

^{*} Item No. A includes Receiver Antenna.

Description of EUT and Support Equipment

No.	Item	Model number	Serial Number	Manufacturer	Remarks
A	Receiver (SMART tuner and TPMS Receiver)	BM2KV	1	Tokai Rika Co Ltd	EUT
B	SMART Transmitter	19CY.Ver3	SMT CH1 (for Mode 1) SMT CH2 (for Mode 2)	Tokai Rika Co Ltd	*1)
C	TPMS Emulator	-	9	Tokai Rika Co Ltd	*2)
D	Dummy ECU	BM2KV	D	Tokai Rika Co Ltd	-
E	TPMS checker	-	13	Tokai Rika Co Ltd	-
F	AC Adapter	M120100-A010	-	Shenzhen Electrical Appliance Co., Ltd.	*2)

*1) Mode 1 and 2 only

*2) Mode 3 only

List of Cables Used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	Signal cable	2.2	Unshielded	Unshielded	-
2	DC Cable	3.0	Unshielded	Unshielded	-
3	DC Cable	2.0	Unshielded	Unshielded	-
4	Signal Cable	0.5	Unshielded	Unshielded	-
5	DC Cable	1.6	Unshielded	Unshielded	-

SECTION 5: Radiated Emission

5.1 Operating environment

Date	Test site	Temperature	Humidity	Engineer	Mode
See data	See data	See data	See data	See data	See data

5.2 Test configuration

EUT was placed on the platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The EUT was set on the edge of the platform.

Test was made with the antenna positioned in both the horizontal and vertical planes of polarization.

The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

Photographs of the set up are shown in APPENDIX.

5.3 Test conditions

Frequency range	30 MHz to 200 MHz (Biconical antenna) 200 MHz to 1000 MHz (Logperiodic antenna) 1000 MHz to 2000 MHz (Horn antenna)
Test distance	See Figure 2
EUT position	Table top
EUT operation mode	See Clause 4.1

5.4 Test procedure


The height of the measuring antenna varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver.

The radiated emission measurements were made with the following detector function of the Test Receiver. Test antenna was aimed at the emission source for receiving the maximum signal and always kept. (Above 1 GHz)

Frequency	Below 1 GHz	Above 1 GHz
Instrument used	Test Receiver	Test Receiver
IF Bandwidth	QP: BW 120 kHz	PK: BW 1 MHz, CAV: BW 1 MHz

Figure 1: Test Setup



- The noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

5.5 Test result

Summary of the test results: Pass


Test results are rounded off and limit are rounded down, so some differences might be observed.

APPENDIX 1: Test data

Radiated Emission

Mode	1				
Date	Test site	Temperature	Humidity	Engineer	Measurement Range
July 25, 2025	SAC4	22 deg. C	53 % RH	Hiroyuki Furutaka	Below 1 GHz

Limit : FCC_Part 15 Subpart B(15.109)_Class B




No.	Freq. [MHz]	Reading (QP)	Ant Fac [dB/m]	Loss [dB]	Gain [dB]	Result (QP)	Limit (QP)	Margin (QP)	Pola [H/V]	Height [cm]	Angle [deg]	Ant. Type	Comment
		[dBuV]				[dBuV/m]	[dBuV/m]	[dB]					
1	31.200	20.50	18.27	6.83	28.57	17.03	40.00	22.97	Hori.	100	0	BA	
2	42.410	20.50	13.96	7.01	28.55	12.92	40.00	27.08	Hori.	100	0	BA	
3	125.882	19.80	13.43	7.92	28.34	12.81	43.50	30.69	Hori.	100	0	BA	
4	155.678	19.80	15.25	8.19	28.22	15.02	43.50	28.48	Hori.	100	0	BA	
5	433.380	19.90	16.23	10.11	28.75	17.49	46.00	28.51	Hori.	100	0	LA23	
6	866.760	19.60	21.88	12.05	28.94	24.59	46.00	21.41	Hori.	100	0	LA23	
7	31.020	20.60	18.34	6.83	28.57	17.20	40.00	22.80	Vert.	100	0	BA	
8	42.410	20.50	13.96	7.01	28.55	12.92	40.00	27.08	Vert.	100	0	BA	
9	125.882	19.80	13.43	7.92	28.34	12.81	43.50	30.69	Vert.	100	0	BA	
10	155.678	19.80	15.25	8.19	28.22	15.02	43.50	28.48	Vert.	100	0	BA	
11	433.380	19.80	16.23	10.11	28.75	17.39	46.00	28.61	Vert.	100	0	LA23	
12	866.760	19.50	21.88	12.05	28.94	24.49	46.00	21.51	Vert.	100	0	LA23	

CHART: WITH FACTOR
ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz -: HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS(CABLE + ATT) - GAIN(AMP)
Except for the above table: adequate margin data below the limits.

Radiated Emission

Mode	2				
Date	Test site	Temperature	Humidity	Engineer	Measurement Range
July 25, 2025	SAC4	22 deg. C	53 % RH	Hiroyuki Furutaka	Below 1 GHz

Limit : FCC_Part 15 Subpart B(15.109)_Class B




No.	Freq. [MHz]	Reading [QP]	Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result [QP]	Limit [QP]	Margin [QP]	Pola. [H/V]	Height [cm]	Angle [deg.]	Ant. Type	Comment
		[dBuV]				[dBuV/m]	[dBuV/m]	[dB]					
1	32.260	21.00	17.82	6.85	28.57	17.10	40.00	22.90	Hori.	100	0	BA	
2	44.280	21.40	13.28	7.04	28.55	13.17	40.00	26.83	Hori.	100	0	BA	
3	118.659	20.00	12.76	7.84	28.36	12.24	43.50	31.26	Hori.	100	0	BA	
4	160.284	20.00	15.44	8.22	28.20	15.46	43.50	28.04	Hori.	100	0	BA	
5	434.220	19.90	16.25	10.12	28.76	17.51	46.00	28.49	Hori.	100	0	LA23	
6	868.440	19.50	21.92	12.06	28.94	24.54	46.00	21.46	Hori.	100	0	LA23	
7	32.260	20.90	17.82	6.85	28.57	17.00	40.00	23.00	Vert.	100	0	BA	
8	44.280	21.40	13.28	7.04	28.55	13.17	40.00	26.83	Vert.	100	0	BA	
9	118.659	20.00	12.76	7.84	28.36	12.24	43.50	31.26	Vert.	100	0	BA	
10	160.284	20.00	15.44	8.22	28.20	15.46	43.50	28.04	Vert.	100	0	BA	
11	434.220	19.90	16.25	10.12	28.76	17.51	46.00	28.49	Vert.	100	0	LA23	
12	868.440	19.50	21.92	12.06	28.94	24.54	46.00	21.46	Vert.	100	0	LA23	

CHART: WITH FACTOR
ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz -: HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS(CABLE + ATT) - GAIN(AMP)
Except for the above table: adequate margin data below the limits.

Radiated Emission

Mode	3				
Date	Test site	Temperature	Humidity	Engineer	Measurement Range
July 27, 2025	SAC4	20 deg. C	50 % RH	Masaya Minami	Below 1 GHz

Limit : FCC_Part 15 Subpart B(15.109)_Class B




No.	Freq. [MHz]	Reading (QP)	Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result (QP)	Limit (QP)	Margin (QP)	Pola. [H/V]	Height [cm]	Angle [deg]	Ant. Type	Comment
		[dBuV]				[dBuV/m]	[dBuV/m]	[dB]					
1	30.000	22.10	18.72	6.81	32.11	15.52	40.00	24.48	Hori.	100	0	BA	
2	53.652	21.30	9.87	7.16	32.10	6.23	40.00	33.77	Hori.	100	0	BA	
3	91.713	21.30	8.85	7.59	32.07	5.67	43.50	37.83	Hori.	100	0	BA	
4	178.650	20.60	16.02	8.37	32.03	12.96	43.50	30.54	Hori.	100	0	BA	
5	433.700	20.50	16.24	10.12	32.19	14.67	46.00	31.33	Hori.	100	0	LA23	
6	867.400	19.70	21.90	12.05	31.35	22.30	46.00	23.70	Hori.	100	0	LA23	
7	30.000	22.10	18.72	6.81	32.11	15.52	40.00	24.48	Vert.	100	0	BA	
8	53.652	21.30	9.87	7.16	32.10	6.23	40.00	33.77	Vert.	100	0	BA	
9	91.713	21.40	8.85	7.59	32.07	5.77	43.50	37.73	Vert.	100	0	BA	
10	178.650	20.60	16.02	8.37	32.03	12.96	43.50	30.54	Vert.	100	0	BA	
11	433.700	20.50	16.24	10.12	32.19	14.67	46.00	31.33	Vert.	100	0	LA23	
12	867.400	19.70	21.90	12.05	31.35	22.30	46.00	23.70	Vert.	100	0	LA23	

CHART: WITH FACTOR
ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz -: HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS(CABLE + ATT) - GAIN(AMP)
Except for the above table: adequate margin data below the limits.

Radiated Emission

Mode	1				
Date	Test site	Temperature	Humidity	Engineer	Measurement Range
July 27, 2025	SAC4	20 deg. C	50 % RH	Masaya Minami	Above 1 GHz

Limit : FCC_Part 15 Subpart B(15.109)_Class B




No.	Freq. [MHz]	Reading		Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Result		Limit		Margin		Pola. [H/V]	Height [m]	Angle [deg]	Ant. Type	Comment
		(AV) [dBuV]	(PK) [dBuV]				(AV) [dBuV/m]	(PK) [dBuV/m]	(AV) [dBuV/m]	(PK) [dBuV/m]	(AV) [dB]	(PK) [dB]					
1	1300.140	30.20	44.10	25.49	1.68	33.92	23.45	37.35	53.90	73.90	30.45	36.55	Hori.	100	0	H21	
2	1733.520	30.20	43.70	25.09	1.95	32.82	24.42	37.92	53.90	73.90	29.48	35.98	Hori.	100	0	H21	
3	1300.140	30.20	44.10	25.49	1.68	33.92	23.45	37.35	53.90	73.90	30.45	36.55	Vert.	100	0	H21	
4	1733.520	30.20	43.70	25.09	1.95	32.82	24.42	37.92	53.90	73.90	29.48	35.98	Vert.	100	0	H21	

CHART: WITH FACTOR
ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz -: HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS(CABLE) - GAIN(AMP)
Except for the above table: adequate margin data below the limits.

Radiated Emission

Mode	2				
Date	Test site	Temperature	Humidity	Engineer	Measurement Range
July 27, 2025	SAC4	20 deg. C	50 % RH	Masaya Minami	Above 1 GHz

Limit : FCC_Part 15 Subpart B(15.109)_Class B




No.	Freq. [MHz]	Reading		Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result		Limit		Margin		Pola. [H/V]	Height [cm]	Angle [deg]	Ant. Type	Comment
		(AV) [dBuV]	(PK) [dBuV]				(AV) [dBuV/m]	(PK) [dBuV/m]	(AV) [dBuV/m]	(PK) [dBuV/m]	(AV) [dB]	(PK) [dB]					
1	1302.660	30.70	44.10	25.50	1.68	33.92	23.96	37.36	53.90	73.90	29.94	36.54	Hori.	100	0	H21	
2	1736.880	30.20	43.90	25.11	1.95	32.81	24.45	38.15	53.90	73.90	29.45	36.75	Hori.	100	0	H21	
3	1302.660	30.70	44.10	25.50	1.68	33.92	23.96	37.36	53.90	73.90	29.94	36.54	Vert.	100	0	H21	
4	1736.880	30.20	43.90	25.11	1.95	32.81	24.45	38.15	53.90	73.90	29.45	36.75	Vert.	100	0	H21	

CHART: WITH FACTOR
ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz -: HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS(CABLE) - GAIN(AMP)
Except for the above table: adequate margin data below the limits.

Radiated Emission

Mode	3				
Date	Test site	Temperature	Humidity	Engineer	Measurement Range
July 27, 2025	SAC4	20 deg. C	50 % RH	Masaya Minami	Above 1 GHz

Limit : FCC_Part 15 Subpart B(15.109)_Class B



No.	Freq. [MHz]	Reading		Ant Fac [dB/m]	Loss [dB]	Gain [dB]	Result		Limit		Margin		Pola. [H/V]	Height [cm]	Angle [deg]	Ant. Type	Comment
		(AV) [dBuV]	(PK) [dBuV]				(AV) [dBuV/m]	(PK) [dBuV/m]	(AV) [dBuV/m]	(PK) [dBuV/m]	(AV) [dB]	(PK) [dB]					
1	1301.100	30.50	44.80	25.49	1.68	33.92	23.75	38.05	53.90	73.90	30.15	35.85	Hori.	100	0	H21	
2	1734.800	30.30	44.60	25.10	1.95	32.82	24.53	38.83	53.90	73.90	29.37	35.07	Hori.	100	0	H21	
3	1301.100	30.50	44.80	25.49	1.68	33.92	23.75	38.05	53.90	73.90	30.15	35.85	Vert.	100	0	H21	
4	1734.800	30.30	44.60	25.10	1.95	32.82	24.53	38.83	53.90	73.90	29.37	35.07	Vert.	100	0	H21	

CHART: WITH FACTOR
ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz -: HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS(CABLE) - GAIN(AMP)
Except for the above table: adequate margin data below the limits.

APPENDIX 2: Test instruments

Test equipment

Test Item	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	141267	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	9111B-192	09/18/2024	12
RE	141397	Coaxial Cable	UL-ISE EMC	-	-	11/29/2024	12
RE	141425	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103+BBA9106	VHA 91031302	08/23/2024	12
RE	141508	Horn Antenna 1-18GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	557	05/20/2025	12
RE	141545	DIGITAL HiTESTER	HIOKI E. E. CORPORATION	3805	51201148	02/25/2025	12
RE	141581	MicroWave System Amplifier	Keysight Technologies Inc	83017A	00650	10/30/2024	12
RE	141583	Pre Amplifier	SONOMA INSTRUMENT	310	260833	04/02/2025	12
RE	141594	Pre Amplifier	Keysight Technologies Inc	8447D	2944A10150	02/19/2025	12
RE	141951	EMI Test Receiver	Rohde & Schwarz	ESR26	101408	05/07/2025	12
RE	142011	AC4_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	12/13/2023	24
RE	142017	AC4_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-10005	04/17/2025	24
RE	142230	Measure, Tape, Steel	KOMELON	KMC-36	-	-	-
RE	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	220646	Attenuator	Huber+Suhner	6806 N-50-1	-	03/06/2025	12
RE	244710	Thermo-Hygrometer	HIOKI E. E. CORPORATION	LR5001	231202104	01/19/2025	12
RE	246002	Microwave Cable	Huber+Suhner	SF103/11PC35/11PC35/1000mm / SF126E/5000mm	800674(1m) / 610205(5m)	03/18/2025	12

*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

RE: Radiated emission