

Date: 2002-01-26

No.: HM106749

TEST REPORT

Page 1 of 19

FCC PART 15 SUBPART C CERTIFICATION REPORT

FOR LOW POWER TRANSMITTER

TEST REPORT No.: HM106749

Equipment Under Test [EUT]:

Walkie Talkie

Model Number:

MIL WT-348

Applicant:

Million Industrial Ltd.

FCC ID :

MQDMILWT-348

Date: 2002-01-26

No.: HM106749

TEST REPORT

Page 2 of 19

CONTENT:

| | |
|------------|----------------|
| Cover | Page 1 of 19 |
| Content | Page 2-3 of 19 |
| Conclusion | Page 4 of 19 |

1.0 General Details

| | | |
|-----|---|--------------|
| 1.1 | Test Laboratory | Page 5 of 19 |
| 1.2 | Applicant Details Applicant HKSTC Code Number for Applicant Manufacturer | Page 5 of 19 |
| 1.3 | Equipment Under Test [EUT] Description of EUT operation | Page 6 of 19 |
| 1.4 | Date of Order | Page 6 of 19 |
| 1.5 | Submitted Sample | Page 6 of 19 |
| 1.6 | Test Duration | Page 6 of 19 |
| 1.7 | Country of Origin | Page 6 of 19 |
| 1.8 | Additional Information of EUT | Page 7 of 19 |

2.0 Technical Details

| | | |
|-----|------------------------------------|--------------|
| 2.1 | Investigations Requested | Page 8 of 19 |
| 2.2 | Test Standards and Results Summary | Page 8 of 19 |

3.0 Test Results

| | | |
|-----|-----------------------|------------------|
| 3.1 | Emission | Page 9-14 of 19 |
| 3.2 | Bandwidth Measurement | Page 15-17 of 19 |

Date: 2002-01-26

No.: HM106749

TEST REPORT

Page 3 of 19

Appendix A

List of Measurement Equipment

Page 18 of 19

Appendix B

Photographs

Page 19 of 19

Date: 2002-01-26

No.: HM106749

TEST REPORT

Page 4 of 19

CONCLUSION

The submitted product was deemed to have COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Verify by

Patrick Wong
for Chief Executive

Date: 2002-01-26

TEST REPORT

Page 5 of 19

No.: HM106749

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd.
EMC Laboratory
10 Dai Wang Street, Taipo Industrial Estate
New Territories, Hong Kong

Telephone: 852 2666 1888
Fax: 852 2664 4353

1.2 Applicant Details

Applicant

MILLION INDUSTRIAL LTD.
Flat A, 9/FI., Rodeo Centre, 73-79 Larch Street,
Tai Kok Tsui, Kowloon, Hong Kong.

Telephone: 852 2396 2098
Fax: 852 2392 8192

HKSTC Code Number for Applicant

MII001

Manufacturer

MILLION INDUSTRIAL LTD.
Flat A, 9/FI., Rodeo Centre, 73-79 Larch Street,
Tai Kok Tsui, Kowloon, Hong Kong.

Telephone: 852 2396 2098
Fax: 852 2392 8192

Date: 2002-01-26

TEST REPORT

Page 6 of 19

No.: HM106749

1.3 Equipment Under Test [EUT]

Description of Sample

Product: Walkie Talkie
Manufacturer: Million Industrial Ltd.
Brand Name: MILLION
Model Number: MIL WT-348
Input Voltage: 9Vd.c. ("6F22" size battery x 1)

1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is an Tiger Electronics Inc., 49.86MHz Walkie Talkie. The transmitter is a 23 button transmitter. The EUT continues to transmit while button is being pressed. It is voice transmission, Modulation by Mic. and tape is frequency modulation.

1.4 Date of Order

2002-01-15

1.5 Submitted Sample(s):

1 Sample per model

1.6 Test Duration

2002-01-23

1.7 Country of Origin

China

Date: 2002-01-26

TEST REPORT

Page 7 of 19

No.: HM106749

1.8 Additional Information of EUT

| | Submitted | Not Available |
|------------------------------------|-------------------------------------|--------------------------|
| User Manual | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Part List | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Circuit Diagram | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Printed Circuit Board [PCB] Layout | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Rating Label | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Block diagram | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| FCC ID Label | <input checked="" type="checkbox"/> | <input type="checkbox"/> |

Date: 2002-01-26

TEST REPORT

Page 8 of 19

No.: HM106749

2.0 Technical Details

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4:2000 for FCC Certification.

2.2 Test Standards and Results Summary Tables

| EMISSION Results Summary | | | | | | |
|--|------------------|-----------------|---------------------|-------------------------------------|--------------------------|-------------------------------------|
| Test Condition | Test Requirement | Test Method | Class / Severity | Test Result | | |
| | | | | Pass | Failed | N/A |
| Field Strength of Fundamental Emissions & Spurious Emissions | FCC 47CFR 15.235 | ANSI C63.4:2000 | N/A | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Radiated Emissions, 30MHz to 1GHz | FCC 47CFR 15.209 | ANSI C63.4:2000 | Class B | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Conducted Emissions on AC, 0.45MHz to 30MHz | FCC 47CFR 15.207 | ANSI C63.4:2000 | Class B | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |

Note: N/A - Not Applicable


3.0 Test Results**3.1 Emission****3.1.1 Radiated Emissions**

| | |
|--------------------|------------------|
| Test Requirement: | FCC 47CFR 15.235 |
| Test Method: | ANSI C63.4:2000 |
| Test Date: | 2002-01-23 |
| Mode of Operation: | On mode |

Test Method:

The sample was placed 0.8m above the ground plane on the OATS *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigate all operating modes, rotated about all 3 axis (X, Y & Z) to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

*: OATS [Open Area Test Site] located at HKSTC with a metal ground plane on filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 90657.

Test Setup:

Date: 2002-01-26

TEST REPORT

Page 10 of 19

No.: HM106749

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.235]:

| Frequency Range of Fundamental [MHz] | Field Strength of Fundamental Emission [Peak] [μ V/m] | Field Strength of Fundamental Emission [Average] [μ V/m] |
|---|--|---|
| 49.82-49.90 | 100,000 | 10,000 |

Results:

| Field Strength of Fundamental Emissions Peak Value | | | | | | |
|---|----------------------------|------------------------------|-----------------------------------|--------------------------------|------------------------------|---------------------|
| Frequency MHz | Level @3m dB μ V | Correction Factor dB/m | Field Strength dB μ V/m | Field Strength μ V/m | Limit ** @3m μ V/m | Antenna Polarity |
| 49.86 | 31.4 | 15.0 | 46.4 | 208.9 | 100,000 | Vertical |

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Remarks:

*: Linear interpolations

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty = 30MHz to 300MHz ± 3.7 dB
300MHz to 1GHz +3.0dB / -2.7dB

Date: 2002-01-26
No.: HM106749

TEST REPORT

Page 11 of 19

Results:

| Field Strength of Fundamental Emissions Average Value * | | | | | | |
|--|----------------------------|------------------------------|-----------------------------------|--------------------------------|------------------------------|---------------------|
| Frequency MHz | Level @3m dB μ V | Correction Factor dB/m | Field Strength dB μ V/m | Field Strength μ V/m | Limit ** @3m μ V/m | Antenna Polarity |
| 49.86 | 30.1 | 15.0 | 45.1 | 179.9 | 100,00 | Vertical |

Remarks:

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be recorded. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth =3MHz
Video Bandwidth =1Hz

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty = 30MHz to 300MHz ± 3.7 dB
300MHz to 1GHz $+3.0$ dB / -2.7 dB

Date: 2002-01-26

TEST REPORT

Page 12 of 19

No.: HM106749

Limited for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

| Frequency Range [MHz] | Quasi-Peak Limits [μ V/m] |
|--------------------------|-----------------------------------|
| 30-88 | 100 |
| 88-216 | 150 |
| 216-960 | 200 |
| Above 960 | 500 |

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results: Transmitter

| Radiated Emissions Quasi-Peak | | | | | | |
|----------------------------------|----------------------------|------------------------------|-----------------------------------|--------------------------------|---------------------------|---------------------|
| Frequency MHz | Level @3m dB μ V | Correction Factor dB/m | Field Strength dB μ V/m | Field Strength μ V/m | Limit @3m μ V/m | Antenna Polarity |
| 99.7 | <1.0 | 12.2 | <13.2 | <4.6 | 150 | Horizontal |
| 149.5 | <1.0 | 9.8 | <10.8 | <3.5 | 150 | Horizontal |
| 199.3 | <1.0 | 11.5 | <12.5 | <4.2 | 150 | Horizontal |
| 249.2 | <1.0 | 15.9 | <16.9 | <7.0 | 200 | Horizontal |
| 299.0 | <1.0 | 17.0 | <18.0 | <7.9 | 200 | Horizontal |
| 348.8 | <1.0 | 17.2 | <18.2 | <8.1 | 200 | Horizontal |
| 398.6 | <1.0 | 18.8 | <19.8 | <9.8 | 200 | Horizontal |
| 448.5 | <1.0 | 19.7 | <20.7 | <10.8 | 200 | Horizontal |
| 498.6 | <1.0 | 20.6 | <21.6 | <12.0 | 200 | Horizontal |

Results: Receiver

| Radiated Emissions Quasi-Peak | | | | | | |
|----------------------------------|----------------------------|------------------------------|-----------------------------------|--------------------------------|---------------------------|---------------------|
| Frequency MHz | Level @3m dB μ V | Correction Factor dB/m | Field Strength dB μ V/m | Field Strength μ V/m | Limit @3m μ V/m | Antenna Polarity |
| 49.86 | 13.6 | 15.0 | 28.6 | 26.9 | 100 | Vertical |


3.1.1 Conducted Emissions (0.45MHz to 30MHz)

Test Requirement: FCC 47CFR 15.207
Test Method: ANSI C63.4:2000
Test Date: 2002-01-23
Mode of Operation: On mode

Test Method:

The test was performed in accordance with ANSI C63.4:2000, with the following: an initial measurement was performed in peak and average detection mode on the live line. Any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Test Setup:



Date: 2002-01-26
No.: HM106749

TEST REPORT

Page 14 of 19

Limit for Conducted Emissions (FCC 47 CFR 15.207):

| Frequency Range [MHz] | Quasi-Peak Limits [μ V/m] |
|--------------------------|-----------------------------------|
| 0.45-30 | 250 |

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram labelled as (QP and AV).

Results: N/A

The EUT is operated by internal battery power only, therefore power line conducted emission was deemed unnecessary.

Remarks:

Calculated measurement uncertainty = ± 2.3 dB

Date: 2002-01-26
No.: HM106749

TEST REPORT

Page 15 of 19

3.2 26dB Bandwidth of Fundamental Emission

| | |
|--------------------|----------------------------------|
| Test Requirement: | FCC 47 CFR 15.235 |
| Test Method: | ANSI C63.4:2000 (Section 13.1.7) |
| Test Date: | 2002-01-23 |
| Mode of Operation: | On mode |

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

A 1KHz tape and other audio signal were used with audio volume set to maximum for worst case.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.

Date: 2002-01-26

TEST REPORT


Page 16 of 19

No.: HM106749

Limits for 26 dB Bandwidth of Fundamental Emission:

| Frequency Range [MHz] | 26dB Bandwidth [KHz] | FCC Limits * [KHz] |
|--------------------------|-------------------------|-----------------------|
| 49.86 | 49.4 | within 49.82-49.90 |

26dB Bandwidth of Fundamental Emission



Date: 2002-01-26

TEST REPORT

Page 17 of 19

No.: HM106749

Appendix A

Test Equipment Audit

Radiated Emission

| EQP NO. | DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | LAST CAL. |
|---------|--|---|--------------------------------|--|-----------|
| EM007 | SPECTRUM ANALYZER | HEWLETT PACKARD | HP85660B | 3144A21192 | 07/09/01 |
| EM008 | SPECTRUM ANALYZER DISPLAY | HEWLETT PACKARD | HP85662A | 3144A20514 | 07/09/01 |
| EM009 | QUASI PEAK ADAPTOR | HEWLETT PACKARD | HP85650A | 3303A01702 | 07/09/01 |
| EM010 | RF PRESELECTOR | HEWLETT PACKARD | HP85685A | 3221A01410 | 07/09/01 |
| EM011 | ATTENUATOR/SWITCH | HEWLETT PACKARD | HP11713A | 2508A10595 | 07/09/01 |
| EM012 | PRE-AMPLIFIER | HEWLETT PACKARD | HP8449B | 3008A00262 | 07/09/01 |
| EM013 | CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE | HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD | HP9000 HP A1097C HP9133L | 6226A60314 3151J39517 2623A02468 | CM |
| EM131 | PORTABLE SPECTRUM ANALYSER | HEWLETT PACKARD | 8595EM | 3710A00155 | 18/12/01 |
| EM017 | ANTENNA | ARA INC. | LPB-2513/A | 1069 | 17/02/00 |
| EM020 | HORN ANTENNA | EMCO | 3115 | 4032 | 09/08/00 |
| EM072 | SIGNAL GENERATOR | HEWLETT PACKARD | 8640B | 1948A11892 | 30/03/98 |
| EM083 | HKSTC OPEN AREA TEST SITE | HKSTC | N/A | N/A | 16/02/01 |
| EM145 | EMI TEST RECEIVER | R & S | ESCS 30 | 830245/021 | 21/06/01 |

Conducted Emission

| EQP NO. | DESCRIPTION | MANUFACTURER | MODEL NO. | SERIAL NO. | LAST CAL |
|---------|-------------------------------------|------------------|------------|--------------|----------|
| EM078 | VARIAC | SHANGHAI VOLTAGE | TDGC-3/0.5 | N/A | CM |
| EM081 | SMALL SCREENED ROOM | MIKO INST HK | N/A | N/A | 04/10/01 |
| EM002 | LISN | EMCO | 3825-2 | 9005-1657 | 22/08/01 |
| EM119 | LISN | R & S | ESH3-Z5 | 0831.5518.52 | 31/08/00 |
| EM145 | EMI TEST RECEIVER | R & S | ESCS 30 | 830245/021 | 14/09/01 |
| EM120 | EMI TEST RECEIVER | R&S | ESHS10 | 1004.0401.10 | CM |
| EM127 | ISOLATION TRANSFORMER 220 TO 300 | WING SUN | N/A | N/A | 04/07/01 |
| EM142 | PLUSE LIMITER | R & S | ESH3Z2 | 357.8810.52 | TBD |

Remarks:

CM Corrective Maintenance
N/A Not Applicable or Not Available
TBD To Be Determined

Date: 2002-01-26
No.: HM106749

TEST REPORT

Page 18 of 19

Appendix B

Photographs of EUT


Front View of the product




Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View



Date: 2002-01-26

No.: HM106749

TEST REPORT

Page 19 of 19

Photographs of EUT

Measurement of Radiated Emission Test Set Up



End of Document