

FCC RF Test Report

APPLICANT : ASUSTek COMPUTER INC.
EQUIPMENT : PDA Phone
BRAND NAME : ASUS
MODEL NAME : E600
FCC ID : MSQ-0121180101
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Transmission System (DTS)

The product was received on Apr. 17, 2010 and completely tested on May 20, 2010. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY.....3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION.....5

 1.1 Applicant.....5

 1.2 Manufacturer.....5

 1.3 Feature of Equipment Under Test5

 1.4 Testing Site.....6

 1.5 Applied Standards6

 1.6 Ancillary Equipment List6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....7

 2.1 RF Power.....7

 2.2 Test Mode.....8

 2.3 Connection Diagram of Test System.....9

 2.4 RF Utility10

3 TEST RESULT.....11

 3.1 6dB Bandwidth Measurement11

 3.2 Output Power Measurement.....16

 3.3 Band Edges Measurement.....18

 3.4 Spurious Emission Measurement.....24

 3.5 Power Spectral Density Measurement31

 3.6 AC Conducted Emission Measurement.....36

 3.7 Radiated Emission Measurement.....40

 3.8 Antenna Requirements.....55

4 LIST OF MEASURING EQUIPMENT56

5 UNCERTAINTY OF EVALUATION.....57

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	A8.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	A8.4	Power Output	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(d)	A8.5	Frequency Band Edges	$\leq 20\text{dBc}$	Pass	-
3.4	15.247(d)	A8.5	Spurious Emission	$< 20\text{ dBc}$	Pass	-
3.5	15.247(e)	A8.2(b)	Power Spectral Density	$\leq 8\text{dBm}$	Pass	-
3.6	15.207	Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 14.6 dB at 0.366 MHz
3.7	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.23 dB at 2389.99 MHz
3.8	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

ASUSTek COMPUTER INC.

4F., No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

1.2 Manufacturer

ProTek (Shanghai) Ltd.

No. 3768, Xiu Yan Road, Nanhui District, 201315 Shanghai, P.R.C.

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	PDA Phone
Brand Name	ASUS
Model Name	E600
FCC ID	MSQ-0121180101
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	11
Carrier Frequency of Each Channel	2412+(n-1)*5 MHz; n=1~11
Channel Spacing	5 MHz
Maximum Output Power to Antenna	802.11b : 16.36 dBm (43.25 mW) 802.11g : 19.20 dBm (83.18 mW)
Antenna Type	PIFA Antenna with gain 4 dBi
HW Version	V1.1
SW Version	V2.3.3_Build_1403 modem: M1.4.7-Q1
Type of Modulation	802.11b : DSSS (BPSK / QPSK / CCK) 802.11g : OFDM (BPSK / QPSK / 16QAM / 64QAM)
EUT Stage	Identical Prototype

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Transmission System (DTS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO05-HY	03CH06-HY	TW1022/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 (Measurement Guidelines of DTS)
- ♦ ANSI C63.4-2003
- ♦ IC RSS-210 Issue 7

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Vostro 1510	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A

2 Test Configuration of Equipment Under Test

2.1 RF Power

Preliminary tests were performed in different data rate and recorded the RF power output in the following table:

Channel	Frequency	2.4GHz 802.11b RF Power (dBm)			
		At DSSS Data Rate			
		1 Mbps	2 Mbps	5.5 Mbps	11 Mbps
CH 01	2412 MHz	15.79	15.90	15.89	15.64
CH 06	2437 MHz	15.60	15.44	15.68	15.29
CH 11	2462 MHz	16.14	16.32	16.15	16.36

Channel	Frequency	2.4GHz 802.11g RF Power (dBm)							
		At OFDM Data Rate							
		6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
CH 01	2412 MHz	19.09	16.76	18.17	18.12	19.04	18.02	17.22	18.70
CH 06	2437 MHz	18.39	16.45	17.95	18.51	18.18	18.20	18.31	18.45
CH 11	2462 MHz	19.20	17.17	18.84	18.43	19.02	18.25	17.85	19.13

Remark:

1. The data rates of WLAN 802.11b/g were set in 11Mbps for 802.11b and 6Mbps for 802.11g, for all the test cases due to the highest RF output power.
2. The EUT is programmed to transmit signals continuously for all testing.

2.2 Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz), radiated emission (30 MHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases and recorded in this report.


Test Cases		
Test Item	802.11b	802.11g
Conducted TCs	Mode 1 : 802.11b CH01_2412 MHz Mode 2 : 802.11b CH06_2437 MHz Mode 3 : 802.11b CH11_2462 MHz	Mode 4 : 802.11g CH01_2412 MHz Mode 5 : 802.11g CH06_2437 MHz Mode 6 : 802.11g CH11_2462 MHz
Radiated TCs	Mode 1 : 802.11b CH01_2412 MHz Mode 2 : 802.11b CH06_2437 MHz Mode 3 : 802.11b CH11_2462 MHz	Mode 4 : 802.11g CH01_2412 MHz Mode 5 : 802.11g CH06_2437 MHz Mode 6 : 802.11g CH11_2462 MHz
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter) + Camera	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<EUT with Adapter Mode>





2.4 RF Utility

The programmed RF utility, "WIFI_Test" is installed in EUT to provide channel selection, power level, data rate and the application type. RF Utility can send transmitting signal for all testing. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.
4. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	26~28°C
Test Engineer :	Andy Yeh	Relative Humidity :	44~47%

Channel	Frequency (MHz)	802.11b 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	7.12	0.5	Pass
06	2437	7.12	0.5	Pass
11	2462	7.12	0.5	Pass


Mode 1 : 6 dB Bandwidth Plot on 802.11b Channel 01



Date: 16.MAY.2010 23:43:21




Mode 2 : 6 dB Bandwidth Plot on 802.11b Channel 06



Date: 16.MAY.2010 23:47:52

Mode 3 : 6 dB Bandwidth Plot on 802.11b Channel 11




Date: 16.MAY.2010 23:51:49



Test Mode :	Mode 4, 5, 6	Temperature :	26~28°C
Test Engineer :	Andy Yeh	Relative Humidity :	44~47%

Channel	Frequency (MHz)	802.11g 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	15.16	0.5	Pass
06	2437	15.68	0.5	Pass
11	2462	15.68	0.5	Pass


Mode 4 : 6 dB Bandwidth Plot on 802.11g Channel 01



Date: 17.MAY.2010 00:07:30




Mode 5 : 6 dB Bandwidth Plot on 802.11g Channel 06



Date: 17.MAY.2010 00:12:15

Mode 6 : 6 dB Bandwidth Plot on 802.11g Channel 11



Date: 17.MAY.2010 00:13:42

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the power meter by a low loss cable.
3. Measure the power by power meter.

3.2.4 Test Setup





3.2.5 Test Result of Output Power

Test Mode :	Mode 1, 2, 3	Temperature :	26~28°C
Test Engineer :	Andy Yeh	Relative Humidity :	44~47%

Channel	Frequency (MHz)	802.11b Measured Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	15.64	30	Pass
06	2437	15.29	30	Pass
11	2462	16.36	30	Pass

Test Mode :	Mode 4, 5, 6	Temperature :	26~28°C
Test Engineer :	Andy Yeh	Relative Humidity :	44~47%

Channel	Frequency (MHz)	802.11g Measured Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	19.09	30	Pass
06	2437	18.39	30	Pass
11	2462	19.20	30	Pass



3.3 Band Edges Measurement

3.3.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB.

3.3.2 Measuring Instruments


See list of measuring instruments of this test report.

3.3.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. Conducted emission test: Set RBW = 100 kHz, Video bandwidth (VBW) \geq RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Apply to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 10 Hz, Sweep=Auto. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation as in FCC Section 15.35(b) and (c).

3.3.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>





3.3.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	24~25°C
Test Band :	802.11b	Relative Humidity :	43~44%
Test Channel :	01	Test Engineer :	Kay Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2385.81	59.51	-14.49	74	58.12	31.86	3.92	34.39	100	354	Peak
2385.81	39.41	-14.59	54	38.02	31.86	3.92	34.39	100	354	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2387.14	55.55	-18.45	74	54.16	31.86	3.92	34.39	100	47	Peak
2387.14	34.84	-19.16	54	33.45	31.86	3.92	34.39	100	47	Average

Test Mode :	Mode 3	Temperature :	24~25°C
Test Band :	802.11b	Relative Humidity :	43~44%
Test Channel :	11	Test Engineer :	Kay Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.66	53.07	-20.93	74	51.41	31.98	4.05	34.37	100	343	Peak
2483.66	33.78	-20.22	54	32.12	31.98	4.05	34.37	100	343	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2487.65	50.02	-23.98	74	48.34	32	4.05	34.37	100	329	Peak
2487.65	33.05	-20.95	54	31.37	32	4.05	34.37	100	329	Average



Test Mode :	Mode 4	Temperature :	24~25°C
Test Band :	802.11g	Relative Humidity :	43~44%
Test Channel :	01	Test Engineer :	Kay Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.99	68.77	-5.23	74	67.38	31.86	3.92	34.39	100	353	Peak
2389.99	47.38	-6.62	54	45.99	31.86	3.92	34.39	100	353	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.99	64.7	-9.3	74	63.31	31.86	3.92	34.39	100	47	Peak
2389.99	44.58	-9.42	54	43.19	31.86	3.92	34.39	100	47	Average

Test Mode :	Mode 6	Temperature :	24~25°C
Test Band :	802.11g	Relative Humidity :	43~44%
Test Channel :	11	Test Engineer :	Kay Wu

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.66	60.93	-13.07	74	59.27	31.98	4.05	34.37	100	341	Peak
2483.66	41.95	-12.05	54	40.29	31.98	4.05	34.37	100	341	Average


ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.85	59.95	-14.05	74	58.29	31.98	4.05	34.37	100	302	Peak
2483.85	41.67	-12.33	54	40.01	31.98	4.05	34.37	100	302	Average



3.3.6 Test Plots of Conducted Band Edges


Test Mode :	Mode 1 and 3	Temperature :	26~28°C
Test Band :	802.11b	Relative Humidity :	44~47%
Test Channel :	01 and 11	Test Engineer :	Andy Yeh

Low Band Edge Plot on 802.11b Channel 01



Date: 16.MAY.2010 23:45:13

High Band Edge Plot on 802.11b Channel 11




Date: 16.MAY.2010 23:52:55




Test Mode :	Mode 4 and 6	Temperature :	26~28°C
Test Band :	802.11g	Relative Humidity :	44~47%
Test Channel :	01 and 11	Test Engineer :	Andy Yeh

Low Band Edge Plot on 802.11g Channel 01



Date: 17.MAY.2010 00:08:37

High Band Edge Plot on 802.11g Channel 11



Date: 17.MAY.2010 00:14:35

3.4 Spurious Emission Measurement

3.4.1 Limit of Spurious Emission Measurement

All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) \geq RBW, scan up through 10th harmonic. All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.

3.4.4 Test Setup






3.4.5 Test Plots of Spurious Emission


Test Mode :	Mode 1	Temperature :	26~28°C
Test Band :	802.11b	Relative Humidity :	44~47%
Test Channel :	01	Test Engineer :	Andy Yeh

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 17.MAY.2010 02:18:24

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 17.MAY.2010 02:09:34




Test Mode :	Mode 2	Temperature :	26~28°C
Test Band :	802.11b	Relative Humidity :	44~47%
Test Channel :	06	Test Engineer :	Andy Yeh

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 17.MAY.2010 02:16:10

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 17.MAY.2010 02:11:24




Test Mode :	Mode 3	Temperature :	26~28°C
Test Band :	802.11b	Relative Humidity :	44~47%
Test Channel :	11	Test Engineer :	Andy Yeh

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 17.MAY.2010 02:14:44

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 17.MAY.2010 02:12:21




Test Mode :	Mode 4	Temperature :	26~28°C
Test Band :	802.11g	Relative Humidity :	44~47%
Test Channel :	01	Test Engineer :	Andy Yeh

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 17.MAY.2010 01:51:06

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 17.MAY.2010 02:07:26




Test Mode :	Mode 5	Temperature :	26~28°C
Test Band :	802.11g	Relative Humidity :	44~47%
Test Channel :	06	Test Engineer :	Andy Yeh

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 17.MAY.2010 01:53:25

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 17.MAY.2010 02:06:08




Test Mode :	Mode 6	Temperature :	26~28°C
Test Band :	802.11g	Relative Humidity :	44~47%
Test Channel :	11	Test Engineer :	Andy Yeh

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 17.MAY.2010 02:03:10

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz



Date: 17.MAY.2010 02:04:26

3.5 Power Spectral Density Measurement

3.5.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The test follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Take the measured data from spectrum analyzer.

3.5.4 Test Setup






3.5.5 Test Result of Power Spectral Density

Test Mode :	Mode 1, 2, 3	Temperature :	26~28°C
Test Engineer :	Andy Yeh	Relative Humidity :	44~47%

Channel	Frequency (MHz)	802.11b Measured PSD (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	-17.02	8	Pass
06	2437	-17.48	8	Pass
11	2462	-16.53	8	Pass


Mode 1 : PSD Plot on 802.11b Channel 01



Date: 17.MAY.2010 01:11:25




Mode 2 : PSD Plot on 802.11b Channel 06



Date: 17.MAY.2010 01:02:23

Mode 3 : PSD Plot on 802.11b Channel 11




Date: 17.MAY.2010 00:51:16



Test Mode :	Mode 4, 5, 6	Temperature :	26~28°C
Test Engineer :	Andy Yeh	Relative Humidity :	44~47%

Channel	Frequency (MHz)	802.11g Measured PSD (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	-11.88	8	Pass
06	2437	-12.18	8	Pass
11	2462	-11.50	8	Pass


Mode 4 : PSD Plot on 802.11g Channel 01



Date: 17.MAY.2010 01:21:44




Mode 5 : PSD Plot on 802.11g Channel 06



Date: 17.MAY.2010 01:32:27

Mode 6 : PSD Plot on 802.11g Channel 11



Date: 17.MAY.2010 01:45:01

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Novic Jiang	Relative Humidity :	34~36%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter) + Camera		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Final Result 1


Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	30.2	Off	L1	19.5	35.4	65.6
0.198000	31.2	Off	L1	19.6	32.5	63.7
0.326000	31.2	Off	L1	19.5	28.4	59.6
0.366000	32.2	Off	L1	19.5	26.4	58.6
12.526000	33.1	Off	L1	19.6	26.9	60.0
17.830000	32.0	Off	L1	19.7	28.0	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	25.5	Off	L1	19.5	30.1	55.6
0.198000	22.7	Off	L1	19.6	31.0	53.7
0.326000	28.7	Off	L1	19.5	20.9	49.6
0.366000	29.3	Off	L1	19.5	19.3	48.6
12.526000	23.2	Off	L1	19.6	26.8	50.0
17.830000	17.1	Off	L1	19.7	32.9	50.0



Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Novic Jiang	Relative Humidity :	34~36%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter) + Camera		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	32.7	Off	N	19.5	32.9	65.6
0.198000	31.7	Off	N	19.5	32.0	63.7
0.326000	33.8	Off	N	19.5	25.8	59.6
0.366000	35.5	Off	N	19.4	23.1	58.6
12.406000	28.5	Off	N	19.6	31.5	60.0
17.734000	24.3	Off	N	19.8	35.7	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	31.1	Off	N	19.5	24.5	55.6
0.198000	29.5	Off	N	19.5	24.2	53.7
0.326000	28.9	Off	N	19.5	20.7	49.6
0.366000	34.0	Off	N	19.4	14.6	48.6
12.406000	18.4	Off	N	19.6	31.6	50.0
17.734000	13.5	Off	N	19.8	36.5	50.0

3.7 Radiated Emission Measurement

3.7.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


1. The testing follows the guidelines in FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. Use the following spectrum analyzer settings:
 - (1) Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
 - (2) Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
Distance extrapolation factor = $20 \log(\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
3. Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.

3.7.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz





3.7.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	Kay Wu	Temperature :	24~25°C
		Relative Humidity :	43~44%

Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.



3.7.6 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	Mode 1	Temperature :	24~25°C
Test Channel :	01	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.54	17.36	-22.64	40	30.19	17.98	0.85	31.66	-	-	Peak
130.44	17.18	-26.32	43.5	35.3	11.59	1.84	31.55	-	-	Peak
188.49	15.45	-28.05	43.5	35.85	8.79	2.32	31.51	-	-	Peak
593.3	23.53	-22.47	46	32.17	18.64	4.4	31.68	-	-	Peak
799.8	25.51	-20.49	46	31.82	20.07	5.11	31.49	-	-	Peak
957.3	30.58	-15.42	46	34.58	20.96	5.59	30.55	100	64	Peak
2385.81	39.41	-14.59	54	38.02	31.86	3.92	34.39	100	354	Average
2385.81	59.51	-14.49	74	58.12	31.86	3.92	34.39	100	354	Peak
2412	110.83	-	-	109.39	31.88	3.95	34.39	100	354	Peak
2412	52.58	-	-	51.14	31.88	3.95	34.39	100	354	Average
2494	37.15	-16.85	54	35.47	32	4.05	34.37	100	354	Average
2494	50.01	-23.99	74	48.33	32	4.05	34.37	100	354	Peak
8217	52.34	-21.66	74	43.2	35.76	7.37	33.99	100	141	Peak
8217	39.39	-14.61	54	30.25	35.76	7.37	33.99	100	141	Average



Test Mode :	Mode 1	Temperature :	24~25°C
Test Channel :	01	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
74.28	20.04	-19.96	40	43.4	6.94	1.33	31.63	-	-	Peak
140.43	18.13	-25.37	43.5	36.68	11.03	1.94	31.52	-	-	Peak
241.14	18.02	-27.98	46	35.65	11.19	2.64	31.46	-	-	Peak
560.4	22.41	-23.59	46	31.59	18.23	4.2	31.61	-	-	Peak
747.3	24.58	-21.42	46	31.64	19.63	4.93	31.62	-	-	Peak
917.4	27.28	-18.72	46	31.81	20.8	5.5	30.83	100	228	Peak
2387.14	34.84	-19.16	54	33.45	31.86	3.92	34.39	100	47	Average
2387.14	55.55	-18.45	74	54.16	31.86	3.92	34.39	100	47	Peak
2412	107.31	-	-	105.87	31.88	3.95	34.39	100	47	Peak
2412	47.92	-	-	46.48	31.88	3.95	34.39	100	47	Average
2492	31.96	-22.04	54	30.28	32	4.05	34.37	100	47	Average
2492	45.55	-28.45	74	43.87	32	4.05	34.37	100	47	Peak
8130	52.05	-21.95	74	42.81	35.78	7.43	33.97	100	33	Peak
8130	39.9	-14.1	54	30.66	35.78	7.43	33.97	100	33	Average



Test Mode :	Mode 2	Temperature :	24~25°C
Test Channel :	06	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
31.89	17.72	-22.28	40	31.05	17.46	0.86	31.65	-	-	Peak
128.28	17.78	-25.72	43.5	35.76	11.75	1.82	31.55	-	-	Peak
195.78	15.85	-27.65	43.5	36.57	8.4	2.37	31.49	-	-	Peak
612.9	24.18	-21.82	46	32.6	18.79	4.47	31.68	-	-	Peak
855.8	26.27	-19.73	46	31.66	20.44	5.33	31.16	-	-	Peak
957.3	29.83	-16.17	46	33.83	20.96	5.59	30.55	100	44	Peak
2356	55.14	-18.86	74	53.88	31.81	3.86	34.41	100	354	Peak
2356	38.37	-15.63	54	37.11	31.81	3.86	34.41	100	354	Average
2437	108.82	-	-	107.28	31.93	3.99	34.38	100	354	Peak
2437	52.17	-	-	50.63	31.93	3.99	34.38	100	354	Average
2484	37.08	-16.92	54	35.42	31.98	4.05	34.37	100	354	Average
2484	49.73	-24.27	74	48.07	31.98	4.05	34.37	100	354	Peak
8202	52.08	-21.92	74	42.93	35.76	7.38	33.99	100	284	Peak
8202	39.41	-14.59	54	30.26	35.76	7.38	33.99	100	284	Average



Test Mode :	Mode 2	Temperature :	24~25°C
Test Channel :	06	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
74.28	20.02	-19.98	40	43.38	6.94	1.33	31.63	-	-	Peak
155.28	17.6	-25.9	43.5	36.76	10.19	2.06	31.41	-	-	Peak
241.14	18.82	-27.18	46	36.45	11.19	2.64	31.46	-	-	Peak
621.3	23.58	-22.42	46	31.92	18.83	4.5	31.67	-	-	Peak
803.3	25.47	-20.53	46	31.73	20.09	5.12	31.47	-	-	Peak
957.3	29.35	-16.65	46	33.35	20.96	5.59	30.55	100	99	Peak
2350	48.1	-25.9	74	46.87	31.78	3.86	34.41	151	58	Peak
2350	32.79	-21.21	54	31.56	31.78	3.86	34.41	151	58	Average
2437	103.49	-	-	101.95	31.93	3.99	34.38	151	58	Peak
2437	47.13	-	-	45.59	31.93	3.99	34.38	151	58	Average
2486	32.09	-21.91	54	30.43	31.98	4.05	34.37	151	58	Average
2486	45.79	-28.21	74	44.13	31.98	4.05	34.37	151	58	Peak
8178	52.18	-21.82	74	42.99	35.77	7.4	33.98	100	31	Peak
8178	39.84	-14.16	54	30.65	35.77	7.4	33.98	100	31	Average



Test Mode :	Mode 3	Temperature :	24~25°C
Test Channel :	11	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.54	17.77	-22.23	40	30.6	17.98	0.85	31.66	-	-	Peak
140.43	17.32	-26.18	43.5	35.87	11.03	1.94	31.52	-	-	Peak
192.54	15.47	-28.03	43.5	36.05	8.55	2.36	31.49	-	-	Peak
584.9	23.2	-22.8	46	31.99	18.53	4.34	31.66	-	-	Peak
785.8	25.52	-20.48	46	32.04	19.95	5.06	31.53	-	-	Peak
957.3	29.71	-16.29	46	33.71	20.96	5.59	30.55	100	91	Peak
2382	52.52	-21.48	74	51.16	31.83	3.92	34.39	100	343	Peak
2382	34.37	-19.63	54	33.01	31.83	3.92	34.39	100	343	Average
2462	106.47	-	-	104.88	31.95	4.02	34.38	100	343	Peak
2462	48.11	-	-	46.52	31.95	4.02	34.38	100	343	Average
2483.66	33.78	-20.22	54	32.12	31.98	4.05	34.37	100	343	Average
2483.66	53.07	-20.93	74	51.41	31.98	4.05	34.37	100	343	Peak
8346	52.74	-21.26	74	43.75	35.73	7.28	34.02	100	296	Peak
8346	39.21	-14.79	54	30.22	35.73	7.28	34.02	100	296	Average



Test Mode :	Mode 3	Temperature :	24~25°C
Test Channel :	11	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
72.93	20.25	-19.75	40	43.72	6.8	1.33	31.6	-	-	Peak
140.43	17.32	-26.18	43.5	35.87	11.03	1.94	31.52	-	-	Peak
240.33	18.65	-27.35	46	36.41	11.07	2.63	31.46	-	-	Peak
512.8	21.75	-24.25	46	31.61	17.64	4.01	31.51	-	-	Peak
647.9	24.12	-21.88	46	32.21	18.97	4.56	31.62	-	-	Peak
957.3	29.71	-16.29	46	33.71	20.96	5.59	30.55	100	75	Peak
2382	47.48	-26.52	74	46.12	31.83	3.92	34.39	100	329	Peak
2382	33.11	-20.89	54	31.75	31.83	3.92	34.39	100	329	Average
2462	102.27	-	-	100.68	31.95	4.02	34.38	100	329	Peak
2462	44.19	-	-	42.6	31.95	4.02	34.38	100	329	Average
2487.65	33.05	-20.95	54	31.37	32	4.05	34.37	100	329	Average
2487.65	50.02	-23.98	74	48.34	32	4.05	34.37	100	329	Peak
8145	52.78	-21.22	74	43.57	35.77	7.42	33.98	100	75	Peak
8145	39.87	-14.13	54	30.66	35.77	7.42	33.98	100	75	Average



Test Mode :	Mode 4	Temperature :	24~25°C
Test Channel :	01	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.43	18.4	-21.6	40	32.22	16.93	0.88	31.63	-	-	Peak
128.28	17.79	-25.71	43.5	35.77	11.75	1.82	31.55	-	-	Peak
195.24	15.52	-27.98	43.5	36.19	8.45	2.37	31.49	-	-	Peak
645.8	23.68	-22.32	46	31.79	18.96	4.56	31.63	-	-	Peak
789.3	25.56	-20.44	46	32.03	19.98	5.07	31.52	-	-	Peak
957.3	30.32	-15.68	46	34.32	20.96	5.59	30.55	100	77	Peak
2389.99	47.38	-6.62	54	45.99	31.86	3.92	34.39	100	353	Average
2389.99	68.77	-5.23	74	67.38	31.86	3.92	34.39	100	353	Peak
2412	104.76	-	-	103.32	31.88	3.95	34.39	100	353	Peak
2412	80.93	-	-	79.49	31.88	3.95	34.39	100	353	Average
2486	34.33	-19.67	54	32.67	31.98	4.05	34.37	100	353	Average
2486	47.34	-26.66	74	45.68	31.98	4.05	34.37	100	353	Peak
8190	52.13	-21.87	74	42.98	35.76	7.38	33.99	100	119	Peak
8190	39.81	-14.19	54	30.66	35.76	7.38	33.99	100	119	Average



Test Mode :	Mode 4	Temperature :	24~25°C
Test Channel :	01	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	2412 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
72.93	20.58	-19.42	40	44.05	6.8	1.33	31.6	-	-	Peak
126.93	17.91	-25.59	43.5	35.85	11.8	1.81	31.55	-	-	Peak
200.64	17.51	-25.99	43.5	38.35	8.24	2.4	31.48	-	-	Peak
649.3	24.1	-21.9	46	32.18	18.97	4.57	31.62	-	-	Peak
805.4	25.5	-20.5	46	31.73	20.1	5.13	31.46	-	-	Peak
957.3	29.83	-16.17	46	33.83	20.96	5.59	30.55	100	88	Peak
2389.99	44.58	-9.42	54	43.19	31.86	3.92	34.39	100	47	Average
2389.99	64.7	-9.3	74	63.31	31.86	3.92	34.39	100	47	Peak
2412	101.47	-	-	100.03	31.88	3.95	34.39	100	47	Peak
2412	78.12	-	-	76.68	31.88	3.95	34.39	100	47	Average
2494	32.48	-21.52	54	30.8	32	4.05	34.37	100	47	Average
2494	44.46	-29.54	74	42.78	32	4.05	34.37	100	47	Peak
8046	52.77	-21.23	74	43.44	35.79	7.49	33.95	100	331	Peak
8046	39.95	-14.05	54	30.62	35.79	7.49	33.95	100	331	Average



Test Mode :	Mode 5	Temperature :	24~25°C
Test Channel :	06	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.54	17.68	-22.32	40	30.51	17.98	0.85	31.66	-	-	Peak
140.43	17.6	-25.9	43.5	36.15	11.03	1.94	31.52	-	-	Peak
241.14	16.22	-29.78	46	33.85	11.19	2.64	31.46	-	-	Peak
596.8	23.47	-22.53	46	32.07	18.67	4.42	31.69	-	-	Peak
761.3	25.61	-20.39	46	32.47	19.75	4.98	31.59	-	-	Peak
957.3	29.71	-16.29	46	33.71	20.96	5.59	30.55	100	57	Peak
2356	50.39	-23.61	74	49.13	31.81	3.86	34.41	100	340	Peak
2356	37.42	-16.58	54	36.16	31.81	3.86	34.41	100	340	Average
2437	103.45	-	-	101.94	31.9	3.99	34.38	100	340	Peak
2437	80.01	-	-	78.47	31.93	3.99	34.38	100	340	Average
2492	34.58	-19.42	54	32.9	32	4.05	34.37	100	340	Average
2492	48	-26	74	46.32	32	4.05	34.37	100	340	Peak
8082	52.41	-21.59	74	43.12	35.78	7.47	33.96	100	66	Peak
8082	38.62	-15.38	54	29.33	35.78	7.47	33.96	100	66	Average



Test Mode :	Mode 5	Temperature :	24~25°C
Test Channel :	06	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	2437 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
73.74	20.75	-19.25	40	44.16	6.87	1.33	31.61	-	-	Peak
140.43	18.07	-25.43	43.5	36.62	11.03	1.94	31.52	-	-	Peak
241.14	19.12	-26.88	46	36.75	11.19	2.64	31.46	-	-	Peak
563.9	22.57	-23.43	46	31.71	18.26	4.21	31.61	-	-	Peak
778.8	25.18	-20.82	46	31.8	19.89	5.04	31.55	-	-	Peak
957.3	29.02	-16.98	46	33.02	20.96	5.59	30.55	100	86	Peak
2350	49.1	-24.9	74	47.87	31.78	3.86	34.41	100	59	Peak
2350	35.85	-18.15	54	34.62	31.78	3.86	34.41	100	59	Average
2437	99.66	-	-	98.15	31.9	3.99	34.38	100	59	Peak
2437	75.95	-	-	74.41	31.93	3.99	34.38	100	59	Average
2484	32.05	-21.95	54	30.39	31.98	4.05	34.37	100	59	Average
2484	43.55	-30.45	74	41.89	31.98	4.05	34.37	100	59	Peak
8286	51.65	-22.35	74	42.6	35.74	7.32	34.01	100	69	Peak
8286	39.71	-14.29	54	30.66	35.74	7.32	34.01	100	69	Average



Test Mode :	Mode 6	Temperature :	24~25°C
Test Channel :	11	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Horizontal
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.54	17.47	-22.53	40	30.3	17.98	0.85	31.66	-	-	Peak
140.43	16.83	-26.67	43.5	35.38	11.03	1.94	31.52	-	-	Peak
247.08	17.12	-28.88	46	34.01	11.91	2.67	31.47	-	-	Peak
658.4	24.27	-21.73	46	32.29	19.02	4.59	31.63	-	-	Peak
764.8	25.5	-20.5	46	32.31	19.78	4.99	31.58	-	-	Peak
957.3	30.16	-15.84	46	34.16	20.96	5.59	30.55	100	221	Peak
2382	48.6	-25.4	74	47.24	31.83	3.92	34.39	100	341	Peak
2382	36	-18	54	34.64	31.83	3.92	34.39	100	341	Average
2462	100.58	-	-	98.99	31.95	4.02	34.38	100	341	Peak
2462	77.52	-	-	75.93	31.95	4.02	34.38	100	341	Average
2483.66	41.95	-12.05	54	40.29	31.98	4.05	34.37	100	341	Average
2483.66	60.93	-13.07	74	59.27	31.98	4.05	34.37	100	341	Peak
8217	52.34	-21.66	74	43.2	35.76	7.37	33.99	100	22	Peak
8217	39.39	-14.61	54	30.25	35.76	7.37	33.99	100	22	Average



Test Mode :	Mode 6	Temperature :	24~25°C
Test Channel :	11	Relative Humidity :	43~44%
Test Engineer :	Kay Wu	Polarization :	Vertical
Remark :	2462 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	18.6	-21.4	40	30.94	18.51	0.83	31.68	-	-	Peak
126.39	17.83	-25.67	43.5	35.72	11.86	1.8	31.55	-	-	Peak
241.14	20.44	-25.56	46	38.07	11.19	2.64	31.46	-	-	Peak
577.2	22.67	-23.33	46	31.58	18.43	4.3	31.64	-	-	Peak
745.9	25.01	-20.99	46	32.09	19.62	4.92	31.62	-	-	Peak
957.3	29.54	-16.46	46	33.54	20.96	5.59	30.55	100	111	Peak
2382	46.74	-27.26	74	45.38	31.83	3.92	34.39	100	302	Peak
2382	34.79	-19.21	54	33.43	31.83	3.92	34.39	100	302	Average
2462	96.14	-	-	94.55	31.95	4.02	34.38	100	302	Peak
2462	74.34	-	-	72.75	31.95	4.02	34.38	100	302	Average
2483.85	41.67	-12.33	54	40.01	31.98	4.05	34.37	100	302	Average
2483.85	59.95	-14.05	74	58.29	31.98	4.05	34.37	100	302	Peak
8130	52.05	-21.95	74	42.81	35.78	7.43	33.97	100	39	Peak
8130	39.46	-14.54	54	30.22	35.78	7.43	33.97	100	39	Average



3.8 Antenna Requirements

3.8.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.8.2 Antenna Connected Construction

The antennas type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

3.8.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 23, 2009	Jun. 22, 2010	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 17, 2009	Sep. 16, 2010	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	0846202	N/A	Sep. 10, 2009	Sep. 09, 2010	Conducted (TH02-HY)
EMI Test Receive	R&S	ESCS 30	100356	9KHz - 2.75GHz	Aug. 05, 2009	Aug. 04, 2010	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100081	9kHz~30MHz	Nov. 30, 2009	Nov. 29, 2010	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100080	9kHz~30MHz	Nov. 23, 2009	Nov. 22, 2010	Conduction (CO05-HY)
AC Power Source	APC	APC-1000W	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
Spectrum Analyzer	Agilent	E4408B	MY442110 30	9KHz-26.5GHz	Oct. 23, 2009	Oct. 22, 2010	Radiation (03CH06-HY)
Spectrum Analyzer	R&S	FSP40	100057	9KHz-40GHz	Oct. 20, 2009	Oct. 19, 2010	Radiation (03CH06-HY)
EMI Test Receiver	R&S	ESVS10	834468/00 3	20MHz-1000MHz	Apr. 28, 2010	Apr. 27, 2011	Radiation (03CH06-HY)
Bilog Antenna	SCHAFFNER	CBL6112B	2885	30MHz -2GHz	Oct. 31, 2009	Oct. 30, 2010	Radiation (03CH06-HY)
Double Ridge Horn Antenna	EMCO	3117	00066583	1GHz~18GHz	Aug. 20, 2009	Aug. 19, 2010	Radiation (03CH06-HY)
Double Ridge Horn Antenna	Training Research	AH-0801	95119	8GHz~18GHz	Nov. 02, 2009	Nov. 01, 2010	Radiation (03CH06-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 251	15GHz- 40GHz	Oct. 14, 2009	Oct. 13, 2010	Radiation (03CH06-HY)
Pre Amplifier	Agilent	8449B	3008A019 17	1GHz- 26.5GHz	Nov. 11, 2009	Nov. 10, 2010	Radiation (03CH06-HY)
Amplifier	Agilent	310N	186713	9KHz~1GHz	Apr. 15, 2010	Apr. 14, 2011	Radiation (03CH06-HY)
Loop Antenna	R&S	HFH2-Z2	860004/00 1	9KHz~30MHz	May 22, 2008	May 21, 2010	Radiation (03CH06-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		



Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	±0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	±1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	±0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site Imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP041702 as below.