

# RF Exposure Evaluation Declaration

Product Name : Dual-band Wireless-AC750 Range Extender  
Model No. : RP-AC52  
FCC ID. : MSQ-RPAC52

Applicant : ASUSTeK COMPUTER INC.

Address : 4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

Date of Receipt : 2015/03/10

Date of Declaration : 2015/05/21

Report No. : 1530179R-RF-US-Exp

Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product	Dual-band Wireless-AC750 Range Extender
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3dBi or 2 in linear scale.

#### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	72.4436	0.02882
6	2437	44.2588	0.01761
11	2462	54.4503	0.02167

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	40.3645	0.01606
6	2437	199.5262	0.07939
11	2462	34.2768	0.01364

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	Dual-band Wireless-AC750 Range Extender
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

**Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3dBi or 2 in linear scale.

**Output Power into Antenna & RF Exposure Evaluation Distance:**

IEEE 802.11n (20MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	41.0204	0.01632
6	2437	182.3896	0.07257
11	2462	41.3048	0.01643

IEEE 802.11n (40MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
3	2422	24.2103	0.00963
6	2437	82.6038	0.03287
9	2452	23.8781	0.00950

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	Dual-band Wireless-AC750 Range Extender
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

**Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3dBi or 2 in linear scale.

**Output Power into Antenna & RF Exposure Evaluation Distance:**

IEEE 802.11a			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
36	5180	58.2103	0.02316
40	5220	104.7129	0.04166
44	5240	108.8930	0.04333

IEEE 802.11a			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
149	5745	72.1107	0.02869
153	5785	136.4583	0.05429
165	5825	125.8925	0.05009

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	Dual-band Wireless-AC750 Range Extender
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

**Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3dBi or 2 in linear scale.

**Output Power into Antenna & RF Exposure Evaluation Distance:**

IEEE 802.11 n(20MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
36	5180	58.2103	0.02316
40	5220	110.1539	0.04383
44	5240	112.4605	0.04475

IEEE 802.11 n(20MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
149	5745	58.0764	0.02311
153	5785	133.3521	0.05306
165	5825	115.8777	0.04611

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	Dual-band Wireless-AC750 Range Extender
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

**Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3dBi or 2 in linear scale.

**Output Power into Antenna & RF Exposure Evaluation Distance:**

IEEE 802.11 n(40MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
38	5190	25.3513	0.01009
46	5230	111.1732	0.04423

IEEE 802.11 n(40MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
151	5755	40.2717	0.01602
159	5795	121.3389	0.04828

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	Dual-band Wireless-AC750 Range Extender
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

**Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3dBi or 2 in linear scale.

**Output Power into Antenna & RF Exposure Evaluation Distance:**

IEEE 802.11 ac(80MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
42	5210	19.2752	0.00767

IEEE 802.11 ac(80MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
155	5775	27.8612	0.01109

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.