

RF Exposure Evaluation declaration

Product Name : Wireless-AC1900 Dual Band Gigabit Router
Model No. : RT-AC68U, RT-AC68R, RT-AC68RW, TM-AC1900
FCC ID. : MSQ-RTAC68U

Applicant : ASUSTeK COMPUTER INC.

Address : 4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

Date of Receipt : 2014/06/17

Date of Declaration : 2014/07/10

Report No. : 146476R-RF-US-Exp

Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (CDD Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.91dBi or 1.55 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	209.4112	0.06457
6	2437	227.5097	0.07016
11	2462	223.8721	0.06903

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	157.3983	0.04854
6	2437	633.8697	0.19546
11	2462	174.1807	0.05371

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (CDD Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.91dBi or 1.55 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (20MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	105.1962	0.03244
6	2437	509.3309	0.15706
11	2462	153.8155	0.04743

IEEE 802.11n (40MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
3	2422	73.9605	0.02281
6	2437	151.0080	0.04657
9	2452	101.6249	0.03134

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (CDD Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.04dBi or 2.54 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11a Ant0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
36	5180	256.0354	0.1291
44	5220	198.5180	0.1001
48	5240	186.1230	0.0939

IEEE 802.11a Ant0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
149	5745	703.3962	0.3548
157	5785	710.8861	0.3585
165	5825	688.3352	0.3472

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (CDD Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.04dBi or 2.54 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11 n(20MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
36	5180	265.0330	0.1337
44	5220	232.7555	0.1174
48	5240	165.9205	0.0837

IEEE 802.11 n(20MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
149	5745	695.8250	0.3509
157	5785	702.7486	0.3544
165	5825	682.0245	0.3440

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (CDD Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.04dBi or 2.54 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11 n(40MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
38	5190	90.4899	0.0456
46	5230	426.7760	0.2152

IEEE 802.11 n(40MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
151	5755	402.1610	0.2028
159	5795	734.1757	0.3703

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (CDD Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.04dBi or 2.54 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11 ac(80MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
42	5210	63.7382	0.0321

IEEE 802.11 ac(80MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
155	5775	297.3035	0.1499

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (SISO Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.91dBi or 1.55 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	187.4995	0.05782
6	2437	189.2344	0.05835
11	2462	154.5254	0.04765

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	97.2747	0.03000
6	2437	317.6874	0.09796
11	2462	68.3912	0.02109

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (Beamforming Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.91dBi or 1.55 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (20MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	171.0015	0.05273
6	2437	522.3962	0.16109
11	2462	147.2313	0.04540

IEEE 802.11n (40MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
3	2422	119.1791	0.03675
6	2437	177.1740	0.05463
9	2452	78.8860	0.02433

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (Beamforming Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.04dBi or 2.54 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11 n(20MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
36	5180	270.8944	0.1366
44	5220	136.3955	0.0688
48	5240	135.7688	0.0685

IEEE 802.11 n(20MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
149	5745	430.0312	0.2169
157	5785	431.4197	0.2176
165	5825	432.7131	0.2182

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (Beamforming Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.04dBi or 2.54 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11 n(40MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
38	5190	63.0667	0.0318
46	5230	185.6949	0.0937

IEEE 802.11 n(40MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
151	5755	403.4596	0.2035
159	5795	427.0709	0.2154

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	Wireless-AC1900 Dual Band Gigabit Router
Test Mode	Transmit (Beamforming Mode)
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.04dBi or 2.54 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11 ac(80MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
42	5210	40.0037	0.0202

IEEE 802.11 ac(80MHz) ANT 0+1+2			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
155	5775	302.1343	0.1524

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².