




FCC RADIO TEST REPORT

FCC ID : MSQ-RTACJ900
Equipment : Wireless AC3000 Tri Band Gigabit Router
Brand Name : ASUS
Model Name : RT-AC95U, ZenWiFi CT8, ZenWiFi, CT8, ASUS ZenWiFi CT8, ASUS ZenWiFi
Applicant : ASUSTeK COMPUTER INC.
4F, No. 150, Li-Te Rd., Peitou, Taipei 112, Taiwan
Manufacturer (1) : Datamax Electronics (DongGuan) Co., Ltd.
Niu Shan Foreign Economic Industrial Park, Dong Cheng District, Dong Guan City, Guang Dong, China
Manufacturer (2) : Lukisen Electronic Corp.
3F., No. 236, Boai St., Shulin Dist., New Taipei City 23845, Taiwan
Manufacturer (3) : Kentec Inc.
No. 5, Tzu-Chiang 1st Rd. Chungli Industrial Zone, Taoyuan City, Taiwan
Standard : 47 CFR FCC Part 15.247

The product was received on Jun. 07, 2019, and testing was started from Jun. 07, 2019 and completed on Jul. 31, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.


Approved by: Sam Chen

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Information.....	5
1.2 Applicable Standards	10
1.3 Testing Location Information	10
1.4 Measurement Uncertainty	10
2 Test Configuration of EUT	11
2.1 Test Channel Mode	11
2.2 The Worst Case Measurement Configuration.....	12
2.3 EUT Operation during Test	13
2.4 Accessories	14
2.5 Support Equipment.....	14
2.6 Test Setup Diagram	15
3 Transmitter Test Result	18
3.1 AC Power-line Conducted Emissions	18
3.2 DTS Bandwidth	20
3.3 Maximum Conducted Output Power	21
3.4 Power Spectral Density	24
3.5 Emissions in Non-restricted Frequency Bands	26
3.6 Emissions in Restricted Frequency Bands.....	27
4 Test Equipment and Calibration Data	31
Appendix A. Test Results of AC Power-line Conducted Emissions	
Appendix B. Test Results of DTS Bandwidth	
Appendix C. Test Results of Maximum Conducted Output Power	
Appendix D. Test Results of Power Spectral Density	
Appendix E. Test Results of Emissions in Non-restricted Frequency Bands	
Appendix F. Test Results of Emissions in Restricted Frequency Bands	
Appendix G. Test Photos	
Photographs of EUT v01	



TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB Ver1.0



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(a)	DTS Bandwidth	PASS	-
3.3	15.247(b)	Maximum Conducted Output Power	PASS	-
3.4	15.247(e)	Power Spectral Density	PASS	-
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	-
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen

Report Producer: Wendy Pan



1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1.0	1TX

Note:

- ♦ Bluetooth LE uses a GFSK modulation.
- ♦ BWch is the nominal channel bandwidth.
- ♦ Nss-Min is the minimum number of spatial streams.
- ♦ Nant is the number of outputs. e.g., 2(2, 3) means have 2 outputs for port 2 and port 3. 2 means have 2 outputs for port 1 and port 2.

1.1.2 Antenna Information

Set	Ant.	Port	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	1	1	PSA	RFDPA230505IMLB901	Dipole Antenna	I-PEX	Note 1
	2	2	PSA	RFDPA230510IMLB901	Dipole Antenna	I-PEX	
	3	3	PSA	RFDPA100610IM5B901	Dipole Antenna	I-PEX	
	4	4	PSA	RFDPA100607IM5B901	Dipole Antenna	I-PEX	
	5	5	PSA	RFDPA100608IM5B901	Dipole Antenna	I-PEX	
	6	6	PSA	RFDPA100605IM5B901	Dipole Antenna	I-PEX	
	7	1	PSA	-	Printed Antenna	N/A	
2	1	1	Whayu	C660-510478-A ANT1 2_5G	Dipole Antenna	I-PEX	
	2	2	Whayu	C660-510478-A ANT2 2_5G	Dipole Antenna	I-PEX	
	3	3	Whayu	C660-510478-A_ANT 3 5G	Dipole Antenna	I-PEX	
	4	4	Whayu	C660-510478-A_ANT 4 5G	Dipole Antenna	I-PEX	
	5	5	Whayu	C660-510478-A_ANT 5 5G	Dipole Antenna	I-PEX	
	6	6	Whayu	C660-510478-A_ANT 6 5G	Dipole Antenna	I-PEX	
3	1	1	Airgain	M2440DMCT-PK1-HSR3-LB1X52BU	Dipole Antenna	I-PEX	
	2	2	Airgain	M2440DMCT-PK1-HSY3-LB1X102BU	Dipole Antenna	I-PEX	
	3	3	Airgain	M5X30CT-PK1-HSE3-LBIX102BU	Dipole Antenna	I-PEX	
	4	4	Airgain	M5X30CT-PK1-HSA3-LB1X75BU	Dipole Antenna	I-PEX	
	5	5	Airgain	M5X30CT-PK1-HSW3-LB 1X85BU	Dipole Antenna	I-PEX	
	6	6	Airgain	M5X30CT-PK1-HSB3-LBIX52BU	Dipole Antenna	I-PEX	

Note 1:

Set	Ant.	Port	Gain (dBi) - CDD mode for output power			
			2.4GHz	5GHz Band 1	5GHz Band 4	Bluetooth
1	1	1	1.36	1.74	-	-
	2	2	1.36	1.74	-	-
	3	1	-	-	1.36	-
	4	2	-	-	1.36	-
	5	3	-	-	1.36	-
	6	4	-	-	1.36	-
	7	1	-	-	-	-2.93
2	1	1	1.17	1.69	-	-
	2	2	1.17	1.69	-	-
	3	1	-	-	0.43	-
	4	2	-	-	0.43	-
	5	3	-	-	0.43	-
	6	4	-	-	0.43	-
3	1	1	0.80	1.47	-	-
	2	2	0.80	1.47	-	-
	3	1	-	-	0.34	-
	4	2	-	-	0.34	-
	5	3	-	-	0.34	-
	6	4	-	-	0.34	-

Set	Ant.	Port	Gain (dBi) - Beamforming mode for output power & PSD, CDD mode for PSD			
			2.4GHz	5GHz Band 1 Nss1	5GHz Band 4 Nss1	5GHz Band 4 Nss2
1	1	1	4.37	4.70	-	-
	2	2	4.37	4.70	-	-
	3	1	-	-	7.21	4.32
	4	2	-	-	7.21	4.32
	5	3	-	-	7.21	4.32
	6	4	-	-	7.21	4.32
2	1	1	4.18	4.54	-	-
	2	2	4.18	4.54	-	-
	3	1	-	-	6.05	3.40
	4	2	-	-	6.05	3.40
	5	3	-	-	6.05	3.40
	6	4	-	-	6.05	3.40
3	1	1	3.79	4.48	-	-
	2	2	3.79	4.48	-	-
	3	1	-	-	6.02	3.33
	4	2	-	-	6.02	3.33
	5	3	-	-	6.02	3.33
	6	4	-	-	6.02	3.33

Note2: The above information was declared by manufacturer.

The EUT has three sets of WLAN antenna and there are six antennas for each set.

There are three sets antenna are the same type antennas, only the higher gain antennas "Set 1" was tested and recorded in the report.

Directional Gain of CDD in Power Measurement = Gant + Array Gain ; Array Gain = 0dB.

For 2.4GHz function:

For IEEE 802.11a/b/g/n/VHT mode (2TX/2RX):

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.



For 5GHz Band 1 function:

For IEEE 802.11a/b/g/n/ac mode (2TX/2RX):

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

For 5GHz Band 4 function:

For IEEE 802.11a/n/ac mode (4TX/4RX):

Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.

Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.

For Bluetooth function

Only Port 1 can be used as transmitting/receiving antenna.

1.1.3 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) $\geq 1/T$
BT-LE(1Mbps)	0.656	1.83	410u	3k

Note:

- ♦ DC is Duty Cycle.
- ♦ DCF is Duty Cycle Factor.

**1.1.4 EUT Operational Condition**

EUT Power Type	From Power Adapter		
Function	☒ Point-to-multipoint	☐ Point-to-point	
Test Software Version	Telnet		
Support Mode	☒	LE 1M PHY: 1 Mb/s	
	☐	LE Coded PHY (S=2): 500 Kb/s	
	☐	LE Coded PHY (S=8): 125 Kb/s	
	☐	LE 2M PHY: 2 Mb/s	

Note: The above information was declared by manufacturer.

1.1.5 Table for Radio information

Radio	Band
1	5GHz Band 1
	2.4GHz
2	5GHz Band 4
3	Bluetooth

Note: The above information was declared by manufacturer.

1.1.6 Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Brand Name	Model Name	Description
ASUS	RT-AC95U	All the models are identical, the difference model served as marketing strategy.
	ZenWiFi CT8	
	ZenWiFi	
	CT8	
	ASUS ZenWiFi CT8	
	ASUS ZenWiFi	

From the above models, model:RT-AC95U was selected as representative model for the test and its data was recorded in this report.



1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ FCC KDB 558074 D01 v05r02

1.3 Testing Location Information

Testing Location				
☐	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	TEL : 886-3-327-3456	FAX : 886-3-327-0973
☒	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.	TEL : 886-3-656-9065	FAX : 886-3-656-9085

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH02-CB	Lucas Huang	25.4~26.9°C / 62~66%	Jun. 07, 2019 ~ Jul. 18, 2019
Radiated<1GHz	03CH05-CB	KJ Chang	24.8~25.5°C / 58~63%	Jul. 06, 2019 ~ Jul. 31, 2019
Radiated>1GHz	03CH03-CB	KJ Chang	25.6~26.9°C / 60~64%	Jul. 06, 2019 ~ Jul. 31, 2019
AC Conduction	CO01-CB	Deven Huang	22~23°C / 58~60%	Jul. 22, 2019

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086B with Industry Canada.

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.0 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	5.1 dB	Confidence levels of 95%
Conducted Emission	2.4 dB	Confidence levels of 95%
Output Power Measurement	1.5 dB	Confidence levels of 95%
Power Density Measurement	2.4 dB	Confidence levels of 95%
Bandwidth Measurement	2%	Confidence levels of 95%



2 Test Configuration of EUT

2.1 Test Channel Mode

Mode	PowerSetting
BT-LE(1Mbps)	-
2402MHz	Default
2440MHz	Default
2480MHz	Default

2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	CTX
1	CTX + Radio 1 WLAN 2.4GHz + Adapter
2	CTX + Radio 1 WLAN 5GHz + Adapter
3	CTX + Radio 2 WLAN 5GHz + Adapter
4	CTX + Radio 3 Bluetooth BR/EDR + Adapter
5	CTX + Radio 3 Bluetooth LE + Adapter
For operating mode 1 is the worst case and it was record in this test report.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emissions in Restricted Frequency Bands
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	CTX
1	CTX + Radio 1 WLAN 2.4GHz + Adapter
2	CTX + Radio 1 WLAN 5GHz + Adapter
3	CTX + Radio 2 WLAN 5GHz + Adapter
4	CTX + Radio 3 Bluetooth BR/EDR + Adapter
5	CTX + Radio 3 Bluetooth LE + Adapter
For operating mode 2 is the worst case and it was record in this test report.	
Operating Mode > 1GHz	CTX



The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation
Operating Mode	
1	Radio 1 WLAN 2.4GHz + Radio 2 WLAN 5GHz + Radio 3 Bluetooth
2	Radio 1 WLAN 5GHz + Radio 2 WLAN 5GHz + Radio 3 Bluetooth
Refer to Sporton Test Report No.: FA850709 for Co-location RF Exposure Evaluation.	

Note: The EUT can only be used Y axis.

2.3 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



2.4 Accessories

Accessories				
Equipment Name	Brand Name	Model Name	Type	Rating
Adapter	ASUS	AD2088320	010LF	Input: 100-240V~50/60Hz, 0.8A Output: 19V, 1.75A
Equipment Name	Brand Name	Model Name		Remark
RJ-45 cable	NIEN-YI	NYT976		Non-Shielding:1.5m

2.5 Support Equipment

For AC Conduction:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Flash disk3.0	Transcend	JetFlash-700	N/A
B	LAN NB	DELL	E6430	N/A


For Radiated:


Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Notebook	DELL	E4300	N/A

For RF Conducted:


Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Notebook	DELL	E4300	N/A

2.6 Test Setup Diagram



Test Setup Diagram - Radiated Test < 1GHz


Item	Connection	Shielded	Length
1	RJ-45 cable	No	10m
2	Power cable	No	2.2m
3	RJ-45 cable	No	1.5m

Test Setup Diagram - Radiated Test > 1GHz


Item	Connection	Shielded	Length
1	RJ-45 cable	No	10m
2	Power cable	No	2.2m



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013 , clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
Systems using digital modulation techniques:	
▪	6 dB bandwidth $\geq$ 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
▪	For the emission bandwidth shall be measured using one of the options below:
☒	Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.1 Option 1 for 6 dB bandwidth measurement.
☐	Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.2 Option 2 for 6 dB bandwidth measurement.
☐	Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	▪ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	▪ Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	▪ Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	▪ Smart antenna system (SAS):
	- Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
Maximum Peak Conducted Output Power	
☐	Refer as FCC KDB 558074, clause 8.3.1.1 & C63.10 clause 11.9.1.1 (RBW ≥ EBW method).
☐	Refer as FCC KDB 558074, clause 8.3.1.3 & C63.10 clause 11.9.1.3 (peak power meter).
Maximum Conducted Output Power	
[duty cycle ≥ 98% or external video / power trigger]	
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.2 Method AVGSA-1.
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.3 Method AVGSA-1A. (alternative)
duty cycle < 98% and average over on/off periods with duty factor	
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.4 Method AVGSA-2.
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.5 Method AVGSA-2A (alternative)
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.6 Method AVGSA-3
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.7 Method AVGSA-3A (alternative)
Measurement using a power meter (PM)	
☒	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.1 Method AVGPM (using an RF average power meter).
☐	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.2 Method AVGPM-G (using an gate RF average power meter).
For conducted measurement.	
If the EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.	
If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$	

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C



3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
Power Spectral Density (PSD) ≤ 8 dBm/3kHz

3.4.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method
Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
☒ Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.2 Method PKPSD. [duty cycle $\geq 98\%$ or external video / power trigger]
☐ Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.3 Method AVGPS-1.
☐ Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.5 Method AVGPS-2.
☐ Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.7 Method AVGPS-3.
duty cycle $< 98\%$ and average over on/off periods with duty factor
☐ Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.4 Method AVGPS-1A. (alternative).
☐ Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.6 Method AVGPS-2A. (alternative)
☐ Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.8 Method AVGPS-3A. (alternative)
For conducted measurement.
If The EUT supports multiple transmit chains using options given below:
☒ Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
☐ Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits,

- | | |
|--|--|
| | ☐ Option 3: Measure and add $10 \log(N)$ dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with $10 \log(N)$. Or each transmit chains shall be add $10 \log(N)$ to compared with the limit. |
|--|--|

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30
Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level. Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
Refer as FCC KDB 558074, clause 8.5 for unwanted emissions into non-restricted bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E



3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.




3.6.3 Test Procedures

Test Method	
The average emission levels shall be measured in [duty cycle ≥ 98 or duty factor].	
Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.	
For the transmitter unwanted emissions shall be measured using following options below:	
	Refer as FCC KDB 558074, clause 8.6 for unwanted emissions into restricted bands.
	☐ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.1(trace averaging for duty cycle $\geq 98\%$).
	☐ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.2(trace averaging + duty factor).
	☒ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.3(Reduced VBW $\geq 1/T$).
	☐ Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW $\geq 1/T$, where T is pulse time.
	☐ Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.
	☒ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.4 measurement procedure peak limit.
For the transmitter band-edge emissions shall be measured using following options below:	
	Refer as FCC KDB 558074 clause 8.7 & c63.10 clause 11.13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	Refer as FCC KDB 558074, clause 8.7 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.
	Refer as FCC KDB 558074, clause 8.7 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
	For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB
	For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.

3.6.4 Test Setup





3.6.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.6.6 Emissions in Restricted Frequency Bands (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10 harmonic or 40 GHz, whichever is appropriate.

3.6.7 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F



4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.45GHz	Jan. 28, 2019	Jan. 29, 2020	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 24, 2018	Dec. 23, 2019	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Jan. 11, 2019	Jan. 10, 2020	Conduction (CO01-CB)
COND Cable	Woken	Cable	Low cable-CO01	9kHz ~ 30MHz	May 21, 2019	May 20, 2020	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	N.C.R.	Conduction (CO01-CB)
Bilog Antenna with 6dB Attenuator	TESE & EMCI	CBL 6112D & N-6-06	35236 & AT-N0610	30MHz ~ 2GHz	Mar. 28, 2019	Mar. 27, 2020	Radiation (03CH05-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 29, 2019	Mar. 28, 2020	Radiation (03CH05-CB)
Pre-Amplifier	EMCI	EMC330N	980331	20MHz ~ 3GHz	May 02, 2019	May 01, 2020	Radiation (03CH05-CB)
Spectrum analyzer	R&S	FSP40	100080	9kHz~40GHz	Oct. 03, 2018	Oct. 02, 2019	Radiation (03CH05-CB)
EMI Test Receiver	R&S	ESCS	826547/017	9kHz ~ 2.75GHz	May 15, 2019	May 14, 2020	Radiation (03CH05-CB)
RF Cable-low	Woken	RG402	LOW Cable-04+23	30MHz~1GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH05-CB)
Horn Antenna	ETS • Lindgren	3115	6821	750MHz~18GHz	Jan. 24, 2019	Jan. 23, 2020	Radiation (03CH03-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jun. 27, 2019	Jun. 26, 2020	Radiation (03CH03-CB)
Pre-Amplifier	Agilent	8449B	3008A02097	1GHz ~ 26.5GHz	Dec. 20, 2018	Dec. 19, 2019	Radiation (03CH03-CB)
Pre-Amplifier	MITEQ	TTA1840-35-H G	1864479	18GHz ~ 40GHz	Jul. 03, 2019	Jul. 02, 2020	Radiation (03CH03-CB)
Spectrum Analyzer	R&S	FSP-40	100019	9kHz ~ 40GHz	Jun. 19, 2019	Jun. 18, 2020	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-20+27	1GHz ~ 18GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-27	1GHz ~ 18GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-40G#1	18GHz ~ 40 GHz	Jul. 27, 2018	Jul. 26, 2019	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-40G#1	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-40G#2	18GHz ~ 40 GHz	Jul. 27, 2018	Jul. 26, 2019	Radiation (03CH03-CB)




Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
RF Cable-high	Woken	RG402	High Cable-40G#2	18GHz ~ 40 GHz	Jul. 24, 2019	Jul. 23, 2020	Radiation (03CH03-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Feb. 25, 2019	Feb. 24, 2020	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-01	1 GHz – 26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-02	1 GHz – 26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-3	1 GHz – 26.5 GHz	Oct. 24, 2018	Oct. 23, 2019	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-04	1 GHz – 26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH02-CB)
RF Cable-high	Woken	RG402	High Cable-05	1 GHz – 26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH02-CB)
Power Sensor	Anritsu	MA2411B	1126203	300MHz~40GHz	Sep. 03, 2018	Sep. 02, 2019	Conducted (TH02-CB)
Power Meter	Anritsu	ML2495A	1210004	300MHz~40GHz	Sep. 03, 2018	Sep. 02, 2019	Conducted (TH02-CB)

Note: Calibration Interval of instruments listed above is one year.


N.C.R. means Non-Calibration required.

Test Mode	Mode 1	Frequency Range	0.15 MHz to 30 MHz
-----------	--------	-----------------	--------------------

Line



Neutral





Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	648.75k	1.031M	1M03F1D	648.75k	1.029M

Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	648.75k	1.029M
2440MHz	Pass	500k	648.75k	1.03M
2480MHz	Pass	500k	648.75k	1.031M


Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

BT-LE(1Mbps)
EBW
2402MHz

18/07/2019



BT-LE(1Mbps)
EBW
2440MHz

18/07/2019



BT-LE(1Mbps)


2480MHz



6dB(Hz)	Fl-6dB(Hz)	Fh-6dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
648.75k	2.47966G	2.480309G	1.031M	2.479486G	2.480517G	500k	1

EBW

18/07/2019



**Summary**

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	4.04	0.00254

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	-2.93	1.31	30.00
2440MHz	Pass	-2.93	3.00	30.00
2480MHz	Pass	-2.93	4.04	30.00

DG = Directional Gain; **Port X** = Port X output power



Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-10.81

RBW=3 kHz.



Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	-2.93	-13.07	8.00
2440MHz	Pass	-2.93	-11.82	8.00
2480MHz	Pass	-2.93	-10.81	8.00

DG = Directional Gain; RBW=3 kHz;


PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port X power density;

BT-LE(1Mbps)

PSD

2402MHz

18/07/2019




BT-LE(1Mbps)

PSD

2440MHz

18/07/2019




BT-LE(1Mbps)

PSD

2480MHz

18/07/2019





Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.47999G	4.37	-25.63	2.39593G	-56.17	2.39993G	-54.00	2.48441G	-54.99	24.93527G	-44.28	1

Result



Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.47999G	4.37	-25.63	2.39593G	-56.17	2.39993G	-54.00	2.48441G	-54.99	24.93527G	-44.28	1
2440MHz	Pass	2.47999G	4.37	-25.63	2.19139G	-55.72	2.39925G	-55.54	2.48372G	-55.09	24.89587G	-44.91	1
2480MHz	Pass	2.47999G	4.37	-25.63	2.14344G	-56.64	2.39864G	-55.51	2.48447G	-54.49	24.86773G	-44.92	1

BT-LE(1Mbps)

2402MHz

CSE NdB

18/07/2019





Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.47999G	4.37	-25.63	2.39993G	-56.17	2.39993G	-54.00	2.48441G	-54.99	2.493527G	-44.28	1

BT-LE(1Mbps)

2440MHz

CSE NdB

18/07/2019



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.47999G	4.37	-25.63	2.19139G	-55.72	2.39925G	-55.54	2.48372G	-55.09	2.489587G	-44.91	1



BT-LE(1Mbps)

2480MHz

CSE NdB

18/07/2019

Port 1



RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak

Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.47999G	4.37	-25.63	2.14344G	-56.64	2.39864G	-55.51	2.48447G	-54.49	2.486773G	-44.92	1




Radiated Emission below 1GHz Result

Appendix F.1


Test Mode	Mode 2	Frequency Range	30 MHz to 1,000 MHz
-----------	--------	-----------------	---------------------

Vertical 30 MHz to 1,000 MHz



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	32.91	35.89	40.00	-4.11	40.92	0.67	22.87	28.57	300	0 Peak	VERTICAL
2	38.73	34.56	40.00	-5.44	42.71	0.73	19.69	28.57	134	55 QP	VERTICAL
3	49.40	33.24	40.00	-6.76	46.46	0.82	14.52	28.56	300	0 Peak	VERTICAL
4	84.32	28.42	40.00	-11.58	41.99	1.07	13.84	28.48	300	0 Peak	VERTICAL
5	166.77	32.23	43.50	-11.27	43.31	1.50	15.61	28.19	300	0 Peak	VERTICAL
6	584.84	37.93	46.00	-8.07	39.62	2.84	24.96	29.49	300	0 Peak	VERTICAL

Horizontal 30 MHz to 1,000 MHz



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	30.97	35.29	40.00	-4.71	39.35	0.65	23.86	28.57	100	0 Peak	HORIZONTAL
2	38.73	33.46	40.00	-6.54	41.61	0.73	19.69	28.57	131	17 QP	HORIZONTAL
3	125.06	35.70	43.50	-7.80	44.84	1.30	17.91	28.35	100	0 Peak	HORIZONTAL
4	250.19	32.93	46.00	-13.07	40.73	1.85	18.34	27.99	100	0 Peak	HORIZONTAL
5	586.78	37.65	46.00	-8.35	39.41	2.84	24.89	29.49	100	0 Peak	HORIZONTAL
6	746.83	40.24	46.00	-5.76	40.53	3.22	25.90	29.41	100	0 Peak	HORIZONTAL




Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	AV	2.4844G	43.70	54.00	-10.30	30.96	3	Horizontal	127	1.51

BT-LE(1Mbps)

2402MHz_TX

13/07/2019




EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.3666G	54.85	74.00	-19.15	30.71	3	Vertical	86	1.02	-				
AV	2.3874G	43.17	54.00	-10.83	30.79	3	Vertical	86	1.02	-				
PK	2.4018G	92.34	Inf	-Inf	30.84	3	Vertical	86	1.02	-				
AV	2.402G	90.82	Inf	-Inf	30.84	3	Vertical	86	1.02	-				

BT-LE(1Mbps)

13/07/2019

2402MHz_TX




EUT V_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.36G	55.09	74.00	-18.91	30.69	3	Horizontal	126	1.77	-				
AV	2.3736G	43.41	54.00	-10.59	30.74	3	Horizontal	126	1.77	-				
PK	2.4018G	91.16	Inf	-Inf	30.84	3	Horizontal	126	1.77	-				
AV	2.402G	89.64	Inf	-Inf	30.84	3	Horizontal	126	1.77	-				

BT-LE(1Mbps)

2402MHz_TX

13/07/2019




EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.804G	45.79	74.00	-28.21	3.49	3	Vertical	319	2.48	-				
AV	4.80448G	33.47	54.00	-20.53	3.50	3	Vertical	319	2.48	-				

BT-LE(1Mbps)

2402MHz_TX

13/07/2019




EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.80397G	46.75	74.00	-27.25	3.49	3	Horizontal	82	1.50	-				
AV	4.8033G	33.51	54.00	-20.49	3.49	3	Horizontal	82	1.50	-				

BT-LE(1Mbps)

2440MHz_TX

13/07/2019




EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.3452G	55.39	74.00	-18.61	30.64	3	Vertical	100	1.04	-				
AV	2.3564G	43.07	54.00	-10.93	30.68	3	Vertical	100	1.04	-				
PK	2.44G	92.02	Inf	-Inf	30.90	3	Vertical	100	1.04	-				
AV	2.44G	90.40	Inf	-Inf	30.90	3	Vertical	100	1.04	-				
PK	2.4856G	54.75	74.00	-19.25	30.97	3	Vertical	100	1.04	-				
AV	2.492G	43.41	54.00	-10.59	30.98	3	Vertical	100	1.04	-				

BT-LE(1Mbps)

2440MHz_TX

13/07/2019




EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.3636G	55.08	74.00	-18.92	30.70	3	Horizontal	60	1.31	-				
AV	2.378G	43.09	54.00	-10.91	30.75	3	Horizontal	60	1.31	-				
PK	2.44G	90.41	Inf	-Inf	30.90	3	Horizontal	60	1.31	-				
AV	2.44G	88.81	Inf	-Inf	30.90	3	Horizontal	60	1.31	-				
PK	2.4852G	56.16	74.00	-17.84	30.97	3	Horizontal	60	1.31	-				
AV	2.4848G	43.34	54.00	-10.66	30.96	3	Horizontal	60	1.31	-				

BT-LE(1Mbps)

13/07/2019

2440MHz_TX




EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.87974G	46.38	74.00	-27.62	3.84	3	Vertical	144	2.40	-				
AV	4.8804G	33.85	54.00	-20.15	3.84	3	Vertical	144	2.40	-				

BT-LE(1Mbps)

2440MHz_TX

13/07/2019




EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.8801G	46.50	74.00	-27.50	3.84	3	Horizontal	25	2.26	-				
AV	4.87981G	33.97	54.00	-20.03	3.84	3	Horizontal	25	2.26	-				

BT-LE(1Mbps)

2480MHz_TX

13/07/2019




EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.48G	90.50	Inf	-Inf	30.96	3	Vertical	75	1.25	-				
AV	2.48G	88.98	Inf	-Inf	30.96	3	Vertical	75	1.25	-				
PK	2.4928G	54.98	74.00	-19.02	30.98	3	Vertical	75	1.25	-				
AV	2.4835G	43.47	54.00	-10.53	30.96	3	Vertical	75	1.25	-				

BT-LE(1Mbps)

2480MHz_TX

13/07/2019




EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.48G	89.10	Inf	-Inf	30.96	3	Horizontal	127	1.51	-				
AV	2.48G	87.56	Inf	-Inf	30.96	3	Horizontal	127	1.51	-				
PK	2.4938G	54.95	74.00	-19.05	30.98	3	Horizontal	127	1.51	-				
AV	2.4844G	43.70	54.00	-10.30	30.96	3	Horizontal	127	1.51	-				

BT-LE(1Mbps)

2480MHz_TX

13/07/2019




EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.95991G	46.59	74.00	-27.41	4.20	3	Vertical	333	1.50	-				
AV	4.95951G	33.75	54.00	-20.25	4.20	3	Vertical	333	1.50	-				

BT-LE(1Mbps)

2480MHz_TX

13/07/2019



EUT Y_1TX
Setting Default
01-M-1
FSP

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.96042G	46.52	74.00	-27.48	4.20	3	Horizontal	98	2.65	-				
AV	4.96071G	33.77	54.00	-20.23	4.20	3	Horizontal	98	2.65	-				