

RF Exposure Evaluation declaration

Product Name : ROG Rapture GT-AX6000 Dual-band Gaming Router/
ROG Rapture GT-AC5400 Dual-band Gaming Router
Trade Name : ASUS
Model No. : GT-AX6000, GT-AC5400
FCC ID. : MSQ-RTAX2E00

Applicant : ASUSTeK COMPUTER INC.

Address : 4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan

Date of Receipt : Aug. 09, 2018

Date of Declaration : Sep. 07, 2018

Report No. : 1880136R-RF-US-Exp

Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd..

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (Minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational/ Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100,000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/ Uncontrolled Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100,000 | -- | -- | 1 | 30 |

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

WiFi

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_CDD mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.2 dBi or 1.66dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11b (ANT 0+1+2+3) | | | |
|----------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 1 | 2412 | 981.296 | 0.324 |
| 6 | 2437 | 975.439 | 0.322 |
| 11 | 2462 | 939.507 | 0.310 |

| IEEE 802.11g (ANT 0+1+2+3) | | | |
|----------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 1 | 2412 | 697.268 | 0.230 |
| 6 | 2437 | 956.093 | 0.316 |
| 11 | 2462 | 440.656 | 0.146 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_CDD mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.2 dBi or 1.66dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ac (20MHz) (ANT 0+1+2+3) | | | |
|-------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 1 | 2412 | 566.109 | 0.187 |
| 6 | 2437 | 972.747 | 0.321 |
| 11 | 2462 | 442.283 | 0.146 |

| IEEE 802.11ac (40MHz) (ANT 0+1+2+3) | | | |
|-------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 3 | 2422 | 606.597 | 0.200 |
| 6 | 2437 | 527.716 | 0.174 |
| 9 | 2452 | 267.055 | 0.088 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_CDD mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.2 dBi or 1.66dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ax (20MHz) (ANT 0+1+2+3) | | | |
|-------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 1 | 2412 | 574.910 | 0.190 |
| 6 | 2437 | 987.188 | 0.326 |
| 11 | 2462 | 362.326 | 0.120 |

| IEEE 802.11ax (40MHz) (ANT 0+1+2+3) | | | |
|-------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 3 | 2422 | 593.335 | 0.196 |
| 6 | 2437 | 470.111 | 0.155 |
| 9 | 2452 | 265.522 | 0.088 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_BF |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.2 dBi or 1.66dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802. 11ac (20MHz) (ANT 0+1+2+3) | | | |
|--------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 1 | 2412 | 386.901 | 0.128 |
| 6 | 2437 | 596.486 | 0.197 |
| 11 | 2462 | 196.472 | 0.065 |

| IEEE 802. 11ac (40MHz) (ANT 0+1+2+3) | | | |
|--------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 3 | 2422 | 402.532 | 0.133 |
| 6 | 2437 | 267.485 | 0.088 |
| 9 | 2452 | 133.567 | 0.044 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_BF |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.2 dBi or 1.66dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802. 11ax (20MHz) (ANT 0+1+2+3) | | | |
|--------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 1 | 2412 | 401.051 | 0.132 |
| 6 | 2437 | 622.587 | 0.206 |
| 11 | 2462 | 199.389 | 0.066 |

| IEEE 802. 11ax (40MHz) (ANT 0+1+2+3) | | | |
|--------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 3 | 2422 | 419.759 | 0.139 |
| 6 | 2437 | 259.060 | 0.086 |
| 9 | 2452 | 131.069 | 0.043 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_CDD mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

5G Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.3 dBi or 2.14 dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11a (ANT 0+1+2+3+4+5+6+8) | | | |
|------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 36 | 5180 | 202.535 | 0.086 |
| 40 | 5220 | 222.485 | 0.095 |
| 44 | 5240 | 216.770 | 0.092 |

| IEEE 802.11a (ANT 0+1+2+3) | | | |
|----------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 149 | 5745 | 952.577 | 0.406 |
| 157 | 5785 | 999.079 | 0.425 |
| 165 | 5825 | 933.469 | 0.397 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_CDD mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

5G Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.3 dBi or 2.14 dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ac (20MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 36 | 5180 | 734.683 | 0.313 |
| 40 | 5220 | 791.590 | 0.337 |
| 44 | 5240 | 770.549 | 0.328 |

| IEEE 802.11ac (20MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 149 | 5745 | 947.327 | 0.403 |
| 157 | 5785 | 988.781 | 0.421 |
| 165 | 5825 | 993.802 | 0.423 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_CDD mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

5G Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.3 dBi or 2.14 dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ac (40MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 38 | 5190 | 417.927 | 0.178 |
| 46 | 5230 | 967.832 | 0.412 |

| IEEE 802.11ac (40MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 151 | 5755 | 950.605 | 0.405 |
| 159 | 5795 | 958.517 | 0.408 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_CDD mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

5G Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.3 dBi or 2.14 dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ac (80MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 42 | 5210 | 514.044 | 0.219 |

| IEEE 802.11ac (80MHz) (ANT 0+1+2+3) | | | |
|-------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 155 | 5775 | 994.947 | 0.424 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_CDD mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

5G Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.3 dBi or 2.14 dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ax (20MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 36 | 5180 | 795.060 | 0.338 |
| 40 | 5220 | 795.976 | 0.339 |
| 44 | 5240 | 737.225 | 0.314 |

| IEEE 802.11ax (20MHz) (ANT 0+1+2+3) | | | |
|-------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 149 | 5745 | 970.957 | 0.413 |
| 157 | 5785 | 941.673 | 0.401 |
| 165 | 5825 | 997.700 | 0.425 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_CDD mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

5G Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.3 dBi or 2.14 dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ax (40MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 38 | 5190 | 433.910 | 0.185 |
| 46 | 5230 | 418.794 | 0.178 |

| IEEE 802.11ax (40MHz) (ANT 0+1+2+3) | | | |
|-------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 151 | 5755 | 934.114 | 0.398 |
| 159 | 5795 | 972.299 | 0.414 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_CDD mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

5G Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.3 dBi or 2.14 dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ax (80MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 42 | 5210 | 941.456 | 0.401 |

| IEEE 802.11ax (80MHz) (ANT 0+1+2+3) | | | |
|-------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 155 | 5775 | 994.260 | 0.423 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_BF mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

5G Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.3 dBi or 2.14 dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ac (20MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 36 | 5180 | 734.683 | 0.313 |
| 40 | 5220 | 791.590 | 0.337 |
| 44 | 5240 | 770.549 | 0.328 |

| IEEE 802.11n (20MHz) (ANT 0+1+2+3) | | | |
|------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 149 | 5745 | 947.327 | 0.403 |
| 157 | 5785 | 953.674 | 0.406 |
| 165 | 5825 | 953.455 | 0.406 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_BF mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

5G Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.3 dBi or 2.14 dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ac (40MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 38 | 5190 | 531.251 | 0.226 |
| 46 | 5230 | 967.832 | 0.412 |

| IEEE 802.11n (40MHz) (ANT 0+1+2+3) | | | |
|------------------------------------|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 151 | 5755 | 892.689 | 0.380 |
| 159 | 5795 | 945.584 | 0.403 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit_BF mode |
| Test Condition | RF Exposure Evaluation |

Antenna Gain

5G Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.3 dBi or 2.14 dBi in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

| IEEE 802.11ac (80MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 42 | 5210 | 415.050 | 0.177 |

| IEEE 802.11ac (80MHz) (ANT 0+1+2+3+4+5+6+8) | | | |
|---|-------------------------|------------------------------|--|
| WLAN Function | | | |
| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm ²) |
| 155 | 5775 | 783.430 | 0.334 |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

| | |
|----------------|--|
| Product | ROG Rapture GT-AX6000 Dual-band Gaming Router/ ROG Rapture GT-AC5400 Dual-band Gaming Router |
| Test Mode | Transmit |
| Test Condition | RF Exposure Evaluation |

| Power Density (2.4GHz) (mW/cm ²) | Power Density (5GHz) (mW/cm ²) | Total Power Density (2.4GHz+5GHz) (mW/cm ²) | Limit (mW/cm ²) |
|---|---|---|--------------------------------|
| 0.326 | 0.425 | 0.751 | 1 |