



WHA YU INDUSTRIAL CO., LTD.(HEAD OFFICE)



DONGGUAN AEON TECH CO.,LTD.(CHINA)

SPECIFICATION FOR APPROVAL

CUSTOMER: ASUS


PART NAME: RF Antenna Assembly

PART NO.:

REVISION:

W. Y. P/NO.: C660-510643-A(SRF20241578)

REV.: X1

	MANUFACTURER SIGNATURE	CUSTOMER SIGNATURE
APPROVED BY :	 Stone	
DATE :		

WHA YU GROUP

WHA YU INDUSTRIAL CO., LTD.(HEAD OFFICE)

譚裕實業股份有限公司

Address: No. 326, Sec. 2, Kung Tao 5 Road, Hsin Chu City, Taiwan, R.O.C.

Tel: +886-3-5714225(REP.)

Fax: +886-3-5713853 · +886-3-5723600

DONGGUAN AEON TECH CO., LTD.(CHINA)

東莞台霖電子通訊有限公司

Address: Hupan Industrial District, Tai Ling Shan Town, Dong Guan City, Guangdong, China

Tel: +86-769-85655858

Fax: +86-769-85655258

Contents

<i>Item</i>	<i>Description</i>	<i>Page</i>
1.	規格表	 1
2.	成品圖	 2
3.	測試報告	 3~14

RF Antenna Assembly

Specification

1. Electrical Properties With housing/With Cable loss(ANT4)

- 1.1 Frequency Range.....5.15~5.895GHz
- 1.2 Impedance 50Ω Nominal
- 1.3 VSWR 1.57 : 1 Max.
- 1.4 Return Loss..... 13 dB Min.
- 1.5 Radiation Omni-directional
- 1.6 2D Peak Gain..... $\leq 2.85\text{dBi}$
- 1.7 Cable Loss..... 0.85dB
- 1.8 Polarization..... Linear
- 1.9 Cable..... 1.37 Low Loss Coaxial Cable
- 1.10 Connector..... IPEX MHF Connector

2. Physical Properties :

- 2.1 Operating Temp. -10°C ~ +60°C
- 2.2 Storage Temp. -10°C ~ +70°C

NE1-24043

RT-BE82U

25Gx2 5Gx2

Version:V2.04

Released Date: 2024/10/28

Prepared By:YUAN

Reviewed By: STONE

Contents

- Revised History
- Conclusion & Comments
- Specification
- Antenna Placement & Solution
- Test Setup for S-parameter Measurement
- Return Loss Results
- Isolation Results
- Test Setup for Radiation Pattern Measurement
- 2D Radiation Pattern Results
- Results Summary (return loss, isolation, peak gain, efficiency)

Revision History

Released Date	Version	Record
2024/04/15	1.01	整機測試 3D 列印桿套
2024/04/15	1.02	單天線測試 3D 列印桿套_ANT1~4
2024/04/15	2.03	整機測試 3D 列印桿套_ANT1~4 + 模具機殼
2024/04/15	2.04	單天線測試 _ANT1~4
2024/04/15	2.04-1	單天線測試 _ANT1
2024/04/15	2.04-2	單天線測試 _ANT2
2024/04/15	2.04-3	單天線測試 _ANT3
2024/04/15	2.04-4	單天線測試 _ANT4


Test Setup for S-parameter Measurement



Equipment	Brand	Model	S/N
Network Analyzer	Keysight	E5071C	MY46107744


Return Loss Results

Ant4-5G (5150MHz – 5895MHz)



Test Setup for Radiation Pattern Measurement





Chamber Information



- SATIMO SG-24L Multi-Probe Antenna Measurement System
 - Angle between probes: 15°
 - Frequency range: 400 MHz – 9 GHz
 - Chamber Room Size: 5m L x 5m W x 5m H

2D Radiation Pattern Results

Ant4-5G



Results Summary

Return Loss

Frequency (MHz)	Ant4-5G
5150	29
5500	31
5895	19

Results Summary

2D Peak gain & Efficiency – Ant4

2D Peak Gain (dBi)			
Frequency (MHz)	XZ	YZ	XY
5150	1.96	2.15	2.38
5250	2.04	2.35	2.42
5350	1.84	2.29	2.31
5490	2.77	2.25	2.73
5570	2.67	2.06	2.71
5650	2.70	1.91	2.70
5710	2.76	1.79	2.76
5815	2.85	2.20	2.85
5895	2.65	2.30	2.72