

Appendix B. Maximum Permissible Exposure

1. Maximum Permissible Exposure

1.1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby that distance of at least 0.2 m is normally maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.31m, as well as the gain of the used antenna, the RF power density can be obtained.

1.3. Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

EUT: Version 1

For 5GHz Band (NII):

Antenna Type : Dipole Antenna

Conducted Power for IEEE 802.11ac MCS0/Nss1 VHT20: 26.47 dBm

Distance (m)	Test Freq. (MHz)	Directional Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
				(dBm)	(mW)			
0.31	5240	9.49	8.8932	26.4684	443.4459	0.326729	1	Complies

Note: $Directional\ Gain = 10\log\left[\frac{\sum_{j=1}^{N_{SS}}\left\{\sum_{K=1}^{N_{ANT}}g_{j,k}\right\}^2}{N_{ANT}}\right]$

For 5GHz Band (DTS):

Antenna Type : Dipole Antenna

Conducted Power for IEEE 802.11ac MCS0/Nss1 VHT80: 26.45 dBm

Distance (m)	Test Freq. (MHz)	Directional Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
				(dBm)	(mW)			
0.31	5775	9.49	8.8932	26.4518	441.7485	0.325478	1	Complies

Note: $Directional\ Gain = 10\log\left[\frac{\sum_{j=1}^{N_{SS}}\left\{\sum_{K=1}^{N_{ANT}}g_{j,k}\right\}^2}{N_{ANT}}\right]$

For 2.4GHz Band:

Antenna Type : Dipole Antenna

Conducted Power for IEEE 802.11ac MCS0/Nss1 VHT20: 27.56 dBm

Distance (m)	Test Freq. (MHz)	Directional Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
				(dBm)	(mW)			
0.31	2437	8.34	6.8243	27.5617	570.3849	0.322489	1	Complies

Note: $Directional\ Gain = 10\log\left[\frac{\sum_{j=1}^{N_{SS}}\left\{\sum_{K=1}^{N_{ANT}}g_{j,k}\right\}^2}{N_{ANT}}\right]$

Conclusion:

Both of the 2.4GHz WLAN function, 5GHz Band 1 WLAN function and 5GHz Band 4 WLAN function can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots\text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is $0.322489 / 1 + 0.326729 / 1 + 0.325478 / 1 = 0.974696$, which is less than "1". This confirmed that the device complies.

EUT: Version 2

For 5GHz Band (NII):

Antenna Type : Dipole Antenna

Conducted Power for IEEE 802.11ac MCS0/Nss1 VHT20: 26.46dBm

Distance (m)	Test Freq. (MHz)	Directional Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
				(dBm)	(mW)			
0.31	5200	9.49	8.8932	26.4625	442.8465	0.326287	1	Complies

Note: $Directional\ Gain = 10 \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{K=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

For 5GHz Band (DTS):

Antenna Type : Dipole Antenna

Conducted Power for IEEE 802.11ac MCS0/Nss1 VHT40: 26.46 dBm

Distance (m)	Test Freq. (MHz)	Directional Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
				(dBm)	(mW)			
0.31	5795	9.49	8.8932	26.4607	442.6563	0.326147	1	Complies

Note: $Directional\ Gain = 10 \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{K=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

For 2.4GHz Band:

Antenna Type : Dipole Antenna

Conducted Power for IEEE 802.11ac MCS0/Nss1 VHT20: 27.50 dBm

Distance (m)	Test Freq. (MHz)	Directional Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
				(dBm)	(mW)			
0.31	2437	8.34	6.8243	27.4956	561.7704	0.317618	1	Complies

Note: $Directional\ Gain = 10 \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{K=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

Conclusion:

Both of the 2.4GHz WLAN function, 5GHz Band 1 WLAN function and 5GHz Band 4 WLAN function can transmit simultaneously, the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is $0.317618 / 1 + 0.326287 / 1 + 0.326147 / 1 = 0.970052$, which is less than "1". This confirmed that the device complies.