

## RF Exposure Evaluation declaration

Product Name : ASUS Wireless SuperSpeedN Router  
Model No. : RT-N12  
FCC ID. : MSQ-RTN12

Applicant : ASUSTeK COMPUTER INC.

Address : No. 15, Li-Te Rd., Peitou, Taipei 112, Taiwan

Date of Receipt : 2009/06/19  
Date of Declaration : 2009/07/14  
Report No. : 096316R-RF-US-Exp  
Report Version : V1.0

The declaration results relate only to the samples calculated.  
The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

**1. RF Exposure Evaluation**

**1.1. Limits**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

**LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

**Friis Formula**

Friis transmission formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

**1.2. Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product	ASUS Wireless SuperSpeedN Router
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.5dBi or 1.78 in linear scale.

#### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	109.3956	0.3874
6	2437	126.4736	0.4479
11	2462	112.7197	0.3992

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	179.4734	0.6355
6	2437	176.1976	0.6239
11	2462	142.5608	0.5048

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	ASUS Wireless SuperSpeedN Router
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.5dBi or 1.78 in linear scale. IEEE 802.11n (ANT A (20M) / ANT A (40M))  
 scale. IEEE 802.11n (ANT B (20M) / ANT B (40M))

### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (ANT A (20MHz) / ANT B (20MHz))			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	272.2701	0.9642
6	2437	267.9168	0.9487
11	2462	254.6830	0.9019

IEEE 802.11n (ANT A (40MHz) / ANT B (40MHz))			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
3	2422	210.8628	0.7467
6	2437	207.4914	0.7348
9	2452	204.1738	0.7230

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.