



FCC 47 CFR PART 15 SUBPART C

for

Wireless-N Router

Model: RT-N12, RT-N12_D1

Brand: ASUS

Test Report Number:

C140929Z01-RP1

Issued Date: January 5, 2015

Issued for

ASUSTeK COMPUTER INC.

4F, No. 150, Li-Te Rd. Peitou, Taipei 112, Taiwan

Issued by:

Compliance Certification Services (Shenzhen) Inc.

No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd.,

Guan Lan Town, Baoan District, Shenzhen, China

TEL: 86-755-28055000

FAX: 86-755-28055221



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample.



Revision History

Rev.	Issue Date.	Revisions	Effect Page	Revised By
00	November 25, 2012	Initial Issue	ALL	Amay Tang
01	October 8, 2013	Update	ALL	Sabrina Wang
02	January 5, 2015	Update	ALL	Nancy Fu

Rev.01: (C130916Z01-RP1)

- 1.The applicant company updated the power rating of the EUT. After the reassessment, all items were retested, except the Power line Conducted Emissions and the radiated emissions of below 1GHz.
- 2.The other information, please refer to the Report No.: C121026Z01-RP1 and this report.

Rev.02: (C140929Z01-RP1)

1. The applicant company added added one model name(RT-N12_D1), added two chip capacitors on the RF module. Please see the internal photos for detail.
2. After the reassessment, the radiated emissions, the peak output power and the band edges were retested.
3. The other information, please refer to the Report No.: C130916Z01-RP1 and this report.



TABLE OF CONTENTS

1 TEST CERTIFICATION	4
2 TEST RESULT SUMMARY	5
3 EUT DESCRIPTION	6
4 TEST METHODOLOGY	7
4.1. DESCRIPTION OF TEST MODES.....	7
5 SETUP OF EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF SUPPORT UNITS.....	8
5.2. CONFIGURATION OF SYSTEM UNDER TEST.....	8
6 FACILITIES AND ACCREDITATIONS.....	9
6.1. FACILITIES	9
6.2. ACCREDITATIONS.....	9
6.3. MEASUREMENT UNCERTAINTY	10
7 FCC PART 15.247 REQUIREMENTS	11
7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT	11
7.2. SPURIOUS EMISSIONS MEASUREMENT	16
7.3. 6dB BANDWIDTH MEASUREMENT	53
7.4. PEAK OUTPUT POWER.....	65
7.5. BAND EDGES MEASUREMENT	68
7.6. PEAK POWER SPECTRAL DENSITY MEASUREMENT	86



1 TEST CERTIFICATION

Table with 2 columns: Field (Product, Model, Brand, Tested, Applicant, Manufacturer, Factory #1, Factory #2) and Value (Wireless-N Router, RT-N12, RT-N12_D1, ASUS, October 26~November 24, 2012 & September 16~October 8, 2013 & September 29, 2014~ January 5, 2015, ASUSTeK COMPUTER INC., Shenzhen Gongjin Electronics Co., Ltd, Shenzhen Gongjin Electrics Co., Ltd, TAICANG T&W ELECTRONICS CO., LTD)

Table titled 'APPLICABLE STANDARDS' with 4 columns: Standard, Test Type, Standard, Test Type. Rows include 15.207(a) Power Line Conducted Emissions, 15.247(a)(2) 6dB Bandwidth Measurement, and 15.247(d) Band Edges Measurement.

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2009 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247. The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Handwritten signature of Sunday Hu

Handwritten signature of Ruby Zhang

Sunday Hu
Supervisor of EMC Dept.
Compliance Certification Service Inc.

Ruby Zhang
Supervisor of Report Dept.
Compliance Certification Service Inc.



2 TEST RESULT SUMMARY

APPLICABLE STANDARDS			
Standard	Test Type	Result	Remark
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.247(d) 15.209(a)	<ul style="list-style-type: none">● Spurious Emissions● Conducted Measurement● Radiated Emissions	Pass	Meet the requirement of limit.
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.

Note: 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.
2. The information of measurement uncertainty is available upon the customer's request.



3 EUT DESCRIPTION

Product	Wireless-N Router
Model Number	RT-N12, RT-N12_D1
Brand	ASUS
Model Discrepancy	All models are identical to each other except their model names.
Identify Number	C140929Z01-RP1
Received Date	September 16, 2013 & September 29, 2014
Power Supply	DC 12V supplied by the adapter
Adapter Manufacturer / Model No.	Adapter1: Shenzhen Gongjin Electronics Co., Ltd. S06A22-120A050-PB I/P: 100-240Vac, 50/60Hz, 0.30A max O/P: 12Vdc, 500mA, DC Output Cable: Unshielded,1.50m Adapter2:RUIDE RD1200500-C55-8MG I/P: 100-240Vac, 50/60Hz, 250mA max O/P: 12Vdc, 500mA, DC Output Cable: Unshielded,1.50m
Frequency Range	IEEE 802.11b/g: 2412 ~ 2462 MHz IEEE 802.11n HT20 : 2412 ~ 2462 MHz IEEE 802.11n HT40 : 2422MHz~ 2452MHz
Transmit Power	IEEE 802.11b mode: 20.27dBm (Antenna 1) IEEE 802.11g mode: 23.57dBm (Antenna 1) IEEE 802.11n HT20 MHz mode: 25.86dBm (Combine with Antenna 1 and Antenna 2) IEEE 802.11n HT40 MHz mode: 24.14dBm (Combine with Antenna 1 and Antenna 2)
Modulation Technique	IEEE 802.11b mode: DSSS(CCK,QPSK, BPSK) IEEE 802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT20 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT40 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM)
Transmit Data Rate	802.11b: 11Mbps(CCK) with fall back rates of 5.5/2/1Mbps 802.11g: 54Mbps with fall back rates of 48/36/24/18/12/9 /6Mbps IEEE 802.11n HT20: 130.0Mbps with fall back rates of 130/ 117/104 /78/52/39/26/13Mbps IEEE 802.11n HT40: 270Mbps with fall back rates of 270/ 243/216 /162/108/81/54/27Mbps
Number of Channels	IEEE 802.11b mode: 11 Channels IEEE 802.11g mode: 11 Channels IEEE 802.11n HT20 MHz mode: 11 Channels IEEE 802.11n HT40 MHz mode: 7 Channels
Antenna Specification	Dipole Antenna with 5.0dBi gain (Max)

Note: 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

2. This submittal(s) (test report) is intended for FCC ID: **MSQ-RTN12D1** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



4 TEST METHODOLOGY

4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Test Item	Test mode	Worse mode
Conducted Emission	Mode 1: Normal Link+ Adapter 1 Mode 2: Normal Link+ Adapter 2	Mode 1 Mode 2
Radiated Emission	Mode 1: TX	Mode 1

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only, and power line conducted emission below 30MHz, which worst case was in normal link mode.

IEEE802.11b mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High(2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE802.11g mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT20 MHz mode: Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 13Mbps data rate were chosen for full testing.

IEEE 802.11n HT40 MHz mode: Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with 27Mbps data rate were chosen for full testing.



5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	NOTEBOOK	B475	WB04861612	N/A	Lenovo	Unshielded 1.80m	N/A
2	NOTEBOOK	2672	992F2VG	N/A	IBM	Unshielded 1.80m	N/A

Note:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.



6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at **No.10-1 Mingkeda Logistics park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China**

The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA	A2LA
China	CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA	FCC
Japan	VCCI(C-3478, R-3135, T-652, G-624)
Canada	INDUSTRY CANADA
Taiwan	BSMI
Norway	Nemko

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>



6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.



7 FCC PART 15.247 REQUIREMENTS

7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

7.1.2. TEST INSTRUMENTS

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2013	03/08/2014
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	04/20/2013	04/19/2014
LISN	EMCO	3825/2	8901-1459	03/09/2013	03/08/2014
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	03/04/2013	03/03/2014
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

- NOTE:**
- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 - 2. N.C.R = No Calibration Request.




7.1.3. TEST PROCEDURES (please refer to measurement standard)

- The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.



7.1.4. TEST SETUP



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.

7.1.5. DATA SAMPLE

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
X.XXXX	32.69	25.65	11.52	44.21	37.17	65.78	55.79	-21.57	-18.62	Pass

- Factor = Insertion loss of LISN + Cable Loss
- Result = Quasi-peak Reading/ Average Reading + Factor
- Limit = Limit stated in standard
- Margin = Result (dBuV) – Limit (dBuV)



7.1.6. TEST RESULTS

Model No.	RT-N12	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 1(S06A22-120A050-PB)
Tested by	Sun Guo	Line	L1

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1580	54.87	36.37	0.48	55.35	36.85	65.56	55.57	-10.21	-18.72	Pass
0.3420	44.87	29.07	0.34	45.21	29.41	59.15	49.15	-13.94	-19.74	Pass
2.2780	38.57	22.84	0.46	39.03	23.30	56.00	46.00	-16.97	-22.70	Pass
3.8900	39.52	24.06	0.50	40.02	24.56	56.00	46.00	-15.98	-21.44	Pass
7.8700	46.70	28.59	0.61	47.31	29.20	60.00	50.00	-12.69	-20.80	Pass
9.4500	46.33	30.69	0.89	47.22	31.58	60.00	50.00	-12.78	-18.42	Pass

Model No.	RT-N12	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 1 (S06A22-120A050-PB)
Tested by	Sun Guo	Line	L2

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1620	54.24	37.33	0.46	54.70	37.79	65.36	55.36	-10.66	-17.57	Pass
0.3420	46.08	35.52	0.54	46.62	36.06	59.15	49.15	-12.53	-13.09	Pass
1.1340	41.37	30.48	0.57	41.94	31.05	56.00	46.00	-14.06	-14.95	Pass
2.1099	42.85	29.42	0.76	43.61	30.18	56.00	46.00	-12.39	-15.82	Pass
4.8140	43.50	29.37	0.46	43.96	29.83	56.00	46.00	-12.04	-16.17	Pass
7.9140	48.66	33.72	0.50	49.16	34.22	60.00	50.00	-10.84	-15.78	Pass

REMARKS: L1 = Line One (Live Line)

L2 = Line Two (Neutral Line)



Model No.	RT-N12	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 2(RD1200500-C55-8MG)
Tested by	Sun Guo	Line	L1

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1500	50.31	36.96	0.52	50.83	37.48	65.99	56.00	-15.16	-18.52	Pass
0.3460	43.81	33.25	0.34	44.15	33.59	59.06	49.06	-14.91	-15.47	Pass
0.6940	35.96	17.23	0.41	36.37	17.64	56.00	46.00	-19.63	-28.36	Pass
1.7900	37.01	20.76	0.44	37.45	21.20	56.00	46.00	-18.55	-24.80	Pass
2.9539	39.99	24.28	0.48	40.47	24.76	56.00	46.00	-15.53	-21.24	Pass
5.8100	34.26	22.56	0.50	34.76	23.06	60.00	50.00	-25.24	-26.94	Pass

Model No.	RT-N12	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 2 (RD1200500-C55-8MG)
Tested by	Sun Guo	Line	L2

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1500	51.27	38.94	0.45	51.72	39.39	65.99	56.00	-14.27	-16.61	Pass
0.1700	48.72	37.53	0.46	49.18	37.99	64.96	54.96	-15.78	-16.97	Pass
0.1980	45.57	33.37	0.49	46.06	33.86	63.69	53.69	-17.63	-19.83	Pass
0.3420	40.73	35.90	0.54	41.27	36.44	59.15	49.15	-17.88	-12.71	Pass
0.7820	33.29	20.76	0.55	33.84	21.31	56.00	46.00	-22.16	-24.69	Pass
3.0780	40.26	26.12	0.65	40.91	26.77	56.00	46.00	-15.09	-19.23	Pass

REMARKS: L1 = Line One (Live Line)

L2 = Line Two (Neutral Line)



7.2. SPURIOUS EMISSIONS MEASUREMENT

7.2.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

§15.247(d) specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

7.2.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	ROHDE&SCHWARZ	FSU	200409	09/23/2013	09/22/2014

7.2.3. TEST PROCEDURE (please refer to measurement standard)

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.


The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.




7.2.4. TEST RESULTS

Test Plot IEEE 802.11b (Antenna 1) mode CH Low (30MHz ~25GHz)



Date: 28.SEP.2013 11:05:54


CH Low



Date: 28.SEP.2013 11:06:27




CH Mid (30MHz ~25GHz)



Date: 28.SEP.2013 11:10:00




CH High (30MHz ~25GHz)



Date: 28.SEP.2013 11:08:04


CH High



Date: 28.SEP.2013 11:08:41




IEEE 802.11g (Antenna 1)mode CH Low (30MHz ~25GHz)



Date: 28.SEP.2013 10:57:38


CH Low



Date: 28.SEP.2013 10:58:10




CH Mid (30MHz ~25GHz)



Date: 28.SEP.2013 11:04:47




CH High (30MHz ~25GHz)



Date: 28.SEP.2013 11:02:28


CH High



Date: 28.SEP.2013 11:03:27




IEEE 802.11n HT20 MHz (Antenna 1) mode CH Low (30MHz ~25GHz)



Date: 28.SEP.2013 10:44:02


CH Low



Date: 28.SEP.2013 10:45:04




CH Mid (30MHz ~25GHz)



Date: 28.SEP.2013 10:46:19




CH High (30MHz ~25GHz)



Date: 28.SEP.2013 10:42:02


CH High



Date: 28.SEP.2013 10:38:27




IEEE 802.11n HT20 MHz (Antenna 2) mode CH Low (30MHz ~25GHz)



Date: 28.SEP.2013 11:22:52


CH Low



Date: 28.SEP.2013 11:23:42




CH Mid (30MHz ~25GHz)



Date: 28.SEP.2013 11:11:55




CH High (30MHz ~25GHz)



Date: 28.SEP.2013 11:24:27


CH High



Date: 28.SEP.2013 11:24:55




IEEE 802.11n HT40 MHz (Antenna 1) mode CH Low (30MHz ~25GHz)



Date: 28.SEP.2013 10:49:50


CH Low



Date: 28.SEP.2013 10:50:26




CH Mid (30MHz ~25GHz)



Date: 28.SEP.2013 10:48:04




CH High (30MHz ~25GHz)



Date: 28.SEP.2013 10:51:46


CH High



Date: 28.SEP.2013 10:52:23




IEEE 802.11n HT40 MHz (Antenna 2) mode CH Low (30MHz ~25GHz)



Date: 28.SEP.2013 11:27:19


CH Low



Date: 28.SEP.2013 11:27:54




CH Mid (30MHz ~25GHz)



Date: 28.SEP.2013 11:26:19




CH High (30MHz ~25GHz)



Date: 28.SEP.2013 11:30:15

CH High



Date: 28.SEP.2013 11:30:56



7.2.4.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

1. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

NOTE:(1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).



7.2.4.2. TEST INSTRUMENTS

Radiated Emission Test Site 966(2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/01/2014	03/01/2015
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2014	03/08/2015
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2015	03/18/2015
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2015	03/18/2015
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	07/10/2014	07/09/2015
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/01/2014	03/01/2015
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/01/2014	03/01/2015
Loop Antenna	A, R, A	PLA-1030/B	1029	09/27/2014	09/26/2015
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/28/2014	02/28/2015
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The FCC Site Registration number is 101879.
 3. N.C.R = No Calibration Required.


7.2.4.3. TEST PROCEDURE (please refer to measurement standard)

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
 Below 1GHz:
 RBW=100kHz / VBW=300kHz / Sweep=AUTO
 Above 1GHz:
 (a) PEAK: RBW=1MHz,VBW=3MHz / Sweep=AUTO
 (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.




7.2.4.4. TEST SETUP

Below 30MHz




Below 1 GHz





Above 1 GHz



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



7.2.4.5. DATA SAPLE

Below 1GHz

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXX.XXXX	36.37	-12.20	24.17	40.00	-15.83	V	QP

Frequency (MHz) = Emission frequency in MHz
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading
 Correct Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)
 Limit (dBuV/m) = Limit stated in standard
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)
 Q.P. = Quasi-peak Reading

Above 1GHz

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXXX.XXXX	62.09	-11.42	50.67	74.00	-23.33	V	Peak
XXXX.XXXX	49.78	-11.42	38.36	54.00	-15.64	V	AVG

Frequency (MHz) = Emission frequency in MHz
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading
 Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)
 Limit (dBuV/m) = Limit stated in standard
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)
 Peak = Peak Reading
 AVG = Average Reading

Calculation Formula

Margin (dB) = Result (dBuV/m) – Limits (dBuV/m)
 Result (dBuV/m) = Reading (dBuV) + Correction Factor



7.2.4.6. TEST RESULTS

Below 1 GHz

Operation Mode: TX

Test Date: September 29, 2014

Temperature: 24°C

Tested by: Sun Guo

Humidity: 52% RH

Polarity: Ver. / Hor.

Table with 8 columns: Frequency (MHz), Reading (dBµV), Correction Factor (dB/m), Result (dBµV/m), Limit (dBµV/m), Margin (dB), Antenna Pole (V/H), Remark. It contains 16 rows of test data.

**Remark: No emission found between lowest internal used/generated frequency to 30MHz.

Notes:

- 1. Radiated emissions measured in frequency range from 9kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
2. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. The IF bandwidth of Receiver between 30MHz to 1GHz was 120kHz.
4. Frequency (MHz). = Emission frequency in MHz
Reading (dBµV/m) = Receiver reading
Correction Factor (dB) = Antenna factor + Cable loss - Amplifier gain
Limit (dBµV/m) = Limit stated in standard
Margin (dB) = Measured (dBµV/m) - Limits (dBµV/m)
Antenna Pol e(H/V) = Current carrying line of reading



Above 1 GHz

Antenna 1

Operation Mode: TX / IEEE 802.11b / CH Low

Test Date: September 29, 2014

Temperature: 24°C

Tested by: Sun Guo

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1999.000	49.26	-8.31	40.95	74.00	-33.05	V	Peak
3214.000	49.16	-3.41	45.75	74.00	-28.25	V	Peak
4825.000	45.73	1.78	47.51	74.00	-26.49	V	Peak
6121.000	41.19	3.91	45.10	74.00	-28.90	V	Peak
7237.000	40.46	8.16	48.62	74.00	-25.38	V	Peak
7759.000	39.82	9.18	49.00	74.00	-25.00	V	Peak
3214.000	43.81	-3.41	40.40	74.00	-33.60	H	Peak
4042.000	41.41	-0.92	40.49	74.00	-33.51	H	Peak
4825.000	42.23	1.78	44.01	74.00	-29.99	H	Peak
5455.000	41.44	2.55	43.99	74.00	-30.01	H	Peak
6985.000	39.83	7.64	47.47	74.00	-26.53	H	Peak
8353.000	40.10	9.46	49.56	74.00	-24.44	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11b / CH Mid

Test Date: September 29, 2014

Temperature: 24°C

Tested by: Sun Guo

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1999.000	50.72	-8.31	42.41	74.00	-31.59	V	peak
3250.000	48.19	-3.34	44.85	74.00	-29.15	V	peak
4870.000	46.40	1.97	48.37	74.00	-25.63	V	peak
6265.000	40.73	4.53	45.26	74.00	-28.74	V	peak
6976.000	39.84	7.60	47.44	74.00	-26.56	V	peak
7912.000	39.66	9.48	49.14	74.00	-24.86	V	peak
2836.000	45.15	-4.59	40.56	74.00	-33.44	H	Peak
4177.000	42.33	-0.52	41.81	74.00	-32.19	H	Peak
5230.000	41.44	2.53	43.97	74.00	-30.03	H	Peak
6391.000	40.09	5.08	45.17	74.00	-28.83	H	Peak
6958.000	40.00	7.52	47.52	74.00	-26.48	H	Peak
7840.000	39.77	9.34	49.11	74.00	-24.89	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11b / CH High

Test Date: September 29, 2014

Temperature: 24°C

Tested by: Sun Guo

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1927.000	49.42	-8.42	41.00	74.00	-33.00	V	peak
2557.000	46.15	-5.93	40.22	74.00	-33.78	V	peak
4276.000	42.64	-0.23	42.41	74.00	-31.59	V	peak
4843.000	41.39	1.86	43.25	74.00	-30.75	V	peak
6013.000	40.34	3.45	43.79	74.00	-30.21	V	peak
7597.000	41.43	8.86	50.29	74.00	-23.71	V	peak
1999.000	49.58	-8.31	41.27	74.00	-32.73	H	Peak
3286.000	46.12	-3.28	42.84	74.00	-31.16	H	Peak
4924.000	44.11	2.19	46.30	74.00	-27.70	H	Peak
6031.000	40.43	3.52	43.95	74.00	-30.05	H	Peak
6886.000	40.35	7.21	47.56	74.00	-26.44	H	Peak
7777.000	39.97	9.22	49.19	74.00	-24.81	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Antenna 1

Operation Mode: TX / IEEE 802.11g / CH Low

Test Date: September 29, 2014

Temperature: 24°C

Tested by: Sun Guo

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1990.000	49.73	-8.32	41.41	74.00	-32.59	V	Peak
3214.000	48.83	-3.41	45.42	74.00	-28.58	V	Peak
4942.000	41.00	2.27	43.27	74.00	-30.73	V	Peak
5986.000	41.73	3.37	45.10	74.00	-28.90	V	Peak
6949.000	40.78	7.48	48.26	74.00	-25.74	V	Peak
7624.000	39.90	8.92	48.82	74.00	-25.18	V	Peak
1999.000	48.36	-8.31	40.05	74.00	-33.95	H	Peak
3214.000	44.77	-3.41	41.36	74.00	-32.64	H	Peak
4231.000	41.72	-0.36	41.36	74.00	-32.64	H	Peak
4933.000	41.85	2.23	44.08	74.00	-29.92	H	Peak
6229.000	40.73	4.38	45.11	74.00	-28.89	H	Peak
7903.000	39.73	9.46	49.19	74.00	-24.81	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH Mid

Test Date: September 29, 2014

Temperature: 24°C

Tested by: Sun Guo

Humidity: 52 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1666.000	50.43	-9.76	40.67	74.00	-33.33	V	Peak
3250.000	47.85	-3.34	44.51	74.00	-29.49	V	Peak
4429.000	41.60	0.22	41.82	74.00	-32.18	V	Peak
4879.000	41.94	2.01	43.95	74.00	-30.05	V	Peak
6985.000	40.52	7.64	48.16	74.00	-25.84	V	Peak
7759.000	40.51	9.18	49.69	74.00	-24.31	V	Peak
1972.000	49.42	-8.35	41.07	74.00	-32.93	H	Peak
3250.000	45.03	-3.34	41.69	74.00	-32.31	H	Peak
3835.000	43.44	-1.65	41.79	74.00	-32.21	H	Peak
5113.000	40.76	2.52	43.28	74.00	-30.72	H	Peak
5824.000	41.73	3.09	44.82	74.00	-29.18	H	Peak
7012.000	40.02	7.72	47.74	74.00	-26.26	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11g / CH High Test Date: September 29, 2014
Temperature: 24°C Tested by: Sun Guo
Humidity: 52 % RH Polarity: Ver. / Hor.

Table with 8 columns: Frequency (MHz), Reading (dBuV), Correction Factor (dB/m), Result (dBuV/m), Limit (dBuV/m), Margin (dB), Antenna Pole (V/H), Remark. It contains two sets of data rows for various frequencies.

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Combine with Antenna 1 and Antenna 2

Operation Mode: TX / IEEE 802.11n HT20 MHz / CH Low Test Date: September 29, 2014

Temperature: 24°C

Tested by: Sun Guo

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1954.000	54.00	-8.38	45.62	74.00	-28.38	V	Peak
3214.000	49.52	-3.41	46.11	74.00	-27.89	V	Peak
4825.000	45.77	1.78	47.55	74.00	-26.45	V	Peak
5815.000	40.71	3.08	43.79	74.00	-30.21	V	Peak
7003.000	40.56	7.71	48.27	74.00	-25.73	V	Peak
8011.000	39.66	9.64	49.30	74.00	-24.70	V	Peak
3214.000	44.69	-3.41	41.28	74.00	-32.72	H	Peak
3907.000	42.37	-1.38	40.99	74.00	-33.01	H	Peak
4618.000	40.95	0.92	41.87	74.00	-32.13	H	Peak
5275.000	40.84	2.53	43.37	74.00	-30.63	H	Peak
6931.000	41.07	7.40	48.47	74.00	-25.53	H	Peak
7930.000	40.04	9.51	49.55	74.00	-24.45	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11n HT20 MHz / CH Mid Test Date: September 29, 2014

Temperature: 24°C Tested by: Sun Guo

Humidity: 52% RH Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1738.000	49.58	-9.14	40.44	74.00	-33.56	V	Peak
2539.000	45.49	-6.01	39.48	74.00	-34.52	V	Peak
3250.000	48.38	-3.34	45.04	74.00	-28.96	V	Peak
4879.000	48.05	2.01	50.06	74.00	-23.94	V	Peak
6832.000	40.48	6.98	47.46	74.00	-26.54	V	Peak
7660.000	40.84	8.99	49.83	74.00	-24.17	V	Peak
1999.000	48.09	-8.31	39.78	74.00	-34.22	H	Peak
3871.000	42.21	-1.52	40.69	74.00	-33.31	H	Peak
4870.000	42.82	1.97	44.79	74.00	-29.21	H	Peak
6832.000	39.91	6.98	46.89	74.00	-27.11	H	Peak
7570.000	39.16	8.81	47.97	74.00	-26.03	H	Peak
7876.000	40.42	9.41	49.83	74.00	-24.17	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11n HT20 MHz / CH High Test Date: September 29, 2014

Temperature: 24°C

Tested by: Sun Guo

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1666.000	50.43	-9.76	40.67	74.00	-33.33	V	Peak
1999.000	50.16	-8.31	41.85	74.00	-32.15	V	Peak
2989.000	45.42	-3.85	41.57	74.00	-32.43	V	Peak
3286.000	45.75	-3.28	42.47	74.00	-31.53	V	Peak
4924.000	46.03	2.19	48.22	74.00	-25.78	V	Peak
6958.000	39.32	7.52	46.84	74.00	-27.16	V	Peak
1909.000	49.50	-8.45	41.05	74.00	-32.95	H	Peak
3439.000	42.74	-3.00	39.74	74.00	-34.26	H	Peak
4240.000	42.39	-0.33	42.06	74.00	-31.94	H	Peak
4924.000	41.85	2.19	44.04	74.00	-29.96	H	Peak
6868.000	40.19	7.13	47.32	74.00	-26.68	H	Peak
7543.000	40.05	8.76	48.81	74.00	-25.19	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Combine with Antenna 1 and Antenna 2

Operation Mode: TX / IEEE 802.11n HT40 MHz / CH Low Test Date: September 29, 2014

Temperature: 24°C

Tested by: Sun Guo

Humidity: 52% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
3232.000	47.70	-3.38	44.32	74.00	-29.68	V	Peak
4942.000	41.32	2.27	43.59	74.00	-30.41	V	Peak
5275.000	41.18	2.53	43.71	74.00	-30.29	V	Peak
6859.000	40.83	7.09	47.92	74.00	-26.08	V	Peak
7561.000	39.95	8.79	48.74	74.00	-25.26	V	Peak
8353.000	40.22	9.46	49.68	74.00	-24.32	V	Peak
1999.000	47.72	-8.31	39.41	74.00	-34.59	H	Peak
3178.000	43.39	-3.48	39.91	74.00	-34.09	H	Peak
5041.000	40.54	2.51	43.05	74.00	-30.95	H	Peak
6148.000	40.59	4.03	44.62	74.00	-29.38	H	Peak
7498.000	39.32	8.67	47.99	74.00	-26.01	H	Peak
7750.000	40.26	9.16	49.42	74.00	-24.58	H	Peak

REMARKS:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).