

## RF Exposure Evaluation declaration

Product Name : 3G MOBILE Wireless Router  
Model No. : WL-330N3G  
FCC ID. : MSQ-WL330N3G

Applicant : ASUSTeK COMPUTER INC.

Address : No.150 Li-Te Rd., Peitou, Taipei, Taiwan

Date of Receipt : 2010/06/04  
Date of Declaration : 2010/10/12  
Report No. : 106118R-RF-US-Exp  
Report Version : V2.0

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product	3G MOBILE Wireless Router
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.6dBi or 1.82 in linear scale.

#### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	262.4219	0.09502
6	2437	206.0630	0.07461
11	2462	165.1962	0.05981

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	618.0164	0.22377
6	2437	582.1032	0.21077
11	2462	559.7576	0.20268

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	3G MOBILE Wireless Router
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.6dBi or 1.82 in linear scale. IEEE 802.11n (20M)

### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (20MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	439.5416	0.15915
6	2437	534.5644	0.19355
11	2462	475.3352	0.17211

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	3G MOBILE Wireless Router
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.6dBi or 1.82 in linear scale. IEEE 802.11n (40M)

### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (40M)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
3	2422	567.5446	0.20549
6	2437	527.2299	0.19090
9	2452	400.8667	0.14514

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

## 1.4. Test result of RF Exposure Evaluation (Collocation Mode)

For collocation mode is simulation when EUT insert WWAN card and use maximum output power for this RF Exposure Evaluation.

### WWAN:

#### Output Power into Antenna & RF Exposure Evaluation Distance:

Frequency band	ERP (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (f/1500mW/cm <sup>2</sup> )
850	1500	0.298416	0.5666

Frequency band	EIRP (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
1900	2000	0.397888	1

#### Result of Collocation Evaluation:

Frequency band	$\frac{(Pd \text{ of WWAN})}{(Pd \text{ WWAN limit})} + \frac{(Pd \text{ of WLAN})}{(Pd \text{ WLAN limit})}$	Limit
850(WWAN)+2412(802.11g)	$(0.298416/0.5666) + (0.22377/1) = 0.75045$	<1
1900(WWAN)+2412(802.11g)	$(0.397888/1) + (0.22377/1) = 0.621658$	<1