N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Right_Low_CH



N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Right_Low_CH_**CHP_PASS**



N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Right_Low_CH

N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Right_Low_CH_**CHP_PASS**

N48(40M)_DFT-s-OFDM_BPSK_Outer_Full_Low_CH



N48(40M)_DFT-s-OFDM_BPSK_Outer_Full_Low_CH_**CHP_PASS**



N48(40M)_DFT-s-OFDM_QPSK_Outer_Full_Low_CH



N48(40M)_DFT-s-OFDM_QPSK_Outer_Full_Low_CH_**CHP_PASS**



N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Mid_CH



N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Mid_CH_**CHP_PASS**

N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH



N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH_**CHP_PASS**

N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Right_Mid_CH

N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Right_Mid_CH_**CHP**_**PASS**



N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Right_Mid_CH



N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Right_Mid_CH_**CHP**_**PASS**

N48(40M)_DFT-s-OFDM_BPSK_Outer_Full_Mid_CH



N48(40M)_DFT-s-OFDM_QPSK_Outer_Full_Mid_CH



N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_High_CH



N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_High_CH_CHP_PASS



N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_High_CH

N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_High_CH_CHP_PASS

N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Right_High_CH



N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Right_High_CH_CHP_PASS



N48(40M)_DFT-s-OFDM_BPSK_Edge_1RB_Right_High_CH_CHP_PASS



N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Right_High_CH



N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Right_High_CH_CHP_PASS

N48(40M)_DFT-s-OFDM_QPSK_Edge_1RB_Right_High_CH_CHP_PASS



N48(40M)_DFT-s-OFDM_BPSK_Outer_Full_High_CH



N48(40M)_DFT-s-OFDM_BPSK_Outer_Full_High_CH_CHP_PASS



N48(40M)_DFT-s-OFDM_QPSK_Outer_Full_High_CH



Note “CHP” means channel power integration method.

Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Qingsheng He	Temperature :	22~25℃
		Relative Humidity :	48~52%

Note: Pre-scanned harmonic for the different antennas, we choose the worst antenna mode to perform final test and record in the report.

SA n48 / 40MHz / QPSK / ANT8									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	7212.80	-59.64	-40	-19.64	-56.26	-62.94	8.30	11.60	H
	10819.20	-53.75	-40	-13.75	-56.71	-55.27	10.48	12.00	H
	14425.60	-50.10	-40	-10.10	-57.36	-51.80	11.80	13.50	H
	7212.80	-59.54	-40	-19.54	-56.2	-62.84	8.30	11.60	V
	10819.20	-54.23	-40	-14.23	-56.96	-55.75	10.48	12.00	V
	14425.60	-50.18	-40	-10.18	-57.22	-51.88	11.80	13.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.