

RF Exposure report



The following samples were submitted and identified on behalf of the client as:

EUT Description	WLAN and BT, 2x2 PCIe M.2 1216 SD adapter card
Brand Name	Intel® Wi-Fi 6E AX211
Model Name	AX211D2W
Applicant	ASUSTeK COMPUTER INC. 1F., No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan
Standards	IEEE/ANSI C95.1-1992, IEEE 1528-2013
FCC ID	MSQAX211D2
Date of EUT Receipt	Aug. 29, 2022
Date of Test(s)	Sep. 08, 2022 ~ Sep. 20, 2022, Oct. 20, 2022
Date of Issue	Nov. 24, 2022

In the configuration tested, the EUT complied with the standards specified above.

Remarks:

This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS Taiwan Ltd. Central RF Lab or testing done by SGS Taiwan Ltd. Central RF Lab in connection with distribution or use of the product described in this report must be approved by SGS Taiwan Ltd. Central RF Lab in writing.

Signed on behalf of SGS

Clerk / Kimmy Chiou	PM / Afu Chen	Approved By / John Yeh

Date: Nov. 24, 2022

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

Contents

1	GENERAL INFORMATION	5
1.1	Test Methodology	5
1.2	Description of EUT.....	6
1.3	Maximum value	7
1.4	Antenna Information.....	7
2	MEASUREMENT SYSTEM	8
2.1	Test Facility	8
2.2	SAR System.....	9
2.3	PD system	13
3	SAR SYSTEM VERIFICATION.....	15
3.1	Tissue Simulating Liquid.....	15
3.2	Tissue Simulant Liquid measurement.....	15
3.3	Measurement results of Tissue Simulant Liquid.....	16
3.4	The composition of the tissue simulating liquid:.....	18
3.5	System check	18
3.6	System check results	19
4	PD SYSTEM VERIFICATION	20
4.1	System check	20
4.2	System check result	21
5	TEST CONFIGURATIONS	22
5.1	Test Environment.....	22
5.2	Test Note.....	22
5.3	Test position.....	24
5.4	Power verification of device mode	26
5.5	Test limit	31
6	Maximum OUTPUT POWER	34
6.1	WLAN	34
6.2	WIFI 6E.....	46
6.3	Bluetooth	54
6.4	BLE.....	54
7	DUTY CYCLE	55
8	SUMMARY OF RESULTS	60
8.1	Decision rules	60
8.2	Summary of SAR Results.....	61
8.3	Summary of PD Results	65
8.4	Reporting statements of conformity	66
8.5	Conclusion	66
9	SIMULTANEOUS TRANSMISSION ANALYSIS.....	67
9.1	Simultaneous Transmission Scenarios:	67
9.2	Estimated SAR calculation.....	68
9.3	SPLSR evaluation and analysis.....	68
9.4	Conclusion	69
10	INSTRUMENTS LIST.....	70
11	UNCERTAINTY BUDGET.....	71

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

12	SAR MEASUREMENT results	75
13	PD measurement result	109
14	SAR SYSTEM check results	125
15	pd system check result.....	138
16	APPENDIXES	140
16.1	SAR_Appendix A Photographs	140
16.2	SAR_Appendix B DAE & Probe Cal. Certificate	140
16.3	SAR_Appendix C Phantom Description & Dipole Cal. Certificate	140

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. | No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

1 GENERAL INFORMATION

1.1 Test Methodology

The SAR testing method and procedure for this device is in accordance with the following standards:

IEEE/ANSI C95.1-1992

IEEE 1528-2013

KDB447498D01v06

KDB865664D01v01r04

KDB865664D02v01r02

KDB616217D04v01r02

KDB248227D01v02r01

IEC/IEEE 62209-1528:2020

SPEAG DASY6 System Handbook

SPEAG DASY6 Application Note (Interim Procedure for Device Operation at 6GHz-10GHz)

IEC TR 63170:2018

IEC 62479:2010

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

1.2 Description of EUT

EUT Description	WLAN and BT, 2x2 PCIe M.2 1216 SD adapter card	
Brand Name	Intel® Wi-Fi 6E AX211	
Model Name	AX211D2W	
FCC ID	MSQAX211D2	
Host Information	Product Type: Notebook PC Trade Name: ASUS Model Name: GZ301V, GZ301VI, GZ301VV, GZ301VU, GZ301VJ, GZ301VF All models are electrically identical, different model names are for marketing purpose.	
Mode	WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE	
Duty Cycle	WLAN802.11	Please refer to page 55-58
	Bluetooth	Please refer to page 55
Supported radios (TX Frequency Range, MHz)	802.11 b/g/n/ax	2.4GHz (2400.0 – 2483.5 MHz)
	802.11a/n/ac/ax	5.2GHz (5150.0 – 5350.0 MHz) 5.6GHz (5470.0 – 5725.0 MHz) 5.8GHz (5725.0 – 5850.0 MHz)
	802.11ax	6.0GHz (5925.0 – 7125.0)
	Bluetooth 5.2	2.4GHz (2400.0 – 2483.5 MHz)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

1.3 Maximum value

Summary of Maximum SAR and Power Density Value			
Mode	Highest SAR 1g Body (W/kg)	Highest APD (W/m ²)	Highest PD (W/m ²)
Bluetooth(GFSK)	0.35	N/A	N/A
2.4G WLAN	0.71	N/A	N/A
5.2G WLAN	0.39	N/A	N/A
5.6G WLAN	0.45	N/A	N/A
5.8G WLAN	0.31	N/A	N/A
6G WLAN	0.98	5.07	4.14

1.4 Antenna Information

Tablet mode WLAN Frist																		
Vendor	Main									Aux								
Antenna	LA9RF399-CS-H									LA9RF400-CS-H								
Part Number	2400-2500	5150-5250	5250-5350	5470-5725	5725-5850	5925-6425	6425-6525	6525-6875	6875-7125	2400-2500	5150-5250	5250-5350	5470-5725	5725-5850	5925-6425	6425-6525	6525-6875	6875-7125
Frequency(MHz)	2.56	3.64	3.64	4.59	3.12	4.33	3.90	3.90	3.90	-0.33	2.24	1.48	3.55	4.5	4.35	3.90	3.90	3.90
Gain (dBi)	2.56	3.64	3.64	4.59	3.12	4.33	3.90	3.90	3.90	-0.33	2.24	1.48	3.55	4.5	4.35	3.90	3.90	3.90

Tablet mode WLAN Second																		
Vendor	Main									Aux								
Antenna	MDA-LE-02-013									MDA-LE-01-005								
Part Number	2400-2500	5150-5250	5250-5350	5470-5725	5725-5850	5925-6425	6425-6525	6525-6875	6875-7125	2400-2500	5150-5250	5250-5350	5470-5725	5725-5850	5925-6425	6425-6525	6525-6875	6875-7125
Frequency(MHz)	2.48	3.51	2.76	4.21	2.52	4.01	3.80	3.83	2.95	-0.74	1.55	0.64	3.55	3.66	3.61	3.72	3.38	3.87
Gain (dBi)	2.48	3.51	2.76	4.21	2.52	4.01	3.80	3.83	2.95	-0.74	1.55	0.64	3.55	3.66	3.61	3.72	3.38	3.87

Note: Antenna information is provided by the applicant.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

2 MEASUREMENT SYSTEM

2.1 Test Facility

Laboratory	Test Site Address	Test Site Name	FCC Designation number	IC CAB identifier
SGS Taiwan Ltd. Central RF Lab. (TAF code 3702)	1F, No. 8, Alley 15, Lane 120, Sec. 1, NeiHu Road, NeiHu District, Taipei City, 11493, Taiwan.	SAR 2	TW0029	TW3702
		SAR 6		
	No. 2, Keji 1st Rd., Guishan Township, Taoyuan County, 33383, Taiwan	SAR 1	TW0028	
		SAR 4		
	No.134, Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan	SAR 3	TW0027	
		SAR 7		

Note: Test site name is remarked on the equipment list in each section of this report as an indication where measurements occurred in specific test site and address.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. | No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

Block Diagram (DASY6)

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Windows 10 and the DASY6 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

EX3DV4 E-Field Probe

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Calibration	Basic Broad Band Calibration in air Conversion Factors (CF) for HSL 2450/5250/5600/5750/6500/7000 MHz Additional CF for other liquids and frequencies upon request	
Frequency	10 MHz to > 6 GHz	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 µW/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 µW/g)	
Dimensions	Tip diameter: 2.5 mm	
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

PHANTOM (ELI)

Model	ELI	
Construction	The ELI phantom is used for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Shell Thickness	2 ± 0.2 mm	
Filling Volume	Approx. 30 liters	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	

DEVICE HOLDER (ELI)

Construction	The device holder (Supporter) for Notebook is made by POM (polyoxymethylene resin), which is non-metal and non-conductive. The height can be adjusted to fit varies kind of notebooks.	 <p style="text-align: center;">Device Holder</p>
--------------	--	---

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

2.3 PD system


Block Diagram (DASY6)

Power density measurements for mmWave frequencies were performed using SPEAG DASY6 with cDASY6 5G module. The DASY6 included a high precision robotics system (Staubli), robot controller, desktop computer, near-field probe, probe alignment sensor, and the 5G phantom cover.



EUmmWVx probe

The EUmmWVx probe is based on the pseudo-vector probe design, which not only measures the field magnitude but also derives its polarization ellipse. The design entails two small 0.8mm dipole sensors mechanically protected by high-density foam, printed on both sides of a 0.9mm wide and 0.12mm thick glass substrate. The body of the probe is specifically constructed to minimize distortion by the scattered fields. The probe consist of two sensors with different angles (1 and 2) arranged in the same plane in the probe axis. Three or more measurements of the two sensors are taken for different probe rotational angles to derive the amplitude and polarization information. The probe design allows measurements at distances as small as 2mm from the sensors to the surface of the device under test (DUT). The typical sensor to probe tip distance is 1.5 mm. The exact distance is calibrated.




Two dipoles optimally arranged to obtain pseudo-vector information. Minimum 3 measurements/point, 120° rotated around probe axis. Sensors (0.8mm length) printed on glass substrate protected by high density foam. Low perturbation of the measured field. Requires positioner which can do accurate probe rotation.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Frequency Range	750 MHz – 110 GHz
Dynamic Range	< 20 V/m – 10,000 V/m with PRE-10 (min < 50 V/m - 3000 V/m)
Position Precision	< 0.2 mm (DASY6)
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: encapsulation 8 mm (internal sensor < 1mm) Distance from probe tip to dipole centers: < 2 mm. Sensor displacement to probe's calibration point: < 0.3 mm
Applications	E-field measurements of 5G devices and other mm-wave transmitters operating above 10GHz in < 2 mm distance from device (free-space). Power density, H-field and far-field analysis using total field reconstruction (cDASY6 5G module required)
Compatibility	cDASY6 + 5G-Module SW1.0 and higher



mmWave Phantom

The mmWave Phantom approximates free-space conditions, allowing for the evaluation of the antenna side of the device and the front (screen) side or any opposite-radiating side of wireless devices operating above 10 GHz without distorting the RF field. It consists of a 40mm thick Rohacell plate used as a test bed, which has a loss tangent ($\tan \delta$) ≤ 0.05 and a relative permittivity (ϵ_r) ≤ 1.2 . High-performance RF absorbers are placed below the foam.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

3 SAR SYSTEM VERIFICATION

3.1 Tissue Simulating Liquid

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with homogeneous tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15cm.

3.2 Tissue Simulant Liquid measurement

The dielectric properties for this Head-simulant fluid were measured by using the SPEAG Dielectric Assessment Kit (DAKS-3.5)

All dielectric parameters of tissue simulates were measured within 24 hours of SAR measurements. The measured conductivity and permittivity are all within $\pm 5\%$ of the target values.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

3.3 Measurement results of Tissue Simulant Liquid

ASAP

Measured Frequency (MHz)	Liquid Temp. (°C)	Target Dielectric Constant, ϵ_r	Target Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ_r	Measured Conductivity, σ (S/m)	% dev ϵ_r	% dev σ	Limit	Measurement Date
2412	22.6°C	39.265	1.766	39.689	1.783	1.08%	0.94%	± 5%	Sep. 08, 2022
2437	22.6°C	39.222	1.788	39.638	1.804	1.06%	0.87%	± 5%	Sep. 08, 2022
2450	22.6°C	39.200	1.800	39.619	1.816	1.07%	0.89%	± 5%	Sep. 08, 2022
2462	22.6°C	39.184	1.813	39.603	1.829	1.07%	0.89%	± 5%	Sep. 08, 2022
2480	22.6°C	39.160	1.832	39.583	1.849	1.08%	0.93%	± 5%	Sep. 08, 2022
5210	22.8°C	35.990	4.670	36.339	4.699	0.97%	0.62%	± 5%	Sep. 10, 2022
5250	22.8°C	35.950	4.710	36.295	4.739	0.96%	0.62%	± 5%	Sep. 10, 2022
5270	22.8°C	35.930	4.730	36.287	4.757	0.99%	0.57%	± 5%	Sep. 10, 2022
5300	22.8°C	35.900	4.760	36.258	4.787	1.00%	0.57%	± 5%	Sep. 10, 2022
5310	22.8°C	35.890	4.770	36.249	4.800	1.00%	0.63%	± 5%	Sep. 10, 2022
5530	22.9°C	35.605	4.997	35.961	5.026	1.00%	0.59%	± 5%	Sep. 11, 2022
5570	22.9°C	35.545	5.039	35.886	5.069	0.96%	0.61%	± 5%	Sep. 11, 2022
5600	22.9°C	35.500	5.070	35.866	5.103	1.03%	0.65%	± 5%	Sep. 11, 2022
5610	22.9°C	35.490	5.080	35.845	5.110	1.00%	0.59%	± 5%	Sep. 11, 2022
5690	22.9°C	35.410	5.160	35.753	5.190	0.97%	0.58%	± 5%	Sep. 11, 2022
5750	22.6°C	35.350	5.220	35.686	5.250	0.95%	0.57%	± 5%	Sep. 12, 2022
5775	22.6°C	35.325	5.245	35.676	5.278	0.99%	0.63%	± 5%	Sep. 12, 2022
5795	22.6°C	35.305	5.265	35.587	5.294	0.80%	0.55%	± 5%	Sep. 12, 2022
6025	22.8°C	35.070	5.510	35.487	5.554	1.19%	0.81%	± 5%	Sep. 13, 2022
6345	22.8°C	34.686	5.887	35.085	5.937	1.15%	0.85%	± 5%	Sep. 13, 2022
6500	22.8°C	34.500	6.070	34.904	6.120	1.17%	0.82%	± 5%	Sep. 13, 2022
6505	22.8°C	34.494	6.076	34.891	6.122	1.15%	0.76%	± 5%	Sep. 13, 2022
6825	22.8°C	34.110	6.447	34.506	6.499	1.16%	0.81%	± 5%	Sep. 13, 2022
6985	22.7°C	33.918	6.633	34.315	6.689	1.17%	0.85%	± 5%	Sep. 13, 2022
7000	22.7°C	33.900	6.650	34.307	6.703	1.20%	0.80%	± 5%	Sep. 13, 2022

Measured Frequency (MHz)	Liquid Temp. (°C)	Target Dielectric Constant, ϵ_r	Target Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ_r	Measured Conductivity, σ (S/m)	% dev ϵ_r	% dev σ	Limit	Measurement Date
6500	22.4°C	34.500	6.070	34.916	6.140	1.21%	1.15%	± 5%	Oct. 20, 2022
6505	22.4°C	34.494	6.076	35.012	6.144	1.50%	1.12%	± 5%	Oct. 20, 2022

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

INPAQ

Measured Frequency (MHz)	Liquid Temp. (°C)	Target Dielectric Constant, ϵ_r	Target Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ_r	Measured Conductivity, σ (S/m)	% dev ϵ_r	% dev σ	Limit	Measurement Date
2412	22.6°C	39.265	1.766	39.693	1.782	1.09%	0.89%	± 5%	Sep. 15, 2022
2437	22.6°C	39.222	1.788	39.673	1.805	1.15%	0.92%	± 5%	Sep. 15, 2022
2450	22.6°C	39.200	1.800	39.642	1.816	1.13%	0.89%	± 5%	Sep. 15, 2022
2462	22.6°C	39.184	1.813	39.631	1.829	1.14%	0.89%	± 5%	Sep. 15, 2022
2480	22.6°C	39.160	1.832	39.583	1.849	1.08%	0.93%	± 5%	Sep. 15, 2022
5210	22.6°C	35.990	4.670	36.336	4.698	0.96%	0.60%	± 5%	Sep. 16, 2022
5250	22.6°C	35.950	4.710	36.315	4.738	1.02%	0.59%	± 5%	Sep. 16, 2022
5270	22.6°C	35.930	4.730	36.307	4.756	1.05%	0.55%	± 5%	Sep. 16, 2022
5300	22.6°C	35.900	4.760	36.266	4.789	1.02%	0.61%	± 5%	Sep. 16, 2022
5310	22.6°C	35.890	4.770	36.260	4.801	1.03%	0.65%	± 5%	Sep. 16, 2022
5530	22.9°C	35.605	4.997	35.965	5.024	1.01%	0.55%	± 5%	Sep. 17, 2022
5570	22.9°C	35.545	5.039	35.900	5.068	1.00%	0.59%	± 5%	Sep. 17, 2022
5600	22.9°C	35.500	5.070	35.855	5.099	1.00%	0.57%	± 5%	Sep. 17, 2022
5610	22.9°C	35.490	5.080	35.838	5.111	0.98%	0.61%	± 5%	Sep. 17, 2022
5690	22.9°C	35.410	5.160	35.757	5.190	0.98%	0.58%	± 5%	Sep. 17, 2022
5750	22.4°C	35.350	5.220	35.718	5.254	1.04%	0.65%	± 5%	Sep. 18, 2022
5775	22.4°C	35.325	5.245	35.664	5.276	0.96%	0.59%	± 5%	Sep. 18, 2022
5795	22.4°C	35.305	5.265	35.554	5.311	0.71%	0.87%	± 5%	Sep. 18, 2022
6025	22.7°C	35.070	5.510	35.487	5.554	1.19%	0.81%	± 5%	Sep. 14, 2022
6345	22.7°C	34.686	5.887	35.095	5.931	1.18%	0.75%	± 5%	Sep. 14, 2022
6500	22.7°C	34.500	6.070	34.931	6.120	1.25%	0.82%	± 5%	Sep. 14, 2022
6505	22.7°C	34.494	6.076	34.922	6.123	1.24%	0.78%	± 5%	Sep. 14, 2022
6825	22.7°C	34.110	6.447	34.516	6.501	1.19%	0.84%	± 5%	Sep. 14, 2022
6985	22.5°C	33.918	6.633	34.322	6.689	1.19%	0.85%	± 5%	Sep. 14, 2022
7000	22.5°C	33.900	6.650	34.314	6.705	1.22%	0.83%	± 5%	Sep. 14, 2022

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

3.4 The composition of the tissue simulating liquid:

Simulating Liquids for 600 MHz -10 GHz, Manufactured by SPEAG:


Broad-band head tissue simulating liquids	SPEAG Product	Frequency range (MHz)	Main Ingredients
	HBBL600-10000V6	600 - 10000	Water, Oil

3.5 System check

The microwave circuit arrangement for system check is sketched in below. The daily system accuracy verification occurs within the flat section of the SAM phantom and ELI phantom. A SAR measurement was performed to see if the measured SAR was within +/- 10% from the target SAR values.

The tests were conducted on the same days as the measurement of the DUT. The obtained results from the system accuracy verification are displayed with SAR values normalized to 1W forward power delivered to the dipole.

During the tests, the liquid depth from the center of the flat phantom to the liquid top surface was 15 cm above in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



The block diagram of system check

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

3.6 System check results

ASAP

Validation Kit	S/N	Frequency (MHz)	1W Target 1g-SAR (W/kg)	pin=250mW Measured 1g-SAR (W/kg)	Normalized to 1W 1g-SAR (W/kg)	Deviation (%)	Limit	Measurement Date
D2450V2	727	2450	52.8	14.1	56.4	6.82	± 10%	Sep.08,2022

Validation Kit	S/N	Frequency (MHz)	1W Target 1g-SAR (W/kg)	pin=100mW Measured 1g-SAR (W/kg)	Normalized to 1W 1g-SAR (W/kg)	Deviation (%)	Limit	Measurement Date
D5GHzV2	1023	5250	81	8.35	83.5	3.09	± 10%	Sep.10,2022
D5GHzV2	1023	5600	84.4	8.47	84.7	0.36	± 10%	Sep.11,2022
D5GHzV2	1023	5750	81	8.41	84.1	3.83	± 10%	Sep.12,2022

Validation Kit	S/N	Frequency (MHz)	1W Target 1g-SAR (W/kg)	pin=100mW Measured 1g-SAR (W/kg)	Normalized to 1W 1g-SAR (W/kg)	Deviation (%)	Limit	Measurement Date
D6.5GHzV2	1006	6500	292	30.1	301	3.08	± 10%	Sep.13,2022
D7GHzV2	1007	7000	278	26.4	264	-5.04	± 10%	Sep.13,2022

Validation Kit	S/N	Frequency (MHz)	1W Target 1g-SAR (W/kg)	pin=100mW Measured 1g-SAR (W/kg)	Normalized to 1W 1g-SAR (W/kg)	Deviation (%)	Limit	Measurement Date
D6.5GHzV2	1006	6500	292	30.9	309	5.82	± 10%	Oct.20,2022

INPAQ

Validation Kit	S/N	Frequency (MHz)	1W Target 1g-SAR (W/kg)	pin=250mW Measured 1g-SAR (W/kg)	Normalized to 1W 1g-SAR (W/kg)	Deviation (%)	Limit	Measurement Date
D2450V2	727	2450	52.8	14	56	6.06	± 10%	Sep.15,2022

Validation Kit	S/N	Frequency (MHz)	1W Target 1g-SAR (W/kg)	pin=100mW Measured 1g-SAR (W/kg)	Normalized to 1W 1g-SAR (W/kg)	Deviation (%)	Limit	Measurement Date
D5GHzV2	1023	5250	81	8.35	83.5	3.09	± 10%	Sep.16,2022
D5GHzV2	1023	5600	84.4	8.44	84.4	0.00	± 10%	Sep.17,2022
D5GHzV2	1023	5750	81	8.22	82.2	1.48	± 10%	Sep.18,2022

Validation Kit	S/N	Frequency (MHz)	1W Target 1g-SAR (W/kg)	pin=100mW Measured 1g-SAR (W/kg)	Normalized to 1W 1g-SAR (W/kg)	Deviation (%)	Limit	Measurement Date
D6.5GHzV2	1006	6500	292	30.2	302	3.42	± 10%	Sep.14,2022
D7GHzV2	1007	7000	278	26.3	263	-5.40	± 10%	Sep.14,2022

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

4 PD SYSTEM VERIFICATION

4.1 System check

The system was verified to be within ± 0.66 dB of the power density targets on the calibration certificate according to the test system specification in the user's manual and calibration facility recommendation. The 0.66 dB deviation threshold represents the expanded uncertainty for system performance checks using SPEAG's mmWave verification sources. The same spatial resolution and measurement region used in the source calibration was applied during the system check.

The measured power density distribution of verification source was also confirmed through visual inspection to have no noticeable differences, both spatially (shape) and numerically (level) from the distribution provided by the manufacturer, per November 2017 TCBC Workshop Notes.



System Verification Setup Photo

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

4.2 System check result

The system was verified to be within ± 0.66 dB of the power density targets on the calibration certificate according to the test system specification in the user's manual and calibration facility recommendation. The 0.66 dB deviation threshold represents the expanded uncertainty for system performance checks using SPEAG's mmWave verification sources. The same spatial resolution and measurement region used in the source calibration was applied during the system check. The measured power density distribution of verification source was also confirmed through visual inspection to have no noticeable differences, both spatially (shape) and numerically (level) from the distribution provided by the manufacturer, per November 2017 TCBC Workshop Notes.

ASAP

Frequency (MHz)	PD Verification Source (MHz)	Probe S/N	DAE S/N	Distance (mm)	Prad (mW)	Measured 4cm ² (W/m ²)	Target 4cm ² (W/m ²)	Deviation (dB)	Date
10000	10000	9399	1665	10	86.1	51.1	51.7	-0.05	Sep.19,2022

INPAQ

Frequency (MHz)	PD Verification Source (MHz)	Probe S/N	DAE S/N	Distance (mm)	Prad (mW)	Measured 4cm ² (W/m ²)	Target 4cm ² (W/m ²)	Deviation (dB)	Date
10000	10000	9399	1665	10	86.1	51.4	51.7	-0.03	Sep.20,2022

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

5 TEST CONFIGURATIONS

5.1 Test Environment

Ambient Temperature: $22\pm 2^{\circ}\text{C}$

Tissue Simulating Liquid: $22\pm 2^{\circ}\text{C}$

5.2 Test Note

- **General:** Measurements are performed respectively on the lowest, middle and highest channels of the operating band(s).
- **General:** The EUT is set to maximum power level during all tests, and at the beginning of each test the battery is fully charged.
- **General:** During the SAR testing, the DASY system checks power drift by comparing the e-field strength of one specific location measured at the beginning with that measured at the end of the SAR testing.
- **General:** According to KDB447498D01v06, testing of other required channels is not required when the reported 1-g SAR for the highest output channel is $\leq 0.8\text{ W/kg}$, when the transmission band is $\leq 100\text{ MHz}$.
- **General:** According to KDB865664D01v01r04, SAR measurement variability must be assessed for each frequency band. When the original highest measured SAR is $\geq 0.8\text{ W/kg}$, repeated that measurement once. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45\text{ W/kg}$ ($\sim 10\%$ from the 1-g SAR limit).
- **WLAN 2.4GHz:** 802.11b DSSS SAR Test Requirements: SAR is measured for 2.4 GHz 802.11b DSSS mode using the highest measured maximum output power channel, when the reported SAR of the highest measured maximum output power channel for the exposure configuration is $\leq 0.8\text{ W/kg}$, no further SAR testing is required for 802.11b DSSS in that exposure configuration. When the reported SAR is $> 0.8\text{ W/kg}$, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is $> 1.2\text{ W/kg}$, SAR is required for the third channel; i.e., all channels require testing.
- **WLAN 2.4GHz:** 802.11g/n OFDM SAR Test Exclusion Requirements: SAR is not required for 802.11g/n since the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2\text{ W/kg}$.
- **WLAN 5GHz:** Initial Test Configuration: An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. When the reported SAR of the initial test configuration is $> 0.8\text{ W/kg}$, SAR measurement is required for the subsequent next highest measured output power channel(s) in the initial test configuration until the reported SAR is $\leq 1.2\text{ W/kg}$ or all required channels are tested. Since the highest reported SAR for the initial test configuration is adjusted by the ratio of the subsequent test configuration to initial test configuration

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for subsequent test configuration.

- **WLAN 5GHz:** Based on FCC guidance, general principles of KDB248227D01 can be applied to 802.11ax to determine initial test configuration with 802.11ax being considered as the highest 802.11 mode for the appropriate frequency band.
- **WLAN 6GHz:** Per October 2020 & April 2021 TCB Workshop Interim procedures and FCC guidance, start instead with a minimum of 5 test channels across the full band, then adapt and apply conducted power and SAR test reduction procedures of KDB Pub. 248227 v02r02. WIFI 6E SAR is measured by using 6-7GHz parameters per IEC/IEEE62209- 1528:2020 and report also estimated absorbed PD (for reference purposes only, not specifically for compliance). For the highest SAR test configurations also measure incident PD (total) using mmW near-field probe and total-field/power-density reconstruction method.
- **WLAN 6GHz:** Per equipment manufacturer guidance, power density was measured at $d=2$ mm with the grid step (0.0625λ) for determining compliance at $d=2$ mm.
- **WLAN 6GHz:** According to October 2020 TCB Workshop Interim procedures, power density results were scaled according to IEC 62479:2010 for the portion of the measurement uncertainty $> 30\%$. Total expanded uncertainty of 2.67 dB (85%) was used to determine the psPD measurement scaling factor.
- **WLAN 6GHz:** Per FCC guidance, for simultaneous transmission evaluation, using SAR sum and SPLSR for simultaneous transmit exclusion analyses and evaluations.
- **General:** The device was tested based on FCC guidance.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. | No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

5.3 Test position

Laptop mode SAR test position (0mm)

For laptop PC, according to KDB 616217 D04, SAR evaluation is required for the bottom surface of the keyboard. This EUT was tested in the base of EUT directly against the flat phantom. The required minimum test separation distance for incorporating transmitters and antennas into laptop computer display is determined with the display screen opened at an angle of 90° to the keyboard compartment. SAR measurement for laptop mode is not required because the antenna to user distance is larger than 20cm.




Illustration for Laptop Setup

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

Tablet mode SAR test position (0mm)

For full-size tablet, according to KDB 616217 D04, SAR evaluation is required for back surface and edges of the devices. The back surface and edges of the tablet are tested with the tablet touching the phantom. Exposures from antennas through the front surface of the display section of a tablet are generally limited to the user’s hands. Exposures to hands for typical consumer transmitters used in tablets are not expected to exceed the extremity SAR limit; therefore, SAR evaluation for the front surface of tablet display screens are generally not necessary. When voice mode is supported on a tablet and it is limited to speaker mode or headset operations only, additional SAR testing for this type of voice use is not required.




Illustration for Tablet Setup

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company’s findings at the time of its intervention only and within the limits of Client’s instructions, if any. The Company’s sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

5.4 Power verification of device mode

For the device modes verification, the measured conducted output power is monitored qualitatively to identify the triggering characteristics and recorded quantitatively.

Results and conclusion

The measured output power versus lid angle is tabulated in the following table based on the guidance from 2019-11 TCB workshop, and the triggering verification complies with the device mode / power level declared by the manufacturer.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. | No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.sgs.com.tw

Member of SGS Group

Device mode verification by power measurement

Antenna	Operation mode	Lid angle	802.11b	802.11a 5.2G	802.11a 5.3G	802.11ac(80M) 5.6G	802.11ac(80M) 5.8G	U-NH-5 802.11ac(160M)	U-NH-6 802.11ac(160M)	U-NH-7 802.11ac(160M)	U-NH-8 802.11ac(160M)	
Main	Lid close	0°	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
		10°	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
	Laptop	20°	20.43	20.30	20.33	20.45	20.47	13.39	13.44	12.73	12.69	
		15°	20.40	20.31	20.33	20.38	20.40	13.44	13.47	12.71	12.72	
	Lid close	10°	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
		11°	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
	Laptop	12°	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
		13°	20.43	20.33	20.27	20.47	20.45	13.48	13.42	12.73	12.70	
		14°	20.39	20.33	20.28	20.39	20.43	13.40	13.40	12.69	12.73	
		15°	20.38	20.35	20.32	20.40	20.39	13.40	13.48	12.73	12.68	
		16°	20.43	20.27	20.33	20.45	20.45	13.39	13.45	12.64	12.64	
		17°	20.43	20.30	20.27	20.39	20.42	13.47	13.41	12.74	12.64	
		18°	20.41	20.32	20.33	20.47	20.38	13.44	13.46	12.69	12.67	
		19°	20.44	20.28	20.34	20.48	20.38	13.39	13.39	12.69	12.64	
		20°	20.39	20.28	20.34	20.47	20.46	13.46	13.41	12.68	12.68	
		30°	20.38	20.36	20.32	20.46	20.45	13.46	13.42	12.68	12.71	
		40°	20.46	20.34	20.30	20.47	20.40	13.44	13.45	12.65	12.65	
		50°	20.46	20.35	20.28	20.40	20.45	13.39	13.39	12.65	12.72	
		60°	20.38	20.32	20.30	20.44	20.37	13.42	13.40	12.67	12.69	
		70°	20.39	20.28	20.34	20.41	20.39	13.48	13.40	12.70	12.72	
		80°	20.39	20.31	20.27	20.42	20.47	13.44	13.41	12.68	12.68	
		90°	20.42	20.32	20.34	20.41	20.41	13.40	13.45	12.67	12.70	
		100°	20.45	20.29	20.28	20.38	20.45	13.41	13.47	12.69	12.68	
		110°	20.48	20.33	20.30	20.39	20.45	13.45	13.44	12.69	12.66	
		120°	20.40	20.28	20.32	20.44	20.46	13.38	13.45	12.71	12.71	
		130°	20.43	20.27	20.26	20.48	20.39	13.44	13.41	12.74	12.71	
		140°	20.43	20.29	20.33	20.41	20.41	13.41	13.42	12.64	12.65	
		150°	20.45	20.30	20.28	20.39	20.38	13.38	13.46	12.73	12.73	
		160°	20.44	20.36	20.35	20.46	20.45	13.41	13.42	12.67	12.67	
		170°	20.38	20.34	20.30	20.48	20.37	13.40	13.40	12.70	12.66	
		180°	20.38	20.30	20.35	20.45	20.42	13.47	13.41	12.72	12.69	
		Flip	190°	20.45	20.35	20.27	20.46	20.47	13.42	13.47	12.73	12.68
			200°	14.92	7.94	7.81	7.91	7.85	7.86	7.84	7.91	7.97
		Laptop	195°	20.45	20.29	20.34	20.39	20.42	13.48	13.42	12.70	12.66
			196°	20.48	20.27	20.29	20.39	20.38	13.40	13.38	12.67	12.74
			197°	20.41	20.27	20.31	20.46	20.39	13.45	13.43	12.72	12.68
	198°		20.40	20.37	20.28	20.40	20.40	13.43	13.46	12.67	12.74	
	199°		20.38	20.30	20.32	20.43	20.44	13.44	13.44	12.67	12.68	
	200°		14.91	7.88	7.80	7.91	7.82	7.84	7.80	7.95	7.98	
	201°		14.90	7.89	7.77	7.91	7.92	7.87	7.80	7.90	7.89	
	202°		14.93	7.93	7.79	7.98	7.85	7.92	7.77	7.96	7.92	
	203°		14.95	7.94	7.81	7.90	7.92	7.87	7.78	7.94	7.95	
	204°		14.88	7.94	7.77	7.87	7.94	7.84	7.81	7.92	7.90	
	Flip	205°	14.93	7.94	7.83	7.95	7.82	7.94	7.82	7.86	7.89	
		206°	14.92	7.88	7.74	7.95	7.92	7.85	7.74	7.90	7.94	
		207°	14.94	7.93	7.83	7.89	7.84	7.86	7.83	7.94	7.97	
		208°	14.88	7.94	7.73	7.98	7.82	7.88	7.74	7.96	7.98	
		209°	14.92	7.89	7.83	7.89	7.84	7.84	7.79	7.88	7.88	
		210°	14.96	7.85	7.83	7.98	7.92	7.95	7.76	7.90	7.93	
		220°	14.97	7.95	7.77	7.96	7.87	7.86	7.74	7.88	7.94	
		230°	14.92	7.90	7.98	7.98	7.92	7.88	7.82	7.94	7.88	
		240°	14.97	7.85	7.83	7.93	7.85	7.91	7.76	7.87	7.95	
		250°	14.95	7.94	7.75	7.95	7.84	7.86	7.84	7.92	7.92	
		260°	14.89	7.90	7.82	7.98	7.87	7.93	7.83	7.94	7.94	
		270°	14.95	7.95	7.76	7.92	7.82	7.95	7.74	7.91	7.98	
		280°	14.93	7.94	7.81	7.99	7.82	7.94	7.81	7.86	7.93	
		290°	14.95	7.91	7.83	7.97	7.91	7.86	7.77	7.96	7.91	
		300°	14.97	7.94	7.77	7.90	7.89	7.85	7.78	7.96	7.92	
		310°	14.98	7.87	7.78	7.89	7.88	7.91	7.80	7.94	7.97	
		320°	14.93	7.88	7.77	7.91	7.91	7.95	7.78	7.88	7.94	
		330°	14.91	7.95	7.78	7.98	7.88	7.85	7.83	7.93	7.93	
		340°	14.96	7.88	7.75	7.93	7.83	7.88	7.77	7.94	7.92	
		350°	14.97	7.90	7.81	7.97	7.90	7.78	7.70	7.91	7.97	
		360°	14.98	7.80	7.73	7.80	7.80	7.88	7.81	7.86	7.92	
		350°	14.96	7.91	7.78	7.92	7.84	7.85	7.81	7.85	7.95	
		340°	14.90	7.85	7.77	7.92	7.83	7.88	7.75	7.87	7.95	
		330°	14.96	7.87	7.82	7.96	7.85	7.87	7.75	7.92	7.90	
		320°	14.90	7.94	7.80	7.97	7.82	7.91	7.77	7.88	7.97	
		310°	14.91	7.91	7.77	7.94	7.87	7.85	7.82	7.91	7.93	
		300°	14.88	7.94	7.78	7.91	7.84	7.82	7.78	7.91	7.90	
		290°	14.98	7.86	7.76	7.98	7.92	7.93	7.84	7.95	7.96	
		280°	14.95	7.93	7.76	7.98	7.86	7.92	7.74	7.95	7.90	
		270°	14.96	7.93	7.76	7.95	7.89	7.95	7.82	7.93	7.97	
	260°	14.92	7.87	7.83	7.95	7.85	7.85	7.82	7.90	7.94		
	250°	14.95	7.95	7.76	7.93	7.89	7.93	7.80	7.95	7.95		
	240°	14.88	7.85	7.74	7.89	7.89	7.94	7.84	7.88	7.93		
	230°	14.93	7.88	7.82	7.95	7.85	7.93	7.77	7.95	7.93		
	220°	14.92	7.89	7.77	7.87	7.87	7.86	7.76	7.95	7.90		
	210°	14.92	7.92	7.83	7.89	7.89	7.91	7.82	7.95	7.92		
	200°	14.96	7.86	7.76	7.98	7.82	7.92	7.78	7.96	7.89		
	190°	14.97	7.87	7.82	7.98	7.84	7.88	7.83	7.98	7.90		
	180°	14.90	7.90	7.74	7.92	7.85	7.87	7.80	7.93	7.98		
	170°	14.90	7.91	7.82	7.97	7.88	7.86	7.74	7.95	7.90		
	160°	14.97	7.86	7.77	7.99	7.84	7.95	7.75	7.94	7.95		
	Laptop	150°	20.38	20.28	20.30	20.44	20.46	13.39	13.48	12.72	12.71	
		165°	20.46	20.30	20.30	20.42	20.42	13.44	13.46	12.74	12.73	
		180°	14.95	7.85	7.77	7.99	7.83	7.86	7.74	7.88	7.88	
		Flip	199°	20.40	20.27	20.30	20.45	20.43	13.40	13.43	12.72	12.71
			158°	20.41	20.27	20.35	20.48	20.42	13.47	13.43	12.72	12.71
			157°	20.47	20.31	20.32	20.41	20.42	13.39	13.47	12.74	12.65
			156°	20.45	20.32	20.36	20.44	20.39	13.44	13.43	12.67	12.66
			155°	20.42	20.30	20.36	20.44	20.44	13.40	13.44	12.64	12.60
			154°	20.44	20.37	20.46	20.38	20.46	13.46	13.42	12.65	12.70
			153°	20.48	20.29	20.29	20.39	20.43	13.45	13.43	12.71	12.67
	152°		20.40	20.27	20.32	20.46	20.43	13.43	13.41	12.67	12.74	
	151°		20.40	20.33	20.27	20.45	20.43	13.43	13.38	12.70	12.69	
	150°		20.42	20.30	20.48	20.37	20.37	13.42	13.40	12.68	12.70	
	Laptop	140°	20.45	20.31	20.29	20.46	20.47	13.41	13.46	12.64	12.71	
		130°	20.38	20.33	20.26	20.39	20.37	13.42	13.38	12.70	12.73	
		120°	20.48	20.31	20.29	20.45	20.39	13.41	13.44	12.70	12.70	
110°		20.42	20.34	20.27	20.46	20.37	13.38	13.42	12.68	12.71		
100°		20.42	20.30	20.31	20.47	20.38	13.42	13.40	12.68	12.70		
90°		20.43	20.30	20.29	20.38	20.45	13.44	13.42	12.67	12.67		
80°		20.43	20.31	20.30	20.42	20.47	13.47	13.38	12.74	12.69		
70°		20.41	20.28	20.34	20.46	20.41	13.48	13.39	12.65	12.72		
60°		20.39	20.37	20.36	20.38	20.46	13.45	13.44	12.67	12.67		
50°		20.43	20.35	20.26	20.46	20.46	13.40	13.46				

Antenna	Operation mode	Lid angle	802.11b	802.11a 5.2G	802.11a 5.3G	802.11ac(80M) 5.6G	802.11ac(80M) 5.8G	U-Ni-5 802.11ax(160M)	U-Ni-6 802.11ax(160M)	U-Ni-7 802.11ax(160M)	U-Ni-8 802.11ax(160M)
Main	Book	13°	14.93	7.87	7.83	7.90	7.88	7.94	7.75	7.88	7.89
		14°	14.91	7.88	7.80	7.95	7.90	7.83	7.88	7.97	7.97
		15°	14.88	7.87	7.83	7.98	7.86	7.88	7.79	7.91	7.95
		16°	14.92	7.92	7.75	7.91	7.87	7.95	7.79	7.91	7.98
		17°	14.88	7.87	7.75	7.89	7.87	7.87	7.83	7.95	7.98
		18°	14.88	7.93	7.83	7.89	7.85	7.89	7.82	7.88	7.90
		19°	14.94	7.88	7.77	7.89	7.84	7.87	7.77	7.96	7.94
		20°	14.88	7.89	7.82	7.89	7.83	7.92	7.74	7.91	7.89
		30°	14.92	7.87	7.75	7.98	7.82	7.94	7.78	7.94	7.91
		40°	14.88	7.87	7.78	7.94	7.87	7.89	7.78	7.89	7.95
		50°	14.91	7.88	7.74	7.95	7.92	7.91	7.83	7.87	7.95
		60°	14.96	7.88	7.76	7.99	7.92	7.85	7.78	7.92	7.89
		70°	14.90	7.91	7.82	7.97	7.82	7.89	7.76	7.90	7.95
		80°	14.98	7.89	7.76	7.93	7.88	7.90	7.76	7.92	7.98
		90°	14.97	7.93	7.82	7.90	7.88	7.85	7.75	7.95	7.97
		100°	14.98	7.95	7.78	7.90	7.91	7.90	7.77	7.91	7.91
		110°	14.92	7.92	7.73	7.91	7.91	7.94	7.81	7.90	7.88
		120°	14.90	7.91	7.73	7.91	7.89	7.94	7.83	7.91	7.95
		130°	14.92	7.94	7.73	7.93	7.87	7.91	7.74	7.94	7.92
		140°	14.98	7.91	7.77	7.96	7.87	7.87	7.82	7.96	7.90
		150°	14.91	7.87	7.73	7.95	7.89	7.92	7.77	7.95	7.93
		160°	14.91	7.95	7.77	7.89	7.90	7.90	7.77	7.91	7.97
		170°	14.93	7.92	7.81	7.93	7.86	7.85	7.76	7.94	7.94
		180°	14.93	7.86	7.83	7.94	7.91	7.89	7.83	7.93	7.88
		190°	14.97	7.91	7.74	7.93	7.84	7.82	7.76	7.96	7.89
		195°	14.90	7.89	7.80	7.89	7.87	7.94	7.81	7.86	7.97
		196°	14.93	7.85	7.74	7.97	7.87	7.87	7.81	7.92	7.98
		197°	14.88	7.88	7.78	7.94	7.82	7.95	7.79	7.88	7.95
		198°	14.88	7.92	7.79	7.97	7.83	7.93	7.78	7.90	7.93
		199°	14.91	7.90	7.79	7.95	7.83	7.87	7.78	7.91	7.96
		199°	14.89	7.89	7.80	7.95	7.82	7.91	7.77	7.93	7.89
		155°	14.92	7.93	7.82	7.92	7.86	7.93	7.80	7.95	7.94
		159°	14.91	7.85	7.73	7.92	7.82	7.86	7.78	7.89	7.88
		158°	14.96	7.87	7.78	7.94	7.89	7.92	7.74	7.91	7.91
		157°	14.98	7.89	7.77	7.99	7.92	7.88	7.77	7.92	7.97
		156°	14.88	7.86	7.83	7.96	7.82	7.93	7.82	7.94	7.95
		155°	14.95	7.87	7.79	7.94	7.87	7.88	7.75	7.87	7.96
		154°	14.90	7.95	7.78	7.95	7.82	7.94	7.78	7.90	7.96
		153°	14.88	7.86	7.83	7.95	7.82	7.92	7.82	7.95	7.95
		152°	14.94	7.95	7.76	7.92	7.82	7.92	7.82	7.94	7.96
		151°	14.98	7.87	7.73	7.94	7.86	7.95	7.83	7.87	7.90
		150°	14.97	7.95	7.82	7.98	7.90	7.95	7.82	7.91	7.93
		140°	14.93	7.92	7.79	7.89	7.86	7.94	7.83	7.95	7.92
		130°	14.95	7.86	7.82	7.98	7.86	7.93	7.84	7.93	7.94
		120°	14.98	7.93	7.73	7.89	7.86	7.90	7.83	7.86	7.94
		110°	14.94	7.93	7.76	7.91	7.92	7.88	7.83	7.90	7.93
		100°	14.98	7.85	7.83	7.98	7.88	7.85	7.78	7.91	7.91
		90°	14.97	7.90	7.83	7.99	7.92	7.87	7.75	7.89	7.97
		80°	14.95	7.89	7.83	7.99	7.83	7.89	7.77	7.92	7.88
		70°	14.95	7.95	7.79	7.97	7.88	7.85	7.81	7.88	7.94
	60°	14.88	7.88	7.79	7.97	7.83	7.87	7.82	7.89	7.96	
	50°	14.98	7.89	7.82	7.96	7.86	7.92	7.80	7.87	7.93	
	40°	14.97	7.87	7.76	7.98	7.92	7.95	7.83	7.91	7.91	
	30°	14.96	7.86	7.73	7.90	7.86	7.95	7.83	7.96	7.97	
	20°	14.91	7.85	7.82	7.90	7.89	7.92	7.83	7.96	7.93	
	15°	14.97	7.86	7.83	7.99	7.84	7.94	7.77	7.95	7.90	
	14°	14.93	7.90	7.78	7.89	7.90	7.94	7.81	7.91	7.89	
	13°	14.96	7.88	7.76	7.96	7.84	7.85	7.80	7.89	7.90	

*The screen orientation is 90° or 270° in book mode, other is laptop mode.

Main	without keyboard	14.91	7.82	7.88	7.92	7.89	7.95	7.88	7.91	7.92
------	------------------	-------	------	------	------	------	------	------	------	------

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Antenna	Operation mode	Lid angle	802.11b	802.11n(40M) 5.2G	802.11ax(40M) 5.3G	802.11ac(80M) 5.6G	802.11n(40M) 5.8G	U-NII-5 802.11ax(160M)	U-NII-6 802.11ax(160M)	U-NII-7 802.11ax(160M)	U-NII-8 802.11ax(160M)	
Laptop	Lid close	0°	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
	Laptop	10°	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
		20°	20.44	20.34	20.34	20.40	20.44	13.47	13.33	12.49	12.59	
		15°	20.45	20.36	20.38	20.44	20.48	13.39	13.37	12.51	12.61	
		10°	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	
		Lid close	11°	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
		12°	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
		13°	20.41	20.34	20.30	20.40	20.44	13.40	13.34	12.52	12.59	
		14°	20.47	20.38	20.36	20.36	20.47	13.44	13.37	12.50	12.68	
		15°	20.45	20.35	20.33	20.36	20.39	13.39	13.39	12.46	12.64	
16°	20.40	20.35	20.38	20.36	20.43	13.42	13.41	12.48	12.65			
17°	20.49	20.36	20.34	20.34	20.48	13.43	13.33	12.45	12.63			
18°	20.47	20.40	20.28	20.41	20.47	13.39	13.42	12.52	12.62			
19°	20.41	20.42	20.32	20.36	20.38	13.39	13.34	12.46	12.65			
20°	20.43	20.41	20.31	20.42	20.42	13.45	13.40	12.51	12.69			
30°	20.46	20.42	20.33	20.40	20.47	13.46	13.32	12.44	12.64			
40°	20.43	20.35	20.38	20.41	20.41	13.40	13.40	12.45	12.61			
50°	20.45	20.34	20.30	20.34	20.39	13.42	13.33	12.49	12.68			
60°	20.44	20.38	20.30	20.35	20.42	13.43	13.40	12.44	12.65			
70°	20.41	20.42	20.30	20.39	20.48	13.46	13.36	12.49	12.63			
80°	20.39	20.35	20.35	20.35	20.38	13.41	13.40	12.45	12.61			
90°	20.47	20.39	20.30	20.39	20.44	13.41	13.42	12.45	12.67			
100°	20.41	20.40	20.34	20.39	20.48	13.42	13.36	12.47	12.67			
110°	20.47	20.36	20.34	20.43	20.38	13.43	13.41	12.51	12.62			
120°	20.45	20.35	20.36	20.42	20.36	13.45	13.39	12.47	12.67			
130°	20.40	20.32	20.28	20.36	20.43	13.39	13.34	12.52	12.68			
140°	20.39	20.38	20.28	20.44	20.39	13.45	13.37	12.50	12.60			
150°	20.39	20.42	20.35	20.43	20.45	13.45	13.34	12.49	12.58			
160°	20.44	20.34	20.28	20.41	20.45	13.41	13.40	12.48	12.68			
170°	20.42	20.42	20.31	20.39	20.45	13.46	13.42	12.45	12.63			
180°	20.49	20.42	20.30	20.39	20.38	13.43	13.32	12.40	12.65			
190°	20.47	20.41	20.28	20.44	20.45	13.40	13.33	12.45	12.63			
200°	16.45	8.72	8.66	8.96	8.69	8.86	8.90	8.79	8.92			
195°	20.47	20.41	20.35	20.35	20.44	13.40	13.35	12.47	12.60			
196°	20.39	20.35	20.35	20.34	20.38	13.40	13.39	12.48	12.62			
197°	20.45	20.35	20.35	20.40	20.42	13.47	13.39	12.49	12.65			
198°	20.46	20.42	20.33	20.36	20.39	13.45	13.39	12.48	12.68			
199°	20.45	20.42	20.31	20.34	20.38	13.44	13.38	12.49	12.63			
200°	16.36	8.71	8.67	8.65	8.90	8.65	8.91	8.76	8.85			
201°	16.43	8.79	8.69	8.91	8.72	8.88	8.87	8.76	8.88			
202°	16.41	8.74	8.62	8.92	8.72	8.87	8.85	8.82	8.91			
203°	16.40	8.73	8.63	8.87	8.74	8.86	8.86	8.76	8.92			
204°	16.44	8.74	8.61	8.89	8.68	8.90	8.85	8.85	8.89			
205°	16.37	8.72	8.65	8.93	8.73	8.87	8.85	8.75	8.86			
206°	16.41	8.73	8.57	8.88	8.69	8.86	8.92	8.80	8.86			
207°	16.40	8.72	8.65	8.88	8.69	8.86	8.93	8.80	8.94			
208°	16.40	8.76	8.58	8.89	8.74	8.86	8.93	8.84	8.91			
209°	16.44	8.75	8.63	8.90	8.68	8.88	8.94	8.85	8.87			
210°	16.39	8.73	8.67	8.88	8.67	8.95	8.93	8.80	8.90			
220°	16.37	8.78	8.58	8.96	8.75	8.96	8.94	8.80	8.88			
230°	16.36	8.72	8.61	8.87	8.68	8.91	8.90	8.80	8.89			
240°	16.45	8.72	8.58	8.89	8.65	8.91	8.85	8.76	8.85			
250°	16.44	8.77	8.66	8.92	8.69	8.87	8.87	8.80	8.87			
260°	16.36	8.77	8.65	8.95	8.71	8.85	8.93	8.75	8.89			
270°	16.40	8.72	8.62	8.92	8.65	8.88	8.93	8.80	8.94			
280°	16.37	8.72	8.60	8.97	8.75	8.88	8.85	8.76	8.94			
290°	16.40	8.76	8.58	8.89	8.74	8.86	8.93	8.80	8.92			
300°	16.38	8.73	8.57	8.93	8.73	8.93	8.90	8.77	8.86			
310°	16.37	8.77	8.62	8.96	8.67	8.94	8.94	8.85	8.93			
320°	16.38	8.71	8.67	8.89	8.70	8.90	8.94	8.75	8.85			
330°	16.46	8.71	8.67	8.94	8.74	8.96	8.93	8.79	8.90			
340°	16.44	8.76	8.57	8.95	8.67	8.89	8.88	8.62	8.88			
350°	16.38	8.70	8.58	8.95	8.72	8.92	8.93	8.82	8.91			
360°	16.45	8.76	8.61	8.93	8.71	8.93	8.94	8.83	8.89			
350°	16.39	8.78	8.63	8.87	8.65	8.93	8.89	8.84	8.90			
340°	16.44	8.71	8.62	8.97	8.70	8.91	8.86	8.76	8.93			
330°	16.37	8.74	8.57	8.88	8.72	8.95	8.94	8.85	8.89			
320°	16.38	8.77	8.63	8.87	8.73	8.96	8.93	8.83	8.87			
310°	16.45	8.70	8.61	8.91	8.73	8.91	8.87	8.82	8.86			
300°	16.37	8.70	8.67	8.87	8.71	8.91	8.85	8.80	8.89			
290°	16.42	8.70	8.65	8.96	8.75	8.89	8.93	8.85	8.90			
280°	16.42	8.72	8.60	8.92	8.72	8.96	8.93	8.85	8.84			
270°	16.40	8.70	8.61	8.90	8.68	8.92	8.93	8.81	8.85			
260°	16.44	8.73	8.63	8.87	8.67	8.90	8.91	8.79	8.87			
250°	16.43	8.69	8.67	8.91	8.73	8.90	8.90	8.79	8.92			
240°	16.36	8.77	8.65	8.90	8.65	8.90	8.86	8.85	8.90			
230°	16.40	8.71	8.66	8.92	8.70	8.90	8.85	8.85	8.88			
220°	16.37	8.75	8.59	8.87	8.65	8.88	8.93	8.78	8.92			
210°	16.48	8.71	8.64	8.94	8.68	8.88	8.87	8.79	8.85			
200°	16.45	8.77	8.66	8.92	8.72	8.93	8.94	8.76	8.90			
190°	16.39	8.70	8.59	8.92	8.71	8.93	8.87	8.75	8.84			
180°	16.41	8.73	8.63	8.95	8.69	8.90	8.87	8.80	8.91			
170°	16.41	8.71	8.64	8.89	8.72	8.87	8.91	8.84	8.88			
160°	16.44	8.78	8.61	8.87	8.66	8.90	8.94	8.84	8.85			
150°	20.47	20.32	20.37	20.34	20.38	13.46	13.41	12.44	12.62			
Laptop	155°	20.49	20.37	20.30	20.40	20.46	13.45	13.32	12.46	12.62		
Flip	160°	16.38	8.75	8.64	8.92	8.70	8.92	8.80	8.84	8.88		
159°	20.48	20.38	20.32	20.38	20.38	13.45	13.38	12.44	12.65			
158°	20.47	20.37	20.38	20.39	20.45	13.48	13.37	12.53	12.60			
157°	20.39	20.35	20.31	20.38	20.44	13.48	13.40	12.52	12.61			
156°	20.46	20.35	20.37	20.35	20.44	13.39	13.38	12.53	12.63			
155°	20.48	20.34	20.36	20.39	20.47	13.41	13.39	12.52	12.59			
154°	20.44	20.37	20.29	20.36	20.44	13.45	13.35	12.49	12.59			
153°	20.49	20.34	20.36	20.34	20.40	13.45	13.32	12.50	12.62			
152°	20.49	20.39	20.28	20.35	20.47	13.45	13.39	12.50	12.66			
151°	20.48	20.38	20.36	20.38	20.41	13.44	13.36	12.51	12.68			
150°	20.46	20.42	20.28	20.44	20.39	13.48	13.41	12.54	12.68			
140°	20.48	20.38	20.37	20.42	20.44	13.40	13.32	12.44	12.61			
130°	20.41	20.37	20.36	20.35	20.45	13.38	13.37	12.45	12.60			
120°	20.47	20.37	20.35	20.44	20.42	13.47	13.34	12.53	12.67			
110°	20.47	20.40	20.37	20.48	20.48	13.41	13.32	12.52	12.62			
100°	20.45	20.34	20.33	20.44	20.45	13.41	13.41	12.50	12.59			
90°	20.49	20.39	20.33	20.36	20.47	13.46	13.32	12.44	12.65			
80°	20.42	20.36	20.33	20.36	20.46	13.48	13.32	12.52	12.61			
70°	20.44	20.33	20.28	20.38	20.38	13.48	13.36	12.48	12.62			
60°	20.42	20.29	20.29	20.45	20.45	13.42	13.41	12.47	12.60			
50°	20.46	20.42	20.37	20.43	20.48	13.39	13.41	12.48	12.60			
40°	20.44	20.36	20.35	20.34	20.44	13.48	13					

Antenna	Operation mode	Lid angle	802.11b	802.11n(40M) 5.2G	802.11ax(40M) 5.3G	802.11ac(80M) 5.6G	802.11n(40M) 5.8G	U-NII-5 802.11ax(160M)	U-NII-6 802.11ax(160M)	U-NII-7 802.11ax(160M)	U-NII-8 802.11ax(160M)		
Aux	Book	13°	16.44	8.79	8.60	8.93	8.70	8.92	8.94	8.82	8.88		
		14°	16.40	8.73	8.64	8.92	8.73	8.87	8.90	8.80	8.84		
		15°	16.44	8.78	8.61	8.95	8.67	8.86	8.87	8.81	8.84		
		16°	16.39	8.71	8.61	8.88	8.74	8.90	8.94	8.84	8.93		
		17°	16.46	8.72	8.60	8.87	8.87	8.87	8.87	8.87	8.84	8.88	
		18°	16.45	8.74	8.57	8.92	8.67	8.91	8.87	8.84	8.86	8.86	
		19°	16.38	8.70	8.67	8.95	8.73	8.91	8.89	8.89	8.78	8.86	
		20°	16.44	8.71	8.57	8.87	8.72	8.88	8.92	8.81	8.88	8.88	
		30°	16.42	8.71	8.62	8.90	8.68	8.96	8.94	8.81	8.94	8.94	
		40°	16.37	8.76	8.61	8.87	8.69	8.89	8.93	8.85	8.90	8.90	
		50°	16.43	8.75	8.65	8.87	8.71	8.92	8.94	8.76	8.88	8.88	
		60°	16.39	8.77	8.66	8.88	8.74	8.90	8.94	8.81	8.92	8.92	
		70°	16.46	8.79	8.58	8.91	8.73	8.87	8.84	8.79	8.85	8.85	
		80°	16.45	8.77	8.61	8.93	8.70	8.88	8.90	8.85	8.85	8.85	
		90°	16.42	8.79	8.57	8.96	8.73	8.88	8.91	8.87	8.78	8.91	
		100°	16.44	8.78	8.61	8.90	8.75	8.88	8.91	8.78	8.84	8.84	
		110°	16.44	8.78	8.66	8.96	8.74	8.89	8.93	8.83	8.86	8.86	
		120°	16.37	8.75	8.67	8.93	8.69	8.88	8.88	8.82	8.91	8.91	
		130°	16.38	8.79	8.57	8.88	8.74	8.90	8.88	8.75	8.91	8.91	
		140°	16.43	8.73	8.58	8.95	8.68	8.91	8.87	8.78	8.91	8.91	
		150°	16.36	8.77	8.62	8.89	8.71	8.88	8.89	8.78	8.87	8.87	
		160°	16.44	8.74	8.65	8.91	8.69	8.92	8.87	8.79	8.90	8.90	
		170°	16.44	8.71	8.64	8.95	8.75	8.92	8.88	8.84	8.84	8.93	
		180°	16.41	8.69	8.57	8.88	8.68	8.85	8.87	8.79	8.85	8.85	
		190°	16.44	8.79	8.62	8.95	8.70	8.95	8.89	8.79	8.90	8.90	
		195°	16.44	8.77	8.57	8.94	8.68	8.91	8.89	8.77	8.86	8.86	
		196°	16.36	8.73	8.58	8.89	8.75	8.92	8.89	8.79	8.91	8.91	
		197°	16.37	8.74	8.61	8.87	8.68	8.86	8.89	8.82	8.85	8.85	
		198°	16.36	8.76	8.63	8.96	8.74	8.89	8.94	8.85	8.93	8.93	
		199°	16.41	8.73	8.61	8.94	8.70	8.96	8.89	8.78	8.88	8.88	
		199°	16.38	8.78	8.63	8.97	8.72	8.96	8.94	8.85	8.92	8.92	
		155°	16.41	8.70	8.59	8.87	8.70	8.91	8.84	8.81	8.93	8.93	
		Book	159°	16.36	8.71	8.62	8.94	8.73	8.95	8.94	8.85	8.84	8.84
			158°	16.38	8.74	8.60	8.95	8.73	8.90	8.89	8.80	8.84	8.84
			157°	16.42	8.76	8.66	8.90	8.71	8.96	8.93	8.84	8.93	8.93
			156°	16.40	8.76	8.64	8.97	8.71	8.96	8.90	8.78	8.92	8.92
			155°	16.43	8.76	8.65	8.90	8.69	8.91	8.91	8.75	8.94	8.94
			154°	16.36	8.70	8.61	8.92	8.75	8.90	8.85	8.77	8.90	8.90
			153°	16.45	8.70	8.62	8.94	8.70	8.90	8.89	8.76	8.90	8.90
			152°	16.36	8.77	8.66	8.96	8.71	8.92	8.84	8.79	8.91	8.91
			151°	16.41	8.76	8.60	8.89	8.66	8.88	8.94	8.77	8.86	8.86
			150°	16.44	8.73	8.58	8.95	8.71	8.91	8.89	8.81	8.90	8.90
			140°	16.44	8.79	8.61	8.95	8.67	8.88	8.85	8.75	8.85	8.85
			130°	16.43	8.71	8.59	8.97	8.66	8.89	8.91	8.82	8.94	8.94
			120°	16.41	8.76	8.60	8.95	8.71	8.88	8.92	8.79	8.89	8.89
			110°	16.40	8.76	8.69	8.91	8.75	8.91	8.91	8.77	8.94	8.94
			100°	16.42	8.72	8.67	8.96	8.68	8.89	8.93	8.78	8.86	8.86
			90°	16.38	8.73	8.59	8.90	8.70	8.94	8.91	8.84	8.85	8.85
			80°	16.45	8.73	8.60	8.92	8.69	8.92	8.93	8.78	8.90	8.90
			70°	16.38	8.76	8.62	8.96	8.72	8.96	8.88	8.78	8.85	8.85
	60°		16.40	8.70	8.58	8.88	8.73	8.89	8.86	8.83	8.86	8.86	
	50°		16.45	8.71	8.65	8.92	8.75	8.96	8.92	8.82	8.94	8.94	
	40°		16.43	8.72	8.63	8.93	8.70	8.95	8.90	8.76	8.92	8.92	
	30°		16.42	8.69	8.69	8.94	8.66	8.89	8.90	8.77	8.90	8.90	
	20°		16.37	8.69	8.66	8.89	8.70	8.91	8.87	8.78	8.84	8.84	
	15°		16.37	8.70	8.64	8.87	8.71	8.88	8.89	8.76	8.84	8.84	
	14°		16.46	8.77	8.58	8.93	8.72	8.93	8.91	8.80	8.85	8.85	
	13°		16.41	8.76	8.62	8.87	8.65	8.90	8.92	8.77	8.85	8.85	

*The screen orientation is 90° or 270° in book mode, other is laptop mode.

Aux	without keyboard	16.44	8.72	8.61	8.82	8.74	8.87	8.92	8.76	8.87
-----	------------------	-------	------	------	------	------	------	------	------	------

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

5.5 Test limit

§ 2.1093(d)(1)

Applications for equipment authorization of portable RF sources subject to routine environmental evaluation must contain a statement confirming compliance with the limits specified in § 1.1310 as part of their application. Technical information showing the basis for this statement must be submitted to the Commission upon request. The SAR limits specified in § 1.1310(a) through (c) of this chapter shall be used for evaluation of portable devices transmitting in the frequency range from 100 kHz to 6 GHz. Portable devices that transmit at frequencies above 6 GHz shall be evaluated in terms of the MPE limits specified in Table 1 to § 1.1310(e)(1). A minimum separation distance applicable to the operating configurations and exposure conditions of the device shall be used for the evaluation. In general, maximum time-averaged power levels must be used for evaluation. All unlicensed personal communications service (PCS) devices and unlicensed NII devices shall be subject to the limits for general population/uncontrolled exposure.

Radiofrequency radiation exposure limits.

§ 1.1310(a)

Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) within the frequency range of 100 kHz to 6 GHz (inclusive).

§ 1.1310(b)

The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.

§ 1.1310(c)

The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

Note to paragraphs (a) through (c):

SAR is a measure of the rate of energy absorption due to exposure to RF electromagnetic energy. These SAR limits to be used for evaluation are based generally on criteria published by the American National Standards Institute (ANSI) for localized SAR in Section 4.2 of "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," ANSI/IEEE Std C95.1-1992, copyright 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017. These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in "Biological Effects and Exposure Criteria for Radiofrequency

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions>, and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Electromagnetic Fields,” NCRP Report No. 86, [Section 17.4.5](#), copyright 1986 by NCRP, Bethesda, Maryland 20814. Limits for whole body SAR and peak spatial-average SAR are based on recommendations made in both of these documents. The MPE limits in Table 1 are based generally on criteria published by the NCRP in “Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” NCRP Report No. 86, Sections 17.4.1, 17.4.1.1, 17.4.2 and 17.4.3, copyright 1986 by NCRP, Bethesda, Maryland 20814. In the frequency range from 100 MHz to 1500 MHz, these MPE exposure limits for field strength and power density are also generally based on criteria recommended by the ANSI in [Section 4.1](#) of “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz,” ANSI/IEEE Std C95.1-1992, copyright 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017.

Portable devices that transmit at frequencies above 6 GHz shall be evaluated in terms of the MPE limits specified in Table 1 to [§ 1.1310\(e\)\(1\)](#).

According to ANSI/IEEE C95.1-1992, the criteria listed in the following Table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Peak Spatially Averaged Power Density was evaluated over a circular area of 4cm² per interim FCC Guidance for near-field power density evaluations per October 2018 TCB Workshop notes

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

Table 1 to [§ 1.1310\(e\)\(1\)](#) - Limits for Maximum Permissible Exposure (MPE)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. | No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

6 MAXIMUM OUTPUT POWER

6.1 WLAN

Notebook mode

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
2.45GHz	802.11b	1	2412	1Mbps	20.50	20.41
		6	2437		20.50	20.48
		11	2462		20.50	20.46
	802.11g	1	2412	6Mbps	19.50	19.23
		6	2437		20.50	20.27
		11	2462		18.00	17.90
	802.11n20-HT0	1	2412	MCS0	19.50	19.26
		6	2437		20.50	20.37
		11	2462		18.00	17.75
	802.11ax20-HE0	1	2412	MCS0	19.50	19.28
		6	2437		20.50	20.28
		11	2462		18.00	17.84
	802.11n40-HT0	3	2422	MCS0	15.50	15.24
		6	2437		17.50	17.29
		9	2452		15.50	15.26
802.11ax40-HE0	3	2422	MCS0	15.50	15.38	
	6	2437		17.50	17.30	
	9	2452		15.50	15.26	
WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.15-5.25 GHz	802.11a	36	5180	6Mbps	19.50	19.46
		40	5200		20.50	20.37
		44	5220		20.375	20.34
		48	5240		19.875	19.71
	802.11n20-HT0	36	5180	MCS0	19.50	19.30
		40	5200		20.50	20.24
		44	5220		20.00	19.72
		48	5240		19.50	19.30
	802.11ax20-HE0	36	5180	MCS0	19.50	19.25
		40	5200		20.50	20.20
		44	5220		20.25	19.94
		48	5240		19.75	19.49
	802.11n40-HT0	38	5190	MCS0	17.75	17.53
		46	5230		20.25	20.02
	802.11ax40-HE0	38	5190	MCS0	17.75	17.57
46		5230	20.125		19.88	
802.11ac80-VHT0	42	5210	MCS0	18.50	18.32	
802.11ax80-HE0	42	5210	MCS0	18.50	18.28	
802.11ac160-VHT0	50	5250	MCS0	14.50	14.26	
802.11ax160-HE0	50	5250	MCS0	14.50	14.29	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.25-5.35 GHz	802.11a	52	5260	6Mbps	19.875	19.66
		56	5280		20.00	19.84
		60	5300		20.375	20.17
		64	5320		20.50	20.36
	802.11n20-HT0	52	5260	MCS0	19.75	19.50
		56	5280		20.375	20.05
		60	5300		20.50	20.31
		64	5320		20.50	20.30
	802.11ax20-HE0	52	5260	MCS0	19.875	19.57
		56	5280		20.25	20.07
		60	5300		20.50	20.28
		64	5320		20.50	20.23
	802.11n40-HT0	54	5270	MCS0	19.875	19.67
		62	5310		17.50	17.22
802.11ax40-HE0	54	5270	MCS0	19.75	19.45	
	62	5310		17.50	17.16	
802.11ac80-VHT0	58	5290	MCS0	17.50	17.18	
802.11ax80-HE0	58	5290	MCS0	17.50	17.18	
WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.6GHz	802.11a	100	5500	6Mbps	20.50	20.37
		120	5600		20.50	20.24
		140	5700		20.25	20.06
		144	5720		20.50	20.25
	802.11n20-HT0	100	5500	MCS0	20.50	20.36
		120	5600		20.50	20.21
		140	5700		20.25	19.97
		144	5720		20.50	20.29
	802.11ax20-HE0	100	5500	MCS0	20.50	20.25
		120	5600		20.50	20.37
		140	5700		20.25	20.02
		144	5720		20.50	20.22
	802.11n40-HT0	102	5510	MCS0	19.75	19.62
		118	5590		20.50	20.40
		134	5670		20.50	20.30
		142	5710		20.50	20.30
	802.11ax40-HE0	102	5510	MCS0	19.75	19.48
		118	5590		20.50	20.25
		134	5670		20.50	20.27
		142	5710		20.50	20.23
	802.11ac80-VHT0	106	5530	MCS0	18.50	18.38
		122	5610		20.50	20.41
		138	5690		20.50	20.48
	802.11ax80-HE0	106	5530	MCS0	18.50	18.29
122		5610	20.50		20.37	
138		5690	20.50		20.32	
802.11ac160-VHT0	114	5570	MCS0	15.50	15.30	
802.11ax160-HE0	114	5570	MCS0	15.50	15.33	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Main						
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.8GHz	802.11a	149	5745	6Mbps	20.50	20.34
		157	5785		20.50	20.21
		165	5825		20.50	20.24
	802.11n20-HT0	149	5745	MCS0	20.50	20.29
		157	5785		20.50	20.27
		165	5825		20.50	20.35
	802.11ax20-HE0	149	5745	MCS0	20.50	20.26
		157	5785		20.50	20.32
		165	5825		20.50	20.40
	802.11n40-HT0	151	5755	MCS0	20.50	20.29
		159	5795		20.50	20.25
	802.11ax40-HE0	151	5755	MCS0	20.50	20.21
		159	5795		20.50	20.34
	802.11ac80-VHT0	155	5775	MCS0	20.50	20.47
802.11ax80-HE0	155	5775	MCS0	20.50	20.20	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
2.45GHz	802.11b	1	2412	1Mbps	20.50	20.48
		6	2437		20.50	20.49
		11	2462		20.50	20.44
	802.11g	1	2412	6Mbps	19.25	18.96
		6	2437		20.50	20.29
		11	2462		18.25	17.97
	802.11n20-HT0	1	2412	MCS0	19.25	19.09
		6	2437		20.50	20.37
		11	2462		18.25	18.15
	802.11ax20-HE0	1	2412	MCS0	19.25	19.03
		6	2437		20.50	20.21
		11	2462		18.25	17.95
	802.11n40-HT0	3	2422	MCS0	15.75	15.54
		6	2437		17.75	17.50
		9	2452		17.00	16.73
802.11ax40-HE0	3	2422	MCS0	15.75	15.47	
	6	2437		17.75	17.59	
	9	2452		17.00	16.85	

WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.15-5.25 GHz	802.11a	36	5180	6Mbps	19.50	19.38
		40	5200		20.50	20.35
		44	5220		20.50	20.33
		48	5240		20.50	20.40
	802.11n20-HT0	36	5180	MCS0	19.50	19.39
		40	5200		20.50	20.28
		44	5220		20.50	20.31
	802.11ax20-HE0	36	5180	MCS0	19.50	19.29
		40	5200		20.50	20.38
		44	5220		20.50	20.21
		48	5240		20.50	20.33
	802.11n40-HT0	38	5190	MCS0	18.75	18.72
		46	5230		20.50	20.42
	802.11ax40-HE0	38	5190	MCS0	18.75	18.57
		46	5230		20.50	20.25
	802.11ac80-VHT0	42	5210	MCS0	18.25	18.12
	802.11ax80-HE0	42	5210	MCS0	18.25	18.14
802.11ac160-VHT0	50	5250	MCS0	14.00	13.80	
802.11ax160-HE0	50	5250	MCS0	14.00	13.82	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.25-5.35 GHz	802.11a	52	5260	6Mbps	20.50	20.35
		56	5280		20.25	20.15
		60	5300		20.50	20.25
		64	5320		20.50	20.23
	802.11n20-HT0	52	5260	MCS0	20.50	20.33
		56	5280		20.25	20.05
		60	5300		20.50	20.23
		64	5320		20.50	20.30
	802.11ax20-HE0	52	5260	MCS0	20.50	20.38
		56	5280		20.13	19.87
		60	5300		20.50	20.27
		64	5320		20.50	20.34
	802.11n40-HT0	54	5270	MCS0	20.25	20.12
		62	5310		17.50	17.38
802.11ax40-HE0	54	5270	MCS0	20.50	20.38	
	62	5310		17.50	17.43	
802.11ac80-VHT0	58	5290	MCS0	17.50	17.32	
802.11ax80-HE0	58	5290	MCS0	17.50	17.24	
WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.6GHz	802.11a	100	5500	6Mbps	20.50	20.30
		120	5600		20.50	20.34
		140	5700		20.25	20.04
		144	5720		20.50	20.35
	802.11n20-HT0	100	5500	MCS0	20.50	20.30
		120	5600		20.50	20.28
		140	5700		20.25	20.05
		144	5720		20.50	20.26
	802.11ax20-HE0	100	5500	MCS0	20.50	20.36
		120	5600		20.50	20.23
		140	5700		20.25	20.03
		144	5720		20.50	20.28
	802.11n40-HT0	102	5510	MCS0	20.25	20.02
		118	5590		20.50	20.38
		134	5670		20.50	20.34
		142	5710		20.50	20.21
	802.11ax40-HE0	102	5510	MCS0	20.25	19.97
		118	5590		20.50	20.28
		134	5670		20.50	20.40
		142	5710		20.50	20.40
	802.11ac80-VHT0	106	5530	MCS0	18.75	18.73
		122	5610		20.50	20.38
		138	5690		20.50	20.44
	802.11ax80-HE0	106	5530	MCS0	18.75	18.58
122		5610	20.50		20.21	
138		5690	20.50		20.34	
802.11ac160-VHT0	114	5570	MCS0	15.50	15.24	
802.11ax160-HE0	114	5570	MCS0	15.50	15.34	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Aux						
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.8GHz	802.11a	149	5745	6Mbps	20.50	20.24
		157	5785		20.50	20.30
		165	5825		20.50	20.30
	802.11n20-HT0	149	5745	MCS0	20.50	20.31
		157	5785		20.50	20.27
		165	5825		20.50	20.22
	802.11ax20-HE0	149	5745	MCS0	20.50	20.23
		157	5785		20.50	20.40
		165	5825		20.50	20.34
	802.11n40-HT0	151	5755	MCS0	20.50	20.41
		159	5795		20.50	20.48
	802.11ax40-HE0	151	5755	MCS0	20.50	20.29
		159	5795		20.50	20.31
	802.11ac80-VHT0	155	5775	MCS0	20.25	20.01
802.11ax80-HE0	155	5775	MCS0	20.25	19.97	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. | No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

Tablet mode

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
2.45GHz	802.11b	1	2412	1Mbps	15.00	14.98
		6	2437		15.00	14.95
		11	2462		15.00	14.96
	802.11g	1	2412	6Mbps	15.00	14.87
		6	2437		15.00	14.80
		11	2462		15.00	14.84
	802.11n20-HT0	1	2412	MCS0	15.00	14.91
		6	2437		15.00	14.82
		11	2462		15.00	14.87
	802.11ax20-HE0	1	2412	MCS0	15.00	14.86
		6	2437		15.00	14.79
		11	2462		15.00	14.82
	802.11n40-HT0	3	2422	MCS0	15.00	14.83
		6	2437		15.00	14.95
		9	2452		15.00	14.79
802.11ax40-HE0	3	2422	MCS0	15.00	14.90	
	6	2437		15.00	14.83	
	9	2452		15.00	14.78	

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.15-5.25 GHz	802.11a	36	5180	6Mbps	8.00	7.86
		40	5200		8.00	7.93
		44	5220		8.00	7.76
		48	5240		8.00	7.95
	802.11n20-HT0	36	5180	MCS0	8.00	7.81
		40	5200		8.00	7.95
		44	5220		8.00	7.91
		48	5240		8.00	7.88
	802.11ax20-HE0	36	5180	MCS0	8.00	7.82
		40	5200		8.00	7.93
		44	5220		8.00	7.84
		48	5240		8.00	7.78
	802.11n40-HT0	38	5190	MCS0	8.00	7.86
		46	5230		8.00	7.92
	802.11ax40-HE0	38	5190	MCS0	8.00	7.92
		46	5230		8.00	7.87
	802.11ac80-VHT0	42	5210	MCS0	8.00	7.92
	802.11ax80-HE0	42	5210	MCS0	8.00	7.86
802.11ac160-VHT0	50	5250	MCS0	8.00	7.97	
802.11ax160-HE0	50	5250	MCS0	8.00	7.90	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.25-5.35 GHz	802.11a	52	5260	6Mbps	8.00	7.76
		56	5280		8.00	7.83
		60	5300		8.00	7.78
		64	5320		8.00	7.82
	802.11n20-HT0	52	5260	MCS0	8.00	7.88
		56	5280		8.00	7.75
		60	5300		8.00	7.89
	802.11ax20-HE0	64	5320	MCS0	8.00	7.81
		52	5260		8.00	7.83
		56	5280		8.00	7.80
		60	5300		8.00	7.73
	802.11n40-HT0	64	5320	MCS0	8.00	7.86
		54	5270		8.00	7.70
		62	5310		8.00	7.70
802.11ax40-HE0	54	5270	MCS0	8.00	7.83	
	62	5310		8.00	7.81	
802.11ac80-VHT0	58	5290	MCS0	8.00	7.93	
802.11ax80-HE0	58	5290	MCS0	8.00	7.80	

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.6GHz	802.11a	100	5500	6Mbps	8.00	7.94
		120	5600		8.00	7.80
		140	5700		8.00	7.76
		144	5720		8.00	7.81
	802.11n20-HT0	100	5500	MCS0	8.00	7.78
		120	5600		8.00	7.93
		140	5700		8.00	7.75
		144	5720		8.00	7.92
	802.11ax20-HE0	100	5500	MCS0	8.00	7.90
		120	5600		8.00	7.83
		140	5700		8.00	7.88
		144	5720		8.00	7.94
	802.11n40-HT0	102	5510	MCS0	8.00	7.88
		118	5590		8.00	7.91
		134	5670		8.00	7.82
		142	5710		8.00	7.81
	802.11ax40-HE0	102	5510	MCS0	8.00	7.92
		118	5590		8.00	7.80
		134	5670		8.00	7.88
		142	5710		8.00	7.78
	802.11ac80-VHT0	106	5530	MCS0	8.00	7.96
		122	5610		8.00	7.87
		138	5690		8.00	7.99
	802.11ax80-HE0	106	5530	MCS0	8.00	7.83
122		5610	8.00		7.84	
138		5690	8.00		7.81	
802.11ac160-VHT0	114	5570	MCS0	8.00	7.91	
802.11ax160-HE0	114	5570	MCS0	8.00	7.94	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Main						
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.8GHz	802.11a	149	5745	6Mbps	8.00	7.89
		157	5785		8.00	7.83
		165	5825		8.00	7.83
	802.11n20-HT0	149	5745	MCS0	8.00	7.80
		157	5785		8.00	7.75
		165	5825		8.00	7.87
	802.11ax20-HE0	149	5745	MCS0	8.00	7.74
		157	5785		8.00	7.78
		165	5825		8.00	7.77
	802.11n40-HT0	151	5755	MCS0	8.00	7.84
		159	5795		8.00	7.83
	802.11ax40-HE0	151	5755	MCS0	8.00	7.87
		159	5795		8.00	7.72
	802.11ac80-VHT0	155	5775	MCS0	8.00	7.92
802.11ax80-HE0	155	5775	MCS0	8.00	7.84	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
2.45GHz	802.11b	1	2412	1Mbps	16.50	16.42
		6	2437		16.50	16.46
		11	2462		16.50	16.45
	802.11g	1	2412	6Mbps	16.50	16.38
		6	2437		16.50	16.32
		11	2462		16.50	16.35
	802.11n20-HT0	1	2412	MCS0	16.50	16.34
		6	2437		16.50	16.39
		11	2462		16.50	16.37
	802.11ax20-HE0	1	2412	MCS0	16.50	16.26
		6	2437		16.50	16.34
		11	2462		16.50	16.35
	802.11n40-HT0	3	2422	MCS0	16.50	16.32
		6	2437		16.50	16.42
		9	2452		16.50	16.44
	802.11ax40-HE0	3	2422	MCS0	16.50	16.33
6		2437	16.50		16.30	
9		2452	16.50		16.32	

WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.15-5.25 GHz	802.11a	36	5180	6Mbps	9.00	8.75
		40	5200		9.00	8.86
		44	5220		9.00	8.81
		48	5240		9.00	8.75
	802.11n20-HT0	36	5180	MCS0	9.00	8.86
		40	5200		9.00	8.75
		44	5220		9.00	8.81
		48	5240		9.00	8.87
	802.11ax20-HE0	36	5180	MCS0	9.00	8.80
		40	5200		9.00	8.83
		44	5220		9.00	8.80
		48	5240		9.00	8.78
	802.11n40-HT0	38	5190	MCS0	9.00	8.71
		46	5230		9.00	8.73
	802.11ax40-HE0	38	5190	MCS0	9.00	8.79
		46	5230		9.00	8.73
802.11ac80-VHT0	42	5210	MCS0	9.00	8.85	
802.11ax80-HE0	42	5210	MCS0	9.00	8.76	
802.11ac160-VHT0	50	5250	MCS0	9.00	8.90	
802.11ax160-HE0	50	5250	MCS0	9.00	8.78	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.25-5.35 GHz	802.11a	52	5260	6Mbps	9.00	8.77
		56	5280		9.00	8.72
		60	5300		9.00	8.74
		64	5320		9.00	8.75
	802.11n20-HTO	52	5260	MCS0	9.00	8.74
		56	5280		9.00	8.79
		60	5300		9.00	8.75
		64	5320		9.00	8.80
	802.11ax20-HE0	52	5260	MCS0	9.00	8.78
		56	5280		9.00	8.66
		60	5300		9.00	8.81
		64	5320		9.00	8.83
	802.11n40-HTO	54	5270	MCS0	9.00	8.79
		62	5310		9.00	8.83
	802.11ax40-HE0	54	5270	MCS0	9.00	8.66
		62	5310		9.00	8.67
802.11ac80-VHT0	58	5290	MCS0	9.00	8.87	
802.11ax80-HE0	58	5290	MCS0	9.00	8.66	
WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.6GHz	802.11a	100	5500	6Mbps	9.00	8.77
		120	5600		9.00	8.92
		140	5700		9.00	8.81
		144	5720		9.00	8.94
	802.11n20-HTO	100	5500	MCS0	9.00	8.82
		120	5600		9.00	8.83
		140	5700		9.00	8.95
		144	5720		9.00	8.81
	802.11ax20-HE0	100	5500	MCS0	9.00	8.83
		120	5600		9.00	8.88
		140	5700		9.00	8.95
		144	5720		9.00	8.90
	802.11n40-HTO	102	5510	MCS0	9.00	8.79
		118	5590		9.00	8.95
		134	5670		9.00	8.79
		142	5710		9.00	8.85
	802.11ax40-HE0	102	5510	MCS0	9.00	8.88
		118	5590		9.00	8.84
		134	5670		9.00	8.86
		142	5710		9.00	8.84
	802.11ac80-VHT0	106	5530	MCS0	9.00	8.93
		122	5610		9.00	8.88
		138	5690		9.00	8.97
	802.11ax80-HE0	106	5530	MCS0	9.00	8.87
122		5610	9.00		8.79	
138		5690	9.00		8.83	
802.11ac160-VHT0	114	5570	MCS0	9.00	8.93	
802.11ax160-HE0	114	5570	MCS0	9.00	8.90	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Aux						
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
5.8GHz	802.11a	149	5745	6Mbps	9.00	8.85
		157	5785		9.00	8.85
		165	5825		9.00	8.74
	802.11n20-HT0	149	5745	MCS0	9.00	8.72
		157	5785		9.00	8.80
		165	5825		9.00	8.89
	802.11ax20-HE0	149	5745	MCS0	9.00	8.77
		157	5785		9.00	8.89
		165	5825		9.00	8.88
	802.11n40-HT0	151	5755	MCS0	9.00	8.75
		159	5795		9.00	8.71
	802.11ax40-HE0	151	5755	MCS0	9.00	8.89
		159	5795		9.00	8.75
	802.11ac80-VHT0	155	5775	MCS0	9.00	8.95
	802.11ax80-HE0	155	5775	MCS0	9.00	8.70

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

6.2 WIFI 6E

Notebook mode

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-5 6.2GHz	802.11ax20-HE0	1	5955	MCS0	5.00	4.88
		45	6175		5.00	4.85
		93	6415		5.00	4.83
	802.11ax40-HE0	3	5965	MCS0	8.25	8.11
		43	6165		8.25	8.04
		91	6405		8.25	8.09
	802.11ax80-HE0	7	5985	MCS0	10.75	10.66
		39	6145		10.75	10.65
		87	6385		10.75	10.50
	802.11ax160-HE0	15	6025	MCS0	13.50	13.48
		47	6185		13.50	13.44
		79	6345		13.50	13.47
WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-6 6.5GHz	802.11ax20-HE0	97	6435	MCS0	5.00	4.90
		105	6475		5.00	4.79
		113	6515		5.00	4.77
	802.11ax40-HE0	99	6445	MCS0	8.25	8.13
		107	6485		8.25	8.10
	802.11ax80-HE0	103	6465	MCS0	10.75	10.51
		119	6545		10.75	10.53
	802.11ax160-HE0	111	6505	MCS0	13.50	13.48

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-7 6.7GHz	802.11ax20-HE0	117	6535	MCS0	4.25	4.12
		149	6695		4.25	4.17
		181	6855		4.25	4.12
	802.11ax40-HE0	115	6525	MCS0	8.25	8.14
		147	6685		7.50	7.30
		179	6845		7.50	7.38
	802.11ax80-HE0	135	6625	MCS0	10.00	9.80
		151	6705		10.00	9.75
		167	6785		10.00	9.91
	802.11ax160-HE0	143	6665	MCS0	12.75	12.70
		175	6825		12.75	12.74
	WLAN Main					
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-8 7.0GHz	802.11ax20-HE0	185	6875	MCS0	4.25	4.16
		209	6995		4.25	4.11
		233	7115		-1.00	-1.20
	802.11ax40-HE0	187	6885	MCS0	7.50	7.31
		227	7085		7.50	7.40
	802.11ax80-HE0	183	6865	MCS0	10.00	9.76
		199	6945		10.00	9.87
		215	7025		10.00	9.82
	802.11ax160-HE0	207	6985	MCS0	12.75	12.74

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-5 6.2GHz	802.11ax20-HE0	1	5955	MCS0	5.00	4.85
		45	6175		5.00	4.83
		93	6415		5.00	4.82
	802.11ax40-HE0	3	5965	MCS0	8.25	8.19
		43	6165		8.25	8.01
		91	6405		8.25	8.12
	802.11ax80-HE0	7	5985	MCS0	10.75	10.65
		39	6145		10.75	10.53
		87	6385		10.75	10.58
	802.11ax160-HE0	15	6025	MCS0	13.50	13.48
		47	6185		13.50	13.28
		79	6345		13.50	13.33
WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-6 6.5GHz	802.11ax20-HE0	97	6435	MCS0	5.00	4.77
		105	6475		5.00	4.76
		113	6515		5.00	4.83
	802.11ax40-HE0	99	6445	MCS0	8.25	8.19
		107	6485		8.25	8.17
	802.11ax80-HE0	103	6465	MCS0	10.75	10.60
		119	6545		10.75	10.51
	802.11ax160-HE0	111	6505	MCS0	13.50	13.42

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-7 6.7GHz	802.11ax20-HE0	117	6535	MCS0	4.25	4.10
		149	6695		4.25	4.03
		181	6855		4.25	4.20
	802.11ax40-HE0	115	6525	MCS0	8.25	8.06
		147	6685		7.50	7.41
		179	6845		7.50	7.36
	802.11ax80-HE0	135	6625	MCS0	10.00	9.75
		151	6705		10.00	9.86
		167	6785		10.00	9.86
	802.11ax160-HE0	143	6665	MCS0	12.75	12.46
		175	6825		12.75	12.54
	WLAN Aux					
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-8 7.0GHz	802.11ax20-HE0	185	6875	MCS0	4.25	4.05
		209	6995		4.25	4.19
		233	7115		-1.00	-1.11
	802.11ax40-HE0	187	6885	MCS0	7.50	7.35
		227	7085		7.50	7.25
	802.11ax80-HE0	183	6865	MCS0	10.00	9.80
		199	6945		10.00	9.89
		215	7025		10.00	9.77
	802.11ax160-HE0	207	6985	MCS0	12.75	12.68

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Tablet mode

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-5 6.2GHz	802.11ax20-HE0	1	5955	MCS0	5.00	4.70
		45	6175		5.00	4.83
		93	6415		5.00	4.90
	802.11ax40-HE0	3	5965	MCS0	8.00	7.76
		43	6165		8.00	7.78
		91	6405		8.00	7.73
	802.11ax80-HE0	7	5985	MCS0	8.00	7.78
		39	6145		8.00	7.90
		87	6385		8.00	7.86
	802.11ax160-HE0	15	6025	MCS0	8.00	7.95
		47	6185		8.00	7.77
		79	6345		8.00	7.81

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-6 6.5GHz	802.11ax20-HE0	97	6435	MCS0	5.00	4.70
		105	6475		5.00	4.77
		113	6515		5.00	4.82
	802.11ax40-HE0	99	6445	MCS0	8.00	7.81
		107	6485		8.00	7.79
	802.11ax80-HE0	103	6465	MCS0	8.00	7.74
		119	6545		8.00	7.81
	802.11ax160-HE0	111	6505	MCS0	8.00	7.84

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Main						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-7 6.7GHz	802.11ax20-HE0	117	6535	MCS0	4.25	4.03
		149	6695		4.25	3.99
		181	6855		4.25	4.01
	802.11ax40-HE0	115	6525	MCS0	8.00	7.86
		147	6685		7.50	7.26
		179	6845		7.50	7.33
	802.11ax80-HE0	135	6625	MCS0	8.00	7.72
		151	6705		8.00	7.90
		167	6785		8.00	7.82
	802.11ax160-HE0	143	6665	MCS0	8.00	7.83
		175	6825		8.00	7.96
	WLAN Main					
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-8 7.0GHz	802.11ax20-HE0	185	6875	MCS0	4.25	4.11
		209	6995		4.25	4.02
		233	7115		-1.00	-1.21
	802.11ax40-HE0	187	6885	MCS0	7.50	7.26
		227	7085		7.50	7.29
	802.11ax80-HE0	183	6865	MCS0	8.00	7.79
		199	6945		8.00	7.86
		215	7025		8.00	7.75
	802.11ax160-HE0	207	6985	MCS0	8.00	7.98

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-5 6.2GHz	802.11ax20-HE0	1	5955	MCS0	5.00	4.80
		45	6175		5.00	4.89
		93	6415		5.00	4.86
	802.11ax40-HE0	3	5965	MCS0	8.25	8.00
		43	6165		8.25	8.09
		91	6405		8.25	7.96
	802.11ax80-HE0	7	5985	MCS0	9.00	8.82
		39	6145		9.00	8.80
		87	6385		9.00	8.78
	802.11ax160-HE0	15	6025	MCS0	9.00	8.96
		47	6185		9.00	8.89
		79	6345		9.00	8.92
WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-6 6.5GHz	802.11ax20-HE0	97	6435	MCS0	5.00	4.80
		105	6475		5.00	4.88
		113	6515		5.00	4.82
	802.11ax40-HE0	99	6445	MCS0	8.25	8.12
		107	6485		8.25	8.12
	802.11ax80-HE0	103	6465	MCS0	9.00	8.74
		119	6545		9.00	8.80
	802.11ax160-HE0	111	6505	MCS0	9.00	8.94

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Aux						
Band	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-7 6.7GHz	802.11ax20-HE0	117	6535	MCS0	4.25	4.05
		149	6695		4.25	4.01
		181	6855		4.25	4.03
	802.11ax40-HE0	115	6525	MCS0	8.25	7.92
		147	6685		7.50	7.30
		179	6845		7.50	7.16
	802.11ax80-HE0	135	6625	MCS0	9.00	8.69
		151	6705		9.00	8.73
		167	6785		9.00	8.73
	802.11ax160-HE0	143	6665	MCS0	9.00	8.83
		175	6825		9.00	8.85
	WLAN Aux					
Mode	Mode	Channel	Frequency (MHz)	Data Rate	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
U-NII-8 7.0GHz	802.11ax20-HE0	185	6875	MCS0	4.25	4.15
		209	6995		4.25	4.00
		233	7115		-1.00	-1.25
	802.11ax40-HE0	187	6885	MCS0	7.50	7.31
		227	7085		7.50	7.34
	802.11ax80-HE0	183	6865	MCS0	9.00	8.86
		199	6945		9.00	8.82
		215	7025		9.00	8.90
	802.11ax160-HE0	207	6985	MCS0	9.00	8.94

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

6.3 Bluetooth

Mode	Channel	Frequency (MHz)	1Mbps		2Mbps		3Mbps	
			Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Average power (dBm)
BR/EDR	CH 00	2402	11.00	9.33	7.00	6.55	7.00	6.61
	CH 39	2441		9.38		6.77		6.80
	CH 78	2480		9.52		6.98		6.86

6.4 BLE


Mode	Channel	Frequency (MHz)	GFSK	
			Max. Rated Avg. Power + Max. Tolerance (dBm)	Average Output Power (dBm)
BLE_1M	CH 00	2402	7	6.77
	CH 19	2440		6.89
	CH 39	2480		6.97
Mode	Channel	Frequency (MHz)	GFSK	
			Max. Rated Avg. Power + Max. Tolerance (dBm)	Average Output Power (dBm)
BLE_2M	CH 00	2402	7	6.94
	CH 19	2440		6.97
	CH 39	2480		6.99

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



7 DUTY CYCLE



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。


This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

8 SUMMARY OF RESULTS

8.1 Decision rules

Reported measurement data comply with Test Methodology in section 1.1.

Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. | No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.sgs.com.tw

Member of SGS Group

8.2 Summary of SAR Results

ASAP

WLAN Main												
Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID	
									Measured	Reported		
WLAN 802.11b	Back Surface	0	1	2412	15.00	14.98	1.01	100.46%	0.631	0.638	001	
WLAN 802.11b	Back Surface	0	6	2437	15.00	14.95	1.01	101.16%	0.532	0.542	-	
WLAN 802.11b	Back Surface	0	11	2462	15.00	14.96	1.01	100.93%	0.511	0.519	-	
WLAN 802.11b	Top Edge	0	1	2412	15.00	14.98	1.01	100.46%	0.462	0.467	-	
WLAN 802.11b	Bottom Edge	0	1	2412	15.00	14.98	1.01	100.46%	0.001	0.001	-	
WLAN 802.11b	Left Edge	0	1	2412	15.00	14.98	1.01	100.46%	0.044	0.045	-	
WLAN 802.11b	Right Edge	0	1	2412	15.00	14.98	1.01	100.46%	0.010	0.010	-	

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(160M) 5.2G	Back Surface	0	50	5250	8.00	7.97	1.01	100.69%	0.190	0.194	-
WLAN 802.11ac(160M) 5.2G	Top Edge	0	50	5250	8.00	7.97	1.01	100.69%	0.385	0.392	002
WLAN 802.11ac(160M) 5.2G	Bottom Edge	0	50	5250	8.00	7.97	1.01	100.69%	0.001	0.001	-
WLAN 802.11ac(160M) 5.2G	Left Edge	0	50	5250	8.00	7.97	1.01	100.69%	0.001	0.001	-
WLAN 802.11ac(160M) 5.2G	Right Edge	0	50	5250	8.00	7.97	1.01	100.69%	0.001	0.001	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(160M) 5.6G	Back Surface	0	114	5570	8.00	7.91	1.01	102.09%	0.214	0.221	-
WLAN 802.11ac(160M) 5.6G	Top Edge	0	114	5570	8.00	7.91	1.01	102.09%	0.349	0.361	004
WLAN 802.11ac(160M) 5.6G	Bottom Edge	0	114	5570	8.00	7.91	1.01	102.09%	0.001	0.001	-
WLAN 802.11ac(160M) 5.6G	Left Edge	0	114	5570	8.00	7.91	1.01	102.09%	0.001	0.001	-
WLAN 802.11ac(160M) 5.6G	Right Edge	0	114	5570	8.00	7.91	1.01	102.09%	0.001	0.001	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(80M) 5.8G	Back Surface	0	155	5775	8.00	7.92	1.01	101.86%	0.156	0.161	-
WLAN 802.11ac(80M) 5.8G	Top Edge	0	155	5775	8.00	7.92	1.01	101.86%	0.245	0.253	005
WLAN 802.11ac(80M) 5.8G	Bottom Edge	0	155	5775	8.00	7.92	1.01	101.86%	0.001	0.001	-
WLAN 802.11ac(80M) 5.8G	Left Edge	0	155	5775	8.00	7.92	1.01	101.86%	0.001	0.001	-
WLAN 802.11ac(80M) 5.8G	Right Edge	0	155	5775	8.00	7.92	1.01	101.86%	0.001	0.001	-

WLAN Aux												
Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID	
									Measured	Reported		
WLAN 802.11b	Back Surface	0	1	2412	16.50	16.42	1.01	101.86%	0.432	0.443	-	
WLAN 802.11b	Back Surface	0	6	2437	16.50	16.46	1.01	100.93%	0.492	0.500	006	
WLAN 802.11b	Back Surface	0	11	2462	16.50	16.45	1.01	101.16%	0.441	0.449	-	
WLAN 802.11b	Top Edge	0	6	2437	16.50	16.46	1.01	100.93%	0.413	0.420	-	
WLAN 802.11b	Bottom Edge	0	6	2437	16.50	16.46	1.01	100.93%	0.001	0.001	-	
WLAN 802.11b	Left Edge	0	6	2437	16.50	16.46	1.01	100.93%	0.020	0.020	-	
WLAN 802.11b	Right Edge	0	6	2437	16.50	16.46	1.01	100.93%	0.033	0.034	-	

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
Bluetooth(GFSK)	Back Surface	0	78	2480	11.00	9.52	1.30	140.60%	0.104	0.189	007
Bluetooth(GFSK)	Top Edge	0	78	2480	11.00	9.52	1.30	140.60%	0.093	0.169	-
Bluetooth(GFSK)	Bottom Edge	0	78	2480	11.00	9.52	1.30	140.60%	0.001	0.002	-
Bluetooth(GFSK)	Left Edge	0	78	2480	11.00	9.52	1.30	140.60%	0.008	0.015	-
Bluetooth(GFSK)	Right Edge	0	78	2480	11.00	9.52	1.30	140.60%	0.011	0.020	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(160M) 5.2G	Back Surface	0	50	5250	9.00	8.90	1.01	102.33%	0.074	0.077	-
WLAN 802.11ac(160M) 5.2G	Top Edge	0	50	5250	9.00	8.90	1.01	102.33%	0.164	0.170	008
WLAN 802.11ac(160M) 5.2G	Bottom Edge	0	50	5250	9.00	8.90	1.01	102.33%	0.001	0.001	-
WLAN 802.11ac(160M) 5.2G	Left Edge	0	50	5250	9.00	8.90	1.01	102.33%	0.001	0.001	-
WLAN 802.11ac(160M) 5.2G	Right Edge	0	50	5250	9.00	8.90	1.01	102.33%	0.027	0.028	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(160M) 5.6G	Back Surface	0	114	5570	9.00	8.93	1.01	101.62%	0.161	0.166	-
WLAN 802.11ac(160M) 5.6G	Top Edge	0	114	5570	9.00	8.93	1.01	101.62%	0.221	0.227	010
WLAN 802.11ac(160M) 5.6G	Bottom Edge	0	114	5570	9.00	8.93	1.01	101.62%	0.001	0.001	-
WLAN 802.11ac(160M) 5.6G	Left Edge	0	114	5570	9.00	8.93	1.01	101.62%	0.001	0.001	-
WLAN 802.11ac(160M) 5.6G	Right Edge	0	114	5570	9.00	8.93	1.01	101.62%	0.030	0.031	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(80M) 5.8G	Back Surface	0	155	5775	9.00	8.95	1.01	101.16%	0.085	0.087	-
WLAN 802.11ac(80M) 5.8G	Top Edge	0	155	5775	9.00	8.95	1.01	101.16%	0.156	0.160	011
WLAN 802.11ac(80M) 5.8G	Bottom Edge	0	155	5775	9.00	8.95	1.01	101.16%	0.001	0.001	-
WLAN 802.11ac(80M) 5.8G	Left Edge	0	155	5775	9.00	8.95	1.01	101.16%	0.001	0.001	-
WLAN 802.11ac(80M) 5.8G	Right Edge	0	155	5775	9.00	8.95	1.01	101.16%	0.027	0.028	-

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WIFI 6E

WLAN Main

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-5 6.2GHz2802.11ax(160M)	Back Surface	0	15	6025	8.00	7.95	1.01	101.16%	0.222	0.227	1.220	1.249	-
U-NII-5 6.2GHz2802.11ax(160M)	Back Surface	0	79	6345	8.00	7.81	1.01	104.47%	0.235	0.248	1.270	1.343	-
U-NII-5 6.2GHz2802.11ax(160M)	Top Edge	0	15	6025	8.00	7.95	1.01	101.16%	0.303	0.310	1.470	1.505	-
U-NII-5 6.2GHz2802.11ax(160M)	Top Edge	0	79	6345	8.00	7.81	1.01	104.47%	0.645	0.682	2.900	3.066	012
U-NII-5 6.2GHz2802.11ax(160M)	Bottom Edge	0	15	6025	8.00	7.95	1.01	101.16%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz2802.11ax(160M)	Bottom Edge	0	79	6345	8.00	7.81	1.01	104.47%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz2802.11ax(160M)	Left Edge	0	15	6025	8.00	7.95	1.01	101.16%	0.012	0.012	0.055	0.056	-
U-NII-5 6.2GHz2802.11ax(160M)	Left Edge	0	79	6345	8.00	7.81	1.01	104.47%	0.015	0.016	0.059	0.062	-
U-NII-5 6.2GHz2802.11ax(160M)	Right Edge	0	15	6025	8.00	7.95	1.01	101.16%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz2802.11ax(160M)	Right Edge	0	79	6345	8.00	7.81	1.01	104.47%	0.001	0.001	0.001	0.001	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-6 6.5GHz2802.11ax(160M)	Back Surface	0	111	6505	8.00	7.84	1.01	103.75%	0.423	0.444	2.240	2.352	-
U-NII-6 6.5GHz2802.11ax(160M)	Top Edge	0	111	6505	8.00	7.84	1.01	103.75%	0.931	0.978	4.830	5.071	013
U-NII-6 6.5GHz2802.11ax(160M)	Bottom Edge	0	111	6505	8.00	7.84	1.01	103.75%	0.001	0.001	0.001	0.001	-
U-NII-6 6.5GHz2802.11ax(160M)	Left Edge	0	111	6505	8.00	7.84	1.01	103.75%	0.029	0.030	0.084	0.088	-
U-NII-6 6.5GHz2802.11ax(160M)	Right Edge	0	111	6505	8.00	7.84	1.01	103.75%	0.001	0.001	0.001	0.001	-
U-NII-6 6.5GHz2802.11ax(160M)	Top Edge*	0	111	6505	8.00	7.84	1.01	103.75%	0.896	0.941	4.680	4.914	-
U-NII-6 6.5GHz2802.11ax(160M)	Top Edge**	0	111	6505	8.00	7.84	1.01	103.75%	0.867	0.910	4.480	4.704	-

* - repeated at the highest SAR measurement according to the KDB 865684 D01

** - Spot-check for EUT with Keyboard in back.

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-7 6.7GHz2802.11ax(160M)	Back Surface	0	175	6825	8.00	7.96	1.01	100.93%	0.255	0.260	1.330	1.358	-
U-NII-7 6.7GHz2802.11ax(160M)	Top Edge	0	175	6825	8.00	7.96	1.01	100.93%	0.675	0.689	3.200	3.268	014
U-NII-7 6.7GHz2802.11ax(160M)	Bottom Edge	0	175	6825	8.00	7.96	1.01	100.93%	0.001	0.001	0.001	0.001	-
U-NII-7 6.7GHz2802.11ax(160M)	Left Edge	0	175	6825	8.00	7.96	1.01	100.93%	0.022	0.022	0.074	0.076	-
U-NII-7 6.7GHz2802.11ax(160M)	Right Edge	0	175	6825	8.00	7.96	1.01	100.93%	0.001	0.001	0.001	0.001	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-8 7.0GHz 802.11ax (160M)	Back Surface	0	207	6985	8.00	7.98	1.01	100.46%	0.175	0.177	1.090	1.103	-
U-NII-8 7.0GHz 802.11ax (160M)	Top Edge	0	207	6985	8.00	7.98	1.01	100.46%	0.423	0.428	2.090	2.114	015
U-NII-8 7.0GHz 802.11ax (160M)	Bottom Edge	0	207	6985	8.00	7.98	1.01	100.46%	0.001	0.001	0.001	0.001	-
U-NII-8 7.0GHz 802.11ax (160M)	Left Edge	0	207	6985	8.00	7.98	1.01	100.46%	0.007	0.007	0.048	0.049	-
U-NII-8 7.0GHz 802.11ax (160M)	Right Edge	0	207	6985	8.00	7.98	1.01	100.46%	0.001	0.001	0.001	0.001	-

WLAN Aux

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-5 6.2GHz2802.11ax(160M)	Back Surface	0	15	6025	9.00	8.96	1.01	100.93%	0.115	0.117	0.789	0.806	-
U-NII-5 6.2GHz2802.11ax(160M)	Back Surface	0	79	6345	9.00	8.92	1.01	101.86%	0.111	0.114	0.786	0.810	-
U-NII-5 6.2GHz2802.11ax(160M)	Top Edge	0	15	6025	9.00	8.96	1.01	100.93%	0.206	0.210	1.240	1.266	016
U-NII-5 6.2GHz2802.11ax(160M)	Top Edge	0	79	6345	9.00	8.92	1.01	101.86%	0.193	0.199	1.190	1.227	-
U-NII-5 6.2GHz2802.11ax(160M)	Bottom Edge	0	15	6025	9.00	8.96	1.01	100.93%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz2802.11ax(160M)	Bottom Edge	0	79	6345	9.00	8.92	1.01	101.86%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz2802.11ax(160M)	Left Edge	0	15	6025	9.00	8.96	1.01	100.93%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz2802.11ax(160M)	Left Edge	0	79	6345	9.00	8.92	1.01	101.86%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz2802.11ax(160M)	Right Edge	0	15	6025	9.00	8.96	1.01	100.93%	0.010	0.010	0.076	0.078	-
U-NII-5 6.2GHz2802.11ax(160M)	Right Edge	0	79	6345	9.00	8.92	1.01	101.86%	0.009	0.010	0.073	0.075	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-6 6.5GHz2802.11ax(160M)	Back Surface	0	111	6505	9.00	8.94	1.01	101.39%	0.123	0.126	0.844	0.866	-
U-NII-6 6.5GHz2802.11ax(160M)	Top Edge	0	111	6505	9.00	8.94	1.01	101.39%	0.320	0.328	1.810	1.857	017
U-NII-6 6.5GHz2802.11ax(160M)	Bottom Edge	0	111	6505	9.00	8.94	1.01	101.39%	0.001	0.001	0.001	0.001	-
U-NII-6 6.5GHz2802.11ax(160M)	Left Edge	0	111	6505	9.00	8.94	1.01	101.39%	0.001	0.001	0.001	0.001	-
U-NII-6 6.5GHz2802.11ax(160M)	Right Edge	0	111	6505	9.00	8.94	1.01	101.39%	0.013	0.013	0.083	0.085	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-7 6.7GHz2802.11ax(160M)	Back Surface	0	175	6825	9.00	8.85	1.01	103.51%	0.155	0.162	0.923	0.967	-
U-NII-7 6.7GHz2802.11ax(160M)	Top Edge	0	175	6825	9.00	8.85	1.01	103.51%	0.618	0.647	3.210	3.363	018
U-NII-7 6.7GHz2802.11ax(160M)	Bottom Edge	0	175	6825	9.00	8.85	1.01	103.51%	0.001	0.001	0.001	0.001	-
U-NII-7 6.7GHz2802.11ax(160M)	Left Edge	0	175	6825	9.00	8.85	1.01	103.51%	0.001	0.001	0.001	0.001	-
U-NII-7 6.7GHz2802.11ax(160M)	Right Edge	0	175	6825	9.00	8.85	1.01	103.51%	0.015	0.016	0.093	0.097	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-8 7.0GHz 802.11ax (160M)	Back Surface	0	207	6985	9.00	8.94	1.01	101.39%	0.147	0.150	0.898	0.917	-
U-NII-8 7.0GHz 802.11ax (160M)	Top Edge	0	207	6985	9.00	8.94	1.01	101.39%	0.678	0.692	3.360	3.431	019
U-NII-8 7.0GHz 802.11ax (160M)	Bottom Edge	0	207	6985	9.00	8.94	1.01	101.39%	0.001	0.001	0.001	0.001	-
U-NII-8 7.0GHz 802.11ax (160M)	Left Edge	0	207	6985	9.00	8.94	1.01	101.39%	0.001	0.001	0.001	0.001	-
U-NII-8 7.0GHz 802.11ax (160M)	Right Edge	0	207	6985	9.00	8.94	1.01	101.39%	0.017	0.017	0.099	0.101	-

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

INPAQ

WLAN Main

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11b	Back Surface	0	1	2412	15.00	14.98	1.01	100.46%	0.583	0.590	020
WLAN 802.11b	Back Surface	0	6	2437	15.00	14.95	1.01	101.16%	0.560	0.570	-
WLAN 802.11b	Back Surface	0	11	2462	15.00	14.96	1.01	100.93%	0.571	0.580	-
WLAN 802.11b	Top Edge	0	1	2412	15.00	14.98	1.01	100.46%	0.572	0.579	-
WLAN 802.11b	Bottom Edge	0	1	2412	15.00	14.98	1.01	100.46%	0.001	0.001	-
WLAN 802.11b	Left Edge	0	1	2412	15.00	14.98	1.01	100.46%	0.035	0.035	-
WLAN 802.11b	Right Edge	0	1	2412	15.00	14.98	1.01	100.46%	0.032	0.032	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(160M) 5.2G	Back Surface	0	50	5250	8.00	7.97	1.01	100.69%	0.112	0.114	-
WLAN 802.11ac(160M) 5.2G	Top Edge	0	50	5250	8.00	7.97	1.01	100.69%	0.377	0.384	021
WLAN 802.11ac(160M) 5.2G	Bottom Edge	0	50	5250	8.00	7.97	1.01	100.69%	0.001	0.001	-
WLAN 802.11ac(160M) 5.2G	Left Edge	0	50	5250	8.00	7.97	1.01	100.69%	0.001	0.001	-
WLAN 802.11ac(160M) 5.2G	Right Edge	0	50	5250	8.00	7.97	1.01	100.69%	0.001	0.001	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(160M) 5.6G	Back Surface	0	114	5570	8.00	7.91	1.01	102.09%	0.298	0.308	-
WLAN 802.11ac(160M) 5.6G	Top Edge	0	114	5570	8.00	7.91	1.01	102.09%	0.436	0.450	023
WLAN 802.11ac(160M) 5.6G	Bottom Edge	0	114	5570	8.00	7.91	1.01	102.09%	0.001	0.001	-
WLAN 802.11ac(160M) 5.6G	Left Edge	0	114	5570	8.00	7.91	1.01	102.09%	0.001	0.001	-
WLAN 802.11ac(160M) 5.6G	Right Edge	0	114	5570	8.00	7.91	1.01	102.09%	0.001	0.001	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(80M) 5.8G	Back Surface	0	155	5775	8.00	7.92	1.01	101.86%	0.084	0.087	-
WLAN 802.11ac(80M) 5.8G	Top Edge	0	155	5775	8.00	7.92	1.01	101.86%	0.301	0.310	024
WLAN 802.11ac(80M) 5.8G	Bottom Edge	0	155	5775	8.00	7.92	1.01	101.86%	0.001	0.001	-
WLAN 802.11ac(80M) 5.8G	Left Edge	0	155	5775	8.00	7.92	1.01	101.86%	0.001	0.001	-
WLAN 802.11ac(80M) 5.8G	Right Edge	0	155	5775	8.00	7.92	1.01	101.86%	0.001	0.001	-

WLAN Aux

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11b	Back Surface	0	1	2412	16.50	16.42	1.01	101.86%	0.632	0.648	-
WLAN 802.11b	Back Surface	0	6	2437	16.50	16.46	1.01	100.93%	0.697	0.708	025
WLAN 802.11b	Back Surface	0	11	2462	16.50	16.45	1.01	101.16%	0.629	0.641	-
WLAN 802.11b	Top Edge	0	6	2437	16.50	16.46	1.01	100.93%	0.463	0.471	-
WLAN 802.11b	Bottom Edge	0	6	2437	16.50	16.46	1.01	100.93%	0.001	0.001	-
WLAN 802.11b	Left Edge	0	6	2437	16.50	16.46	1.01	100.93%	0.064	0.065	-
WLAN 802.11b	Right Edge	0	6	2437	16.50	16.46	1.01	100.93%	0.051	0.052	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
Bluetooth(GFSK)	Back Surface	0	78	2480	11.00	9.52	1.30	140.60%	0.193	0.351	026
Bluetooth(GFSK)	Top Edge	0	78	2480	11.00	9.52	1.30	140.60%	0.111	0.202	-
Bluetooth(GFSK)	Bottom Edge	0	78	2480	11.00	9.52	1.30	140.60%	0.001	0.002	-
Bluetooth(GFSK)	Left Edge	0	78	2480	11.00	9.52	1.30	140.60%	0.011	0.020	-
Bluetooth(GFSK)	Right Edge	0	78	2480	11.00	9.52	1.30	140.60%	0.014	0.025	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(160M) 5.2G	Back Surface	0	50	5250	9.00	8.90	1.01	102.33%	0.073	0.076	-
WLAN 802.11ac(160M) 5.2G	Top Edge	0	50	5250	9.00	8.90	1.01	102.33%	0.176	0.182	027
WLAN 802.11ac(160M) 5.2G	Bottom Edge	0	50	5250	9.00	8.90	1.01	102.33%	0.001	0.001	-
WLAN 802.11ac(160M) 5.2G	Left Edge	0	50	5250	9.00	8.90	1.01	102.33%	0.001	0.001	-
WLAN 802.11ac(160M) 5.2G	Right Edge	0	50	5250	9.00	8.90	1.01	102.33%	0.030	0.031	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(160M) 5.6G	Back Surface	0	114	5570	9.00	8.93	1.01	101.62%	0.316	0.325	-
WLAN 802.11ac(160M) 5.6G	Top Edge	0	114	5570	9.00	8.93	1.01	101.62%	0.335	0.345	029
WLAN 802.11ac(160M) 5.6G	Bottom Edge	0	114	5570	9.00	8.93	1.01	101.62%	0.001	0.001	-
WLAN 802.11ac(160M) 5.6G	Left Edge	0	114	5570	9.00	8.93	1.01	101.62%	0.001	0.001	-
WLAN 802.11ac(160M) 5.6G	Right Edge	0	114	5570	9.00	8.93	1.01	101.62%	0.001	0.001	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		ID
									Measured	Reported	
WLAN 802.11ac(80M) 5.8G	Back Surface	0	155	5775	9.00	8.95	1.01	101.16%	0.119	0.122	-
WLAN 802.11ac(80M) 5.8G	Top Edge	0	155	5775	9.00	8.95	1.01	101.16%	0.214	0.219	030
WLAN 802.11ac(80M) 5.8G	Bottom Edge	0	155	5775	9.00	8.95	1.01	101.16%	0.001	0.001	-
WLAN 802.11ac(80M) 5.8G	Left Edge	0	155	5775	9.00	8.95	1.01	101.16%	0.001	0.001	-
WLAN 802.11ac(80M) 5.8G	Right Edge	0	155	5775	9.00	8.95	1.01	101.16%	0.042	0.043	-

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WIFI 6E

WLAN Main

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-5 6.2GHz802.11ax(160M)	Back Surface	0	15	6025	8.00	7.95	1.01	101.16%	0.219	0.224	1.110	1.136	-
U-NII-5 6.2GHz802.11ax(160M)	Back Surface	0	79	6345	8.00	7.81	1.01	104.47%	0.225	0.238	1.250	1.322	-
U-NII-5 6.2GHz802.11ax(160M)	Top Edge	0	15	6025	8.00	7.95	1.01	101.16%	0.238	0.244	1.250	1.280	-
U-NII-5 6.2GHz802.11ax(160M)	Top Edge	0	79	6345	8.00	7.81	1.01	104.47%	0.519	0.549	2.360	2.495	031
U-NII-5 6.2GHz802.11ax(160M)	Bottom Edge	0	15	6025	8.00	7.95	1.01	101.16%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz802.11ax(160M)	Bottom Edge	0	79	6345	8.00	7.81	1.01	104.47%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz802.11ax(160M)	Left Edge	0	15	6025	8.00	7.95	1.01	101.16%	0.009	0.009	0.039	0.040	-
U-NII-5 6.2GHz802.11ax(160M)	Left Edge	0	79	6345	8.00	7.81	1.01	104.47%	0.007	0.008	0.037	0.039	-
U-NII-5 6.2GHz802.11ax(160M)	Right Edge	0	15	6025	8.00	7.95	1.01	101.16%	0.004	0.005	0.022	0.023	-
U-NII-5 6.2GHz802.11ax(160M)	Right Edge	0	79	6345	8.00	7.81	1.01	104.47%	0.005	0.005	0.024	0.025	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-6 6.5GHz802.11ax(160M)	Back Surface	0	111	6505	8.00	7.84	1.01	103.75%	0.313	0.329	1.970	2.068	-
U-NII-6 6.5GHz802.11ax(160M)	Top Edge	0	111	6505	8.00	7.84	1.01	103.75%	0.585	0.614	2.730	2.866	032
U-NII-6 6.5GHz802.11ax(160M)	Bottom Edge	0	111	6505	8.00	7.84	1.01	103.75%	0.001	0.001	0.001	0.001	-
U-NII-6 6.5GHz802.11ax(160M)	Left Edge	0	111	6505	8.00	7.84	1.01	103.75%	0.016	0.017	0.045	0.047	-
U-NII-6 6.5GHz802.11ax(160M)	Right Edge	0	111	6505	8.00	7.84	1.01	103.75%	0.006	0.007	0.001	0.001	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-7 6.7GHz802.11ax(160M)	Back Surface	0	175	6825	8.00	7.96	1.01	100.93%	0.322	0.329	2.040	2.084	-
U-NII-7 6.7GHz802.11ax(160M)	Top Edge	0	175	6825	8.00	7.96	1.01	100.93%	0.629	0.642	3.080	3.146	033
U-NII-7 6.7GHz802.11ax(160M)	Bottom Edge	0	175	6825	8.00	7.96	1.01	100.93%	0.001	0.001	0.001	0.001	-
U-NII-7 6.7GHz802.11ax(160M)	Left Edge	0	175	6825	8.00	7.96	1.01	100.93%	0.016	0.016	0.046	0.047	-
U-NII-7 6.7GHz802.11ax(160M)	Right Edge	0	175	6825	8.00	7.96	1.01	100.93%	0.007	0.007	0.001	0.001	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-8 7.0GHz 802.11ax (160M)	Back Surface	0	207	6985	8.00	7.98	1.01	100.46%	0.344	0.348	1.820	1.841	-
U-NII-8 7.0GHz 802.11ax (160M)	Top Edge	0	207	6985	8.00	7.98	1.01	100.46%	0.404	0.409	2.070	2.094	034
U-NII-8 7.0GHz 802.11ax (160M)	Bottom Edge	0	207	6985	8.00	7.98	1.01	100.46%	0.001	0.001	0.001	0.001	-
U-NII-8 7.0GHz 802.11ax (160M)	Left Edge	0	207	6985	8.00	7.98	1.01	100.46%	0.005	0.005	0.035	0.035	-
U-NII-8 7.0GHz 802.11ax (160M)	Right Edge	0	207	6985	8.00	7.98	1.01	100.46%	0.005	0.005	0.046	0.047	-

WLAN Aux

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-5 6.2GHz802.11ax(160M)	Back Surface	0	15	6025	9.00	8.96	1.01	100.93%	0.121	0.124	0.813	0.830	-
U-NII-5 6.2GHz802.11ax(160M)	Back Surface	0	79	6345	9.00	8.92	1.01	101.86%	0.114	0.118	0.791	0.815	-
U-NII-5 6.2GHz802.11ax(160M)	Top Edge	0	15	6025	9.00	8.96	1.01	100.93%	0.237	0.242	1.480	1.512	035
U-NII-5 6.2GHz802.11ax(160M)	Top Edge	0	79	6345	9.00	8.92	1.01	101.86%	0.208	0.214	1.240	1.278	-
U-NII-5 6.2GHz802.11ax(160M)	Bottom Edge	0	15	6025	9.00	8.96	1.01	100.93%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz802.11ax(160M)	Bottom Edge	0	79	6345	9.00	8.92	1.01	101.86%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz802.11ax(160M)	Left Edge	0	15	6025	9.00	8.96	1.01	100.93%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz802.11ax(160M)	Left Edge	0	79	6345	9.00	8.92	1.01	101.86%	0.001	0.001	0.001	0.001	-
U-NII-5 6.2GHz802.11ax(160M)	Right Edge	0	15	6025	9.00	8.96	1.01	100.93%	0.007	0.007	0.059	0.060	-
U-NII-5 6.2GHz802.11ax(160M)	Right Edge	0	79	6345	9.00	8.92	1.01	101.86%	0.006	0.007	0.055	0.057	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-6 6.5GHz802.11ax(160M)	Back Surface	0	111	6505	9.00	8.94	1.01	101.39%	0.154	0.158	1.030	1.057	-
U-NII-6 6.5GHz802.11ax(160M)	Top Edge	0	111	6505	9.00	8.94	1.01	101.39%	0.347	0.356	2.110	2.165	036
U-NII-6 6.5GHz802.11ax(160M)	Bottom Edge	0	111	6505	9.00	8.94	1.01	101.39%	0.001	0.001	0.001	0.001	-
U-NII-6 6.5GHz802.11ax(160M)	Left Edge	0	111	6505	9.00	8.94	1.01	101.39%	0.001	0.001	0.001	0.001	-
U-NII-6 6.5GHz802.11ax(160M)	Right Edge	0	111	6505	9.00	8.94	1.01	101.39%	0.009	0.009	0.077	0.079	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-7 6.7GHz802.11ax(160M)	Back Surface	0	175	6825	9.00	8.85	1.01	103.51%	0.100	0.105	0.848	0.888	-
U-NII-7 6.7GHz802.11ax(160M)	Top Edge	0	143	6665	9.00	8.83	1.01	103.99%	0.420	0.442	2.430	2.557	-
U-NII-7 6.7GHz802.11ax(160M)	Top Edge	0	175	6825	9.00	8.85	1.01	103.51%	0.454	0.476	2.470	2.587	037
U-NII-7 6.7GHz802.11ax(160M)	Bottom Edge	0	175	6825	9.00	8.85	1.01	103.51%	0.001	0.001	0.001	0.001	-
U-NII-7 6.7GHz802.11ax(160M)	Left Edge	0	175	6825	9.00	8.85	1.01	103.51%	0.001	0.001	0.001	0.001	-
U-NII-7 6.7GHz802.11ax(160M)	Right Edge	0	175	6825	9.00	8.85	1.01	103.51%	0.012	0.013	0.085	0.089	-

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Duty cycle scaling	Power scaling	Averaged SAR over 1g (W/kg)		Estimated Measured APD W/m ² (4cm ²)	Estimated Reported APD W/m ² (4cm ²)	ID
									Measured	Reported			
U-NII-8 7.0GHz 802.11ax (160M)	Back Surface	0	207	6985	9.00	8.94	1.01	101.39%	0.215	0.220	1.090	1.103	-
U-NII-8 7.0GHz 802.11ax (160M)	Top Edge	0	207	6985	9.00	8.94	1.01	101.39%	0.377	0.385	2.020	2.062	038
U-NII-8 7.0GHz 802.11ax (160M)	Bottom Edge	0	207	6985	9.00	8.94	1.01	101.39%	0.001	0.001	0.002	0.002	-
U-NII-8 7.0GHz 802.11ax (160M)	Left Edge	0	207	6985	9.00	8.94	1.01	101.39%	0.001	0.001	0.005	0.005	-
U-NII-8 7.0GHz 802.11ax (160M)	Right Edge	0	207	6985	9.00	8.94	1.01	101.39%	0.010	0.010	0.066	0.067	-

Note:

Reported SAR = measured SAR * Power scaling * Duty cycle scaling

Reported APD = measured APD * Power scaling * Duty cycle scaling

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

8.3 Summary of PD Results

ASAP

WLAN Main

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Tune-up Scaling	Duty cycle scaling	Measurement uncertainty	PD result(4cm)				ID
										Measured Total psPD (W/m ²)	Reported Total psPD (W/m ²)	Measured Normal psPD (W/m ²)	Reported Normal psPD (W/m ²)	
WLAN 6E 802.11ax(160M) U-NII-5	Top Edge	2	15	6025	8.00	7.95	101.16%	1.01	1.55	1.050	1.666	1.000	1.587	-
	Top Edge	2	79	6345	8.00	7.81	104.47%	1.01	1.55	1.350	2.212	1.110	1.819	039
WLAN 6E 802.11ax(160M) U-NII-6	Top Edge	2	111	6505	8.00	7.84	103.75%	1.01	1.55	2.120	3.450	1.950	3.174	040
WLAN 6E 802.11ax(160M) U-NII-7	Top Edge	2	175	6825	8.00	7.96	100.93%	1.01	1.55	2.300	3.641	1.970	3.119	041
WLAN 6E 802.11ax(160M) U-NII-8	Top Edge	2	207	6985	8.00	7.98	100.46%	1.01	1.55	2.070	3.262	1.830	2.884	042

WLAN Aux

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Tune-up Scaling	Duty cycle scaling	Measurement uncertainty	PD result(4cm)				ID
										Measured Total psPD (W/m ²)	Reported Total psPD (W/m ²)	Measured Normal psPD (W/m ²)	Reported Normal psPD (W/m ²)	
WLAN 6E 802.11ax(160M) U-NII-5	Top Edge	2	15	6025	9.00	8.96	100.93%	1.01	1.55	1.730	2.739	1.570	2.485	043
	Top Edge	2	79	6345	9.00	8.92	101.86%	1.01	1.55	1.450	2.317	1.400	2.237	-
WLAN 6E 802.11ax(160M) U-NII-6	Top Edge	2	111	6505	9.00	8.94	101.39%	1.01	1.55	2.060	3.276	1.900	3.022	044
WLAN 6E 802.11ax(160M) U-NII-7	Top Edge	2	175	6825	9.00	8.85	103.51%	1.01	1.55	2.470	4.011	2.280	3.702	045
WLAN 6E 802.11ax(160M) U-NII-8	Top Edge	2	207	6985	9.00	8.94	101.39%	1.01	1.55	2.380	3.785	2.190	3.483	046

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

WLAN Main

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Tune-up Scaling	Duty cycle scaling	Measurement uncertainty	PD result(4cm)				ID
										Measured Total psPD (W/m ²)	Reported Total psPD (W/m ²)	Measured Normal psPD (W/m ²)	Reported Normal psPD (W/m ²)	
WLAN 6E 802.11ax(160M) U-NII-5	Top Edge	2	15	6025	8.00	7.95	101.16%	1.01	1.55	0.714	1.133	0.457	0.725	-
	Top Edge	2	79	6345	8.00	7.81	104.47%	1.01	1.55	1.250	2.048	1.080	1.770	047
WLAN 6E 802.11ax(160M) U-NII-6	Top Edge	2	111	6505	8.00	7.84	103.75%	1.01	1.55	1.100	1.790	0.826	1.344	048
WLAN 6E 802.11ax(160M) U-NII-7	Top Edge	2	175	6825	8.00	7.96	100.93%	1.01	1.55	2.450	3.879	2.110	3.340	049
WLAN 6E 802.11ax(160M) U-NII-8	Top Edge	2	207	6985	8.00	7.98	100.46%	1.01	1.55	1.950	3.073	1.760	2.773	050

WLAN Aux

Mode	Position	Distance (mm)	Channel	Freq. (MHz)	Max. Rated Avg. Power + Max. Tolerance (dBm)	Measured Avg. Power (dBm)	Tune-up Scaling	Duty cycle scaling	Measurement uncertainty	PD result(4cm)				ID
										Measured Total psPD (W/m ²)	Reported Total psPD (W/m ²)	Measured Normal psPD (W/m ²)	Reported Normal psPD (W/m ²)	
WLAN 6E 802.11ax(160M) U-NII-5	Top Edge	2	15	6025	9.00	8.96	100.93%	1.01	1.55	1.840	2.913	1.600	2.533	051
	Top Edge	2	79	6345	9.00	8.92	101.86%	1.01	1.55	1.390	2.221	1.270	2.029	-
WLAN 6E 802.11ax(160M) U-NII-6	Top Edge	2	111	6505	9.00	8.94	101.39%	1.01	1.55	2.090	3.324	1.810	2.879	052
WLAN 6E 802.11ax(160M) U-NII-7	Top Edge	2	175	6825	9.00	8.85	103.51%	1.01	1.55	2.550	4.140	2.260	3.670	053
WLAN 6E 802.11ax(160M) U-NII-8	Top Edge	2	207	6985	9.00	8.94	101.39%	1.01	1.55	1.880	2.990	1.650	2.624	054

Note:

Reported PD = measured PD * Power scaling * Duty cycle scaling * Uncertainty scaling

8.4 Reporting statements of conformity

The conformity statement in this report is based solely on the test results, measurement uncertainty is excluded.

8.5 Conclusion

The device is compliant because all the standalone results are less than their corresponding criteria.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

9 SIMULTANEOUS TRANSMISSION ANALYSIS

9.1 Simultaneous Transmission Scenarios:

Simultaneous Transmit Configurations	Body
WLAN 2.4GHz Main + BT Aux	Yes
WLAN 2.4GHz Main + WLAN 2.4GHz Aux	Yes
WLAN 5GHz Main + BT Aux	Yes
WLAN 5GHz Main + WLAN 5GHz Aux	Yes
WLAN 5GHz Main + WLAN 5GHz Aux + BT Aux	Yes
WLAN 6GHz Main + BT Aux	Yes
WLAN 6GHz Main + WLAN 6GHz Aux	Yes
WLAN 6GHz Main + WLAN 6GHz Aux + BT Aux	Yes
<p>Note:</p> <ol style="list-style-type: none"> 1. Bluetooth and WLAN Aux share the same antenna path, and BT can transmit with WLAN Main simultaneously. 2. For 2.4/5GHz WLAN Main and Aux antennas, the maximum output power of each antenna during simultaneous transmission is the same with or less than that used in standalone transmission, and we used the sum of 1-g SAR provision in KDB447498D01 to exclude the simultaneous transmitted SAR measurement. 	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

9.2 Estimated SAR calculation

According to KDB447498 D01v06 – When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$\text{Estimated SAR} = \frac{\text{Max. tune up power (mW)}}{\text{Min. test separation distance(mm)}} \times \frac{\sqrt{f(\text{GHz})}}{7.5}$$

If the minimum test separation distance is < 5mm, a distance of 5mm is used for estimated SAR calculation. When the test separation distance is >50mm, the 0.4W/kg is used for SAR-1g.

9.3 SPLSR evaluation and analysis

Per KDB447498D01, when the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR sum to peak location separation ratio(SPLSR).

The simultaneous transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SAR to peak location separation ratio to qualify for test exclusion.

The ratio is determined by $(\text{SAR1} + \text{SAR2})^{1.5}/R_i$, rounded to two decimal digits, and must be ≤ 0.04 for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

SAR1 and SAR2 are the highest reported or estimated SAR for each antenna in the pair, and R_i is the separation distance between the peak SAR locations for the antenna pair in mm.

When standalone test exclusion applies, SAR is estimated; the peak location is assumed to be at the feed-point or geometric center of the antenna.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

Simultaneous Transmission Combination

ASAP

Exposure Position		FCC Reported SAR							Scenario 1	Scenario 2	Scenario 3	Scenario 4	Scenario 5	Scenario 6	Scenario 7	Scenario 8
		1	2	3	4	5	6	7	1+2	1+5	3+4	3+5	3+4+5	6+7	6+8	6+1+7
		2.4GHz WLAN Main 1g SAR (W/kg)	2.4GHz WLAN Aux 1g SAR (W/kg)	5GHz WLAN Main 1g SAR (W/kg)	5GHz WLAN Aux 1g SAR (W/kg)	Bluetooth Aux 1g SAR (W/kg)	6GHz WLAN Main 1g SAR (W/kg)	6GHz WLAN Aux 1g SAR (W/kg)	Summed 1g SAR (W/kg)							
Back Surface	0	0.638	0.500	0.221	0.166	0.189	0.444	0.162	1.138	0.827	0.387	0.410	0.576	0.606	0.633	0.795
Top Edge	0	0.467	0.400	0.362	0.227	0.189	0.978	0.662	0.887	0.636	0.619	0.561	0.788	1.070	1.147	1.230
Bottom Edge	0	0.021	0.021	0.001	0.001	0.002	0.001	0.001	0.002	0.003	0.002	0.003	0.004	0.002	0.003	0.004
Left Edge	0	0.045	0.020	0.001	0.001	0.015	0.030	0.001	0.065	0.060	0.002	0.016	0.017	0.031	0.045	0.046
Right Edge	0	0.010	0.034	0.001	0.032	0.020	0.001	0.017	0.044	0.030	0.033	0.021	0.053	0.018	0.021	0.038

Scenario 8:									
Position	Conditions	SAR Value (W/kg)	Coordinates (cm)			ΣSAR (W/kg)	Peak Location Separation Distance (mm)	SPLSR	Simultaneous Transmission SAR Test
			x	y	z				
Top Edge	WLAN 6E Main	0.978	-7.00	-50.20	-3.99	-	-	-	-
	WLAN 6E Aux	0.692	-14.80	69.60	-4.06	1.670	120.05	0.018	SPLSR ≤ 0.04, Not required
	BT Aux	0.169	-10.80	57.40	-3.97	1.147	107.67	0.011	SPLSR ≤ 0.04, Not required
	WLAN 6E Aux + BT	0.861	-10.80	57.40	-3.97	1.839	107.67	0.023	SPLSR ≤ 0.04, Not required



INPAQ

Exposure Position		FCC Reported SAR							Scenario 1	Scenario 2	Scenario 3	Scenario 4	Scenario 5	Scenario 6	Scenario 7	Scenario 8
		1	2	3	4	5	6	7	1+2	1+5	3+4	3+5	3+4+5	6+7	6+8	6+1+7
		2.4GHz WLAN Main 1g SAR (W/kg)	2.4GHz WLAN Aux 1g SAR (W/kg)	5GHz WLAN Main 1g SAR (W/kg)	5GHz WLAN Aux 1g SAR (W/kg)	Bluetooth Aux 1g SAR (W/kg)	6GHz WLAN Main 1g SAR (W/kg)	6GHz WLAN Aux 1g SAR (W/kg)	Summed 1g SAR (W/kg)							
Back Surface	0	0.590	0.708	0.308	0.325	0.351	0.348	0.220	1.288	0.941	0.633	0.659	0.984	0.668	0.699	0.919
Top Edge	0	0.579	0.471	0.450	0.345	0.202	0.642	0.476	1.050	0.781	0.795	0.652	0.997	1.118	0.844	1.320
Bottom Edge	0	0.001	0.001	0.001	0.001	0.002	0.001	0.001	0.002	0.003	0.002	0.003	0.004	0.002	0.003	0.004
Left Edge	0	0.005	0.005	0.001	0.001	0.009	0.017	0.001	0.019	0.005	0.002	0.021	0.022	0.018	0.037	0.038
Right Edge	0	0.032	0.052	0.001	0.043	0.025	0.007	0.013	0.084	0.057	0.044	0.026	0.069	0.020	0.032	0.045

9.4 Conclusion

The simultaneous transmission is compliant because both SAR sum and/or SPLSR are less than their corresponding criteria.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

10 INSTRUMENTS LIST

Equipment List					
Manufacturer	Device	Type	Serial number	Date of last calibration	Date of next calibration
SPEAG	Data acquisition Electronics	DAE4	1665	Feb/28/2022	Feb/27/2023
SPEAG	Dosimetric E-Field Probe	EX3DV4	7686	Oct/05/2021	Oct/04/2022
SPEAG	Dosimetric E-Field Probe	EX3DV4	7642	Mar/02/2022	Mar/01/2023
SPEAG	E-field Probe for Near Field Application	EUmmWV3	9399	Jan/26/2022	Jan/25/2023
SPEAG	System Validation Dipole	D2450V2	727	Apr/25/2022	Apr/24/2023
SPEAG	System Validation Dipole	D5GHzV2	1023	Jan/27/2022	Jan/26/2023
SPEAG	System Validation Dipole	D6.5GHzV2	1006	Aug/23/2022	Aug/22/2023
SPEAG	System Validation Dipole	D7GHzV2	1007	Aug/24/2022	Aug/23/2023
SPEAG	5G Verification Source 10GHz	5G-Veri10	1021	Jan/24/2022	Jan/23/2023
SPEAG	Dielectric Assessment Kit	DAKS-3.5	1053	Feb/28/2022	Feb/27/2023
R&S	MXG Analog Signal Generator	SMB100A03	182012	Jun/13/2022	Jun/12/2023
Agilent	Dual-directional coupler	772D	MY52180142	Nov/02/2021	Nov/01/2022
Agilent	Dual-directional coupler	778D	MY52180302	Oct/29/2021	Oct/28/2022
R&S	Power Meter	NRX	102034	Dec/28/2021	Dec/27/2022
R&S	Power Sensor	NRP18S	101974	Oct/12/2021	Oct/11/2022
R&S	Power Sensor	NRP18S	109066	Oct/12/2021	Oct/11/2022
R&S	Power Sensor	NRP18S	101973	Jan/22/2022	Jan/21/2023
R&S	Power Sensor	NRP18S	101358	Jan/22/2022	Jan/21/2023
SPEAG	Software	DASY 6 V16.0.2.136	N/A	Calibration not required	Calibration not required
SPEAG	Software	DASY 52 V52.10.4	N/A	Calibration not required	Calibration not required
SPEAG	Software	DASY 6 mmWave V2.4.2.62	N/A	Calibration not required	Calibration not required
SPEAG	Phantom	ELI	N/A	Calibration not required	Calibration not required
SPEAG	Phantom	mmWave Phantom	N/A	Calibration not required	Calibration not required
LKM	Digital thermometer	DTM3000	Nr3192	Nov/09/2021	Nov/08/2022
TECPEL	Digital thermometer	DTM-303A	TP130075	Oct/28/2021	Oct/27/2022

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

11 UNCERTAINTY BUDGET

Measurement Uncertainty evaluation template for DUT SAR test (3-6G)

A	c	D	e		f	g	h=c * f / e	i=c * g / e	k
Source of Uncertainty	Tolerance/ Uncertainty	Probability Distributio	Div	Div Value	ci (1g)	ci (10g)	Standard uncertainty	Standard uncertainty	vi, or Veff
Measurement system									
Probe calibration	6.55%	N	1	1	1	1	6.55%	6.55%	∞
Isotropy , Axial	3.50%	R	√3	1.732	1	1	2.02%	2.02%	∞
Isotropy, Hemispherical	9.60%	R	√3	1.732	1	1	5.54%	5.54%	∞
Modulation Response	2.40%	R	√3	1.732	1	1	1.40%	1.40%	∞
Boundary Effect	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Linearity	4.70%	R	√3	1.732	1	1	2.71%	2.71%	∞
Detection Limits	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Readout Electronics	0.30%	N	1	1	1	1	0.30%	0.30%	∞
Response time	0.80%	R	√3	1.732	1	1	0.46%	0.46%	∞
Integration Time	2.60%	R	√3	1.732	1	1	1.50%	1.50%	∞
Measurement drift (class A evaluation)									
RF ambient condition - noise	3.00%	R	√3	1.732	1	1	1.73%	1.73%	∞
RF ambient conditions - reflections	3.00%	R	√3	1.732	1	1	1.73%	1.73%	∞
Probe positioner	0.40%	R	√3	1.732	1	1	0.23%	0.23%	∞
Mechanical restrictions									
Probe Positioning with respect to phantom shell	2.90%	R	√3	1.732	1	1	1.67%	1.67%	∞
Post-processing	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Max SAR Eval	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Test Sample related									
Test sample positioning	2.90%	N	1	1	1	1	2.90%	2.90%	M-1
Device Holder Uncertainty	3.60%	N	1	1	1	1	3.60%	3.60%	M-1
Drift of output power	5.00%	R	√3	1.732	1	1	2.89%	2.89%	∞
Phantom and Setup									
Phantom Uncertainty	4.00%	R	√3	1.732	1	1	2.31%	2.31%	∞
Liquid permittivity (mea.)	1.05%	N	1	1	0.64	0.43	0.67%	0.45%	M
Liquid Conductivity (mea.)	0.87%	N	1	1	0.6	0.49	0.52%	0.43%	M
Combined standard uncertainty		RSS					11.75%	11.72%	
Expant uncertainty (95% confidence interval), K=2							23.49%	23.45%	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Measurement Uncertainty evaluation template for DUT SAR test (0.3-3G)

A	c	D	e		f	g	h=c * f / e	i=c * g / e	k
Source of Uncertainty	Tolerance/ Uncertainty	Probability/ Distributio	Div	Div Value	ci (1g)	ci (10g)	Standard uncertainty	Standard uncertainty	vi, or Veff
Measurement system									
Probe calibration	6.00%	N	1	1	1	1	6.00%	6.00%	∞
<i>Isotropy , Axial</i>	3.50%	R	√3	1.732	1	1	2.02%	2.02%	∞
<i>Isotropy, Hemispherical</i>	9.60%	R	√3	1.732	1	1	5.54%	5.54%	∞
Modulation Response	2.40%	R	√3	1.732	1	1	1.40%	1.40%	∞
Boundary Effect	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Linearity	4.70%	R	√3	1.732	1	1	2.71%	2.71%	∞
Detection Limits	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Readout Electronics	0.30%	N	1	1	1	1	0.30%	0.30%	∞
Response time	0.80%	R	√3	1.732	1	1	0.46%	0.46%	∞
Integration Time	2.60%	R	√3	1.732	1	1	1.50%	1.50%	∞
Measurement drift (class A evaluation)									
RF ambient condition - noise	3.00%	R	√3	1.732	1	1	1.73%	1.73%	∞
RF ambient conditions - reflections	3.00%	R	√3	1.732	1	1	1.73%	1.73%	∞
Probe positioner Mechanical restrictions	0.40%	R	√3	1.732	1	1	0.23%	0.23%	∞
Probe Positioning with respect to phantom shell	2.90%	R	√3	1.732	1	1	1.67%	1.67%	∞
Post-processing	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Max SAR Eval	1.00%	R	√3	1.732	1	1	0.58%	0.58%	∞
Test Sample related									
Test sample positioning	2.90%	N	1	1	1	1	2.90%	2.90%	M-1
Device Holder Uncertainty	3.60%	N	1	1	1	1	3.60%	3.60%	M-1
Drift of output power	5.00%	R	√3	1.732	1	1	2.89%	2.89%	∞
Phantom and Setup									
Phantom Uncertainty	4.00%	R	√3	1.732	1	1	2.31%	2.31%	∞
Liquid permittivity (mea.)	1.15%	N	1	1	0.64	0.43	0.74%	0.49%	M
Liquid Conductivity (mea.)	0.94%	N	1	1	0.6	0.49	0.56%	0.46%	M
Combined standard uncertainty		RSS					11.46%	11.43%	
Expant uncertainty (95% confidence interval), K=2							22.91%	22.86%	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

DASY6 Uncertainty Budget
According to IEC/IEEE 62209-1528
(Frequency band: 6GHz - 10GHz range)

a	b	c	d		e	e	f=b * e / d	f=b * e / d
Source of Uncertainty	Uncertainty Value (±%)	Probability Distribution	Div.	Div. Value	(ci) 1g	(ci) 10g	Std. uncertainty (1g) (±%)	Std. uncertainty (10g) (±%)
Measurement system errors								
Probe calibration	18.6	N	2	2	1	1	9.3	9.3
Probe Calibration Drift	1.7	R	√3	1.732	1	1	1.0	1.0
Probe Linearity	4.7	R	√3	1.732	1	1	2.7	2.7
Broadband Signal	2.8	R	√3	1.732	1	1	1.6	1.6
Probe Isotropy	7.6	R	√3	1.732	1	1	4.4	4.4
Data Acquisition	0.3	N	1	1	1	1	0.3	0.3
RF Ambient	1.8	N	1	1	1	1	1.8	1.8
Probe positioning	0.2	N	1	1	0.67	0.67	0.1	0.1
Data Processing	3.5	N	1	1	1	1	3.5	3.5
Phantom and device errors								
Conductivity (meas.)DAK	2.5	N	1	1	0.78	0.71	2.0	1.8
Conductivity (temp.)BB	2.4	R	√3	1.732	0.78	0.71	1.1	1.0
Phantom Permittivity	14.0	R	√3	1.732	0.5	0.5	4.0	4.0
Distance DUT - TSL	2.0	N	1	1	2	2	4.0	4.0
Device Positioning (±0.5mm)	1.0	N	1	1	1	1	1.0	1.0
Device Holder	3.6	N	1	1	1	1	3.6	3.6
DUT Modulationm	2.4	R	√3	1.732	1	1	1.4	1.4
Time-average SAR	0.0	R	√3	1.732	1	1	0.0	0.0
DUT drift	2.5	N	1	1	1	1	2.5	2.5
Val Antenna Unc.	0.0	N	1	1	1	1	0.0	0.0
Unc. Input Power	0.0	N	1	1	1	1	0.0	0.0
Correction to the SAR results								
Deviation to Target	1.90	N	1	1	1	0.84	1.9	1.6
SAR scaling	0.987	R	√3	1.732	1	1	0.6	0.6
Combined Std. uncertainty							14.0	13.9
Expanded Std. uncertainty (95% confidence interval), K=2							28.0	27.8

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

**cDASY6 Module mmWave Uncertainty Budget for PD
Evaluation Distances to the Antennas $\geq \lambda / 5$
In Compliance with IEC/IEEE 63195**

a	b	c	d		e	f=b * e / d	g
Source of Uncertainty	Uncertainty Value (+dB)	Probability Distribution	Div.	Div. Value	ci	Std. uncertainty (+dB)	(vi) Veff
Uncertainty terms dependent on the measurement system							
Probe calibration	0.49	N	1	1	1	0.49	∞
Probe correction	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Frequency response (BW \leq 1GHz)	0.20	R	$\sqrt{3}$	1.732	1	0.12	∞
Sensor cross coupling	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Isotropy	0.50	R	$\sqrt{3}$	1.732	1	0.29	∞
Linearity	0.20	R	$\sqrt{3}$	1.732	1	0.12	∞
Probe scattering	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Probe positioning offset	0.30	R	$\sqrt{3}$	1.732	1	0.17	∞
Probe positioning repeatability	0.04	R	$\sqrt{3}$	1.732	1	0.02	∞
Sensor mechanical offset	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Probe spatial resolution	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Field impedance dependence	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Amplitude and phase drift	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Amplitude and phase noise	0.04	R	$\sqrt{3}$	1.732	1	0.02	∞
Measurement area truncation	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Data acquisition	0.03	N	1	1	1	0.03	∞
Sampling	0.00	R	$\sqrt{3}$	1	1	0.00	∞
Field reconstruction	2.00	R	$\sqrt{3}$	1.732	1	1.15	∞
Forward transformation	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Power density scaling	-	R	$\sqrt{3}$	1.732	1	-	∞
Spatial averaging	0.10	R	$\sqrt{3}$	1.732	1	0.06	∞
System detection limit	0.04	R	$\sqrt{3}$	1.732	1	0.02	∞
Uncertainty terms dependent on the DUT and environmental factors							
Probe coupling with DUT	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Modulation response	0.40	R	$\sqrt{3}$	1.732	1	0.23	∞
Integration time	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Response time	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Device holder influence	0.10	R	$\sqrt{3}$	1.732	1	0.06	∞
DUT alignment	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
RF ambient conditions	0.04	R	$\sqrt{3}$	1.732	1	0.02	∞
Ambient reflections	0.04	R	$\sqrt{3}$	1.732	1	0.02	∞
Immunity / secondary reception	0.00	R	$\sqrt{3}$	1.732	1	0.00	∞
Drift of the DUT	-	R	$\sqrt{3}$	1.732	1	-	∞
Combined Std. uncertainty						1.33	
Expanded Std. uncertainty (95% confidence interval), K=2						2.67	

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

12 SAR MEASUREMENT RESULTS

Date: 2022/9/8

ID: 001

Report No. :TESA2208000320ES

WLAN 802.11b_Body_Back Surface_CH 1_Main_0mm

Communication System: WLAN; Frequency: 2412 MHz;Duty Cycle: 1:1.007

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.783$ S/m; $\epsilon_r = 39.689$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient temperature: 22.4°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(8.32, 8.32, 8.32); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (101x131x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.932 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.426 V/m; Power Drift = 0.14 dB



Peak SAR (extrapolated) = 1.44 W/kg

SAR(1 g) = 0.631 W/kg; SAR(10 g) = 0.289 W/kg

Smallest distance from peaks to all points 3 dB below = 8.5 mm

Ratio of SAR at M2 to SAR at M1 = 44.5%

Maximum value of SAR (measured) = 0.969 W/kg



0 dB = 0.969 W/kg = -0.14 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.sgs.com.tw

Member of SGS Group

ID: 002

Report No. :TESA2208000320ES

WLAN 802.11ac(160M) 5.2G_Body_Top Edge_CH 50_Main_0mm

Communication System: WLAN; Frequency: 5250 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5250 \text{ MHz}$; $\sigma = 4.739 \text{ S/m}$; $\epsilon_r = 36.295$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.3°C; Liquid temperature: 22.8°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.81, 5.81, 5.81); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (91x121x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 1.01 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.162 V/m; Power Drift = 0.09 dB



Peak SAR (extrapolated) = 1.70 W/kg

SAR(1 g) = 0.385 W/kg; SAR(10 g) = 0.095 W/kg

Smallest distance from peaks to all points 3 dB below = 5.1 mm

Ratio of SAR at M2 to SAR at M1 = 56.2%

Maximum value of SAR (measured) = 0.844 W/kg



0 dB = 0.844 W/kg = -0.74 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 004

Report No. :TESA2208000320ES

WLAN 802.11ac(160M) 5.6G_Body_Top Edge_CH 114_Main_0mm

Communication System: WLAN; Frequency: 5570 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5570 \text{ MHz}$; $\sigma = 5.069 \text{ S/m}$; $\epsilon_r = 35.886$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.3°C; Liquid temperature: 22.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.16, 5.16, 5.16); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (91x121x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 0.986 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.856 V/m; Power Drift = 0.06 dB


Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 0.349 W/kg; SAR(10 g) = 0.071 W/kg

Smallest distance from peaks to all points 3 dB below = 5.1 mm

Ratio of SAR at M2 to SAR at M1 = 52%

Maximum value of SAR (measured) = 0.862 W/kg



0 dB = 0.862 W/kg = -0.64 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 005

Report No. :TESA2208000320ES

WLAN 802.11ac(80M) 5.8G_Body_Top Edge_CH 155_Main_0mm

Communication System: WLAN; Frequency: 5775 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5775 \text{ MHz}$; $\sigma = 5.278 \text{ S/m}$; $\epsilon_r = 35.676$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.5°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.3, 5.3, 5.3); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (91x121x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 0.445 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.158 V/m; Power Drift = 0.16 dB


Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.245 W/kg; SAR(10 g) = 0.051 W/kg

Smallest distance from peaks to all points 3 dB below = 5.1 mm

Ratio of SAR at M2 to SAR at M1 = 51.2%

Maximum value of SAR (measured) = 0.596 W/kg



0 dB = 0.596 W/kg = -2.25 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

ID: 006

Report No. :TESA2208000320ES

WLAN 802.11b_Body_Back Surface_CH 6_Aux_0mm

Communication System: WLAN; Frequency: 2437 MHz;Duty Cycle: 1:1.007

Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.804 \text{ S/m}$; $\epsilon_r = 39.638$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.4°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(8.32, 8.32, 8.32); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (81x131x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.859 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.278 V/m; Power Drift = -0.16 dB


Peak SAR (extrapolated) = 1.21 W/kg

SAR(1 g) = 0.492 W/kg; SAR(10 g) = 0.201 W/kg

Smallest distance from peaks to all points 3 dB below = 7.6 mm

Ratio of SAR at M2 to SAR at M1 = 43.3%

Maximum value of SAR (measured) = 0.822 W/kg



0 dB = 0.822 W/kg = -0.85 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 007

Report No. :TESA2208000320ES

Bluetooth(GFSK)_Body_Back Surface_CH 78_Aux_0mm

Communication System: Bluetooth; Frequency: 2480 MHz;Duty Cycle: 1:1.295

Medium parameters used: $f = 2480 \text{ MHz}$; $\sigma = 1.849 \text{ S/m}$; $\epsilon_r = 39.583$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.4°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(8.32, 8.32, 8.32); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (81x101x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.181 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.854 V/m; Power Drift = 0.12 dB


Peak SAR (extrapolated) = 0.265 W/kg

SAR(1 g) = 0.104 W/kg; SAR(10 g) = 0.041 W/kg

Smallest distance from peaks to all points 3 dB below = 7.1 mm

Ratio of SAR at M2 to SAR at M1 = 40.8%

Maximum value of SAR (measured) = 0.165 W/kg



0 dB = 0.165 W/kg = -7.83 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 008

Report No. :TESA2208000320ES

WLAN 802.11ac(160M) 5.2G_Body_Top Edge_CH 50_Aux_0mm

Communication System: WLAN; Frequency: 5250 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5250 \text{ MHz}$; $\sigma = 4.739 \text{ S/m}$; $\epsilon_r = 36.295$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.3°C; Liquid temperature: 22.8°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.81, 5.81, 5.81); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (121x161x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 0.668 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.562 V/m; Power Drift = 0.08 dB



Peak SAR (extrapolated) = 0.724 W/kg

SAR(1 g) = 0.164 W/kg; SAR(10 g) = 0.050 W/kg

Smallest distance from peaks to all points 3 dB below = 5.7 mm

Ratio of SAR at M2 to SAR at M1 = 54.5%

Maximum value of SAR (measured) = 0.315 W/kg



0 dB = 0.315 W/kg = -5.02 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 010

Report No. :TESA2208000320ES

WLAN 802.11ac(160M) 5.6G_Body_Top Edge_CH 114_Aux_0mm

Communication System: WLAN; Frequency: 5570 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5570 \text{ MHz}$; $\sigma = 5.069 \text{ S/m}$; $\epsilon_r = 35.886$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.3°C; Liquid temperature: 22.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.16, 5.16, 5.16); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (101x121x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 0.806 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.682 V/m; Power Drift = 0.17 dB


Peak SAR (extrapolated) = 1.53 W/kg

SAR(1 g) = 0.221 W/kg; SAR(10 g) = 0.048 W/kg

Smallest distance from peaks to all points 3 dB below = 4.7 mm

Ratio of SAR at M2 to SAR at M1 = 52.3%

Maximum value of SAR (measured) = 0.609 W/kg



0 dB = 0.609 W/kg = -2.15 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 011

Report No. :TESA2208000320ES

WLAN 802.11ac(80M) 5.8G_Body_Top Edge_CH 155_Aux_0mm

Communication System: WLAN; Frequency: 5775 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5775 \text{ MHz}$; $\sigma = 5.278 \text{ S/m}$; $\epsilon_r = 35.676$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.5°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.3, 5.3, 5.3); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (101x121x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 1.01 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.638 V/m; Power Drift = 0.11 dB



Peak SAR (extrapolated) = 1.49 W/kg

SAR(1 g) = 0.156 W/kg; SAR(10 g) = 0.038 W/kg

Smallest distance from peaks to all points 3 dB below = 5.6 mm

Ratio of SAR at M2 to SAR at M1 = 44.9%

Maximum value of SAR (measured) = 0.397 W/kg



0 dB = 0.397 W/kg = -4.01 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 012

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-5,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 79 (6345.0 MHz)_Main_0mm

Ambient temperature: 22.4; Liquid temperature: 22.8

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	5.937	35.085

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-13	2022-09-13
psSAR1g [W/kg]	0.482	0.645
psSAR8g [W/kg]	0.133	0.145
psSAR10g [W/kg]	0.111	0.119
psPDab (4.0cm2, sq) [W/m2]		2.90
Power Drift [dB]	0.07	0.05
M2/M1 [%]		50.9
Dist 3dB Peak [mm]		4.0



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 013

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-6,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 111 (6505.0 MHz)_Main_0mm

Ambient temperature: 22.4; Liquid temperature: 22.8

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	6.122	34.891

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.2
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-13	2022-09-13
psSAR1g [W/kg]	0.809	0.931
psSAR8g [W/kg]	0.192	0.241
psSAR10g [W/kg]	0.159	0.199
psPDab (4.0cm2, sq) [W/m2]		4.83
Power Drift [dB]	-0.11	0.08
M2/M1 [%]		55.7
Dist 3dB Peak [mm]		4.1



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 014

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-7,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 175 (6825.0 MHz)_Main_0mm

Ambient temperature: 22.4; Liquid temperature: 22.8

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	6.499	34.506

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-13	2022-09-13
psSAR1g [W/kg]	0.512	0.675
psSAR8g [W/kg]	0.153	0.160
psSAR10g [W/kg]	0.129	0.132
psPDab (4.0cm2, sq) [W/m2]		3.20
Power Drift [dB]	0.12	0.12
M2/M1 [%]		48.8
Dist 3dB Peak [mm]		4.1



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 015

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-8,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 207 (6985.0 MHz)_Main_0mm

Ambient temperature: 22.4; Liquid temperature: 22.7

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.14	6.689	34.315

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-13	2022-09-13
psSAR1g [W/kg]	0.365	0.423
psSAR8g [W/kg]	0.106	0.105
psSAR10g [W/kg]	0.089	0.087
psPDab (4.0cm2, sq) [W/m2]		2.09
Power Drift [dB]	0.14	-0.12
M2/M1 [%]		47.2
Dist 3dB Peak [mm]		4.1



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 016

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-5,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 15 (6025.0 MHz)_Aux_0mm

Ambient temperature: 22.4; Liquid temperature: 22.8

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	5.554	35.487

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-13	2022-09-13
psSAR1g [W/kg]	0.220	0.206
psSAR8g [W/kg]	0.072	0.062
psSAR10g [W/kg]	0.061	0.053
psPDab (4.0cm2, sq) [W/m2]		1.24
Power Drift [dB]	0.16	0.09
M2/M1 [%]		60.8
Dist 3dB Peak [mm]		5.4



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 017

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-6,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 111 (6505.0 MHz)_Aux_0mm

Ambient temperature: 22.4; Liquid temperature: 22.8

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	6.122	34.891

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-13	2022-09-13
psSAR1g [W/kg]	0.254	0.320
psSAR8g [W/kg]	0.082	0.090
psSAR10g [W/kg]	0.070	0.075
psPDab (4.0cm2, sq) [W/m2]		1.81
Power Drift [dB]	0.16	0.15
M2/M1 [%]		48.3
Dist 3dB Peak [mm]		4.3



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 018

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-7,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 175 (6825.0 MHz)_Aux_0mm

Ambient temperature: 22.4; Liquid temperature: 22.8

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	6.499	34.506

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-13	2022-09-13
psSAR1g [W/kg]	0.487	0.618
psSAR8g [W/kg]	0.151	0.161
psSAR10g [W/kg]	0.128	0.133
psPDab (4.0cm2, sq) [W/m2]		3.21
Power Drift [dB]	0.05	0.06
M2/M1 [%]		49.2
Dist 3dB Peak [mm]		4.0



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 019

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-8,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 207 (6985.0 MHz)_Aux_0mm

Ambient temperature: 22.4; Liquid temperature: 22.7

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.14	6.689	34.315

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-13	2022-09-13
psSAR1g [W/kg]	0.660	0.678
psSAR8g [W/kg]	0.176	0.168
psSAR10g [W/kg]	0.147	0.139
psPDab (4.0cm2, sq) [W/m2]		3.36
Power Drift [dB]	0.14	-0.13
M2/M1 [%]		48.3
Dist 3dB Peak [mm]		4.0



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 020

Report No. :TESA2208000320ES

WLAN 802.11b_Body_Back Surface_CH 1_Main_0mm

Communication System: WLAN; Frequency: 2412 MHz;Duty Cycle: 1:1.007

Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.782 \text{ S/m}$; $\epsilon_r = 39.693$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.8°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(8.32, 8.32, 8.32); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Maximum value of SAR (interpolated) = 0.990 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.268 V/m; Power Drift = 0.15 dB


Peak SAR (extrapolated) = 1.55 W/kg

SAR(1 g) = 0.583 W/kg; SAR(10 g) = 0.246 W/kg

Smallest distance from peaks to all points 3 dB below = 7.6 mm

Ratio of SAR at M2 to SAR at M1 = 37.1%

Maximum value of SAR (measured) = 1.02 W/kg



0 dB = 1.02 W/kg = 0.09 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 021

Report No. :TESA2208000320ES

WLAN 802.11ac(160M) 5.2G_Body_Top Edge_CH 50_Main_0mm

Communication System: WLAN; Frequency: 5250 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5250 \text{ MHz}$; $\sigma = 4.738 \text{ S/m}$; $\epsilon_r = 36.315$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.6°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.81, 5.81, 5.81); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (91x121x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 1.03 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 4.276 V/m; Power Drift = 0.18 dB



Peak SAR (extrapolated) = 1.61 W/kg

SAR(1 g) = 0.377 W/kg; SAR(10 g) = 0.093 W/kg

Smallest distance from peaks to all points 3 dB below = 5.4 mm

Ratio of SAR at M2 to SAR at M1 = 57.1%

Maximum value of SAR (measured) = 0.828 W/kg



0 dB = 0.828 W/kg = -0.82 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 023

Report No. :TESA2208000320ES

WLAN 802.11ac(160M) 5.6G_Body_Top Edge_CH 114_Main_0mm

Communication System: WLAN; Frequency: 5570 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5570 \text{ MHz}$; $\sigma = 5.068 \text{ S/m}$; $\epsilon_r = 35.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.6°C; Liquid temperature: 22.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.16, 5.16, 5.16); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (81x121x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 1.05 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 4.562 V/m; Power Drift = 0.12 dB



Peak SAR (extrapolated) = 2.16 W/kg

SAR(1 g) = 0.436 W/kg; SAR(10 g) = 0.100 W/kg

Smallest distance from peaks to all points 3 dB below = 5.1 mm

Ratio of SAR at M2 to SAR at M1 = 54.5%

Maximum value of SAR (measured) = 1.04 W/kg



0 dB = 1.04 W/kg = 0.19 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 024

Report No. :TESA2208000320ES

WLAN 802.11ac(80M) 5.8G_Body_Top Edge_CH 155_Main_0mm

Communication System: WLAN; Frequency: 5775 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5775 \text{ MHz}$; $\sigma = 5.276 \text{ S/m}$; $\epsilon_r = 35.664$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.4°C; Liquid temperature: 22.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.3, 5.3, 5.3); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (81x81x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 0.733 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.768 V/m; Power Drift = 0.09 dB


Peak SAR (extrapolated) = 1.43 W/kg

SAR(1 g) = 0.301 W/kg; SAR(10 g) = 0.056 W/kg

Smallest distance from peaks to all points 3 dB below = 5.4 mm

Ratio of SAR at M2 to SAR at M1 = 50.1%

Maximum value of SAR (measured) = 0.795 W/kg



0 dB = 0.795 W/kg = -1.00 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 025

Report No. :TESA2208000320ES

WLAN 802.11b_Body_Back Surface_CH 6_Aux_0mm

Communication System: WLAN; Frequency: 2437 MHz;Duty Cycle: 1:1.007

Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.805 \text{ S/m}$; $\epsilon_r = 39.673$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.8°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(8.32, 8.32, 8.32); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (91x131x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.978 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.684 V/m; Power Drift = 0.11 dB



Peak SAR (extrapolated) = 1.83 W/kg

SAR(1 g) = 0.697 W/kg; SAR(10 g) = 0.268 W/kg

Smallest distance from peaks to all points 3 dB below = 6.4 mm

Ratio of SAR at M2 to SAR at M1 = 40.2%

Maximum value of SAR (measured) = 1.23 W/kg



0 dB = 1.23 W/kg = 0.91 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 026

Report No. : TESA2208000320ES

Bluetooth(GFSK)_Body_Back Surface_CH 78_Aux_0mm

Communication System: Bluetooth; Frequency: 2480 MHz; Duty Cycle: 1:1.295

Medium parameters used: $f = 2480 \text{ MHz}$; $\sigma = 1.849 \text{ S/m}$; $\epsilon_r = 39.583$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.8°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(8.32, 8.32, 8.32); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (91x131x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 0.314 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.432 V/m; Power Drift = 0.07 dB


Peak SAR (extrapolated) = 0.524 W/kg

SAR(1 g) = 0.193 W/kg; SAR(10 g) = 0.070 W/kg

Smallest distance from peaks to all points 3 dB below = 5.7 mm

Ratio of SAR at M2 to SAR at M1 = 38.5%

Maximum value of SAR (measured) = 0.338 W/kg



0 dB = 0.338 W/kg = -4.71 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 027

Report No. :TESA2208000320ES

WLAN 802.11ac(160M) 5.2G_Body_Top Edge_CH 50_Aux_0mm

Communication System: WLAN; Frequency: 5250 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5250 \text{ MHz}$; $\sigma = 4.738 \text{ S/m}$; $\epsilon_r = 36.315$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.6°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.81, 5.81, 5.81); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (101x141x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 0.961 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.216 V/m; Power Drift = 0.14 dB



Peak SAR (extrapolated) = 0.602 W/kg

SAR(1 g) = 0.176 W/kg; SAR(10 g) = 0.057 W/kg

Smallest distance from peaks to all points 3 dB below = 6.4 mm

Ratio of SAR at M2 to SAR at M1 = 54%

Maximum value of SAR (measured) = 0.348 W/kg



0 dB = 0.348 W/kg = -4.58 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 029

Report No. :TESA2208000320ES

WLAN 802.11ac(160M) 5.6G_Body_Top Edge_CH 114_Aux_0mm

Communication System: WLAN; Frequency: 5570 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5570 \text{ MHz}$; $\sigma = 5.068 \text{ S/m}$; $\epsilon_r = 35.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.6°C; Liquid temperature: 22.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.16, 5.16, 5.16); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (81x161x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 0.768 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.824 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 0.335 W/kg; SAR(10 g) = 0.093 W/kg

Smallest distance from peaks to all points 3 dB below = 6.8 mm

Ratio of SAR at M2 to SAR at M1 = 52.1%

Maximum value of SAR (measured) = 0.688 W/kg

Zoom Scan (7x7x12)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.824 V/m; Power Drift = 0.11 dB



Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.243 W/kg; SAR(10 g) = 0.060 W/kg

Smallest distance from peaks to all points 3 dB below = 6.1 mm

Ratio of SAR at M2 to SAR at M1 = 54.4%

Maximum value of SAR (measured) = 0.527 W/kg



0 dB = 0.527 W/kg = -2.79 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 030

Report No. :TESA2208000320ES

WLAN 802.11ac(80M) 5.8G_Body_Top Edge_CH 155_Aux_0mm

Communication System: WLAN; Frequency: 5775 MHz;Duty Cycle: 1:1.012

Medium parameters used: $f = 5775 \text{ MHz}$; $\sigma = 5.276 \text{ S/m}$; $\epsilon_r = 35.664$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.4°C; Liquid temperature: 22.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.3, 5.3, 5.3); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (81x161x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 0.923 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.734 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.214 W/kg; SAR(10 g) = 0.057 W/kg

Smallest distance from peaks to all points 3 dB below = 6.2 mm

Ratio of SAR at M2 to SAR at M1 = 47.8%

Maximum value of SAR (measured) = 0.453 W/kg

Zoom Scan (7x7x12)/Cube 1: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.734 V/m; Power Drift = 0.08 dB



Peak SAR (extrapolated) = 1.96 W/kg

SAR(1 g) = 0.180 W/kg; SAR(10 g) = 0.042 W/kg

Smallest distance from peaks to all points 3 dB below = 4.9 mm

Ratio of SAR at M2 to SAR at M1 = 48.1%

Maximum value of SAR (measured) = 0.419 W/kg



0 dB = 0.419 W/kg = -3.77 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 031

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-5,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 79 (6345.0 MHz)_Main_0mm

Ambient temperature: 22.2; Liquid temperature: 22.7

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	5.931	35.095

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-14	2022-09-14
psSAR1g [W/kg]	0.442	0.519
psSAR8g [W/kg]	0.112	0.118
psSAR10g [W/kg]	0.094	0.097
psPDab (4.0cm2, sq) [W/m2]		2.36
Power Drift [dB]	0.19	-0.15
M2/M1 [%]		51.5
Dist 3dB Peak [mm]		4.3



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 032

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-6,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 111 (6505.0 MHz)_Main_0mm

Ambient temperature: 22.2; Liquid temperature: 22.7

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	6.123	34.922

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-14	2022-09-14
psSAR1g [W/kg]	0.516	0.585
psSAR8g [W/kg]	0.131	0.136
psSAR10g [W/kg]	0.109	0.113
psPDab (4.0cm2, sq) [W/m2]		2.73
Power Drift [dB]	0.11	0.08
M2/M1 [%]		51.1
Dist 3dB Peak [mm]		4.0



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 033

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-7,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 175 (6825.0 MHz)_Main_0mm

Ambient temperature: 22.2; Liquid temperature: 22.7

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	6.501	34.516

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-14	2022-09-14
psSAR1g [W/kg]	0.607	0.629
psSAR8g [W/kg]	0.172	0.154
psSAR10g [W/kg]	0.147	0.127
psPDab (4.0cm2, sq) [W/m2]		3.08
Power Drift [dB]	-0.05	-0.02
M2/M1 [%]		48.8
Dist 3dB Peak [mm]		4.3



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 034

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-8,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 207 (6985.0 MHz)_Main_0mm

Ambient temperature: 22.2; Liquid temperature: 22.5

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.14	6.689	34.322

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-14	2022-09-14
psSAR1g [W/kg]	0.374	0.404
psSAR8g [W/kg]	0.105	0.104
psSAR10g [W/kg]	0.090	0.086
psPDab (4.0cm2, sq) [W/m2]		2.07
Power Drift [dB]	0.12	0.07
M2/M1 [%]		52.8
Dist 3dB Peak [mm]		4.1



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 035

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-5,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 15 (6025.0 MHz)_Aux_0mm

Ambient temperature: 22.2; Liquid temperature: 22.7

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	5.554	35.487

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-14	2022-09-14
psSAR1g [W/kg]	0.223	0.237
psSAR8g [W/kg]	0.075	0.074
psSAR10g [W/kg]	0.064	0.063
psPDab (4.0cm2, sq) [W/m2]		1.48
Power Drift [dB]	-0.14	-0.12
M2/M1 [%]		59.5
Dist 3dB Peak [mm]		4.8



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 036

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-6,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 111 (6505.0 MHz)_Aux_0mm

Ambient temperature: 22.2; Liquid temperature: 22.7

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	6.123	34.922

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-14	2022-09-14
psSAR1g [W/kg]	0.305	0.347
psSAR8g [W/kg]	0.104	0.105
psSAR10g [W/kg]	0.090	0.088
psPDab (4.0cm2, sq) [W/m2]		2.11
Power Drift [dB]	0.14	-0.16
M2/M1 [%]		50.2
Dist 3dB Peak [mm]		5.0



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 037

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-7,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 175 (6825.0 MHz)_Aux_0mm

Ambient temperature: 22.2; Liquid temperature: 22.7

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.2	6.501	34.516

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-14	2022-09-14
psSAR1g [W/kg]	0.382	0.454
psSAR8g [W/kg]	0.119	0.124
psSAR10g [W/kg]	0.102	0.104
psPDab (4.0cm2, sq) [W/m2]		2.47
Power Drift [dB]	0.16	0.13
M2/M1 [%]		47.9
Dist 3dB Peak [mm]		4.8



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 038

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-8,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 207 (6985.0 MHz)_Aux_0mm

Ambient temperature: 22.2; Liquid temperature: 22.5

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	TOP EDGE, 0.00	6.14	6.689	34.322

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 136.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-14	2022-09-14
psSAR1g [W/kg]	0.396	0.377
psSAR8g [W/kg]	0.113	0.101
psSAR10g [W/kg]	0.096	0.084
psPDab (4.0cm2, sq) [W/m2]		2.02
Power Drift [dB]	0.12	-0.07
M2/M1 [%]		47.9
Dist 3dB Peak [mm]		4.8



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

13 PD MEASUREMENT RESULT

ID: 039

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-5,

IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 79 (6345.0 MHz)_Main_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-19
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.11
psPDtot+ [W/m ²]	1.35
psPDmod+ [W/m ²]	1.67
E _{max} [V/m]	35.1
Power Drift [dB]	0.19



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 040

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-6,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 111 (6505.0 MHz)_Main_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-19
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.95
psPDtot+ [W/m ²]	2.12
psPDmod+ [W/m ²]	2.27
E _{max} [V/m]	39.6
Power Drift [dB]	-0.19



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 041

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-7,

IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 175 (6825.0 MHz)_Main_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-19
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.97
psPDtot+ [W/m ²]	2.30
psPDmod+ [W/m ²]	2.48
E _{max} [V/m]	42.0
Power Drift [dB]	0.15



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 042

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-8,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 207 (6985.0 MHz)_Main_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-19
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.83
psPDtot+ [W/m ²]	2.07
psPDmod+ [W/m ²]	2.18
E _{max} [V/m]	39.2
Power Drift [dB]	-0.09



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 043

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-5,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 15 (6025.0 MHz)_Aux_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-19
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.57
psPDtot+ [W/m ²]	1.73
psPDmod+ [W/m ²]	1.85
E _{max} [V/m]	32.8
Power Drift [dB]	0.03



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 044

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-6,

IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 111 (6505.0 MHz)_Aux_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-19
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.90
psPDtot+ [W/m ²]	2.06
psPDmod+ [W/m ²]	2.24
E _{max} [V/m]	36.5
Power Drift [dB]	0.10



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 045

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-7,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 175 (6825.0 MHz)_Aux_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-19
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	2.28
psPDtot+ [W/m ²]	2.47
psPDmod+ [W/m ²]	2.78
E _{max} [V/m]	39.5
Power Drift [dB]	0.14



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 046

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-8,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 207 (6985.0 MHz)_Aux_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-19
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	2.19
psPDtot+ [W/m ²]	2.38
psPDmod+ [W/m ²]	2.63
E _{max} [V/m]	39.2
Power Drift [dB]	-0.14



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 047

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-5,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 79 (6345.0 MHz)_Main_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-20
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.08
psPDtot+ [W/m ²]	1.25
psPDmod+ [W/m ²]	1.36
E _{max} [V/m]	30.0
Power Drift [dB]	-0.16



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 048

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-6,

IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 111 (6505.0 MHz)_Main_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-20
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	0.826
psPDtot+ [W/m ²]	1.10
psPDmod+ [W/m ²]	1.32
E _{max} [V/m]	31.7
Power Drift [dB]	-0.18



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 049

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-7,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 175 (6825.0 MHz)_Main_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-20
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	2.11
psPDtot+ [W/m ²]	2.45
psPDmod+ [W/m ²]	2.60
E _{max} [V/m]	39.3
Power Drift [dB]	0.09



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 050

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-8,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 207 (6985.0 MHz)_Main_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-20
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.76
psPDtot+ [W/m ²]	1.95
psPDmod+ [W/m ²]	2.14
E _{max} [V/m]	35.6
Power Drift [dB]	-0.06



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 051

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-5,

IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 15 (6025.0 MHz)_Aux_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-20
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.60
psPDtot+ [W/m ²]	1.84
psPDmod+ [W/m ²]	2.01
E _{max} [V/m]	34.4
Power Drift [dB]	-0.06



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 052

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-6,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 111 (6505.0 MHz)_Aux_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-20
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.81
psPDtot+ [W/m ²]	2.09
psPDmod+ [W/m ²]	2.28
E _{max} [V/m]	39.6
Power Drift [dB]	0.15



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 053

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-7,
IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 175 (6825.0 MHz)_Aux_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-20
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	2.26
psPDtot+ [W/m ²]	2.55
psPDmod+ [W/m ²]	2.92
E _{max} [V/m]	40.9
Power Drift [dB]	-0.01



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

ID: 054

Report No. :TESA2208000320ES

Measurement Report for Device, TOP EDGE, U-NII-8,

IEEE 802.11ax (160MHz, MCS0, 99pc duty cycle), Channel 207 (6985.0 MHz)_Aux_2mm

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	TOP EDGE, 2.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	100.0 x 120.0
Grid Steps [lambda]	0.0625 x 0.0625
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-20
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	1.65
psPDtot+ [W/m ²]	1.88
psPDmod+ [W/m ²]	2.10
E _{max} [V/m]	35.7
Power Drift [dB]	0.01



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

14 SAR SYSTEM CHECK RESULTS

Date: 2022/9/8

Report No. :TESA2208000320ES

Dipole 2450 MHz_SN:727

Communication System: CW; Frequency: 2450 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.816$ S/m; $\epsilon_r = 39.619$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient temperature: 22.4°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(8.32, 8.32, 8.32); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (51x61x1): Interpolated grid: dx=12 mm, dy=12 mm

Maximum value of SAR (interpolated) = 22.5 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.97 V/m; Power Drift = 0.02 dB


Peak SAR (extrapolated) = 28.3 W/kg

SAR(1 g) = 14.1 W/kg; SAR(10 g) = 6.86 W/kg

Smallest distance from peaks to all points 3 dB below = 10 mm

Ratio of SAR at M2 to SAR at M1 = 49.4%

Maximum value of SAR (measured) = 21.1 W/kg



0 dB = 21.1 W/kg = 13.25 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES

Dipole 5250 MHz_SN:1023

Communication System: CW; Frequency: 5250 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 5250 \text{ MHz}$; $\sigma = 4.739 \text{ S/m}$; $\epsilon_r = 36.295$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.3°C; Liquid temperature: 22.8°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.81, 5.81, 5.81); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (51x51x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 16.8 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 60.29 V/m; Power Drift = 0.06 dB


Peak SAR (extrapolated) = 32.5 W/kg

SAR(1 g) = 8.35 W/kg; SAR(10 g) = 2.4 W/kg

Smallest distance from peaks to all points 3 dB below = 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 56.1%

Maximum value of SAR (measured) = 17.3 W/kg



0 dB = 17.3 W/kg = 12.38 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES

Dipole 5600 MHz_SN:1023

Communication System: CW; Frequency: 5600 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 5600 \text{ MHz}$; $\sigma = 5.103 \text{ S/m}$; $\epsilon_r = 35.866$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.3°C; Liquid temperature: 22.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.16, 5.16, 5.16); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (61x91x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 19.1 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 63.17 V/m; Power Drift = 0.02 dB


Peak SAR (extrapolated) = 36.4 W/kg

SAR(1 g) = 8.47 W/kg; SAR(10 g) = 2.37 W/kg

Smallest distance from peaks to all points 3 dB below = 7.4 mm

Ratio of SAR at M2 to SAR at M1 = 53.4%

Maximum value of SAR (measured) = 18.0 W/kg



0 dB = 18.0 W/kg = 12.56 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES

Dipole 5750 MHz_SN:1023

Communication System: CW; Frequency: 5750 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 5750 \text{ MHz}$; $\sigma = 5.25 \text{ S/m}$; $\epsilon_r = 35.686$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.5°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.3, 5.3, 5.3); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (61x91x1): Interpolated grid: $dx=10 \text{ mm}$, $dy=10 \text{ mm}$

Maximum value of SAR (interpolated) = 19.0 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 60.49 V/m; Power Drift = 0.03 dB



Peak SAR (extrapolated) = 39.1 W/kg

SAR(1 g) = 8.41 W/kg; SAR(10 g) = 2.32 W/kg

Smallest distance from peaks to all points 3 dB below = 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 50.8%

Maximum value of SAR (measured) = 18.1 W/kg



0 dB = 18.1 W/kg = 12.59 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
 除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES
 Measurement Report for Device, FRONT, Validation band,
 CW, Channel 6500 (6500.0 MHz)_SN:1006
 Ambient temperature: 22.4; Liquid temperature: 22.8

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	6.2	6.12	34.904

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	36.0 x 51.0	28.0 x 28.0 x 24.0
Grid Steps [mm]	6.0 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-13	2022-09-13
psSAR1g [W/kg]	27.0	30.1
psSAR8g [W/kg]	6.27	6.69
psSAR10g [W/kg]	5.17	5.49
psPDab (4.0cm2, sq) [W/m2]		134
Power Drift [dB]	0.03	0.01
M2/M1 [%]		50.9
Dist 3dB Peak [mm]		4.3



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES
 Measurement Report for Device, FRONT, Validation band,
 CW, Channel 6500 (6500.0 MHz)_SN:1006
 Ambient temperature: 22.3; Liquid temperature: 22.4

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	5.8	6.14	34.916

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7642, 2022-03-02	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	36.0 x 51.0	28.0 x 28.0 x 24.0
Grid Steps [mm]	6.0 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-10-20	2022-10-20
psSAR1g [W/kg]	27.2	30.9
psSAR8g [W/kg]	6.33	6.52
psSAR10g [W/kg]	5.20	5.33
psPDab (4.0cm2, sq) [W/m2]		130
Power Drift [dB]	0.04	-0.02
M2/M1 [%]		50.9
Dist 3dB Peak [mm]		4.8



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES

Measurement Report for Device, FRONT, Validation band, CW, Channel 7000 (7000.0 MHz)_SN:1007

Ambient temperature: 22.4; Liquid temperature: 22.7

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	6.14	6.703	34.307

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	36.0 x 45.0	28.0 x 28.0 x 24.0
Grid Steps [mm]	6.0 x 7.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-13	2022-09-13
psSAR1g [W/kg]	25.1	26.4
psSAR8g [W/kg]	5.56	5.65
psSAR10g [W/kg]	4.58	4.62
psPDab (4.0cm2, sq) [W/m2]		113
Power Drift [dB]	0.06	0.06
M2/M1 [%]		48.2
Dist 3dB Peak [mm]		4.6



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Date: 2022/9/15

Report No. :TESA2208000320ES

Dipole 2450 MHz_SN:727

Communication System: CW; Frequency: 2450 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 2450 \text{ MHz}$; $\sigma = 1.816 \text{ S/m}$; $\epsilon_r = 39.642$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.8°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(8.32, 8.32, 8.32); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (51x61x1): Interpolated grid: $dx=12 \text{ mm}$, $dy=12 \text{ mm}$

Maximum value of SAR (interpolated) = 22.5 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 97.75 V/m; Power Drift = 0.03 dB



Peak SAR (extrapolated) = 28.0 W/kg

SAR(1 g) = 14 W/kg; SAR(10 g) = 6.81 W/kg

Smallest distance from peaks to all points 3 dB below = 10 mm

Ratio of SAR at M2 to SAR at M1 = 49.6%

Maximum value of SAR (measured) = 20.9 W/kg



0 dB = 20.9 W/kg = 13.20 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES

Dipole 5250 MHz_SN:1023

Communication System: CW; Frequency: 5250 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 5250 \text{ MHz}$; $\sigma = 4.738 \text{ S/m}$; $\epsilon_r = 36.315$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.6°C; Liquid temperature: 22.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.81, 5.81, 5.81); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (51x51x1): Interpolated grid: $dx=10 \text{ mm}$, $dy=10 \text{ mm}$

Maximum value of SAR (interpolated) = 16.8 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 60.29 V/m; Power Drift = 0.06 dB


Peak SAR (extrapolated) = 32.5 W/kg

SAR(1 g) = 8.35 W/kg; SAR(10 g) = 2.4 W/kg

Smallest distance from peaks to all points 3 dB below = 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 56.1%

Maximum value of SAR (measured) = 17.3 W/kg



0 dB = 17.3 W/kg = 12.38 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES

Dipole 5600 MHz_SN:1023

Communication System: CW; Frequency: 5600 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 5600 \text{ MHz}$; $\sigma = 5.099 \text{ S/m}$; $\epsilon_r = 35.855$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.6°C; Liquid temperature: 22.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.16, 5.16, 5.16); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (61x91x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 18.9 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 62.73 V/m; Power Drift = 0.01 dB


Peak SAR (extrapolated) = 36.4 W/kg

SAR(1 g) = 8.44 W/kg; SAR(10 g) = 2.36 W/kg

Smallest distance from peaks to all points 3 dB below = 7.4 mm

Ratio of SAR at M2 to SAR at M1 = 53.4%

Maximum value of SAR (measured) = 18.0 W/kg



0 dB = 18.0 W/kg = 12.54 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Date: 2022/9/18

Report No. :TESA2208000320ES

Dipole 5750 MHz_SN:1023

Communication System: CW; Frequency: 5750 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 5750 \text{ MHz}$; $\sigma = 5.254 \text{ S/m}$; $\epsilon_r = 35.718$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Ambient temperature: 22.4°C; Liquid temperature: 22.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7686; ConvF(5.3, 5.3, 5.3); Calibrated: 2021/10/05
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1665; Calibrated: 2022/02/28
- Phantom: ELI
- DASY52 52.10.4(1527); SEMCAD X 14.6.14(7483)

Area Scan (61x91x1): Interpolated grid: dx=10 mm, dy=10 mm

Maximum value of SAR (interpolated) = 18.6 W/kg

Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 60.07 V/m; Power Drift = 0.04 dB



Peak SAR (extrapolated) = 38.2 W/kg

SAR(1 g) = 8.22 W/kg; SAR(10 g) = 2.27 W/kg

Smallest distance from peaks to all points 3 dB below = 7.2 mm

Ratio of SAR at M2 to SAR at M1 = 50.7%

Maximum value of SAR (measured) = 17.8 W/kg



0 dB = 17.8 W/kg = 12.49 dBW/kg

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES
Measurement Report for Device, FRONT, Validation band,
CW, Channel 6500 (6500.0 MHz)_SN:1006
Ambient temperature: 22.2; Liquid temperature: 22.7
Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	6.2	6.12	34.931

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	36.0 x 51.0	28.0 x 28.0 x 24.0
Grid Steps [mm]	6.0 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-14	2022-09-14
psSAR1g [W/kg]	27.1	30.2
psSAR8g [W/kg]	6.27	6.70
psSAR10g [W/kg]	5.17	5.50
psPDab (4.0cm2, sq) [W/m2]		134
Power Drift [dB]	0.04	-0.01
M2/M1 [%]		50.8
Dist 3dB Peak [mm]		4.3



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES
 Measurement Report for Device, FRONT, Validation band,
 CW, Channel 7000 (7000.0 MHz)_SN:1007
 Ambient temperature: 22.2; Liquid temperature: 22.5

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	FRONT, 0.00	6.14	6.705	34.314

Hardware Setup


Phantom	Probe, Calibration Date	DAE, Calibration Date
ELI V5.0 (20deg probe tilt) - 1141	EX3DV4 - SN7686, 2021-10-05	DAE4 Sn1665, 2022-02-28

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	36.0 x 45.0	28.0 x 28.0 x 24.0
Grid Steps [mm]	6.0 x 7.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2022-09-14	2022-09-14
psSAR1g [W/kg]	25.0	26.3
psSAR8g [W/kg]	5.56	5.64
psSAR10g [W/kg]	4.58	4.62
psPDab (4.0cm2, sq) [W/m2]		113
Power Drift [dB]	0.04	0.04
M2/M1 [%]		48.5
Dist 3dB Peak [mm]		4.6



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

15 PD SYSTEM CHECK RESULT

Report No. :TESA2208000320ES

Measurement Report for Device, FRONT, Validation band,
CW, Channel 10000 (10000.0 MHz)_SN:1021

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	FRONT, 10.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	120.0 x 120.0
Grid Steps [lambda]	0.25 x 0.25
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-20
Avg. Area [cm ²]	1.00
psPDn+ [W/m ²]	51.2
psPDtot+ [W/m ²]	51.4
psPDmod+ [W/m ²]	51.5
E _{max} [V/m]	144
Power Drift [dB]	-0.01



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Report No. :TESA2208000320ES
Measurement Report for Device, FRONT, Validation band,
CW, Channel 10000 (10000.0 MHz)_SN:1021
Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Conversion Factor
5G	FRONT, 10.00	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - 1076	Air -	EUmmWV3 - SN9399_F1-55GHz, 2022-01-26	DAE4 Sn1665, 2022-02-28

Scans Setup

Scan Type	5G Scan
Grid Extents [mm]	120.0 x 120.0
Grid Steps [lambda]	0.25 x 0.25
Sensor Surface [mm]	2.0

Measurement Results

Scan Type	5G Scan
Date	2022-09-19
Avg. Area [cm ²]	1.00
psPDn+ [W/m ²]	51.0
psPDtot+ [W/m ²]	51.1
psPDmod+ [W/m ²]	51.2
E _{max} [V/m]	144
Power Drift [dB]	0.03



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Refer to separated files for the following appendixes.

- 16.1 SAR_Appendix A Photographs**
- 16.2 SAR_Appendix B DAE & Probe Cal. Certificate**
- 16.3 SAR_Appendix C Phantom Description & Dipole Cal. Certificate**

- End of report -

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. | No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

台灣檢驗科技股份有限公司

t (886-2) 2299-3279

f (886-2) 2298-0488

www.sgs.com.tw

Member of SGS Group