

Partial FCC Test Report (PART 90S)

Report No.: RFBFLF-WTW-P22010014A-3 R1

Test Model: B2502CB, B2502CBA, P2552CB, PX560CB, BW560CB, B2502FB,
B2502FBA, P2552FB, PX560FB, BW560FB
(refer to item 3.1 for more details)

Received Date: Dec. 20, 2021

Test Date: Jun. 24 ~ Jun. 25, 2022

Issued Date: Jul. 08, 2022

Applicant: ASUSTeK COMPUTER INC.

Address: 1F., No. 15, Lide Rd., Beitou Dist., Taipei City 112, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

**FCC Registration /
Designation Number:** 281270 / TW0032



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	6
2.2 Test Site and Instruments	7
3 General Information	8
3.1 General Description of EUT	8
3.2 Configuration of System under Test.....	12
3.2.1 Description of Support Units	12
3.3 Test Mode Applicability and Tested Channel Detail	13
3.4 General Description of Applied Standards and references.....	13
4 Test Types and Results	14
4.1 Radiated Emission Measurement.....	14
4.1.1 Limits of Radiated Emission Measurement	14
4.1.2 Test Procedure	14
4.1.3 Deviation from Test Standard	14
4.1.4 Test Setup.....	15
4.1.5 Test Results	16
5 Pictures of Test Arrangements	21
Appendix – Information of the Testing Laboratories	22

Release Control Record

Issue No.	Description	Date Issued
RFBFLF-WTW-P22010014A-3	Original Release	Jul. 05, 2022
RFBFLF-WTW-P22010014A-3 R1	Revise Gain	Jul. 08, 2022

2 Summary of Test Results

Applied Standard: FCC Part 90 & Part 2 (LTE 14)			
FCC Clause	Test Item	Result	Remarks
2.1046 90.542 (a)(7)	Effective Radiated Power	N/A	Refer to Note
2.1047	Modulation Characteristics	N/A	Refer to Note
2.1055 90.539 (e)	Frequency Stability	N/A	Refer to Note
2.1049	Occupied Bandwidth	N/A	Refer to Note
90.210 (n)	Emission Masks	N/A	Refer to Note
2.1053 90.543 (e)(2)(3)	Band Edge Measurements	N/A	Refer to Note
2.1051 90.543 (e)(3)	Conducted Spurious Emissions	N/A	Refer to Note
2.1053 90.543 (e)(f)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -6.52 dB at 1586.00 MHz.

Applied Standard: FCC Part 90 & Part 2 (LTE 26)			
FCC Clause	Test Item	Result	Remarks
2.1046 90.635 (b)	Effective Radiated Power	N/A	Refer to Note
2.1047	Modulation Characteristics	N/A	Refer to Note
2.1055 90.213	Frequency Stability	N/A	Refer to Note
2.1049 90.209	Occupied Bandwidth	N/A	Refer to Note
2.1051 90.691	Emission Masks	N/A	Refer to Note
2.1051 90.691	Conducted Spurious Emissions	N/A	Refer to Note
2.1053 90.691	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -45.11 dB at 1673.00 MHz.

Note:

1. This report is a partial report, only test items of Radiated Spurious Emissions tests was performed for this report. Other testing data please refer to Sporton report no.: FG051802D_R01, FW051802_R01 for module (Brand: Fibocom, Model: FM350-GL).
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (\pm)
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.00 dB
	30MHz ~ 200MHz	2.91 dB
	200MHz ~ 1000MHz	2.93 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	1.76 dB
	18GHz ~ 40GHz	1.77 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Rohde & Schwarz	ESR3	102783	Dec. 20, 2021	Dec. 19, 2022
Spectrum Analyzer KEYSIGHT	N9020B	MY60110513	Dec. 24, 2021	Dec. 23, 2022
BILOG Antenna SCHWARZBECK	VULB9168	1214	Oct. 27, 2021	Oct. 26, 2022
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-1170	Nov. 14, 2021	Nov. 13, 2022
HORN Antenna SCHWARZBECK	BBHA 9170	995	Nov. 14, 2021	Nov. 13, 2022
Loop Antenna EMCI	EM-6879	269	Sep. 16, 2021	Sep. 15, 2022
Loop Antenna TESEQ	HLA 6121	45745	Jul. 21, 2021	Jul. 20, 2022
Preamplifier EMCI	EMC330N	980798	Jan. 17, 2022	Jan. 16, 2023
Preamplifier EMCI	EMC118A45SE	980809	Dec. 30, 2021	Dec. 29, 2022
Preamplifier EMCI	EMC184045SE	980786	Jan. 17, 2022	Jan. 16, 2023
RF signal cable EMCI	EMC104-SM-SM- (9000+2000+1000)	201244+ 201232+ 210103	Jan. 17, 2022	Jan. 16, 2023
RF signal cable EMCI	EMCCFD400-NM- NM-(9000+300+500)	201251+ 201249+ 201248	Jan. 17, 2022	Jan. 16, 2023
RF signal cable EMCI	EMC101G-KM-KM- (5000+3000+2000)	201261+201258+2 01249	Jan. 17, 2022	Jan. 16, 2023
Software BV ADT	ADT_Radiated_V7.6. 15.9.5	NA	NA	NA
Antenna Tower Max-Full	MFA-515BSN	NA	NA	NA
Turn Table Max-Full	MFT-201SS	NA	NA	NA
Turn Table Controller Max-Full	MF-7802BS	MF780208676	NA	NA
USB Wideband Power Sensor KEYSIGHT	U2021XA	MY55050005/MY551 90004/MY55190007/ MY55210005	Jul. 12, 2021	Jul. 11, 2022
Radio Communication Test Station Anritsu	MT8000A	6262135011	Nov. 18, 2021	Nov. 17, 2022
Radio Communication Test Station Anritsu	MT8821C	6261806803	Feb. 16, 2022	Feb. 15, 2023

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in WM Chamber 9.

3 General Information

3.1 General Description of EUT

Product	Notebook PC/ExpertBook	
Brand	ASUS	
Test Model	B2502CB, B2502CBA, P2552CB, PX560CB, BW560CB, B2502FB, B2502FBA, P2552FB, PX560FB, BW560FB	
Model Difference	Refer to Note as below	
Status of EUT	Engineering Sample	
Power Supply Rating	11.4 Vdc (Battery) 5V/9V/15V/20V Vdc (Adapter)	
Modulation Type	LTE	QPSK, 16QAM, 64QAM, 256QAM
Frequency Range	LTE Band 14 (Channel Bandwidth: 5 MHz)	790.5 ~ 795.5 MHz
	LTE Band 14 (Channel Bandwidth: 10 MHz)	793 MHz
	LTE Band 26 (Channel Bandwidth: 1.4 MHz)	814.7 ~ 823.3 MHz
	LTE Band 26 (Channel Bandwidth: 3 MHz)	815.5 ~ 822.5 MHz
	LTE Band 26 (Channel Bandwidth: 5 MHz)	816.5 ~ 821.5 MHz
	LTE Band 26 (Channel Bandwidth: 10 MHz)	819 MHz
Antenna Type	Refer to Note as below	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	
Tx / Rx Function	1Tx / 4Rx	

Note:

- All models are listed as below.

Brand	Model	Difference
ASUS	B2502CB	For marketing purpose
	B2502CBA	
	P2552CB	
	PX560CB	
	BW560CB	
	B2502FB	
	B2502FBA	
	P2552FB	
	PX560FB	
	BW560FB	

2. The EUT contains the following accessories.

Accessories information		
Main Board	Brand	ASUS
	Model	B2402FBA MB
LCD Panel 1	Brand	BOE
	Model	NT156WHM-N44
	spec	LCD 15.6' HD US EDP
LCD Panel 2	Brand	INNOLUX
	Model	N156BGA-EA3
	spec	LCD 15.6' HD US EDP
LCD Panel 3	Brand	BOE
	Model	NT156FHM-N62
	spec	LCD 15.6' FHD EDP
LCD Panel 4	Brand	INNOLUX
	Model	N156HGA-EA3
	spec	LCD 15.6' FHD EDP
LCD Panel 5	Brand	BOE
	Model	NE156FHM-N41
	spec	LCD 15.6' FHD WVV EDP
LCD Panel 6	Brand	AUO
	Model	B156HAN02.1
	spec	LCD 15.6' FHD WVV EDP
LCD Panel 7	Brand	INNOLUX
	Model	N156HCE-EN1
	spec	LCD 15.6' FHD WV US EDP 400NITS
Camera 1	Brand	AZWAVE
	Model	AM-9BF56EB-D
	spec	CAMERA HD RGB/IR ARRAY MIC CR
Camera 2	Brand	SUPREME
	Model	AHDFN050
	spec	CAMERA HD FIX 3.3V ARRAYMIC CL
Camera 3	Brand	AZWAVE
	Model	AM-6SF56A2-J
	spec	CAMERA HD FIX 3.3V ARRAYMIC CL
Camera 4	Brand	SUPREME
	Model	AHDFN171
	spec	CAMERA HD FIX 3.3V ARRAYMIC CL
CPU 1	Brand	Intel/BGA1744
	Model	I7-1260P 12C
	spec	2.1G
CPU 2	Brand	Intel/BGA1744
	Model	I5-1240P 12C
	spec	1.7G
CPU 3	Brand	Intel/BGA1744
	Model	I3-1215U 6C
	spec	1.2GHz
V-Pro CPU 1	Brand	Intel/BGA1744
	Model	I5-1250P
	spec	1.7GHz
V-Pro CPU 2	Brand	Intel/BGA1744
	Model	I7-1270P
	spec	2.2GHz
M.2 SSD 1	Brand	WD
	Model	SDBPNPZ-256G-1002
	spec	256GB M2 2280 NVME
M.2 SSD 2	Brand	KST
	Model	OM8PDP3256B-AB1
	spec	256GB M2 2280 NVME
M.2 SSD 3	Brand	INT
	Model	SSDPEKNU512GZ
	spec	512GB M2 2280 NVME
M.2 SSD 4	Brand	MICRON
	Model	MTFDHBA512QFD
	spec	512G M2 2280 NVME

Accessories information		
M.2 SSD 5	Brand	INT
	Model	SSDPEKNU010TZ
	spec	1TB M2 2280 NVME
M.2 SSD 6	Brand	MICRON
	Model	MTFDHBA1T0QFD
	spec	1TB M2 2280 NVME
M.2 SSD 7	Brand	SAMSUNG
	Model	MZVL2512HCJQ
	spec	512GB M2 2280 NVME
M.2 SSD 8	Brand	MICRON
	Model	MTFDKBA512TFH
	spec	512GB M2 2280 NVME
M.2 SSD 9	Brand	SAMSUNG
	Model	MZVL21T0HCLR
	spec	1TB M2 2280 NVME
M.2 SSD 10	Brand	MICRON
	Model	MTFDKBA1T0TFH
	spec	1TB M2 2280 NVME
M.2 SSD 11	Brand	SAMSUNG
	Model	MZVL22T0HBLB
	spec	2TB M2 2280 NVME
M.2 SSD 12	Brand	MICRON
	Model	MTFDKBA2T0TFH
	spec	2TB M2 2280 NVME
HDD 1	Brand	TOSHIBA
	Model	MQ04ABF100
	spec	1 TB-5400rpm
HDD 2	Brand	SEAGATE
	Model	ST1000LM035
	spec	1 TB-5400rpm
HDD 3	Brand	SEAGATE
	Model	ST1000LM049
	spec	1 TB-7200rpm
HDD 4	Brand	SEAGATE
	Model	ST2000LM007
	spec	2 TB-5400rpm
BT/WLAN Module	Brand	INTEL
	Model	AX211D2W
WWAN Module	Brand	Fibocom
	Model	FM350-GL
Battery 1	Brand	ASUS
	Model	B31N1909
	Power Rating	CPT/GLP606080R/3S1P/11.4V/48WH
	Manufacturer	CPT
SO-DIMM	SPEC	DDR4, 3200 MHz (4G/8G/16G/32G)
AC Adapter 1	Brand	ASUS
	Model	AD10380
	AC Input	100 - 240 Vac; 50 - 60 Hz; 1.5 A
	DC Output	5Vdc; 3A / 9Vdc; 3A / 15Vdc; 3A / 20Vdc; 3.25A
	DC Output Cable	1.5m / 0 core shielding
	Manufacturer	R33164
AC Adapter 2	Brand	PI
	Model	ASUS
	AC Input	A19-065N3A
	DC Output	100 - 240 Vac; 50 - 60 Hz; 1.5 A
	DC Output Cable	5Vdc; 3A / 9Vdc; 3A / 15Vdc; 3A / 20Vdc; 3.25A
AC power cable	Manufacturer	1.5m / 0 core shielding
	Signal Line	0.8 meter / no shielding/ 0 core

Accessories information		
AC Adapter 3	Brand	ASUS
	Model	ADP-65TW A
	AC Input	100 - 240 Vac; 50 - 60 Hz; 1.5 A
	DC Output	5Vdc; 3A / 9Vdc; 3A / 15Vdc; 3A / 20Vdc; 3.25A
Type C to Type C USB Cable 1	Manufacturer	DELTA
	Brand	MECIMEX
	Model	USB2.0 TYPE C TO C CABLE
Stylus Pen	Signal Line	1.5 meter
	Brand	Shenzhen qianfenyi intelligent technology co., LTD.
	Model	Active Stylus SA201H
	Manufacturer	MAXEYE

**After pretesting, Adapter 1 was the worst case and chosen for final test.

3. The antenna information is listed as below.

Ant. Type	Brand	Model
PIFA	PULSE	Ant. 0: TZ21131 (1415-08YT0A9)
		Ant. 1: TZ21134 (1415-08YQ0A9)
		Ant. 2: TZ21138 (1415-08YR0A9)
		Ant. 3: TZ21139 (1415-08YS0A9)

Band	WCDMA			LTE																	
	II	IV	V	2	4	5	7	12	13	14	17	25	26	30	38	41	48	66	71		
Peak Gain (dBi)	NB	Ant. 0	2.1	2.33	-0.74	2.1	2.33	-0.74	2.71	0.8	1.49	1.54	0.77	2.1	0.22	3.38	2.3	2.71	1.78	2.47	1.03
		Ant. 1	0.23	2.96	-0.07	0.23	2.96	-0.07	2.77	-	0.6	0.36	-	0.23	-0.07	3.9	0.86	2.77	2.21	2.96	-
		Ant. 2	3.33	-	-	3.33	-	-	2.48	-	-	-	-	3.33	-	1.35	3.09	3.09	5.07	-	-
		Ant. 3	2.44	1.52	-	2.44	1.52	-	1.79	-	-	-	-	2.44	-	1.1	1.89	1.89	2.67	1.52	-
	TB	Ant. 0	2.21	1.35	-3.19	2.21	1.35	-3.19	2.57	-2.15	-3.91	-4.53	-2.21	2.25	-3.19	2.85	2.57	2.78	6.67	1.35	-1.81
		Ant. 1	0.35	-0.29	-3.13	0.35	-0.29	-3.13	1.71	-	-5.84	-4.41	-	0.35	-3.13	0.99	2.36	2.36	4.89	-0.29	-
		Ant. 2	1.65	-	-	1.65	-	-	2.2	-	-	-	-	1.65	-	1.42	3.25	3.34	7.94	-	-
		Ant. 3	1.7	-0.12	-	1.7	-0.12	-	1.75	-	-	-	-	1.7	-	4.16	2.17	2.17	3.05	-0.12	-


Band	5GNR												
	2	5	7	25	30	38	41	66	71	77	78		
Peak Gain (dBi)	NB	Ant. 0	2.1	-0.74	2.71	2.1	3.38	2.3	2.71	2.47	1.03	1.78	1.78
		Ant. 1	0.23	-0.07	2.77	0.23	3.9	0.86	2.77	2.96	-	2.6	2.6
		Ant. 2	3.33	-	2.48	3.33	1.35	3.09	3.09	-	-	3.51	3.51
		Ant. 3	2.44	-	1.79	2.44	1.1	1.89	1.89	1.52	-	3.36	3.36
	TB	Ant. 0	2.21	-3.19	2.57	2.25	2.85	2.57	2.78	1.35	-1.81	7.8	7.8
		Ant. 1	0.35	-3.13	1.71	0.35	0.99	2.36	2.36	-0.29	-	5.34	5.34
		Ant. 2	1.65	-	2.2	1.65	1.42	3.25	3.34	-	-	7.94	7.94
		Ant. 3	1.7	-	1.75	1.7	4.16	2.17	2.17	-0.12	-	3.75	3.75

- The above Antenna information refers to the manufacturer's antenna specifications, the laboratory shall not be held responsible.
- The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.
- The EUT contains certified WWAN module with FCC ID: MSQFM350GL.

3.2 Configuration of System under Test

<Radiated Emission Test>

LTE



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
A	Monitor	ASUS	VP247	N/A	N/A
B	Load	N/A	N/A	N/A	N/A
C	Flash	HP	v250W	05	N/A
D	Flash	SanDisk	SDDDC3-032G	N/A	N/A
E	Earphone	Apple	MB77PFEB	N/A	N/A
F	Radio Communication Test Station	Anritsu	MT8000A	6262135011	N/A
G	Radio Communication Test Station	Anritsu	MT8821C	6261806803	N/A

No.	Signal Cable Description of The Above Support Units
1.	HDMI Cable: 2m
2.	LAN Cable: 1.5m
3.	Audio Cable: 1.6m

Note:

1. All power cords of the above support units are non-shielded (1.8m).

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports

The worst case was found when positioned on X-plane Following channel(s) was (were) selected for the final test as listed below:

LTE Band 14

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Radiated Emission	23330	23330	10 MHz	QPSK	1 RB / 0 RB Offset

LTE Band 26

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Radiated Emission	26740	26740	10 MHz	QPSK	1 RB / 0 RB Offset

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
Radiated Emission	22 deg. C, 67 % RH	120 Vac, 60 Hz	Edison Lee, Wade Huang

3.4 General Description of Applied Standards and references

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC 47 CFR Part 2

FCC 47 CFR Part 90

ANSI 63.26-2015

Note: All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 971168 D01 Power Meas License Digital Systems v03r01

KDB 971168 D02 Misc Rev Approv License Devices v02r01

ANSI/TIA/EIA-603-E 2016

Note: All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission Measurement

4.1.1 Limits of Radiated Emission Measurement

- (1) The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. The limit of emission is equal to -13 dBm.
- (2) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

4.1.2 Test Procedure

- a. In the semi-anechoic chamber, EUT placed on the 0.8m(below or equal 1GHz) and/or 1.5m(above 1GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- d. Following C63.26 section 5.5 and 5.2.7
EIRP (dBm) = $E \text{ (dB}\mu\text{V/m)} + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
ERP (dBm) = $E \text{ (dB}\mu\text{V/m)} + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.


Note: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.1.3 Deviation from Test Standard


No deviation.

4.1.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.5 Test Results

Below 1GHz


LTE Band 14

RF Mode	TX LTE Band XIV-10MHz	Channel	CH 23330 :793.0MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	94.02	-70.66	-13.00	-57.66	1.50 H	11	45.51	-116.17
2	230.79	-58.87	-13.00	-45.87	1.01 H	188	54.51	-113.38
3	357.86	-64.78	-13.00	-51.78	1.01 H	351	44.32	-109.10
4	450.98	-67.17	-13.00	-54.17	2.00 H	95	39.30	-106.47
5	555.74	-65.41	-13.00	-52.41	1.01 H	282	39.15	-104.56
6	587.75	-65.14	-13.00	-52.14	1.01 H	5	38.56	-103.70

Remarks:

1. ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + 20log(D) – 104.8 – 2.15
3. Margin value = ERP – Limit value
4. The other ERP levels were very low against the limit.




RF Mode	TX LTE Band XIV-10MHz	Channel	CH 23330 :793.0MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	60.07	-62.88	-13.00	-49.88	1.50 V	260	48.65	-111.53
2	118.27	-65.32	-13.00	-52.32	1.01 V	212	47.75	-113.07
3	207.51	-67.70	-13.00	-54.70	1.01 V	296	46.74	-114.44
4	384.05	-68.81	-13.00	-55.81	1.50 V	192	39.46	-108.27
5	477.17	-67.48	-13.00	-54.48	2.00 V	343	38.65	-106.13
6	545.07	-63.15	-13.00	-50.15	1.01 V	348	41.70	-104.85

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. $Margin\ value = ERP - Limit\ value$
4. The other ERP levels were very low against the limit.




LTE Band 26

RF Mode	TX LTE Band XXVI-10MHz	Channel	CH 26740 :819.0MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	37.76	-61.17	-13.00	-48.17	2.00 H	17	50.09	-111.26
2	154.16	-63.66	-13.00	-50.66	2.00 H	296	46.84	-110.50
3	272.50	-63.39	-13.00	-50.39	1.01 H	162	47.76	-111.15
4	435.46	-71.72	-13.00	-58.72	1.01 H	138	35.02	-106.74
5	575.14	-68.43	-13.00	-55.43	1.50 H	132	35.56	-103.99
6	708.03	-66.88	-13.00	-53.88	1.01 H	2	34.81	-101.69

Remarks:

1. ERP(dBm) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB) + 20log(D) – 104.8 – 2.15
3. Margin value = ERP – Limit value
4. The other ERP levels were very low against the limit.




RF Mode	TX LTE Band XXVI-10MHz	Channel	CH 26740 :819.0MHz
Frequency Range	30MHz ~ 1GHz		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	144.46	-61.12	-13.00	-48.12	2.00 V	166	49.62	-110.74
2	257.95	-70.98	-13.00	-57.98	1.01 V	325	40.96	-111.94
3	316.15	-70.54	-13.00	-57.54	1.01 V	234	39.37	-109.91
4	405.39	-72.46	-13.00	-59.46	1.01 V	55	35.27	-107.73
5	527.61	-69.67	-13.00	-56.67	1.50 V	318	35.33	-105.00
6	604.24	-66.60	-13.00	-53.60	1.01 V	18	36.62	-103.22

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. $Margin\ value = ERP - Limit\ value$
4. The other ERP levels were very low against the limit.



Above 1GHz
LTE Band 14

RF Mode	TX LTE Band XIV-10MHz	Channel	CH 23330: 793.0MHz
Frequency Range	1GHz ~ 18GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1586.00	-46.52	-40.00	-6.52	2.19 H	147	56.88	-103.40
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1586.00	-47.48	-40.00	-7.48	1.97 V	203	55.92	-103.40

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

LTE Band 26

RF Mode	TX LTE Band XXVI-10MHz	Channel	CH 26740 :819.0MHz
Frequency Range	1GHz ~ 18GHz		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1673.00	-58.11	-13.00	-45.11	1.99 H	47	47.35	-105.46
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1673.00	-58.35	-13.00	-45.35	1.89 V	20	47.11	-105.46

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value
4. The other ERP levels were very low against the limit.

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---