



FCC TEST REPORT (15.247)

REPORT NO.: RF150319C06-1
MODEL NO.: P01M
FCC ID: MSQP01M
RECEIVED: Mar. 19, 2015
TESTED: Apr. 07, 2015 ~ Apr. 25, 2015
ISSUED: May 04, 2015

APPLICANT: ASUSTek COMPUTER INC.

ADDRESS: 4F., No. 150, LI-TE Rd., PEITOU, TAIPEI 112, TAIWAN

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New
Taipei City, Taiwan (R.O.C)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan
Dist., Taoyuan City 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

- RELEASE CONTROL RECORD 4
- 1. CERTIFICATION..... 5
- 2. SUMMARY OF TEST RESULTS 6
 - 2.1 MEASUREMENT UNCERTAINTY 6
- 3. GENERAL INFORMATION..... 7
 - 3.1 GENERAL DESCRIPTION OF EUT..... 7
 - 3.2 DESCRIPTION OF TEST MODES..... 9
 - 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 10
 - 3.3 DESCRIPTION OF SUPPORT UNITS..... 12
 - 3.3.1 CONFIGURATION OF SYSTEM UNDER TEST 12
 - 3.4 DUTY CYCLE TEST SIGNAL..... 13
 - 3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS..... 13
- 4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND)..... 14
 - 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT 14
 - 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 14
 - 4.1.2 TEST INSTRUMENTS..... 15
 - 4.1.3 TEST PROCEDURES 16
 - 4.1.4 DEVIATION FROM TEST STANDARD 16
 - 4.1.5 TEST SETUP..... 17
 - 4.1.6 EUT OPERATING CONDITIONS 17
 - 4.1.7 TEST RESULTS..... 18
 - 4.2 CONDUCTED EMISSION MEASUREMENT 32
 - 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 32
 - 4.2.2 TEST INSTRUMENTS..... 32
 - 4.2.3 TEST PROCEDURES 33
 - 4.2.4 DEVIATION FROM TEST STANDARD 33
 - 4.2.5 TEST SETUP..... 34
 - 4.2.6 EUT OPERATING CONDITIONS 34
 - 4.2.7 TEST RESULTS..... 35
 - 4.3 6dB BANDWIDTH MEASUREMENT 41
 - 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT 41
 - 4.3.2 TEST SETUP..... 41
 - 4.3.3 TEST INSTRUMENTS..... 41
 - 4.3.4 TEST PROCEDURE..... 41
 - 4.3.5 DEVIATION FROM TEST STANDARD 41
 - 4.3.6 EUT OPERATING CONDITIONS 41
 - 4.3.7 TEST RESULTS..... 42
 - 4.4 CONDUCTED OUTPUT POWER 44
 - 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT..... 44
 - 4.4.2 TEST SETUP..... 44
 - 4.4.3 TEST INSTRUMENTS..... 44
 - 4.4.4 TEST PROCEDURES 44
 - 4.4.5 DEVIATION FROM TEST STANDARD 44
 - 4.4.6 EUT OPERATING CONDITIONS 44
 - 4.4.7 TEST RESULTS..... 45
 - 4.5 POWER SPECTRAL DENSITY MEASUREMENT..... 46
 - 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 46
 - 4.5.2 TEST SETUP..... 46
 - 4.5.3 TEST INSTRUMENTS..... 46
 - 4.5.4 TEST PROCEDURE..... 46
 - 4.5.5 DEVIATION FROM TEST STANDARD 46
 - 4.5.6 EUT OPERATING CONDITION..... 46



A D T

4.5.7	TEST RESULTS.....	47
4.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT	49
4.6.1	LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT.....	49
4.6.2	TEST SETUP	49
4.6.3	TEST INSTRUMENTS	49
4.6.4	TEST PROCEDURE	49
4.6.5	DEVIATION FROM TEST STANDARD	49
4.6.6	EUT OPERATING CONDITION.....	49
4.6.7	TEST RESULTS.....	50
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	56
6.	INFORMATION ON THE TESTING LABORATORIES	57
7.	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	58



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF150319C06-1	Original release	May 04, 2015



1. CERTIFICATION

PRODUCT: ASUS Tablet
MODEL NO.: P01M
BRAND: ASUS
APPLICANT: ASUSTek COMPUTER INC.
TESTED: Apr. 07, 2015 ~ Apr. 25, 2015
TEST SAMPLE: Production Unit
STANDARDS: **FCC Part 15, Subpart C (Section 15.247)**
ANSI C63.10-2013

The above equipment (model: P01M) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Vera Huang , **DATE :** May 04, 2015
Vera Huang / Specialist

APPROVED BY : Sam chen , **DATE :** May 04, 2015
Sam Chen / Senior Project Engineer

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -10.52dB at 0.75585MHz.
15.205 & 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.05dB at 2483.5MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



A D T

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	ASUS Tablet
MODEL NO.	P01M
POWER SUPPLY	5.2Vdc (adapter) 5.0Vdc (host equipment) 3.8Vdc (Li-ion battery)
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7
OPERATING FREQUENCY	2412 ~ 2462MHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (20MHz)
OUTPUT POWER	183.65mW
ANTENNA TYPE	PIFA antenna with 2.93dBi gain
ANTENNA CONNECTOR	NA
DATA CABLE	Refer to Note as below
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	Refer to Note as below

NOTE:

1. The EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX FUNCTION
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	1TX



2. The EUT contains following accessory devices.

ITEM	BRAND	MODEL	SPECIFICATION
Adapter 1	ASUS	PA-1070-07	I/P: 100-240Vac, 50/60Hz, 0.25A O/P: 5.2Vdc, 1.35A
Adapter 2	ASUS	PSM06A-050Q	I/P: 100-240Vac, 50-60Hz, 0.25A O/P: 5.2Vdc, 1.35A
Adapter 3	ASUS	AD2005320	I/P: 100-240Vac, 50/60Hz, 0.25A O/P: 5.2Vdc, 1.35A
Battery	ASUS	C11P1426	3.8Vdc, 15.2Wh
USB Cable 1	ASUS	AA781000	0.9m cable
USB Cable 2	ASUS	CUBB04M-AS0D0-EF	0.9m cable
CPU 1	INTEL	Moorefield Z3560 935218	Intel Moorefield Quad-Core Atom™ Z3560 1.83GHz, 64bit
CPU 2	INTEL	Moorefield Z3530 935962	Intel Moorefield Quad-Core Atom™ Z3530 1.33 GHz, 64bit
DDR 1	SAMSUNG	K3QF2F20EM-FGCE	2G LPDDR3 1600 256M*32*2 CS
DDR 2	ELPIDA	EDFA164A2PF-GD-F	2G LPDDR3 1600 128*32*4 FBGA-256
DDR 3	HYNIX	H9CKNNNBKTMRPR-NUH	2GB LPDDR3 256M*32*2 1.8V FBGA-256
DDR 4	HYNIX	H9CKNNNCPTMRPR-NUH	4GB LPDDR3 256M*32*4 1.8V FBGA-256
EMMC 1	HYNIX	H26M78103CCR	64 GB
EMMC 2	SAMSUNG	KLMBG4WEBD-B031	32 GB
EMMC 3	SAMSUNG	KLMAG2GEND-B031	16 GB
EMMC 4	SAMSUNG	KLM8G1GEND-B031	8 GB
EMMC 5	Kingston	08G-S100-A08	8 GB
EMMC 6	Kingston	32G-S100-WB	32 GB
LCD Panel 1	AUO	B080QAN03.4	LCD TFT 8.0' QXGA GL SLIM LED
LCD Panel 2	Tianma	TL079QDXP01-00	LCD TFT 8.0' QXGA GL SLIM LED
Touch panel 1	Atmel/ GIS	9AT07967-001 9AT07966-021	0.4 mm
Touch panel 2	Goodix/ GIS	TTCB079005 TTCB079004	0.7 mm
Camera 1	Chicony	CBAE82320003872LH	8M
Camera 2	Chicony	CBFE55720003870LH	5M
Camera 3	Chicony	CJAE56020003870LH	5M
Camera 4	Chicony	CIFE22120003870LH	2M
WLAN / BT Module	BROADCOM	BCM4343S	--

3. There're 3 configurations for the EUT listed as below.

Sample A: Tablet + LCD Panel 2 + Touch Panel 1 + Camera 1 & 2 + Touch pen

Sample B: Tablet + LCD Panel 1 + Touch Panel 1 + Camera 1 & 2 + Touch pen

Sample C: Tablet + LCD Panel 1 + Touch Panel 2 + Camera 3 & 4

4. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

3.2 DESCRIPTION OF TEST MODES

FOR 2.4GHz:

11 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

WLAN 2.4GHz:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE \geq 1G	RE $<$ 1G	PLC	APCM	
A	√	√	√	√	Sample A
B	√	√	√	-	Sample B
C	√	√	√	-	Sample C

Where **RE \geq 1G**: Radiated Emission above 1GHz

RE $<$ 1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.

RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
B, C	802.11n (20MHz)	1 to 11	11	OFDM	BPSK	MCS0

RADIATED EMISSION TEST (BELOW 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A, B, C	802.11n (20MHz)	1 to 11	11	OFDM	BPSK	MCS0



POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A, B, C	802.11n (20MHz)	1 to 11	11	OFDM	BPSK	MCS0

BANDEDGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	MCS0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Hwa Chiang
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Hwa Chiang
PLC	25deg. C, 65%RH	120Vac, 60Hz	Toby Tian
APCM	25deg. C, 65%RH	120Vac, 60Hz	Howard Kao

3.3 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Touch pen	ASUS AC Touch pen	C96AA	N/A	N/A
2	Earphone	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	N/A

NOTE: 1. All power cords of the above support units are non shielded (1.8m).
 2. Item 1 was provided by client.

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST



3.4 DUTY CYCLE TEST SIGNAL

WLAN 2.4GHz

802.11b: Duty cycle of test signal is 100 %

802.11g: Duty cycle = $1.385/1.700 = 0.815$, Duty factor = $10 * \log(1/0.815) = 0.89$

802.11n (20MHz): Duty cycle = $1.300/1.616 = 0.804$, Duty factor = $10 * \log(1/0.804) = 0.95$



3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

558074 D01 DTS Meas Guidance v03r02

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND)

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver Agilent	N9038A	MY51210203	Jan. 21, 2015	Jan. 21, 2016
Spectrum Analyzer Agilent	N9010A	MY52220314	Sep. 03, 2014	Sep. 02, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 10, 2014	Dec. 09, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 09, 2015	Feb. 09, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Feb. 04, 2015	Feb. 04, 2016
Loop Antenna	EM-6879	269	Aug.13, 2014	Aug.12, 2015
Preamplifier EMCI	EMC 012645	980115	Dec. 12, 2014	Dec. 11, 2015
Preamplifier EMCI	EMC 184045	980116	Jan. 09, 2015	Jan. 08, 2016
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2014	Dec. 26, 2015
Power Meter Anritsu	ML2495A	1232002	Sep. 17, 2014	Sep. 16, 2015
Power Sensor Anritsu	MA2411B	1207325	Sep. 17, 2014	Sep. 16, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2014	Oct. 17, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2014	Oct. 17, 2015
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Nov. 07, 2014	Nov. 06, 2015
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. The test was performed in HwaYa Chamber 10.
 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 5. The FCC Site Registration No. is 690701.
 6. The IC Site Registration No. is IC 7450F-10.

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

4.1.5 TEST SETUP

<Frequency Range 30MHz ~ 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



A D T

4.1.7 TEST RESULTS

MODE A

ABOVE 1GHz WORST-CASE DATA

802.11b

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.83	45.1	54	-7.17	31.8	5.4	35.47	100	142	Average
2390	55.2	53.47	74	-18.8	31.8	5.4	35.47	100	142	Peak
2412	108.01	106.24			31.81	5.43	35.47	100	142	Average
2412	111.05	109.28			31.81	5.43	35.47	100	142	Peak
2488	42.2	40.19	54	-11.8	31.9	5.53	35.42	100	142	Average
2488	55.56	53.55	74	-18.44	31.9	5.53	35.42	100	142	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2382	42.55	40.86	54	-11.45	31.78	5.4	35.49	135	4	Average
2382	55.4	53.71	74	-18.6	31.78	5.4	35.49	135	4	Peak
2412	104.92	103.15			31.81	5.43	35.47	135	4	Average
2412	107.81	106.04			31.81	5.43	35.47	135	4	Peak
2500	40.67	38.65	54	-13.33	31.9	5.53	35.41	135	4	Average
2500	54.54	52.52	74	-19.46	31.9	5.53	35.41	135	4	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
2. 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2314	41.06	39.57	54	-12.94	31.71	5.3	35.52	100	144	Average
2314	56.04	54.55	74	-17.96	31.71	5.3	35.52	100	144	Peak
2437	109.27	107.42			31.85	5.46	35.46	100	144	Average
2437	111.89	110.04			31.85	5.46	35.46	100	144	Peak
2488	42.67	40.66	54	-11.33	31.9	5.53	35.42	100	144	Average
2488	56.17	54.16	74	-17.83	31.9	5.53	35.42	100	144	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2366	40.36	38.72	54	-13.64	31.76	5.37	35.49	132	0	Average
2366	54.6	52.96	74	-19.4	31.76	5.37	35.49	132	0	Peak
2437	104.13	102.28			31.85	5.46	35.46	132	0	Average
2437	107.04	105.19			31.85	5.46	35.46	132	0	Peak
2484	40.94	38.98	54	-13.06	31.88	5.5	35.42	132	0	Average
2484	56.04	54.08	74	-17.96	31.88	5.5	35.42	132	0	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2374	40.67	39.01	54	-13.33	31.78	5.37	35.49	100	142	Average
2374	54.65	52.99	74	-19.35	31.78	5.37	35.49	100	142	Peak
2462	108.85	106.92			31.87	5.5	35.44	100	142	Average
2462	111.89	109.96			31.87	5.5	35.44	100	142	Peak
2483.5	47.51	45.55	54	-6.49	31.88	5.5	35.42	100	142	Average
2483.5	57.02	55.06	74	-16.98	31.88	5.5	35.42	100	142	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2352	40.62	39.03	54	-13.38	31.76	5.33	35.5	132	0	Average
2352	55.09	53.5	74	-18.91	31.76	5.33	35.5	132	0	Peak
2462	104.35	102.42			31.87	5.5	35.44	132	0	Average
2462	107.95	106.02			31.87	5.5	35.44	132	0	Peak
2496	42.6	40.58	54	-11.4	31.9	5.53	35.41	132	0	Average
2496	55.62	53.6	74	-18.38	31.9	5.53	35.41	132	0	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.



A D T

802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.89	45.16	54	-7.11	31.8	5.4	35.47	100	143	Average
2390	59.43	57.7	74	-14.57	31.8	5.4	35.47	100	143	Peak
2412	101.11	99.34			31.81	5.43	35.47	100	143	Average
2412	109.53	107.76			31.81	5.43	35.47	100	143	Peak
2494	40.96	38.94	54	-13.04	31.9	5.53	35.41	100	143	Average
2494	55.37	53.35	74	-18.63	31.9	5.53	35.41	100	143	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.66	44.93	54	-7.34	31.8	5.4	35.47	120	3	Average
2390	56.69	54.96	74	-17.31	31.8	5.4	35.47	120	3	Peak
2412	96.71	94.94			31.81	5.43	35.47	120	3	Average
2412	105.36	103.59			31.81	5.43	35.47	120	3	Peak
2492	40.96	38.94	54	-13.04	31.9	5.53	35.41	120	3	Average
2492	55.13	53.11	74	-18.87	31.9	5.53	35.41	120	3	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2374	40.38	38.72	54	-13.62	31.78	5.37	35.49	100	146	Average
2374	56.85	55.19	74	-17.15	31.78	5.37	35.49	100	146	Peak
2437	100.88	99.03			31.85	5.46	35.46	100	146	Average
2437	109.26	107.41			31.85	5.46	35.46	100	146	Peak
2500	41.32	39.3	54	-12.68	31.9	5.53	35.41	100	146	Average
2500	56.43	54.41	74	-17.57	31.9	5.53	35.41	100	146	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2342	40.5	38.93	54	-13.5	31.74	5.33	35.5	135	349	Average
2342	55.33	53.76	74	-18.67	31.74	5.33	35.5	135	349	Peak
2437	97.82	95.97			31.85	5.46	35.46	135	349	Average
2437	105.82	103.97			31.85	5.46	35.46	135	349	Peak
2492	40.96	38.94	54	-13.04	31.9	5.53	35.41	135	349	Average
2492	55.63	53.61	74	-18.37	31.9	5.53	35.41	135	349	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2334	40.3	38.76	54	-13.7	31.73	5.33	35.52	100	144	Average
2334	55.93	54.39	74	-18.07	31.73	5.33	35.52	100	144	Peak
2462	100.8	98.87			31.87	5.5	35.44	100	144	Average
2462	109.03	107.1			31.87	5.5	35.44	100	144	Peak
2483.5	50.81	48.85	54	-3.19	31.88	5.5	35.42	100	144	Average
2483.5	67.82	65.86	74	-6.18	31.88	5.5	35.42	100	144	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2364	40.65	39.02	54	-13.35	31.76	5.37	35.5	146	349	Average
2364	55.2	53.57	74	-18.8	31.76	5.37	35.5	146	349	Peak
2462	96.89	94.96			31.87	5.5	35.44	146	349	Average
2462	105.46	103.53			31.87	5.5	35.44	146	349	Peak
2483.5	48.6	46.64	54	-5.4	31.88	5.5	35.42	146	349	Average
2483.5	63.77	61.81	74	-10.23	31.88	5.5	35.42	146	349	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.



A D T

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	47.38	45.65	54	-6.62	31.8	5.4	35.47	100	144	Average
2390	58.53	56.8	74	-15.47	31.8	5.4	35.47	100	144	Peak
2412	100.48	98.71			31.81	5.43	35.47	100	144	Average
2412	108.34	106.57			31.81	5.43	35.47	100	144	Peak
2486	40.74	38.75	54	-13.26	31.88	5.53	35.42	100	144	Average
2486	55.94	53.95	74	-18.06	31.88	5.53	35.42	100	144	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	44.04	42.31	54	-9.96	31.8	5.4	35.47	121	3	Average
2390	56.72	54.99	74	-17.28	31.8	5.4	35.47	121	3	Peak
2412	96.48	94.71			31.81	5.43	35.47	121	3	Average
2412	104.36	102.59			31.81	5.43	35.47	121	3	Peak
2494	40.67	38.65	54	-13.33	31.9	5.53	35.41	121	3	Average
2494	55.95	53.93	74	-18.05	31.9	5.53	35.41	121	3	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2412MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2386	40.72	39.01	54	-13.28	31.8	5.4	35.49	100	144	Average
2386	55.84	54.13	74	-18.16	31.8	5.4	35.49	100	144	Peak
2437	100.55	98.7			31.85	5.46	35.46	100	144	Average
2437	108.68	106.83			31.85	5.46	35.46	100	144	Peak
2488	40.67	38.66	54	-13.33	31.9	5.53	35.42	100	144	Average
2488	56.2	54.19	74	-17.8	31.9	5.53	35.42	100	144	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2338	40.55	39	54	-13.45	31.74	5.33	35.52	149	330	Average
2338	55.72	54.17	74	-18.28	31.74	5.33	35.52	149	330	Peak
2437	96.35	94.5			31.85	5.46	35.46	149	330	Average
2437	104.63	102.78			31.85	5.46	35.46	149	330	Peak
2486	40.97	38.98	54	-13.03	31.88	5.53	35.42	149	330	Average
2486	55.86	53.87	74	-18.14	31.88	5.53	35.42	149	330	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2437MHz: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2330	40.32	38.78	54	-13.68	31.73	5.33	35.52	100	142	Average
2330	54.96	53.42	74	-19.04	31.73	5.33	35.52	100	142	Peak
2462	100.92	98.99			31.87	5.5	35.44	100	142	Average
2462	108.7	106.77			31.87	5.5	35.44	100	142	Peak
2483.5	50.95	48.99	54	-3.05	31.88	5.5	35.42	100	142	Average
2483.5	67.15	65.19	74	-6.85	31.88	5.5	35.42	100	142	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2364	40.36	38.73	54	-13.64	31.76	5.37	35.5	149	330	Average
2364	55.47	53.84	74	-18.53	31.76	5.37	35.5	149	330	Peak
2462	95.84	93.91			31.87	5.5	35.44	149	330	Average
2462	104.25	102.32			31.87	5.5	35.44	149	330	Peak
2483.5	43.91	41.95	54	-10.09	31.88	5.5	35.42	149	330	Average
2483.5	58.73	56.77	74	-15.27	31.88	5.5	35.42	149	330	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.



A D T

BELOW 1GHz WORST-CASE DATA:

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
31.89	22.66	37.85	40	-17.34	16.33	0.74	32.26	179	269	Peak
103.71	28.96	50.35	43.5	-14.54	9.59	1.28	32.26	141	147	Peak
210.9	27.88	47.14	43.5	-15.62	11.35	1.65	32.26	133	205	Peak
533.8	21.55	30.45	46	-24.45	20.57	2.7	32.17	153	182	Peak
716.5	24.91	30.64	46	-21.09	23.27	3.11	32.11	142	166	Peak
916	28.17	30.05	46	-17.83	25.96	3.53	31.37	171	332	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
31.89	32.32	47.51	40	-7.68	16.33	0.74	32.26	161	151	Peak
47.55	29.65	52.4	40	-10.35	8.57	0.9	32.22	144	315	Peak
198.48	20.66	40.5	43.5	-22.84	10.84	1.61	32.29	176	277	Peak
491.8	20.97	31.47	46	-25.03	18.97	2.63	32.1	154	22	Peak
679.4	24.52	30.27	46	-21.48	23.31	3.05	32.11	182	167	Peak
920.9	29.19	30.79	46	-16.81	26.2	3.53	31.33	169	118	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value



A D T

MODE B

ABOVE 1GHz WORST-CASE DATA

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2382	40.4	38.71	54	-13.6	31.78	5.4	35.49	115	145	Average
2382	55.47	53.78	74	-18.53	31.78	5.4	35.49	115	145	Peak
2462	100.31	98.38			31.87	5.5	35.44	115	145	Average
2462	108.88	106.95			31.87	5.5	35.44	115	145	Peak
2484	46.99	45.03	54	-7.01	31.88	5.5	35.42	115	145	Average
2484	65.03	63.07	74	-8.97	31.88	5.5	35.42	115	145	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2352	40.16	38.57	54	-13.84	31.76	5.33	35.5	292	95	Average
2352	55.97	54.38	74	-18.03	31.76	5.33	35.5	292	95	Peak
2462	95.57	93.64			31.87	5.5	35.44	292	95	Average
2462	104.2	102.27			31.87	5.5	35.44	292	95	Peak
2484	45.91	43.95	54	-8.09	31.88	5.5	35.42	292	95	Average
2484	63.67	61.71	74	-10.33	31.88	5.5	35.42	292	95	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.



A D T

BELOW 1GHz WORST-CASE DATA:

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
99.12	30.08	51.39	43.5	-13.42	9.62	1.28	32.21	196	222	Peak
145.56	25.34	46.44	43.5	-18.16	9.79	1.38	32.27	125	145	Peak
210.9	30.98	50.24	43.5	-12.52	11.35	1.65	32.26	109	308	Peak
521.2	21.38	30.31	46	-24.62	20.51	2.7	32.14	152	214	Peak
694.8	25.66	31.5	46	-20.34	23.14	3.11	32.09	142	286	Peak
923.7	28.08	29.66	46	-17.92	26.2	3.53	31.31	128	92	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
32.43	31.98	47.53	40	-8.02	15.96	0.74	32.25	134	44	Peak
47.82	31.11	53.95	40	-8.89	8.48	0.9	32.22	184	48	Peak
206.58	21.47	40.92	43.5	-22.03	11.17	1.65	32.27	140	91	Peak
729.8	24.56	30.15	46	-21.44	23.37	3.16	32.12	122	233	Peak
880.3	26.67	29.94	46	-19.33	24.84	3.49	31.6	126	80	Peak
953.1	28.57	29.83	46	-17.43	26.12	3.67	31.05	174	241	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value



A D T

MODE C

ABOVE 1GHz WORST-CASE DATA

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2310	40.01	38.53	54	-13.99	31.71	5.3	35.53	126	336	Average
2310	55.52	54.04	74	-18.48	31.71	5.3	35.53	126	336	Peak
2462	100.46	98.53			31.87	5.5	35.44	126	336	Average
2462	108.78	106.85			31.87	5.5	35.44	126	336	Peak
2484	48.54	46.58	54	-5.46	31.88	5.5	35.42	126	336	Average
2484	66.9	64.94	74	-7.1	31.88	5.5	35.42	126	336	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2350	40.38	38.81	54	-13.62	31.74	5.33	35.5	103	310	Average
2350	55.7	54.13	74	-18.3	31.74	5.33	35.5	103	310	Peak
2462	96.36	94.43			31.87	5.5	35.44	103	310	Average
2462	104.71	102.78			31.87	5.5	35.44	103	310	Peak
2484	48.83	46.87	54	-5.17	31.88	5.5	35.42	103	310	Average
2484	66.69	64.73	74	-7.31	31.88	5.5	35.42	103	310	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
Margin value = Emission level – Limit value
- 2462MHz: Fundamental frequency.



A D T

BELOW 1GHz WORST-CASE DATA:

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Hwa Chiang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
98.85	29.55	50.9	43.5	-13.95	9.58	1.28	32.21	135	245	Peak
160.14	26.12	46.07	43.5	-17.38	10.8	1.52	32.27	188	287	Peak
212.52	31.14	50.34	43.5	-12.36	11.4	1.65	32.25	165	216	Peak
349	22.55	36.12	46	-23.45	16.31	2.19	32.07	151	115	Peak
671.7	25.27	30.94	46	-20.73	23.4	3.05	32.12	162	222	Peak
924.4	28.65	30.22	46	-17.35	26.2	3.53	31.3	121	34	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
32.7	32.78	48.45	40	-7.22	15.84	0.74	32.25	103	209	Peak
48.36	29.56	52.57	40	-10.44	8.31	0.9	32.22	122	302	Peak
203.61	23.49	43.08	43.5	-20.01	11.04	1.65	32.28	134	182	Peak
533.8	21.54	30.44	46	-24.46	20.57	2.7	32.17	154	229	Peak
709.5	24.75	30.51	46	-21.25	23.23	3.11	32.1	106	6	Peak
957.3	28.69	29.96	46	-17.31	26.04	3.67	30.98	125	302	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 11, 2014	Nov. 10, 2015
RF signal cable Woken	5D-FB	Cable-HYC01-01	Dec. 26, 2014	Dec. 25, 2015
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Mar. 02, 2015	Mar. 01, 2016
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 21, 2014	Jul. 20, 2015
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.

4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as section 4.1.6.



A D T

4.2.7 TEST RESULTS

CONDUCTED WORST-CASE DATA :


MODE A

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Toby Tian	Test Date	2015/4/21

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16569	0.05	39.97	28.99	40.02	29.04	65.17	55.17	-25.15	-26.13
2	0.37678	0.06	37.94	30.67	38.00	30.73	58.35	48.35	-20.35	-17.62
3	0.47453	0.06	41.47	32.13	41.53	32.19	56.43	46.43	-14.90	-14.24
4	1.22134	0.09	36.65	26.74	36.74	26.83	56.00	46.00	-19.26	-19.17
5	2.16365	0.13	37.78	25.26	37.91	25.39	56.00	46.00	-18.09	-20.61
6	16.17318	0.73	41.61	32.89	42.34	33.62	60.00	50.00	-17.66	-16.38

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value






A D T

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Toby Tian	Test Date	2015/4/21

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17374	0.05	39.22	29.49	39.27	29.54	64.78	54.78	-25.51	-25.24
2	0.37304	0.06	37.35	31.01	37.41	31.07	58.43	48.43	-21.02	-17.36
3	0.49408	0.06	39.17	32.05	39.23	32.11	56.10	46.10	-16.87	-13.99
4	1.62016	0.10	37.80	27.35	37.90	27.45	56.00	46.00	-18.10	-18.55
5	2.73842	0.14	38.01	27.33	38.15	27.47	56.00	46.00	-17.85	-18.53
6	15.69225	0.60	43.97	36.22	44.57	36.82	60.00	50.00	-15.43	-13.18

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value





A D T


MODE B

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Toby Tian	Test Date	2015/4/24

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	0.05	52.04	33.25	52.09	33.30	65.79	55.79	-13.70	-22.49
2	0.18910	0.06	52.86	33.49	52.92	33.55	64.08	54.08	-11.16	-20.53
3	0.24775	0.06	42.09	23.71	42.15	23.77	61.83	51.83	-19.68	-28.06
4	0.66430	0.07	41.96	32.94	42.03	33.01	56.00	46.00	-13.97	-12.99
5	0.75585	0.07	42.97	35.41	43.04	35.48	56.00	46.00	-12.96	-10.52
6	14.26901	0.64	44.43	34.49	45.07	35.13	60.00	50.00	-14.93	-14.87

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value






A D T

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Toby Tian	Test Date	2015/4/24

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.05	48.75	29.98	48.80	30.03	66.00	56.00	-17.20	-25.97
2	0.18363	0.05	45.09	26.55	45.14	26.60	64.32	54.32	-19.18	-27.72
3	0.22820	0.05	38.46	21.63	38.51	21.68	62.51	52.51	-24.00	-30.83
4	0.65830	0.07	37.15	27.97	37.22	28.04	56.00	46.00	-18.78	-17.96
5	0.74792	0.07	39.97	31.55	40.04	31.62	56.00	46.00	-15.96	-14.38
6	13.89365	0.54	41.70	31.07	42.24	31.61	60.00	50.00	-17.76	-18.39

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value





A D T


MODE C

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Toby Tian	Test Date	2015/4/24

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	0.05	44.77	27.83	44.82	27.88	65.79	55.79	-20.97	-27.91
2	0.19692	0.06	40.17	23.29	40.23	23.35	63.74	53.74	-23.51	-30.39
3	0.65907	0.07	43.91	34.39	43.98	34.46	56.00	46.00	-12.02	-11.54
4	0.76386	0.07	42.89	34.50	42.96	34.57	56.00	46.00	-13.04	-11.43
5	0.99456	0.08	38.47	29.32	38.55	29.40	56.00	46.00	-17.45	-16.60
6	13.82718	0.62	43.01	33.90	43.63	34.52	60.00	50.00	-16.37	-15.48

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value






A D T

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25°C, 65%RH
Tested by	Toby Tian	Test Date	2015/4/24

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16564	0.05	39.45	21.49	39.50	21.54	65.18	55.18	-25.68	-33.64
2	0.19305	0.05	40.67	23.73	40.72	23.78	63.90	53.90	-23.18	-30.12
3	0.56055	0.07	36.49	28.95	36.56	29.02	56.00	46.00	-19.44	-16.98
4	0.65439	0.07	37.65	28.45	37.72	28.52	56.00	46.00	-18.28	-17.48
5	0.75585	0.07	39.60	31.06	39.67	31.13	56.00	46.00	-16.33	-14.87
6	13.61604	0.53	40.94	30.51	41.47	31.04	60.00	50.00	-18.53	-18.96

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURE

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



A D T

4.3.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.55	0.5	PASS
6	2437	9.04	0.5	PASS
11	2462	8.57	0.5	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	15.14	0.5	PASS
6	2437	15.16	0.5	PASS
11	2462	15.16	0.5	PASS

802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	15.11	0.5	PASS
6	2437	15.16	0.5	PASS
11	2462	15.14	0.5	PASS




A D T

SPECTRUM PLOT OF WORST VALUE


802.11b



802.11g



802.11n (20MHz)




4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as section 4.3.6.



A D T

4.4.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS / FAIL
1	2412	71.45	18.54	30	PASS
6	2437	73.11	18.64	30	PASS
11	2462	69.66	18.43	30	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS / FAIL
1	2412	174.18	22.41	30	PASS
6	2437	183.65	22.64	30	PASS
11	2462	182.81	22.62	30	PASS

802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS / FAIL
1	2412	168.27	22.26	30	PASS
6	2437	170.61	22.32	30	PASS
11	2462	159.96	22.04	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
- Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as section 4.3.6.



4.5.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS / FAIL
1	2412	-6.07	8	PASS
6	2437	-6.78	8	PASS
11	2462	-6.81	8	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS / FAIL
1	2412	-11.01	8	PASS
6	2437	-11.46	8	PASS
11	2462	-11.10	8	PASS

802.11n (20MHz)


CHANNEL	FREQUENCY (MHz)	PSD (dBm/3kHz)	LIMIT (dBm/3kHz)	PASS / FAIL
1	2412	-12.31	8	PASS
6	2437	-12.41	8	PASS
11	2462	-12.59	8	PASS




A D T

SPECTRUM PLOT OF WORST VALUE


802.11b



802.11g



802.11n (20MHz)




4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

Same as section 4.3.6.




A D T

4.6.7 TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

802.11b






A D T






A D T

802.11g






A D T






A D T

802.11n (20MHz)





A D T





A D T

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---