

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C AND CANADIAN RSS 210 ISSUE 8
REQUIREMENT**

OF

ASUS RT-N10U_BLACK

MODEL No.: RT-N10U_BLACK, RT-N10U

FCC ID: MSQRTN10UB

IC ID: 3568A-RTN10UB

REPORT NO: ES110521096F

ISSUE DATE: June 16, 2011

Prepared for

ASUSTEK COMPUTER INC

No. 15, Li-Te Rd., Peitou, Taipei 112, Taiwan

Prepared by

SHENZHEN EMTEK CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China**

TEL: 86-755-26954280

FAX: 86-755-26954282

VERIFICATION OF COMPLIANCE


Applicant:	ASUSTEK COMPUTER INC No. 15, Li-Te Rd., Peitou, Taipei 112, Taiwan
Manufacturer:	ASUSTEK COMPUTER INC No. 15, Li-Te Rd., Peitou, Taipei 112, Taiwan
Trademark:	ASUS
Product Description:	ASUS RT-N10U_BLACK
Model Number:	RT-N10U_BLACK, RT-N10U (Note: The two sample are the same, except model number are different. We prepare RT-N10U_BLACK for FCC test.)
File Number:	ES110521096F
Date of Test:	May 21, 2011 to June 15, 2011

We hereby certify that:

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009), RSS GEN Issue 2 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247 and RSS 210 Issue 8.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : May 21, 2011 to June 15, 2011

Prepared by : 
(Engineer)

Reviewer : 
(Quality Manager)

Approve & Authorized Signer : 
(Manager)

Table of Contents

1. General Information	5
1.1 Product Description.....	5
1.2 Related Submittal(s) / Grant(s)	5
1.3 Test Methodology.....	6
1.4 Special Accessories	6
1.5 Equipment Modifications.....	6
1.6 Test Facility	6
2. System Test Configuration	7
2.1 EUT Configuration.....	7
2.2 EUT Exercise	7
2.3 Test Procedure	7
2.4 Configuration of Tested System.....	7
3. Description of Test Modes	9
4. Summary of Test Results	10
5. Conducted Emissions Test	11
5.1 Measurement Procedure.....	11
5.2 Test SET-UP (Block Diagram of Configuration)	11
5.3 Measurement Equipment Used	11
5.4 Conducted Emission Limit.....	11
5.5 Measurement Result.....	12
5.6 Conducted Measurement Photo	13
6. Radiated Emission Test.....	14
6.1 Measurement Procedure.....	14
6.2 Test SET-UP (Block Diagram of Configuration)	14
6.3 Measurement Equipment Used	15
6.4 Radiated Emission Limit.....	15
6.5 Measurement Result.....	16
6.6 Radiated Measurement Photos.....	37
7. Occupied Bandwidth Test.....	37
7.1 Measurement Procedure.....	37
7.2 Test SET-UP (Block Diagram of Configuration)	37
7.3 Measurement Equipment Used	37
7.4 Measurement Results	37
8. Maximum Peak Output Power Test	37
8.1 Measurement Procedure.....	37
8.2 Test SET-UP (Block Diagram of Configuration)	37
8.3 Measurement Equipment Used	37
8.4 Peak Power output limit	37
8.5 Measurement Results	37

9. Band Edge Test	37
9.1 Measurement Procedure	37
9.2 Test SET-UP (Block Diagram of Configuration)	37
9.3 Measurement Equipment Used	37
9.4 Measurement Results	37
10. Power Density.....	37
10.1 Test Equipment.....	37
10.2 Measuring Instruments and Setting.....	37
10.3 Test Procedures	37
10.4 Block Diagram of Test Setup	37
10.5 Limit.....	37
10.6 Test Result.....	37
11. Antenna Port Emission	37
11.1 Test Equipment.....	37
11.2 Measuring Instruments and Setting.....	37
11.3 Test Procedures	37
11.4 Block Diagram of Test setup.....	37
11.5 Test Result.....	37
12. Antenna Application.....	37
12.1 Antenna Requirement.....	37
12.2 Result.....	37

1. General Information

1.1 Product Description

A major technical descriptions of EUT is described as following:

A). Standards: IEEE802.11b/g/n

B). Operation Frequency: IEEE802.11b/g/n 20MHz: 2.412GHz – 2.462GHz

IEEE802.11b/g/n 40MHz: 2.422GHz – 2.452GHz

C). Modulation: 802.11n: OFDM

802.11g: QPSK, QDBPS, CCK, OFDM

802.11b: QPSK, QDBPS, CCK

D). Number of Channel: 11

E). Data Rate (Max): 802.11b: 11Mbps

802.11g: 54Mbps

802.11n: 150Mbps

F). Conducted Power: 16.87dBm(802.11b), 16.17dBm(802.11g), 16.02dBm(802.11n, HT20), 15.89dBm(802.11n, HT40)

G) Antenna Gain: 5dBi

H). Antenna Type: SMA Male Reverse Antenna

I). Power Supply: DC5V /1A

J). Adapter: Model: DSA-12PFA-05 FUS 050150

Input: AC 100-240V, 50/60Hz, 0.5A Max

Output: DC 5V, 1.5A

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Note:

1. This device is a ASUS RT-N10U_BLACK included 802.11b, 802.11g and 802.11n 2.4GHz transceiver function.
2. Test of channel was included the lowest middle and highest frequency in highest data rate and to perform the test, then record on this report.

1.2 Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: MSQRTN10UB, IC ID: 3568A-RTN10UB filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules and Canadian RSS 210 Issue 8. The composite system (receiver) is compliance with Subpart B is authorized under a DOC procedure.

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4 (2009) and RSS GEN. Radiated testing was performed at an antenna to EUT distance 3 meters.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description

EMC Lab.

: Accredited by CNAS, 2010.10.29

The certificate is valid until 2013.10.28

The Laboratory has been assessed and proved to be in compliance with CNAS/CL01: 2006(identical to ISO/IEC17025: 2005)

The Certificate Registration Number is L2291

Accredited by TUV Rheinland Shenzhen 2010.5.25

The Laboratory has been assessed according to the requirements ISO/IEC 17025

Accredited by FCC, October 28, 2010

The Certificate Registration Number is 406365.

Accredited by Industry Canada, March 05, 2010

The Certificate Registration Number is 46405-4480.

Name of Firm

: SHENZHEN EMTEK CO., LTD.

Site Location

: Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. the Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2009 and in RSS GEN Table 2 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	ASUS RT-N10U_BLACK K	ASUS	RT-N10U_BLACK	MSQRTN10 UB	N/A	EUT
2	Adapter	DVE	DSA-12PFA-05 FUS 050150	N/A	N/A	
3	PC	LENOVO	9702	N/A	L3C4410	
4	LCD Monitor	LENOVO	9227-AE6	N/A	4M0293084302824	
5	Keyboard	LENOVO	KU-0225	N/A	0585494	
6	Mouse	LENOVO	MO28UOL	N/A	44G7862 068	

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The Transmitter of EUT is a ASUS RT-N10U_BLACK and powered by host equipment. The max data rates of this Digital Transmission system(DTS) are 11Mbps(802.11b), 54Mbps(802.11g) & 150Mbps(802.11n).

The equipment enables high-speed access without wires to network assets. This adapter uses the IEEE 802.11b/g/n protocol to enable wireless communications between the host ASUS RT-N10U_BLACK and Wireless router, in the same way that the ASUS RT-N10U_BLACK would use an Ethernet adapter.

1. For lowest channel : 2412MHz (Channel 1)
2. For middle channel : 2437MHz (Channel 6)
3. For highest channel: 2462MHz (Channel 11)

EUT operating conditions:

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to typical use, The exercise sequence is listed as below:

1. Setup the EUT and simulators as shown on 2.4.
2. Turn on the power of all equipments.
3. The EUT Ping with the wireless router.
4. Repeat the above steps.

4. Summary of Test Results


IC Rules	FCC Rules	Description Of Test	Result
RSS 210 A8.2(a)	§15.247(a)(2)	6dB bandwidth	Compliant
RSS Gen	---	99% bandwidth	Compliant
RSS 210 A8.4(4)	§15.247(b)(3)	Max Peak output Power test	Compliant
RSS 210 A8.2(b)	§15.247(e)	Power density	Compliant
RSS 210 A8.5	§15.247(d)	Band edge test	Compliant
RSS GEN Table 2	§15.207	AC Power Conducted Emission	Compliant
RSS 210 Table 2	§15.247(d), §15.209	Radiated Emission	Compliant
RSS 210 A8.4(6)	§15.203	Antenna Port Emission	Compliant
---	§15.109	Antenna Application	Compliant

5. Conducted Emissions Test

5.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2011	05/29/2012
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/29/2011	05/29/2012
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/29/2011	05/29/2012
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/29/2011	05/29/2012
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/29/2011	05/29/2012

5.4 Conducted Emission Limit

Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.5 Measurement Result

Date of Test:	May 24, 2011	Temperature:	22
Frequency Detector:	0.15~30MHz	Humidity:	50%
Test Result:	PASS	Test Mode:	WIFI Mode

Test Line	Frequency MHz	Emission Level QP dB(μV)	Emission Level AV dB(μV)	Limits QP dB(μV)	Limits AV dB(μV)	Over QP dB(μV)	Over AV dB(μV)
Line	0.16	56.24	38.99	65.46	55.46	-9.22	-16.47
	0.20	51.46	35.50	63.61	53.61	-12.15	-18.11
	0.27	48.03	32.60	61.12	51.12	-13.09	-18.52
	0.62	38.21	23.73	56.00	46.00	-17.79	-22.27
	0.88	37.09	23.51	56.00	46.00	-18.91	-22.49
	6.33	43.25	30.69	60.00	50.00	-16.75	-19.31
Neutral	0.17	55.35	39.20	64.96	54.96	-9.61	-15.76
	0.27	47.66	39.08	61.12	51.12	-13.46	-12.04
	0.63	39.24	29.41	56.00	46.00	-16.76	-16.59
	1.12	39.34	29.20	56.00	46.00	-16.66	-16.80
	1.85	40.34	28.55	56.00	46.00	-15.66	-17.45
	6.49	45.95	32.68	60.00	50.00	-14.05	-17.32

5.6 Conducted Measurement Photo




6. Radiated Emission Test

6.1 Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



6.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Pre-Amplifier	HP	8447D	2944A07999	05/29/2011	05/29/2012
Bilog Antenna	Schwarzbeck	VULB9163	142	05/29/2011	05/29/2012
Loop Antenna	ARA	PLA-1030/B	1029	05/29/2011	05/29/2012
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/29/2011	05/29/2012
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/29/2011	05/29/2012
Cable	Schwarzbeck	AK9513	ACRX1	05/29/2011	05/29/2012
Cable	Rosenberger	N/A	FP2RX2	05/29/2011	05/29/2012
Cable	Schwarzbeck	AK9513	CRPX1	05/29/2011	05/29/2012
Cable	Schwarzbeck	AK9513	CRRX2	05/29/2011	05/29/2012
Pre-Amplifier	HP	8447D	2944A07999	05/29/2011	05/29/2012

6.4 Radiated Emission Limit

FCC Class B Limit at 3m:

Frequency MHz	Distance Meter	Field Strength uV/m	Field Strength dBuV/m
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
Above 960	3	500	54.0

Note: The frequencies above 1000MHz, as measured using instrumentation with a peak detector function was corresponding to 20dB above maximum permitted average limit.

6.5 Measurement Result

TX Mode:

Operation Mode:	802.11b TX Channel 1	Test Date :	June 7, 2011
Frequency Range:	30~1000MHz	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
31.00	V	37.16	40.00	-2.84	PK
50.21	V	33.07	40.00	-6.93	PK
101.51	V	39.40	43.50	-4.10	PK
140.37	V	32.25	43.50	-11.25	PK
375.10	V	28.99	46.00	-17.01	PK
499.46	V	37.84	46.00	-8.16	PK
30.78	H	28.63	40.00	-11.37	PK
54.87	H	27.13	40.00	-12.87	PK
101.51	H	31.26	43.50	-12.24	PK
249.18	H	32.48	46.00	-13.52	PK
375.10	H	32.39	46.00	-13.61	PK
499.46	H	35.13	46.00	-10.87	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11b TX Channel 6 Test Date : June 7, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
33.05	V	37.04	40	-2.96	PK
51.53	V	32.72	40	-7.28	PK
105.08	V	39.19	43.5	-4.31	PK
136.37	V	31.62	43.5	-11.88	PK
372.14	V	29.47	46	-16.53	PK
498.41	V	37.57	46	-8.43	PK
31.26	H	28.10	40	-11.90	PK
51.93	H	27.91	40	-12.09	PK
103.91	H	31.76	43.5	-11.74	PK
248.11	H	31.97	46	-14.03	PK
371.13	H	32.56	46	-13.44	PK
496.42	H	34.68	46	-11.32	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11b TX Channel 11 Test Date : June 7, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
32.12	V	36.71	40	-3.29	PK
49.14	V	32.04	40	-7.96	PK
100.26	V	38.35	43.5	-5.15	PK
142.38	V	30.57	43.5	-12.93	PK
375.05	V	25.15	46	-20.85	PK
499.44	V	34.13	46	-11.87	PK
32.05	H	25.97	40	-14.03	PK
56.08	H	28.16	40	-11.84	PK
97.88	H	28.65	43.5	-14.85	PK
252.42	H	34.96	46	-11.04	PK
376.52	H	30.51	46	-15.49	PK
522.51	H	34.79	46	-11.21	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11g TX Channel 1 Test Date : June 7, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
32.22	V	36.69	40.00	-3.31	PK
51.26	V	31.84	40.00	-8.16	PK
100.73	V	39.22	43.50	-4.28	PK
141.42	V	31.69	43.50	-11.81	PK
376.22	V	28.63	46.00	-17.37	PK
499.19	V	37.62	46.00	-8.38	PK
31.02	H	27.89	40.00	-12.11	PK
55.65	H	27.75	40.00	-12.25	PK
102.00	H	32.27	43.50	-11.23	PK
248.67	H	31.04	46.00	-14.96	PK
375.27	H	32.75	46.00	-13.25	PK
499.91	H	34.72	46.00	-11.28	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11g TX Channel 6 Test Date : June 7, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65%
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
33.47	V	36.18	40	-3.82	PK
50.91	V	30.79	40	-9.21	PK
104.24	V	39.01	43.5	-4.49	PK
138.37	V	31.14	43.5	-12.36	PK
373.76	V	28.51	46	-17.49	PK
498.14	V	37.54	46	-8.46	PK
32.07	H	27.46	40	-12.54	PK
53.17	H	28.41	40	-11.59	PK
103.45	H	33.29	43.5	-10.21	PK
246.62	H	29.99	46	-16.01	PK
371.63	H	32.90	46	-13.10	PK
495.55	H	34.27	46	-11.73	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11g TX Channel 11 Test Date : June 7, 2011
 Frequency Range: 30~1000MHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
33.27	V	36.33	40	-3.67	PK
50.21	V	30.72	40	-9.28	PK
98.37	V	37.17	43.5	-6.33	PK
143.77	V	29.47	43.5	-14.03	PK
376.10	V	24.79	46	-21.21	PK
498.75	V	34.18	46	-11.82	PK
32.38	H	25.23	40	-14.77	PK
57.13	H	27.37	40	-12.63	PK
98.27	H	29.22	43.5	-14.28	PK
250.73	H	29.92	46	-16.08	PK
376.02	H	31.39	46	-14.61	PK
515.54	H	33.95	46	-12.05	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode:	802.11n HT20	Test Date :	June 7, 2011
	TX Channel 1		
Frequency Range:	30~1000MHz	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
30.33	V	37.01	40.00	-2.99	PK
49.00	V	31.95	40.00	-8.05	PK
101.30	V	39.15	43.50	-4.35	PK
139.82	V	32.11	43.50	-11.39	PK
376.16	V	28.64	46.00	-17.36	PK
499.38	V	37.66	46.00	-8.34	PK
34.05	H	28.52	40.00	-11.48	PK
55.53	H	28.15	40.00	-11.85	PK
102.53	H	32.27	43.50	-11.23	PK
248.13	H	31.96	46.00	-14.04	PK
375.25	H	32.84	46.00	-13.16	PK
500.72	H	34.35	46.00	-11.65	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11n HT20

Test Date : June 7, 2011

TX Channel 6

Frequency Range: 30~1000MHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
32.69	V	36.54	40	-3.46	PK
47.95	V	30.72	40	-9.28	PK
103.33	V	38.97	43.5	-4.53	PK
136.37	V	31.55	43.5	-11.95	PK
374.05	V	28.28	46	-17.72	PK
497.35	V	37.44	46	-8.56	PK
31.60	H	27.78	40	-12.22	PK
52.90	H	28.77	40	-11.23	PK
103.97	H	33.28	43.5	-10.22	PK
246.12	H	30.52	46	-15.48	PK
372.00	H	33.20	46	-12.80	PK
499.67	H	33.94	46	-12.06	PK

Note: (1) All Readings are Peak Value.

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11n HT20
TX Channel 11

Test Date : June 7, 2011

Frequency Range: 30~1000MHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
33.94	V	36.36	40	-3.64	PK
47.95	V	30.7	40	-9.30	PK
98.94	V	37.46	43.5	-6.04	PK
142.17	V	29.89	43.5	-13.61	PK
376.04	V	24.87	46	-21.13	PK
498.94	V	34.45	46	-11.55	PK
35.41	H	26.07	40	-13.93	PK
57.01	H	27.93	40	-12.07	PK
98.80	H	30.14	43.5	-13.36	PK
250.19	H	30.18	46	-15.82	PK
376.00	H	31.3	46	-14.70	PK
516.35	H	33.3	46	-12.70	PK

Note: (1) All Readings are Peak Value.

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode:	802.11n HT40 TX Channel 1	Test Date :	June 7, 2011
Frequency Range:	30~1000MHz	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
31.00	V	37.11	40.00	-2.89	PK
101.51	V	31.88	40.00	-8.12	PK
143.48	V	36.05	43.50	-7.45	PK
300.48	V	33.65	46.00	-12.35	PK
499.46	V	38.08	46.00	-7.92	PK
600.50	V	43.64	46.00	-2.36	PK
54.87	H	28.4	40.00	-11.60	PK
106.17	H	28.49	43.50	-15.01	PK
138.81	H	30.8	43.50	-12.70	PK
183.89	H	32.89	43.50	-10.61	PK
249.18	H	31.73	46.00	-14.27	PK
499.46	H	33.08	46.00	-12.92	PK

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11n HT40

Test Date : June 7, 2011

TX Channel 6

Frequency Range: 30~1000MHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
33.36	V	36.64	40	-3.36	PK
100.46	V	30.65	40	-9.35	PK
145.51	V	35.87	43.5	-7.63	PK
297.03	V	33.09	46	-12.91	PK
497.35	V	37.72	46	-8.28	PK
598.47	V	43.42	46	-2.58	PK
52.42	H	27.66	40	-12.34	PK
103.54	H	29.11	43.5	-14.39	PK
140.25	H	31.81	43.5	-11.69	PK
181.88	H	31.45	43.5	-12.05	PK
245.93	H	32.09	46	-13.91	PK
498.41	H	32.67	46	-13.33	PK

Note: (1) All Readings are Peak Value.

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11n HT40
TX Channel 11

Test Date : June 7, 2011

Frequency Range: 30~1000MHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
34.61	V	36.1	40	-3.90	PK
100.46	V	31.41	40	-8.59	PK
141.12	V	34.94	43.5	-8.56	PK
302.83	V	31.43	46	-14.57	PK
499.34	V	35.96	46	-10.04	PK
600.06	V	43.43	46	-2.57	PK
56.23	H	25.95	40	-14.05	PK
107.65	H	28.27	43.5	-15.23	PK
135.08	H	29.75	43.5	-13.75	PK
185.95	H	31.77	43.5	-11.73	PK
249.93	H	30.95	46	-15.05	PK
515.09	H	32.03	46	-13.97	PK

Note: (1) All Readings are Peak Value.

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: 802.11b TX Channel 1

Test Date : June 7, 2011

Frequency Range: Above 1GHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8673.07	V	52.24	41.65	74	54	-21.76	-12.35
9923.07	V	56.82	45.31	74	54	-17.18	-8.69
10884.61	V	56.04	45.59	74	54	-17.96	-8.41
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9346.15	H	55.84	44.04	74	54	-18.16	-9.96
9826.92	H	57.01	45.58	74	54	-16.99	-8.42
10865.38	H	58.1	45.91	74	54	-15.9	-8.09

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11b TX (Channel 6) Test Date : June 7, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8688.39	V	50.44	40.45	74	54	-23.56	-13.55
9933.42	V	59.27	45.98	74	54	-14.73	-8.02
10863.46	V	55.02	44.56	74	54	-18.98	-9.44
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9356.82	H	59.34	44.9	74	54	-14.66	-9.1
9842.6	H	57.79	42.93	74	54	-16.21	-11.07
10854.15	H	59.33	44.79	74	54	-14.67	-9.21

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11b TX (Channel 11) Test Date : June 7, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8686.72	V	50.74	39.25	74	54	-23.26	-14.75
9932.07	V	56.37	43.41	74	54	-17.63	-10.59
10873.27	V	58.38	46.15	74	54	-15.62	-7.85
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9347.38	H	60.4	45.5	74	54	-13.6	-8.5
9837.7	H	59.35	46.16	74	54	-14.65	-7.84
10850.04	H	55.07	43.93	74	54	-18.93	-10.07

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11g TX Channel 1

Test Date : June 7, 2011

Frequency Range: Above 1GHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8678.25	V	54.62	40.71	74	54	-19.38	-13.29
9921.32	V	55.87	45.71	74	54	-18.13	-8.29
10451.23	V	54.11	42.53	74	54	-19.89	-11.47
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9263.05	H	55.66	40.58	74	54	-18.34	-13.42
9981.26	H	52.78	43.93	74	54	-21.22	-10.07
10489.36	H	56.33	43.02	74	54	-17.67	-10.98

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level +Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11g TX (Channel 6) Test Date : June 7, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8688.75	V	53.17	39.69	74	54	-20.83	-14.31
9931.37	V	57.99	46.38	74	54	-16.01	-7.62
10431.02	V	57.57	43.98	74	54	-16.43	-10.02
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9265.55	H	57.76	41.42	74	54	-16.24	-12.58
9996.72	H	53.53	41.3	74	54	-20.47	-12.7
10478.18	H	57.54	43.14	74	54	-16.46	-10.86

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note:

- (1) All Readings are Peak Value and AV.
- (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
- (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11g TX (Channel 11) Test Date : June 7, 2011
 Frequency Range: Above 1GHz Temperature : 28
 Test Result: PASS Humidity : 65 %
 Measured Distance: 3m Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8688.30	V	52.97	38.56	74	54	-21.03	-15.44
9926.68	V	55.46	43.87	74	54	-18.54	-10.13
10440.87	V	56.44	43.1	74	54	-17.56	-10.9
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9271.10	H	60.19	42.01	74	54	-13.81	-11.99
9990.89	H	55.09	43.98	74	54	-18.91	-10.02
10479.13	H	53.28	41.55	74	54	-20.72	-12.45

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n HT20

Test Date : June 7, 2011

TX Channel 1

Frequency Range: Above 1GHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8685.43	V	53.27	43.06	74	54	-20.73	-10.94
9927.48	V	54.05	44.52	74	54	-19.95	-9.48
10884.05	V	53.78	41.12	74	54	-20.22	-12.88
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9348.59	H	55.02	41.07	74	54	-18.98	-12.93
9832.23	H	52.37	40.69	74	54	-21.63	-13.31
10864.3	H	53.69	39.68	74	54	-20.31	-14.32

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n HT20
TX (Channel 6)

Test Date : June 7, 2011

Frequency Range: Above 1GHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8689.48	V	54.48	43.69	74	54	-19.52	-10.31
9931.6	V	55.07	44.57	74	54	-18.93	-9.43
10885.55	V	52.34	40.1	74	54	-21.66	-13.9
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9358.64	H	55.13	41.14	74	54	-18.87	-12.86
9839.28	H	53.1	41.47	74	54	-20.9	-12.53
10863.19	H	54.94	40.73	74	54	-19.06	-13.27

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n HT20
TX (Channel 11)

Test Date : June 7, 2011

Frequency Range: Above 1GHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8688.35	V	52.2	41.94	74	54	-21.8	-12.06
9930.04	V	53.49	43.81	74	54	-20.51	-10.19
10874	V	54.85	41.81	74	54	-19.15	-12.19
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9352.04	H	55.91	40.51	74	54	-18.09	-13.49
9835.44	H	51.5	41.13	74	54	-22.5	-12.87
10865.35	H	51.64	38.94	74	54	-22.36	-15.06

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n HT40
TX Channel 1

Test Date : June 7, 2011

Frequency Range: Above 1GHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8678.09	V	51.37	43.33	74	54	-22.63	-10.67
9926.12	V	56.85	40.86	74	54	-17.15	-13.14
10874.54	V	57.25	44.5	74	54	-16.75	-9.5
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9354.26	H	56.33	42.27	74	54	-17.67	-11.73
9836.28	H	55.86	47.36	74	54	-18.14	-6.64
10857.03	H	53.83	40.15	74	54	-20.17	-13.85

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Note: (1) All Readings are Peak Value and AV.

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n HT40
TX (Channel 6)

Test Date : June 7, 2011

Frequency Range: Above 1GHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8673.07	V	52.78	44.35	74	54	-21.22	-9.65
9923.07	V	57.21	43.26	74	54	-16.79	-10.74
10884.61	V	55.15	44.05	74	54	-18.85	-9.95
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9346.15	H	53.28	41.02	74	54	-20.72	-12.98
9826.92	H	54.74	46.85	74	54	-19.26	-7.15
10865.38	H	54.85	41.6	74	54	-19.15	-12.4

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode: 802.11n HT40
TX (Channel 11)

Test Date : June 7, 2011

Frequency Range: Above 1GHz

Temperature : 28

Test Result: PASS

Humidity : 65 %

Measured Distance: 3m

Test By: WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8688.43	V	51.04	43	74	54	-22.96	-11
9940.33	V	58.23	43.62	74	54	-15.77	-10.38
10864.36	V	57.2	45.82	74	54	-16.8	-8.18
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
9358.18	H	56.3	41.76	74	54	-17.7	-12.24
9830.94	H	55.45	45.82	74	54	-18.55	-8.18
10864.33	H	56.17	42.05	74	54	-17.83	-11.95

No others harmonics emissions are higher than 20dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

RX mode:

Operation Mode:	RX	Test Date :	June 7, 2011
Frequency Range:	30-1GHz	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Over (dB)	Note
143.12	V	24.66	43.5	-18.84	PK
207.05	V	25.19	43.5	-18.31	PK
349.26	V	25.12	46	-20.88	PK
390.36	V	26.12	46	-19.88	PK
442.12	V	26.05	46	-19.95	PK
661.12	V	26.08	46	-19.92	PK
192.05	H	24.25	43.5	-19.25	PK
208.23	H	26.65	43.5	-16.85	PK
225.06	H	27.78	46	-18.22	PK
376.64	H	29.17	46	-16.83	PK
393.18	H	28.55	46	-17.45	PK
445.65	H	29.05	46	-16.95	PK

Other harmonics emissions are lower than 20dB below the allowable limit.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Operation Mode:	RX	Test Date :	June 7, 2011
Frequency Range:	1-12.75GHz	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4921.65	V	52.65	36.35	74	54	-21.35	-17.65
6825.47	V	51.43	35.31	74	54	-22.57	-18.69
7381.05	V	52.08	36.47	74	54	-21.92	-17.53
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
--	V	--	--	--	--	--	--
4918.05	H	53.05	38.89	74	54	-20.95	-15.11
6815.08	H	54.21	37.95	74	54	-19.79	-16.05
7411.21	H	53.22	39.05	74	54	-20.78	-14.95

Other harmonics emissions are lower than 20dB below the allowable limit.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

6.6 Radiated Measurement Photos




7. Occupied Bandwidth Test

7.1 Measurement Procedure

The EUT was operating in IEEE 802.11b/g/n mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	HP	8594E	88156318	05/29/2011	05/29/2012

7.4 Measurement Results

6 Bandwidth Test Data Chart:

Refer to attached data chart.

Spectrum Detector:

PK

Test Date :

June 7, 2011

Test By:

Andy

Temperature :

28

Test Result:


PASS



Humidity :

65 %

Operation Mode: 802.11b

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	9.12	>500
6	2437	9.12	>500
11	2462	9.12	>500





Spectrum Detector:

PK

Test Date :

June 7, 2011

Test By:

Andy

Temperature :

28

Test Result:


PASS


Humidity :

65 %

Operation Mode: 802.11 g

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	16.13	>500
6	2437	16.25	>500
11	2462	16.13	>500





Spectrum Detector:

PK

Test Date :

June 7, 2011

Test By:

Andy

Temperature :

28

Test Result:

PASS

Humidity :

65 %

Operation Mode: 802.11 n HT20

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
1	2412	16.63	>500
6	2437	16.75	>500
11	2462	16.25	>500





Spectrum Detector:

PK

Test Date :

June 7, 2011

Test By:

Andy

Temperature :

28

Test Result:


PASS



Humidity :

65 %

Operation Mode: 802.11 n HT40

Channel number	Channel frequency (MHz)	Measurement level (MHz)	Required Limit (kHz)
3	2421.25	35.63	>500
6	2437.5	36.63	>500
9	2452.0	36.50	>500






99% Bandwidth Test Data Chart:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	June 7, 2011
Test By:	Andy	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Operation Mode:	802.11b		

Channel number	Channel frequency (MHz)	99% Bandwidth (MHz)
1	2412	10.25
6	2437	10.00
11	2462	10.00





Spectrum Detector: PK

Test Date : June 7, 2011

Test By: Andy

Temperature : 28


Test Result: PASS

Humidity : 65 %

Operation Mode: 802.11g

Channel number	Channel frequency (MHz)	99% Bandwidth
1	2412	16.38
6	2437	16.38
11	2462	16.38





Spectrum Detector:	PK	Test Date :	June 7, 2011
Test By:	Andy	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Operation Mode: 802.11n HT20			


Channel number	Channel frequency (MHz)	99% Bandwidth
1	2412	17.50
6	2437	17.50
11	2462	17.50







Spectrum Detector:	PK	Test Date :	June 7, 2011
Test By:	Andy	Temperature :	28
Test Result:	PASS	Humidity :	65 %
Operation Mode: 802.11n HT40			

Channel number	Channel frequency (MHz)	99% Bandwidth
3	2422.0	36.37
6	2437.5	36.12
9	2452.5	36.12






8. Maximum Peak Output Power Test

8.1 Measurement Procedure

- The Transmitter output (antenna port) was connected to the power meter.
- Turn on the EUT and power meter and then record the peak power value.
- Repeat above procedures on all channels needed to be tested.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	Boonton	4232A	29001	05/29/2011	05/29/2012
Power sensor	Boonton	51011-EMC	31184	05/29/2011	05/29/2012

8.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

8.5 Measurement Results

Spectrum Detector: PK Test Date : June 7, 2011
 Test By: Andy Temperature : 28
 Test Result: PASS Humidity : 65 %
 Operation Mode: 802.11b

Channel number	Channel Frequency(MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	16.83	1W(30dBm)	PASS
6	2437.00	16.87	1W(30dBm)	PASS
11	2462.00	16.78	1W(30dBm)	PASS

Spectrum Detector:

PK

Test Date :

June 7, 2011

Test By:

Andy

Temperature :

28

Test Result:

PASS

Humidity :

65 %

Operation Mode: 802.11g

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	16.17	1W(30dBm)	PASS
6	2437.00	16.05	1W(30dBm)	PASS
11	2462.00	16.03	1W(30dBm)	PASS

Spectrum Detector:

PK

Test Date :

June 7, 2011

Test By:

Andy

Temperature :

28

Test Result:

PASS

Humidity :

65 %

Operation Mode: 802.11n HT20

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
1	2412.00	15.98	1W(30dBm)	PASS
6	2437.00	16.02	1W(30dBm)	PASS
11	2462.00	15.98	1W(30dBm)	PASS

Spectrum Detector:

PK

Test Date :

June 7, 2011

Test By:

Andy

Temperature :

28

Test Result:

PASS

Humidity :

65 %

Operation Mode: 802.11n HT40

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power Limit(W)	Pass/Fail
3	2422.00	15.57	1W(30dBm)	PASS
6	2437.00	15.89	1W(30dBm)	PASS
9	2452.00	15.63	1W(30dBm)	PASS

9. Band Edge Test

9.1 Measurement Procedure

1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

9.2 Test SET-UP (Block Diagram of Configuration)

As 6.2 Test set up (B) and (C)

9.3 Measurement Equipment Used

Same as 6.3 Radiated Emission Measurement.

9.4 Measurement Results

Operation mode: 802.11b

Spectrum Detector: PK/AV

Test Date : June 7, 2011

Test By: Andy

Temperature : 28

Test channel: 01

Humidity : 65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2385.89	H	47.32	36.23	74	54
2384.56	V	46.36	34.34	74	54

Spectrum Detector: PK/AV

Test Date : June 7, 2011

Test By: Andy

Temperature : 28

Test channel: 11

Humidity : 65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2484.54	H	52.54	40.56	74	54
2483.75	V	50.98	39.90	74	54

Operation mode: 802.11g

Spectrum Detector: PK/AV

Test Date : June 7, 2011

Test By: Andy

Temperature : 28

Test channel: 01

Humidity : 65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2385.73	H	48.21	37.06	74	54
2384.66	V	47.15	35.22	74	54

Spectrum Detector: PK/AV

Test Date : June 7, 2011

Test By: Andy

Temperature : 28

Test channel: 11

Humidity : 65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2482.18	H	50.19	39.33	74	54
2483.06	V	49.05	38.18	74	54

Operation mode: 802.11n HT20

Spectrum Detector: PK/AV

Test Date : June 7, 2011

Test By: Andy

Temperature : 28

Test channel: 01

Humidity : 65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2389.81	H	48.55	36.67	74	54
2385.21	V	47.31	34.30	74	54

Spectrum Detector: PK/AV

Test Date : June 7, 2011

Test By: Andy

Temperature : 28

Test channel: 11

Humidity : 65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2484.17	H	49.51	40.44	74	54
2483.62	V	48.36	39.35	74	54

Operation mode: 802.11n HT40

Spectrum Detector: PK/AV

Test Date : June 7, 2011

Test By: Andy

Temperature : 28

Test channel: 01

Humidity : 65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2388.81	H	48.35	36.05	74	54
2384.52	V	47.23	34.12	74	54

Spectrum Detector: PK/AV

Test Date : June 7, 2011

Test By: Andy

Temperature : 28

Test channel: 11

Humidity : 65 %

Frequency (MHz)	Polarity	Level (dBuV/m)		Limited (dBuV/m)	
		PK	AV	PK	AV
2484.52	H	51.46	39.51	74	54
2483.79	V	50.38	39.95	74	54

10. Power Density

10.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	HP	8594E	88156318	05/29/2011	05/29/2012

10.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	300kHz
RB	3kHz
VB	30kHz
Detector	Peak
Trace	Max hold
Sweep Time	100s

10.3 Test Procedures

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz, Set Detector to Peak, Trace to Max Hold.
- Mark the frequency with maximum peak power as the center of the display of the spectrum.
- Set the span to 300kHz and the sweep time to 100s and record the maximum peak value.

10.4 Block Diagram of Test Setup



10.5 Limit

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

10.6 Test Result

Spectrum Detector:

PK

Test Date :

June 7, 2011

Test By:

Andy

Temperature :

28

Test Result:


PASS

Humidity :

65 %

Operation Mode: 802.11 b

Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
2414.74	4.77	<8dBm	PASS
2436.43	-9.09	<8dBm	PASS
2460.62	5.22	<8dBm	PASS





Spectrum Detector:

PK

Test Date :

June 7, 2011

Test By:

Andy

Temperature :

28

Test Result:

PASS



Humidity :

65 %

Operation Mode: 802.11 g

Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
2413.00	-12.43	<8dBm	PASS
2438.00	-12.48	<8dBm	PASS
2463.00	-12.76	<8dBm	PASS





Spectrum Detector: PK
 Test By: Andy
 Test Result: PASS
 Operation Mode: 802.11 n HT20

Test Date : June 7, 2011
 Temperature : 28
 Humidity : 65 %

Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
2413.00	-12.10	<8dBm	PASS
2438.00	-12.21	<8dBm	PASS
2463.00	-12.23	<8dBm	PASS








Spectrum Detector: PK
 Test By: Andy
 Test Result: PASS
 Operation Mode: 802.11 n HT40

Test Date : June 7, 2011
 Temperature : 28
 Humidity : 65 %

Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
2421.00	-16.50	<8dBm	PASS
2434.00	-14.73	<8dBm	PASS
2449.80	-16.10	<8dBm	PASS





11. Antenna Port Emission

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/29/2011	05/29/2012

11.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

11.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, mid, and hi channels, The limit was determined by attenuation 20dB of the RF peak power output.


11.4 Block Diagram of Test setup





11.5 Test Result

PASS.



802.11b Low Channel 1



802.11g Mid Channel 6



802.11n High Channel 11



12. Antenna Application

12.1 Antenna Requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203.

12.2 Result

The EUT'S antenna is Reverse-SMA Antenna. The antenna's gain is 5dBi and meets the requirement.