



RF EXPOSURE REPORT

REPORT NO.: SA980508L08A

MODEL NO.: USB-N13

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: ASUSTeK COMPUTER INC

ADDRESS: No. 150, Li-Te Rd., Peitou, Taipei, 112 Taiwan

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.



No evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.412	24.620
High	2.462	

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)	
Conducted Power	12.96	19.754
EIRP Power	9.96	9.908

***Note:** The antenna is Printed antenna with -3dBi gain

Threshold for no SAR evaluation is 24.620mW
Transmitter power is 9.908mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold