

MEASUREMENT REPORT of *Pocket Wireless Access Point*

Applicant : ASUSTek Computer Inc.
EUT : Pocket Wireless Access Point
Model No. : WL-330g
FCC ID : MSQWL330G
Report No. : A5415052

Tested by :

Training Research Co., Ltd.

TEL : 886-2-26935155 FAX : 886-2-26934440
No. 255, Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C.

CERTIFICATION

We here by verify that:

The test data, data evaluation, test procedures and equipment configurations shown in this report were made mainly in accordance with the procedures given in ANSI C63.4 (1992) as a reference. All test were conducted by *Training Research Co., Ltd.*, 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. Also, we attest to the accuracy of each.

We further submit that the energy emitted by the sample EUT tested as described in the report is **in compliance with** the technical requirements set forth in the FCC Rules Part 15 Subpart B (Declaration of Conformity) and C Section 15.247.

Applicant : ASUSTek Computer Inc.
Applicant address : 4F, No. 150, Li-Te Rd., Peitou, Taipei, Taiwan, R.O.C.
Product Name : Pocket Wireless Access Point
Model Name : WL-330g
FCC ID : MSQWL330G
Report No. : A5415052
Test Date : January 31, 2004

Prepared by: 
Jack Tsai

Approved by: 
Frank Tsai

Conditions of issue :

- (1) **This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.**
- (2) **This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.**

★ **NVLAP LAB CODE: 200174-0**

Federal Communications Commission **Declaration of Conformity** **(DoC)**

For the Following Equipment:

Product name : Pocket Wireless Access Point
 Model name : WL-330g
 Trade name : ASUS; TERAYON

Is herewith confirmed and found to comply with the requirements of CFR 47 part15 Subpart B - Unintentional Radiators regulation. The results of electromagnetic mission evaluation are shown in the report number : A5415052

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation

Manufacturer	USA local representative
Company name: ASUSTeK Computer Inc.	To be determined
Computer address: 4/F, 150, Li-Te Rd., Peitou, Taipei, Taiwan	
ZIP / Postal code 112	
Contact person: Lawrence Yu	
Title: Manager	
Internet e-mail address: lawrence_yu@asus.com.tw	
Tel / Fax: 886-2-28943447 / 886-2-28950113	

Tables of Contents

I. GENERAL	6
1.1 Introduction	6
1.2 Description of EUT	6
1.3 Test method	6
1.4 Description of Support Equipment	7
1.5 Configuration of System Under Test	10
1.6 Verify the Frequency and Channel	12
1.7 Test Procedure	13
1.8 Location of the Test Site	13
1.9 General Test Condition	13
II. Section 15.101(a) : Equipment Authorization of Unintentional Radiators	14
III. Section 15.203 : Antenna Requirement	15
IV. Section 15.207 : Power Line Conducted Emissions for AC Powered Units	16
3.1 Test Condition & Setup	16
3.2 List of Test Instruments	17
3.3 Test Result of Conducted Emissions	18
Standby mode	18
IEEE 802.11b	19
IEEE 802.11g	20
V. Section 15.247(a) : Technical Description of the EUT	22
VI. Section 15.247(a)(2) : Bandwidth for Direct Sequence System	23
6.1 Test Condition & Setup	23
6.2 Test Instruments Configuration	23
6.3 List of Test Instruments	23
6.4 Test Result of Bandwidth	23
Channel 01	24
Channel 06	25
Chamel 11	26

VII. Section 15.247(b) : Power Output	27
6.1 Test Condition & Setup	27
6.2 List of Test Instruments	27
6.3 Test Result	27
VIII. Section 15.247(c) : Spurious Emissions (Radiated)	28
7.1 Test Condition & Setup	28
7.2 List of Test Instruments	30
7.3 Test Result of Spurious Radiated Emissions	31
for 30MHz to 1GHz	31
for 1GHz to 25GHz	34
7.4 Test Result of Bandedge	41
IEEE 802.11b	42
IEEE 802.11g	44
IX. Section 15.247(d) : Power Spectral Density	46
9.1 Test Condition & Setup	46
9.2 Test Instruments Configuration	46
9.3 List of Test Instruments	46
9.4 Test Result of Power Spectral Density	47
Channel 01	48
Channel 06	49
Channel 11	50

I . GENERAL

1.1 Introduction

The following measurement report is submitted on behalf of applicant in support that the certification in accordance with Part 2 Subpart J and Part 15 Subpart A, B and C of the Commission's Rules and Regulations.

1.2 Description of EUT

Granted FCC ID : MSQWL330G
Product Name : Pocket Wireless Access Point
Model Name : WL-330g
Frequency Range : 2.412 GHz ~ 2.462GHz
Support Channel : 11 Channels
Modulation Skill : DBPSK, DQPSK, CCK, OFDM
Power Type : Powered by the adapter,
Model: DSA-0051-03 FCH 40100F
I/P: 100-240VAC, 50/60Hz, 0.2A; O/P: 4VDC, 1.0A
188cm length, non-shielded, incorporates a ferrite core

1.3 Test method

1. Connected the LAN jack of EUT with the LAN card of installed in PC.
2. Using the PC and software provided by the manufacturer to control EUT, the test is performed under the specific conditions.
3. Set different data rate and channel (CH1/CH6/CH11) being tested and repeat the procedures above.
 - (a) Radiated for Intentional test:
making EUT to the mode of continuous transmission
 - (b) Conducted test and Radiated for unintentional test:
making EUT to the linking (Rx/Tx) mode with far support equipments

1.4 Description of Support Equipment

In order to construct the minimum testing, following equipment were used as the support units.

PC : HP Pavilion
Model No. : P8574A
Serial No. : TW21920435
FCC ID : N/A, DoC (Declaration of Confirmation) Approved
檢磁 : 3902H097
Power type : 100 ~ 127VAC / 4A, 200 ~ 240VAC/2A, 50 ~ 60Hz, 5A,
Switching
Power cord : Non-shielded, 2.33 m length, Plastic hood, No ferrite core

Monitor : HP 15' Color Monitor
Model No. : D2827A
Serial No. : KR91161719
FCC ID : C5F7NFCMC1518X
檢磁 : 3872B039
Power type : 110 ~ 240 VAC / 50 ~ 60 Hz, Switching
Power cord : Shielded, 1.83m long, No ferrite core
Data cable : Shielded, 1.46m long, with two ferrite cores

Printer : HP
Model No. : C6464A
Serial No. : TH16LEB5PK
FCC ID : N/A, DoC Approved
檢磁 : 3892H381
Power type : Switching adaptor
Power cord : Non-shielded, 173cm length, No ferrite core
(between adaptor and AC source)
Non-shielded, 180cm length, with ferrite core
(between printer and adaptor)
Data cable : Shielded, 1.70m length, No ferrite core

PS/2 Keyboard : **HP**
Model No. : 5187-0343
Serial No. : BE21700404
FCC ID : DoC Approved
檢磁 : 3892C981
Data cable : Shielded, 1.73m length, Plastic hood, No ferrite core

PS/2 Mouse : **HP**
Model No. : M-S34
Serial No. : LZB90910464
FCC ID : DZL211029
檢磁 : 4862A011
Power type : By PC
Power cord : Non-shielded, 1.88m long, No ferrite core

Modem : **ACEEX**
Model No. : XDM-56V14
FCC ID : IFAXDM-56V14
Power type : Linear
Power cord : Non-shielded, 1.9m length, No ferrite cord
Data cable : RS232, Shielded, 1.2m length, No ferrite core
RJ11C x 2, 7' length non-shielded, No ferrite core

USB gamepad : **Rockfire**
Model No. : QF-337uv
Serial No. : 10600545, KR91379759
FCC ID : None (CE approval)
檢磁 : 3862A574
Power type : By computer
Data Cable : Shielded, 1.81m length, Plastic, with ferrite core

Notebook : IBM Think Pad X20

Model No. : 2662-11T
Serial No. : FX-1192200/09
FCC ID : N/A, Doc Approved
檢磁 : 3892B565

Adaptor : IBM

Model No. : PA2450U
Serial No. : 02K6654
FCC ID : N/A, Doc Approved
Power type : I/P: 100 ~ 240Vac, 50 ~ 60 Hz, 0.5A ~ 1.2A
O/P: 16Vdc, 4.5A
Power cord : Non-shielded, 1.80m long, Plastic, with ferrite core

Notebook : ASUSTek Computer

Model No. : AB00F
Serial No. : 24NP016361
FCC ID : DoC Approved
BSMI : 41016012
Power type : 100 ~ 240VAC, 1A 50/60 Hz, Switching

Adaptor of PC : LITE-ON Electronics, Inc.


Model No. : PA-1530-01
Serial No. : 00151184
FCC ID : Doc Approved
檢磁 : 3882B259
Power cable : Non-shielded, 1.72m length, Plastic hood, No ferrite core
(Between power adaptor and AC power source)
Power cable : Shielded, 1.48m length, Plastic hood, with ferrite core
(Between power adaptor and notebook)

WLAN Card : Gemtek Technology Co., Ltd.

Model No. : C911003
FCC ID : MXF-C911003

1.5 Configuration of System Under Test


1.5.1 Conducted and Radiated for unintentional



Connections of Equipment

- PC:** *Parallel Port --- a printer
- *VGA Port --- a monitor
- *Serial Port --- an external modem
- *USB Port --- a USB gamepad
- *LAN Interface --- EUT
- *PS/2-key Port --- a PS/2 keyboard
- *PS/2-mouse Port --- a PS/2 mouse

1.5.2 Radiated of intentional



The tests below are carried with the EUT transmitter set at high power in TDD mode. The EUT is forced to select of output power level and channel number by computer.

The setting up procedure was recorded in 1.3 test method.

1.6 Verify the Frequency and Channel

Channel	Frequency (GHz)
1	2.412
2	2.417
3	2.422
4	2.427
5	2.432
6	2.437
7	2.442
8	2.447
9	2.452
10	2.457
11	2.462

Note:

1. This is for confirming that all frequencies are in 2.412GHz to 2.462GHz.
2. Section 15.31(m): Measurements on intentional radiators or receivers shall be performed at three frequencies for operating frequency range over 10 MHz.
(The locations of these frequencies one near the top, one near the middle and one near the bottom.)
3. After test, the EUT operating frequencies are in 2.412GHz to 2.462GHz. So all the items as followed in testing report are need to test these three frequencies:
Top: Channel – 1; Middle: Channel – 6; Bottom: Channel – 11.

1.7 Test Procedure

All measurements contained in this report were performed mainly according to the techniques described in ANSI C63.4 (1992) and the pre-setup was written on 1.3 test method, the detail setup was written on each test item.

1.8 Location of the Test Site

The radiated emissions measurements required by the rules were performed on the **three-meter, Anechoic Chamber (FCC Registration Number: 93906)** maintained by *Training Research Co., Ltd.* 1F, No. 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. Complete description and measurement data have been placed on file with the commission. The conducted power line emissions tests and other test items were performed in a anechoic chamber also located at Training Research Co., Ltd.

No. 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. *Training Research Co., Ltd.* is listed by the FCC as a facility available to do measurement work for others on a contract basis.

1.9 General Test Condition

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests were chosen as that which produced the highest emission levels. However, only those conditions, which the EUT was considered likely to encounter in normal use were investigated.

In test, they were set in high power and continuously transmitting mode that controlled by computer. The ch01, ch06 and ch11 of EUT were all tested. The setting up procedure is recorded on 1.3 test method.

II. Section 15.101(a): Equipment authorization of unintentional radiators

The EUT equipped with a LAN interface and should be operated with the computer. It was categorized to *Class B personal computers and peripherals* as cannot be operated stand-alone. The authorization requires **Declaration of Conformity (DoC)** and the items required such as Sect.15.107 (Conducted limits) and Section15.109 (Radiated emission limits) is same as Section15.207 and 15.247(C).

III. Section 15.203: Antenna requirement

The EUT 's integral chip antennas on PCB. In addition, there is no external antenna or external connector employed. The antenna requirement stated in Sect.15.203 is inapplicable to this EUT.

The antenna specification of list as below:

Antenna Type : Chip Antenna
Antenna Gain : 1.25dBi (Max.)

VI. Section 15.207: Power Line Conducted Emissions for AC Powered Units

4.1 Test Condition & Setup

The power line conducted emission measurements were performed in an anechoic chamber. The EUT was assembled on a wooden table, which is 80 centimeters high, was placed 40 centimeters from the backwall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and Line Impedance Stabilization Networks (LISNs). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer (or EMI receiver) was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPR quasi-peak and average detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 150 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 2.4.

There is a test condition apply in this test item, the test procedure description as <1.3>. Three channels were tested, one in the top (CH01), one in the middle (CH06) and the other in bottom (CH11).

4.2 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	<u>Calibration Date</u>	
				Last time	Next time
EMI Receiver	8546A	HP	3520A00242	07/28/03	07/28/04
RF Filter Section	85460A	HP	3448A00217	07/28/03	07/28/04
LISN (EUT)	LISN-01	TRC	99-05	06/21/03	06/21/04
LISN (Support E.)	LISN-01	TRC	9912-03, 04	07/21/03	07/21/04
Pre-amplifier	15542 ZFL-500	Mini – Circuits	0 0117	05/20/03	05/20/04
6dB Attenuator	MCL BW-S6W2	Mini – Circuits	9915 – Conducted	05/20/03	05/20/04
10dB Attenuator	A5542 VAT010	Mini – Circuits	0215 – Conducted	05/20/03	05/20/04
Coaxial Cable (2 meter)	A30A30-0058-50FS-2M	Jyebao	SMA-08	05/20/03	05/20/04
Coaxial Cable (1.1 meter)	A30A30-0058-50FS-1M	Jyebao	SMA-09	05/20/03	05/20/04
Coaxial Cable (20 meter)	RG-214/U	Jyebao	NP-01	05/20/03	05/20/04
Coaxial Cable (20 meter)	RG-214/U	Jyebao	NP-02	05/20/03	05/20/04
Auto Switch Box (< 30MHz)	ASB-01	TRC	9904-01	05/20/03	05/20/04

4.3 Test Result of Power Line Conducted Emissions

The following table shows a summary of the highest emissions of power line conducted emissions on the LIVE and NETURAL conductors of the EUT power cord. Show as follows.

Test Conditions: Temperature : 20 °C Humidity : 65 % RH

Test mode: Standby mode

<i>Power Connected Emissions</i>					<i>Class B</i>		
<i>Conductor</i>	<i>Frequency (KHz)</i>	<i>Peak (dBµV)</i>	<i>QP (dBµV)</i>	<i>Average (dBµV)</i>	<i>QP-limit (dBµV)</i>	<i>AVG-limit (dBµV)</i>	<i>Margin (dB)</i>
Line 1	199.000	43.86	---	---	64.60	54.60	-10.74
	339.620	48.91	44.62	24.31	60.74	50.74	-16.12
	548.090	47.84	43.04	26.37	56.00	46.00	-12.96
	730.690	47.28	40.07	17.29	56.00	46.00	-15.93
	1020.320	47.65	42.44	19.02	56.00	46.00	-13.56
	1374.000	45.90	39.63	17.52	56.00	46.00	-16.37
	1994.000	41.98	---	---	56.00	46.00	-4.02
	3819.000	40.27	---	---	56.00	46.00	-5.73
Line 2	201.000	46.81	---	---	64.54	54.54	-7.73
	269.000	44.86	---	---	62.60	52.60	-7.74
	341.000	46.62	---	---	60.54	50.54	-3.92
	461.000	42.17	---	---	57.11	47.11	-4.94
	548.040	45.09	43.06	24.14	56.00	46.00	-12.94
	723.930	43.47	40.45	15.72	56.00	46.00	-15.55
	1020.650	45.09	42.36	18.95	56.00	46.00	-13.64
	1500.660	44.29	41.74	17.64	56.00	46.00	-14.26

NOTE:

- (1)Margin = Peak Amplitude – Limit, *The reading amplitudes are all under limit.*
- (2)A "+" sign in the margin column means the emission is OVER the Class B Limit and "-" sign of means UNDER the Class B limit

Test mode: IEEE 802.11b, Channel 1

<i>Power Connected Emissions</i>					<i>Class B</i>		
<i>Conductor</i>	<i>Frequency (KHz)</i>	<i>Peak (dBμV)</i>	<i>QP (dBμV)</i>	<i>Average (dBμV)</i>	<i>QP-limit (dBμV)</i>	<i>AVG-limit (dBμV)</i>	<i>Margin (dB)</i>
Line 1	165.440	56.64	55.87	35.45	65.54	55.54	-9.67
	457.960	46.33	42.83	24.90	57.51	47.51	-14.68
	620.670	45.85	40.88	19.14	56.00	46.00	-15.12
	922.720	45.83	38.85	21.37	56.00	46.00	-17.15
	1354.500	44.77	40.87	18.14	56.00	46.00	-15.13
	1859.230	43.12	40.67	19.99	56.00	46.00	-15.33
Line 2	164.790	58.62	55.17	34.24	65.60	55.60	-10.43
	222.300	52.92	48.74	27.14	64.00	54.00	-15.26
	277.000	48.47	---	---	62.37	52.37	-3.90
	458.560	44.79	43.02	26.27	57.63	47.63	-14.61
	870.140	44.00	42.58	23.91	56.00	46.00	-13.15
	1450.330	44.95	42.85	21.24	56.00	46.00	-10.82

Test mode: IEEE 802.11b, Channel 6

<i>Power Connected Emissions</i>					<i>Class B</i>		
<i>Conductor</i>	<i>Frequency (KHz)</i>	<i>Peak (dBμV)</i>	<i>QP (dBμV)</i>	<i>Average (dBμV)</i>	<i>QP-limit (dBμV)</i>	<i>AVG-limit (dBμV)</i>	<i>Margin (dB)</i>
Line 1	164.810	55.02	55.48	34.75	65.54	55.54	-10.06
	271.000	47.63	---	---	62.54	52.54	-4.91
	460.060	46.62	43.78	27.58	57.74	47.74	-13.96
	620.500	46.12	41.34	20.69	56.00	46.00	-14.66
	914.530	46.10	38.31	20.62	56.00	46.00	-17.69
	1666.200	43.86	41.47	22.85	56.00	46.00	-14.53
Line 2	165.340	59.39	56.48	35.76	65.54	55.54	-9.06
	218.810	53.41	48.43	24.11	64.00	54.00	-15.57
	436.940	45.39	40.08	17.80	57.74	47.74	-17.66
	629.400	43.28	41.52	24.94	56.00	46.00	-14.48
	1269.380	44.55	42.93	21.93	56.00	46.00	-13.07
	2029.000	41.98	---	---	56.00	46.00	-4.02

Test mode: IEEE 802.11b, Channel 11

Power Connected Emissions					Class B		
Conductor	Frequency (KHz)	Peak (dBμV)	QP (dBμV)	Average (dBμV)	QP-limit (dBμV)	AVG-limit (dBμV)	Margin (dB)
Line 1	163.570	55.80	56.14	33.13	65.60	55.60	-9.46
	218.380	51.40	48.77	24.26	64.06	54.06	-15.29
	455.850	46.95	43.79	27.74	57.74	47.74	-13.95
	610.850	46.49	40.87	18.65	56.00	46.00	-15.13
	915.2240	46.14	39.34	23.32	56.00	46.00	-16.66
	1499.570	45.16	40.22	17.34	56.00	46.00	-15.78
Line 2	163.000	59.06	56.19	33.66	65.54	55.54	-9.35
	271.000	47.13	---	---	62.54	52.54	-5.41
	438.000	44.88	40.59	18.94	57.37	47.37	-16.78
	627.000	43.47	41.80	25.72	56.00	46.00	-14.20
	1023.000	44.43	42.55	23.88	56.00	46.00	-13.45
	1748.000	42.49	---	---	56.00	46.00	-3.51

Test mode: IEEE 802.11g, Channel 1

Power Connected Emissions					Class B		
Conductor	Frequency (KHz)	Peak (dBμV)	QP (dBμV)	Average (dBμV)	QP-limit (dBμV)	AVG-limit (dBμV)	Margin (dB)
Line 1	162.860	55.02	57.14	34.36	65.69	55.69	-8.55
	218.150	51.22	49.25	25.05	64.11	54.11	-14.86
	274.000	48.30	---	---	62.46	52.46	-4.16
	435.120	45.78	39.82	18.28	57.74	47.74	-17.92
	784.310	45.46	39.94	16.40	56.00	46.00	-16.06
	1499.970	44.59	40.89	23.34	56.00	46.00	-15.11
Line 2	165.650	59.25	56.70	34.40	65.63	55.63	-8.93
	220.320	52.78	49.13	27.45	64.11	54.11	-14.98
	267.000	49.26	---	---	62.66	52.66	-3.40
	598.000	42.68	---	---	56.00	46.00	-3.32
	1022.860	44.72	43.07	24.53	56.00	46.00	-12.93
	1731.000	42.93	---	---	56.00	46.00	-3.07

Test mode: IEEE 802.11g, Channel 6

Power Connected Emissions					Class B		
Conductor	Frequency (KHz)	Peak (dBμV)	QP (dBμV)	Average (dBμV)	QP-limit (dBμV)	AVG-limit (dBμV)	Margin (dB)
Line 1	163.290	55.48	57.08	34.59	65.54	55.54	-8.46
	216.000	51.08	---	---	64.11	54.11	-3.03
	271.330	49.66	44.95	20.52	62.54	52.54	-17.59
	433.320	46.83	39.45	17.53	57.74	47.74	-18.29
	775.760	45.92	39.98	16.48	56.00	46.00	-16.02
	1333.580	44.95	40.27	17.09	56.00	46.00	-15.73
Line 2	163.660	59.72	56.84	37.20	65.54	55.54	-8.70
	214.000	50.79	---	---	64.17	54.17	-3.38
	269.000	48.05	---	---	62.60	52.60	-4.55
	612.280	43.63	41.40	20.08	56.00	46.00	-14.60
	1024.620	44.36	42.42	23.96	56.00	46.00	-13.58
	1424.420	44.03	42.13	21.09	56.00	46.00	-13.87

Test mode: IEEE 802.11g, Channel 11

Power Connected Emissions					FCC Class B		
Conductor	Frequency (KHz)	Peak (dBμV)	QP (dBμV)	Average (dBμV)	QP-limit (dBμV)	AVG-limit (dBμV)	Margin (dB)
Line 1	165.670	55.66	57.12	35.35	65.63	55.63	-8.51
	274.000	49.07	---	---	62.46	52.46	-3.39
	440.720	46.92	40.86	16.44	57.74	47.74	-16.88
	606.370	46.69	38.80	12.76	56.00	46.00	-17.20
	1097.410	45.14	41.91	23.15	56.00	46.00	-14.09
	1501.610	44.86	41.36	19.07	56.00	46.00	-14.64
Line 2	165.620	59.67	56.88	34.24	65.63	55.63	-8.75
	220.590	51.96	49.77	25.22	63.94	53.94	-14.17
	435.890	44.88	39.81	18.79	57.51	47.51	-17.70
	1021.870	44.06	41.66	20.50	56.00	46.00	-14.34
	1427.320	44.62	42.30	21.32	56.00	46.00	-13.70
	1994.000	42.17	---	---	56.00	46.00	-3.83

V. Section 15.247 (a): Technical description of the EUT


Based on the Section 2.1, *Direct Sequence System* is a spread spectrum system in which the carrier has been modulated by a high speed spreading code and an information data stream. The high speed code sequence dominates the “modulating function” and is the direct cause of the wide spreading of the transmitted signal. In the operational description demonstrates the operation principles of the Baseband processor employed by the EUT, shows that which is a complete DSSS baseband processor and meets the definition of the direct sequence spread spectrum system.

VI. Section 15.247(a)(2): Bandwidth for Direct Sequence System.

6.1 Test Condition & Setup

The transmitter bandwidth measurements were performed by the contact manner. The EUT was set to transmit continuously, also various channels were investigated to find the maximum occupied bandwidth. The output of the EUT was connected to the spectrum analyzer. The bandwidth of the fundamental frequency is observed by the spectrum analyzer with 100kHz RBW and 100kHz VBW.

6.2 Test Instruments Configuration



P.S.: Notebook computer to control the EUT at maximal power output and channel Number and set antenna kit

6.3 List of Test Instruments


Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
Spectrum Analyzer	MS2665C	ANRITSU	6200175476	09/30/03	09/30/04

6.4 Test Result of Bandwidth


Channel	802.11b	802.11g
01	8.32 MHz	16.80 MHz
06	8.32 MHz	16.64 MHz
11	9.12 MHz	16.68 MHz

- Note:
- The data in the above table are summarizing the following attachment spectrum analyzer hard copy. According to the guidance, we'd made the measurement with the spectrum analyzer's resolution bandwidth (RBW)=100kHz and set the $span \gg RBW$. The results show the measured 6dB bandwidth comply with the minimum 500kHz requirement.
 - The attachments show these on the following pages.

6dB Bandwidth of Channel 1 (The minimum 6dB BW at least 500kHz)




IEEE 802.11b




IEEE 802.11g

6dB Bandwidth of Channel 6 (The minimum 6dB BW at least 500kHz)




IEEE 802.11b




IEEE 802.11g

6dB Bandwidth of Channel 11 (The minimum 6dB BW at least 500kHz)




IEEE 802.11b



IEEE 802.11g

VII. Section 15.247(b): Power Output

7.1 Test Condition & Setup



1. The output of the transmitter is connected to the BOONTON RF Power Meter.
2. The calibration is performed before every test. The values of the output power of the EUT will shown in the dBm directly are the transmitter output peak power. Recording as follows.

7.2 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
RF Power Meter	4532	BOONTON	117501	04/12/03	04/12/04
Peak Power Sensor	57340	BOONTON	2698	04/12/03	04/12/04

7.3 Test Result

Formula:

$$\text{RF Output of EUT} + |\text{Cable Loss}| = \text{Output Peak Power}$$

IEEE 802.11b

Channel	RF Output	Cable Loss	Output Peak Power	
	dBm	dBm	dBm	mW
CH 1	18.70	0.70	19.40	87.096
CH 6	17.99	0.70	18.69	73.961
CH 11	17.16	0.70	17.86	61.094

IEEE 802.11g

Channel	RF Output	Cable Loss	Output Peak Power	
	dBm	dBm	dBm	mW
CH 1	22.13	0.70	22.83	191.867
CH 6	22.02	0.70	22.72	187.068
CH 11	21.64	0.70	22.34	171.396

VIII. Section 15.247 (C): Spurious Emissions (Radiated)

8.1 Test Condition & Setup

We'd performed the test by the *radiated emission* skill: The EUT was placed in an anechoic chamber, and set the EUT transmitting continuously and scanned at 3-meter distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration, which produced the highest emissions was noted so it could be reproduced later during the final tests. For the measurement above 1GHz, according to the guidance we'd set the spectrum analyzer's 6dB bandwidth RBW to 1MHz.

This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

Final radiation measurements were made on a three-meter, anechoic chamber. The EUT system was placed on a nonconductive turntable, which is 0.8 meters height, top surface 1.0 x 1.5 meter.

The spectrum was examined from 30 MHz to 1000 MHz using an Hewlett Packard 85460A EMI Receiver, SCHWARZECK whole range Small Biconical Antenna (Model No.: UBAA9114 & BBVU9135) is used to measure frequency from 30 MHz to 1GHz. The final test is used the HP 85460A spectrum and 8564E spectrum was examined from 1GHz to 25GHz using an Hewlett Packard Spectrum Analyzer, EMCO/HP Horn Antenna (Model 3115 / 84125-80008) for 1G - 25GHz.

At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. There are two spectrum analyzers use on this testing, HP 85460A for frequency 30MHz to 1000MHz, and 8564E for frequency 1GHz to 25GHz. No post-detector video filters were used in the test. The spectrum analyzer's 6dB bandwidth was set to 120KHz (spectrum was examined from 30 MHz to 1000 MHz), the spectrum analyzer's 6 dB bandwidth was set to 1 MHz (spectrum was examined from 1GHz to 25GHz) and the analyzer was operated in the maximum hold mode. There is a test condition applies in this test item, the test procedure description as the following:

Three channels were tested, one in the top (CH01), one in the middle (CH06) and the other in bottom (CH11). The setting up procedure is recorded on <1.3>

With the transmitter operating from a AC source and using the internal of EUT, radiates spurious emissions falling within the restricted bands of 15.209 were measured at operating frequencies corresponding to upper, middle and bottom channels in the 2400 ~ 2483.5 MHz band.

The actual field intensity in decibels referenced to 1 microvolt per meter (dB μ V/m) is determined by algebraically adding the measured reading in dB μ V, the antenna factor (dB), and cable loss (dB) at the appropriate frequency. Since the EUT was set to transmit continuously, no *duty cycle* is present.

For frequency between 30MHz to 1000MHz

$$F_{Ia} \text{ (dB}\mu\text{V/m)} = F_{Ir} \text{ (dB}\mu\text{V)} + \text{Correction Factors}$$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

$$\text{Correction Factors} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

For frequency between 1GHz to 25GHz

$$F_{Ia} \text{ (dB}\mu\text{V/m)} = F_{Ir} \text{ (dB}\mu\text{V)} + \text{Correction Factor}$$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

$$\text{Correction Factors} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

8.2 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Calibration Date	
				Last time	Next time
EMI Receiver	8546A	HP	3520A00242	07/28/03	07/28/04
RF Filter Section	85460A	HP	3448A00217	07/28/03	07/28/04
Small Biconical Antenna	UBAA9114 & BBVU9135	SCHWARZECK	127	06/21/03	06/21/04
Pre-amplifier	PA1F	TRC	1FAC	05/20/03	05/20/04
Auto Switch Box (>30MHz)	ASB-01	TRC	9904-01	05/20/03	05/20/04
Coaxial Cable (Double shielded, 15 meter)	A30A30-0058-50FS-15M	JYEBAO	SMA-01	05/20/03	05/20/04
Coaxial Cable (1.1 meter)	A30A30-0058-50FS-1M	JYEBAO	SMA-02	05/20/03	05/20/04
Spectrum Analyzer	8564E	HP	3720A00840	07/23/03	07/23/04
Microwave Preamplifier	84125C	HP	US36433002	07/30/03	07/30/04
Horn Antenna	3115	EMCO	9104-3668	12/24/02	12/24/03
Standard Guide Horn Antenna	84125-80008	HP	18-26.5GHz	09/18/03	09/18/04
Standard Guide Horn Antenna	84125-80001	HP	26.5-40GHz	09/18/03	09/18/04
Pre-amplifier	84125C	HP	US36433002	11/19/03	11/19/04
Horn Antenna	1196E (3115)	HP (EMCO)	9704-5178	12/12/03	12/12/04
Pre-amplifier	PA2F	TRC	2F1GZ	05/20/03	05/20/04
Coaxial Cable (3 miter)	A30A30-0058-50FST118	JYEBAO	MSA-05	05/20/03	05/20/04
Coaxial Cable (1 meter)	A30A30-0058-50FST118	JYEBAO	MSA-04	05/20/03	05/20/04

8.3 Test Result of Spurious Radiated Emissions

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarizations, EUT orientation, etc. are recorded on the following. (worst cast)

Test Conditions: Temperature : 25 ° C Humidity : 73 % RH

Test mode: Standby mode [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBµV)	Ant. H. (m)	Table (°)			Limit (dBµV/m)	Margin (dB)
102.75	32.69	1.00	147	0.16	32.85	43.50	-10.65
145.19	42.47	1.00	50	-1.83	40.64	43.50	-2.86
436.19	32.32	1.00	317	1.72	34.04	46.00	-11.96
533.19	31.27	1.00	43	6.01	37.28	46.00	-8.72
599.87	26.83	1.00	84	8.99	35.82	46.00	-10.18
801.15	24.58	1.00	112	13.75	38.33	46.00	-7.67

Test mode: Standby mode [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBµV)	Ant. H. (m)	Table (°)			Limit (dBµV/m)	Margin (dB)
56.67	31.85	1.00	49	3.14	34.99	40.00	-5.01
162.16	38.15	1.00	24	-2.51	35.64	43.50	-7.86
403.45	36.40	1.00	270	0.83	37.23	46.00	-8.77
666.56	27.62	1.00	229	10.41	38.03	46.00	-7.97
801.15	24.27	1.00	69	13.75	38.02	46.00	-7.98
912.70	23.20	1.00	228	17.59	40.79	46.00	-5.21

Note:

1. Margin = Amplitude – limit, if margin is minus means under limit.
2. Corrected Amplitude = Reading Amplitude + Correction Factors
3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain)

Test mode: IEEE 802.11b for 30MHz to 1GHz [Horizontal]

<i>Radiated Emission</i>				<i>Correction Factors</i>	<i>Corrected Amplitude</i>	<i>Class B (3 m)</i>	
<i>Frequency (MHz)</i>	<i>Amplitude (dBµV)</i>	<i>Ant. H. (m)</i>	<i>Table (°)</i>			<i>Limit (dBµV/m)</i>	<i>Margin (dB)</i>
91.84	26.99	1.00	265	0.59	27.58	43.50	-15.92
102.45	31.43	1.00	297	0.16	31.59	43.50	-11.91
133.06	31.55	1.00	118	-1.85	29.70	43.50	-13.80
167.01	28.70	1.00	298	-2.47	26.23	43.50	-17.27
564.71	21.90	1.00	211	7.48	29.38	46.00	-16.62
801.15	24.15	1.00	105	13.75	37.90	46.00	-8.10

Test mode: IEEE 802.11b for 30MHz to 1GHz [Vertical]

<i>Radiated Emission</i>				<i>Correction Factors</i>	<i>Corrected Amplitude</i>	<i>Class B (3 m)</i>	
<i>Frequency (MHz)</i>	<i>Amplitude (dBµV)</i>	<i>Ant. H. (m)</i>	<i>Table (°)</i>			<i>Limit (dBµV/m)</i>	<i>Margin (dB)</i>
56.67	31.28	1.00	279	3.14	34.42	40.00	-5.58
142.76	35.48	1.00	229	-1.77	33.71	43.50	-9.79
160.95	37.89	1.00	51	-2.52	35.37	43.50	-8.13
287.05	33.70	1.00	189	-2.39	31.31	46.00	-14.69
641.10	24.80	1.00	137	9.64	34.44	46.00	-11.56
801.15	22.84	1.00	329	13.75	36.59	46.00	-9.41

Test mode: IEEE 802.11g for 30MHz to 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)			Limit (dBμV/m)	Margin (dB)
80.92	25.87	1.00	20	1.59	27.46	40.00	-12.54
102.75	33.13	1.00	67	0.16	33.29	43.50	-10.21
108.81	30.57	1.00	62	-0.12	30.45	43.50	-13.05
129.43	32.37	1.00	313	-1.87	30.50	43.50	-13.00
641.10	24.24	1.00	41	9.64	33.88	46.00	-12.12
801.15	23.59	1.00	107	13.75	37.34	46.00	-8.66

Test mode: IEEE 802.11g for 30MHz to 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	Class B (3 m)	
Frequency (MHz)	Amplitude (dBμV)	Ant. H. (m)	Table (°)			Limit (dBμV/m)	Margin (dB)
56.67	31.80	1.00	312	3.14	34.94	40.00	-5.06
145.19	35.04	1.00	221	-1.83	33.21	43.50	-10.29
162.16	37.57	1.00	41	-2.51	35.06	43.50	-8.44
251.89	34.02	1.00	93	-2.64	31.38	46.00	-14.62
287.05	32.82	1.00	3	-2.39	30.43	46.00	-15.57
641.10	24.13	1.00	39	9.64	33.77	46.00	-12.23

Test mode: Standby mode for 1GHz to 25GHz [Horizontal]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
1595.00	1.00	309	0.30	38.20	---	74.00	53.96	-15.76
1793.33	1.00	331	1.36	40.76	---	74.00	53.96	-13.20
1913.75	1.00	100	3.17	41.75	---	74.00	53.96	-12.21
2239.58	1.00	349	5.49	39.73	---	74.00	53.96	-14.23
2558.33	1.00	339	7.32	39.56	---	74.00	53.96	-14.40

Test mode: Standby mode for 1GHz to 25GHz [Vertical]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
1595.00	1.00	126	0.30	43.87	---	74.00	53.96	-10.09
1807.50	1.00	334	1.58	45.49	---	74.00	53.96	-8.47
1913.75	1.00	279	3.17	43.25	---	74.00	53.96	-10.71
2232.50	1.00	268	5.46	41.03	---	74.00	53.96	-12.93
4074.17	1.00	84	12.61	42.18	---	74.00	53.96	-11.78

Note:

1. Margin = Corrected - Limit.
2. The EUT utilizes a *permanently attached antenna*. In addition the spurious RF radiated emissions levels do comply with the *20dBc limit* both at its bandedges and other spurious emissions
3. As stated in Section 15.35(b), for any frequencies above 1000MHz, radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. As the results of our test, the peak amplitudes are already below the FCC limit. Thus the average amplitudes of the rest are omitted.

Test mode: Channel 1 of IEEE 802.11b for 1GHz to 25GHz [Horizontal]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
2037.50	1.00	98	1.96	44.63	---	74.00	53.96	-9.33
4823.12	1.00	343	3.76	42.86	---	74.00	53.96	-11.10
7239.79	1.00	24	10.11	47.55	---	74.00	53.96	-6.41
9647.95	1.00	308	11.46	54.41	44.90	74.00	53.96	-9.06
12061.04	1.00	120	9.81	47.25	---	74.00	53.96	-6.71

Test mode: Channel 1 of IEEE 802.11b for 1GHz to 25GHz [Vertical]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
1918.75	1.00	110	2.13	40.13	---	74.00	53.96	-13.83
4823.12	1.00	349	3.76	41.53	---	74.00	53.96	-12.43
7239.79	1.00	70	10.11	45.21	---	74.00	53.96	-8.75
9647.97	1.00	182	11.46	51.08	43.90	74.00	53.96	-10.06
12061.04	1.00	78	9.81	48.41	---	74.00	53.96	-5.55

Test mode: Channel 6 of IEEE 802.11b for 1GHz to 25GHz [Horizontal]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBμV/m)		Limit (dBμV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
2062.50	1.00	74	2.05	42.05	---	74.00	53.96	-11.91
2239.58	1.00	80	2.64	41.80	---	74.00	53.96	-12.16
4877.50	1.00	252	3.97	41.41	---	74.00	53.96	-12.55
7306.25	1.00	41	10.29	47.23	---	74.00	53.96	-6.73
9747.08	1.00	22	11.89	48.66	---	74.00	53.96	-5.30
12187.92	1.00	252	9.74	47.34	---	74.00	53.96	-6.62

Test mode: Channel 6 of IEEE 802.11b for 1GHz to 25GHz [Vertical]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBμV/m)		Limit (dBμV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
1920.83	1.00	246	2.13	41.13	---	74.00	53.96	-12.83
4877.50	1.00	266	3.97	42.58	---	74.00	53.96	-11.38
7306.25	1.00	14	10.29	48.39	---	74.00	53.96	-5.57
9747.97	1.00	18	11.89	54.51	47.66	74.00	53.96	-6.30
12187.92	1.00	254	9.74	48.01	---	74.00	53.96	-5.95

Test mode: Channel 11 of IEEE 802.11b for 1GHz to 25GHz [Horizontal]

<i>Radiated Emission</i>				<i>Corrected Amplitude</i>		<i>Class B (3m)</i>		
<i>Frequency (MHz)</i>	<i>Ant. H. (m)</i>	<i>Table (°)</i>	<i>Correction Factors (dB)</i>	<i>(dBµV/m)</i>		<i>Limit (dBµV/m)</i>		<i>Margin (dB)</i>
				<i>Peak</i>	<i>Average</i>	<i>Peak</i>	<i>Ave.</i>	
2087.50	1.00	90	2.13	44.30	---	74.00	53.96	-9.66
4925.83	1.00	319	4.13	44.07	---	74.00	53.96	-9.89
7384.79	1.00	26	10.42	47.36	---	74.00	53.96	-6.60
9849.79	1.00	284	11.93	49.21	---	74.00	53.96	-4.75
12308.75	1.00	167	9.56	45.33	---	74.00	53.96	-8.63

Test mode: Channel 11 of IEEE 802.11b for 1GHz to 25GHz [Vertical]

<i>Radiated Emission</i>				<i>Corrected Amplitude</i>		<i>Class B (3m)</i>		
<i>Frequency (MHz)</i>	<i>Ant. H. (m)</i>	<i>Table (°)</i>	<i>Correction Factors (dB)</i>	<i>(dBµV/m)</i>		<i>Limit (dBµV/m)</i>		<i>Margin (dB)</i>
				<i>Peak</i>	<i>Average</i>	<i>Peak</i>	<i>Ave.</i>	
1920.83	1.00	251	2.13	40.46	---	74.00	53.96	-13.50
2087.50	1.00	337	2.13	40.63	---	74.00	53.96	-13.33
4925.83	1.00	259	4.13	43.24	---	74.00	53.96	-10.72
7384.79	1.00	199	10.42	47.20	---	74.00	53.96	-6.76
9847.99	1.00	91	11.93	51.54	45.54	74.00	53.96	-8.42
12308.75	1.00	141	9.56	44.83	---	74.00	53.96	-9.13

Test mode: Channel 1 of IEEE 802.11g for 1GHz to 25GHz [Horizontal]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
1920.83	1.00	77	2.13	43.63	---	74.00	53.96	-10.33
2037.50	1.00	75	1.96	45.63	---	74.00	53.96	-8.33
2239.58	1.00	73	2.64	41.64	---	74.00	53.96	-12.32
7239.79	1.00	208	10.11	44.55	---	74.00	53.96	-9.41
9650.42	1.00	287	11.47	44.58	---	74.00	53.96	-9.38
12061.04	1.00	58	9.81	45.25	---	74.00	53.96	-8.71

Test mode: Channel 1 of IEEE 802.11g for 1GHz to 25GHz [Vertical]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
1920.83	1.00	38	2.13	40.29	---	74.00	53.96	-13.67
2037.50	1.00	328	1.96	41.80	---	74.00	53.96	-12.16
4823.12	1.00	135	3.76	39.20	---	74.00	53.96	-14.76
7239.79	1.00	255	10.11	45.05	---	74.00	53.96	-8.91
9650.42	1.00	146	11.47	44.91	---	74.00	53.96	-9.05
12061.04	1.00	247	9.81	46.08	---	74.00	53.96	-7.88

Test mode: Channel 6 of IEEE 802.11g for 1GHz to 25GHz [Horizontal]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBμV/m)		Limit (dBμV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
1920.83	1.00	108	2.13	42.79	---	74.00	53.96	-11.17
2062.50	1.00	99	2.05	43.38	---	74.00	53.96	-10.58
2239.58	1.00	99	2.64	40.97	---	74.00	53.96	-12.99
7306.25	1.00	173	10.29	44.39	---	74.00	53.96	-9.57
9747.08	1.00	179	11.89	44.99	---	74.00	53.96	-8.97
12187.92	1.00	183	9.74	48.68	---	74.00	53.96	-5.28

Test mode: Channel 6 of IEEE 802.11g for 1GHz to 25GHz [Vertical]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBμV/m)		Limit (dBμV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
1920.83	1.00	122	2.13	40.79	---	74.00	53.96	-13.17
2062.50	1.00	344	2.05	39.88	---	74.00	53.96	-14.08
4877.50	1.00	263	3.97	40.74	---	74.00	53.96	-13.22
7306.25	1.00	86	10.29	44.56	---	74.00	53.96	-9.40
9747.08	1.00	360	11.89	45.99	---	74.00	53.96	-7.97
12187.92	1.00	225	9.74	47.18	---	74.00	53.96	-6.78

Test mode: Channel 11 of IEEE 802.11g for 1GHz to 25GHz [Horizontal]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
1920.83	1.00	300	2.13	42.96	---	74.00	53.96	-11.00
2087.50	1.00	146	2.13	44.13	---	74.00	53.96	-9.83
2239.58	1.00	138	2.64	42.30	---	74.00	53.96	-11.66
4925.83	1.00	304	4.13	42.74	---	74.00	53.96	-11.22
7384.79	1.00	25	10.42	42.70	---	74.00	53.96	-11.26
9843.75	1.00	188	11.93	46.37	---	74.00	53.96	-7.59
12308.75	1.00	230	9.56	44.33	---	74.00	53.96	-9.63

Test mode: Channel 11 of IEEE 802.11g for 1GHz to 25GHz [Vertical]

Radiated Emission				Corrected Amplitude		Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
1600.00	1.00	109	3.29	40.79	---	74.00	53.96	-13.17
2087.50	1.00	181	2.13	41.63	---	74.00	53.96	-12.33
4925.83	1.00	297	4.13	42.57	---	74.00	53.96	-11.39
7384.79	1.00	311	10.42	42.86	---	74.00	53.96	-11.10
9843.75	1.00	289	11.93	46.20	---	74.00	53.96	-7.76
12308.75	1.00	101	9.56	44.50	---	74.00	53.96	-9.46

8.5 Test Result of the Bandedge


If any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either *at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in § 15.209(a)*,

We perform this section by the *radiated manner*, the RBW is set to 100kHz and VBW>RBW. We'd made the observation *up to 10th harmonics and the criterion is all the harmonic/spurious emissions must be 20dB below the highest emission level measured*. If the emissions fall in the restricted bands stated in the Part15.205(a) must also *comply with the radiated emission limits specified in Part15.209(a)*. (*Peak mode: RBW=VBW=1MHz, Average mode: RBW=1MHz; VBW=10Hz*)

The following pages show our observations referring to the channel 1 and 11 respectively.

Test Condition & Setup: same as < 8.1 >

Channel 1 of IEEE 802.11b




This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of channel 1.

1. The lobe left by the fundamental side is already 20dB below the highest emission level.
2. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below.

<i>Radiated Emission</i>					<i>Corrected Amplitude</i>		<i>Class B (3m)</i>		
<i>Frequency (MHz)</i>	<i>Ant. P.</i>	<i>Ant. H. (m)</i>	<i>Table (°)</i>	<i>Factors (dB)</i>	<i>(dBµV/m)</i>		<i>Limit (dBµV/m)</i>		<i>Margin (dB)</i>
					<i>Peak</i>	<i>Average</i>	<i>Peak</i>	<i>Ave.</i>	
2388.61	Hor	1.00	318	3.13	42.46	---	74.00	53.96	-11.50
2390.02	Hor	1.00	360	3.13	42.13	---	74.00	53.96	-11.83
2376.96	Ver	1.00	137	3.09	39.26	---	74.00	53.96	-14.70
2390.02	Ver	1.00	264	3.13	37.97	---	74.00	53.96	-15.99

Channel 11 of IEEE 802.11b




This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of channel 11.

- 3. The lobe right by the fundamental side is already 20dB below the highest emission level.
- 4. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below

<i>Radiated Emission</i>					<i>Corrected Amplitude</i>		<i>Class B (3m)</i>		
<i>Frequency (MHz)</i>	<i>Ant. P.</i>	<i>Ant. H. (m)</i>	<i>Table (°)</i>	<i>Factors (dB)</i>	<i>(dBµV/m)</i>		<i>Limit (dBµV/m)</i>		<i>Margin (dB)</i>
					<i>Peak</i>	<i>Average</i>	<i>Peak</i>	<i>Ave.</i>	
2499.54	Hor	1.00	357	3.50	39.00	---	74.00	53.96	-14.96
2500.01	Hor	1.00	334	3.50	38.17	---	74.00	53.96	-15.79
2541.66	Hor	1.00	125	3.55	39.89	---	74.00	53.96	-14.07
2483.68	Ver	1.00	103	3.45	40.11	---	74.00	53.96	-13.85
2500.07	Ver	1.00	98	3.45	43.11	---	74.00	53.96	-10.85
2503.45	Ver	1.00	104	3.50	40.34	---	74.00	53.96	-13.62

Channel 1 of IEEE 802.11g




This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of channel 1.

- 5. The lobe left by the fundamental side is already 20dB below the highest emission level.
- 6. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below.

<i>Radiated Emission</i>					<i>Corrected Amplitude</i>		<i>Class B (3m)</i>		
<i>Frequency (MHz)</i>	<i>Ant. P.</i>	<i>Ant. H. (m)</i>	<i>Table (°)</i>	<i>Factors (dB)</i>	<i>(dBµV/m)</i>		<i>Limit (dBµV/m)</i>		<i>Margin (dB)</i>
					<i>Peak</i>	<i>Average</i>	<i>Peak</i>	<i>Ave.</i>	
2389.39	Hor	1.00	21	3.13	42.80	---	74.00	53.96	-11.16
2390.02	Hor	1.00	22	3.13	41.30	---	74.00	53.96	-12.66
2388.23	Ver	1.00	233	3.13	39.30	---	74.00	53.96	-14.66
2390.02	Ver	1.00	274	3.13	37.30	---	74.00	53.96	-16.66

Channel 11 of IEEE 802.11g



This is the hard copy of our bandedge measurement generated by our bandedge testing program. The plot shown above is the bandedge of channel 11.

- 7. The lobe right by the fundamental side is already 20dB below the highest emission level.
- 8. The emissions recorded in the restricted band is do comply with the Part 15.209(a) – as below


<i>Radiated Emission</i>					<i>Corrected Amplitude</i>		<i>Class B (3m)</i>		
<i>Frequency (MHz)</i>	<i>Ant. P.</i>	<i>Ant. H. (m)</i>	<i>Table (°)</i>	<i>Factors (dB)</i>	<i>(dBμV/m)</i>		<i>Limit (dBμV/m)</i>		<i>Margin (dB)</i>
					<i>Peak</i>	<i>Average</i>	<i>Peak</i>	<i>Ave.</i>	
2483.50	Hor	1.00	158	3.45	39.28	---	74.00	53.96	-14.68
2484.32	Hor	1.00	154	3.45	41.45	---	74.00	53.96	-12.51
2507.88	Hor	1.00	163	3.51	39.84	---	74.00	53.96	-14.12
2486.71	Ver	1.00	120	3.46	39.29	---	74.00	53.96	-14.67
2500.01	Ver	1.00	206	3.50	37.67	---	74.00	53.96	-16.29
2520.72	Ver	1.00	17	3.53	39.69	---	74.00	53.96	-14.27

IX. Section 15.247(d): Power Spectral Density

9.1 Test Condition & Setup

The tests below are running with the EUT transmitter set at high power in TDD mode. The EUT is needed to force selection of output power level and channel number. While testing, the EUT was set to transmit continuously and to be tested by the contact manner with the spectrum analyzer.

9.2 Test Instruments Configuration



P.S.: Notebook computer to control the EUT at maximal power output and channel Number and set antenna kit

9.3 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
Spectrum Analyzer	MS2665C	ANRITSU	6200175476	09/30/03	09/30/04

9.4 Test Result of Power spectral density

The following table shows a summary of the test results of the Power Spectral Density.

IEEE 802.11b

<i>Channel</i>	<i>Ppr (dBm)</i>	<i>Cable Loss (dB)</i>	<i>Ppq (dBm)</i>	<i>Limit (dB)</i>	<i>Margin (dB)</i>
CH 01	-5.30	0.70	-4.60	8.00	-12.60
CH 06	-5.73	0.70	-5.03	8.00	-13.03
CH 11	-7.94	0.70	-7.24	8.00	-15.24

IEEE 802.11g

<i>Channel</i>	<i>Ppr (dBm)</i>	<i>Cable Loss (dB)</i>	<i>Ppq (dBm)</i>	<i>Limit (dB)</i>	<i>Margin (dB)</i>
CH 01	-27.23	0.70	-26.53	8.00	-34.53
CH 06	-24.92	0.70	-24.22	8.00	-32.22
CH 11	-24.10	0.70	-23.40	8.00	-31.40

Note:

1. The following pages show the results of spectrum reading.
2. Ppr: spectrum read power density (using peak search mode),
Ppq: actual peak power density in the spread spectrum band.
3. $Ppq = Ppr + |Cable Loss|$

Channel 01



IEEE 802.11b




IEEE 802.11g

Channel 6




IEEE 802.11b




IEEE 802.11g

Channel 11



IEEE 802.11b



IEEE 802.11g