



FCC RF Test Report

APPLICANT : ASUSTeK COMPUTER INC.
EQUIPMENT : ASUS Phone(Mobile Phone)
BRAND NAME : ASUS
MODEL NAME : ASUS_X01AD
FCC ID : MSQX01AD
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Jul. 20, 2018 and testing was completed on Nov. 19, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Product Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test..... 5

 1.5 Modification of EUT 6

 1.6 Testing Location 6

 1.7 Applicable Standards..... 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 7

 2.1 Carrier Frequency and Channel 7

 2.2 Test Mode 8

 2.3 Connection Diagram of Test System 9

 2.4 Support Unit used in test configuration and system 9

 2.5 EUT Operation Test Setup 10

 2.6 Measurement Results Explanation Example..... 10

3 TEST RESULT 11

 3.1 6dB and 99% Bandwidth Measurement 11

 3.2 Output Power Measurement..... 13

 3.3 Power Spectral Density Measurement 14

 3.4 Conducted Band Edges and Spurious Emission Measurement 16

 3.5 Radiated Band Edges and Spurious Emission Measurement 29

 3.6 AC Conducted Emission Measurement..... 33

 3.7 Antenna Requirements 35

4 LIST OF MEASURING EQUIPMENT 36

5 UNCERTAINTY OF EVALUATION 37

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. AC CONDUCTED EMISSION TEST RESULT

APPENDIX C. RADIATED SPURIOUS EMISSION

APPENDIX D. DUTY CYCLE PLOTS

APPENDIX E. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.06 dB at 2483.620 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 7.46 dB at 0.162 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

ASUSTeK COMPUTER INC.
4F, No.150, Li-Te Rd., Peitou, Taipei 112, Taiwan

1.2 Manufacturer

ASUSTeK COMPUTER INC.
4F, No.150, Li-Te Rd., Peitou, Taipei 112, Taiwan

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	ASUS Phone(Mobile Phone)
Brand Name	ASUS
Model Name	ASUS_X01AD
FCC ID	MSQX01AD
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth BR/EDR/LE
IMEI Code	Conducted: 352203100056807/352203100056815 Conduction: 352203100057102/352203100057110 Radiation: 352203100057029/352203100057037
HW Version	A8r8a
SW Version	DailyBuildOPM1.WW_Phone-15.2016.1805.000-20180913
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 20.01 dBm (0.1002 W) 802.11g : 22.34 dBm (0.1714 W) 802.11n HT20 : 22.21 dBm (0.1663 W) 802.11n HT40 : 21.88 dBm (0.1542 W)
99% Occupied Bandwidth	802.11b : 14.04MHz 802.11g : 18.13MHz 802.11n HT20 : 18.63MHz 802.11n HT40 : 36.96MHz
Antenna Type / Gain	PIFA Antenna with gain -1.00 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.
	TH01-KS CO01-KS 03CH06-KS	CN5013	630927

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		




2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :GSM 850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable 1(Charging from Adapter 2) + Earphone 1
Remark: For Radiated Test Cases, The tests were performed with Adapter 1, Battery, Earphone 1, USB Cable 1.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A



2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.4dB

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 5.4 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup







3.4.5 Test Result of Conducted Band Edges and Spurious Emission




Test Engineer : Silent Hai	Temperature :	21~25°C
	Relative Humidity :	49~51%

Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----







Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----







Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----








Test Mode : 802.11g Test Channel : 01







Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----







Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----








Test Mode : 802.11n HT20 Test Channel : 01







Test Mode :	802.11n HT20	Test Channel :	06
-------------	--------------	----------------	----







Test Mode : 802.11n HT20 Test Channel : 11








Test Mode : 802.11n HT40 Test Channel : 03







Test Mode :	802.11n HT40	Test Channel :	06
-------------	--------------	----------------	----





Test Mode : 802.11n HT40 Test Channel : 09





3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	Oct. 15, 2018~ Oct. 19, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 18, 2018	Oct. 15, 2018~ Oct. 19, 2018	Jan. 17, 2019	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 18, 2018	Oct. 15, 2018~ Oct. 19, 2018	Jan. 17, 2019	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY564000 23	3Hz~8.5GHz;Max 30dBm	Oct. 12, 2018	Oct. 28, 2018- Nov. 19, 2018	Oct. 11, 2019	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY574710 84	10Hz-44GHz	Jun. 25, 2018	Oct. 28, 2018- Nov. 19, 2018	Jun. 24, 2019	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Oct. 28, 2018- Nov. 19, 2018	Oct. 18, 2019	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Jan. 29, 2018	Oct. 28, 2018- Nov. 19, 2018	Jan. 28, 2019	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 20, 2018	Oct. 28, 2018- Nov. 19, 2018	Oct. 19, 2019	Radiation (03CH06-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Feb. 07, 2018	Oct. 28, 2018- Nov. 19, 2018	Feb. 06, 2019	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Aug. 06, 2018	Oct. 28, 2018- Nov. 19, 2018	Aug. 05, 2019	Radiation (03CH06-KS)
Amplifier	MITEQ	TTA1840-35-HG	2014749	18~40GHz	Feb. 08, 2018	Oct. 28, 2018- Nov. 19, 2018	Feb. 07, 2019	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Apr. 17, 2018	Oct. 28, 2018- Nov. 19, 2018	Apr. 16, 2019	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY532702 03	500MHz~26.5GHz	Dec. 16, 2017	Oct. 28, 2018- Nov. 19, 2018	Dec. 15, 2018	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Oct. 28, 2018- Nov. 19, 2018	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Oct. 28, 2018- Nov. 19, 2018	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Oct. 28, 2018- Nov. 19, 2018	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	Oct. 14, 2018	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Oct. 14, 2018	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 23, 2017	Oct. 14, 2018	Nov. 22, 2018	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Oct. 14, 2018	Oct. 11, 2019	Conduction (CO01-KS)

NCR: No Calibration Required



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Silent Hai	Temperature:	21~25	°C
Test Date:	2018/10/15~201//10/19	Relative Humidity:	49~51	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	14.04	9.55	0.50	Pass
11b	1Mbps	1	6	2437	14.04	10.05	0.50	Pass
11b	1Mbps	1	11	2462	14.04	9.55	0.50	Pass
11g	6Mbps	1	1	2412	18.13	15.70	0.50	Pass
11g	6Mbps	1	6	2437	17.93	15.78	0.50	Pass
11g	6Mbps	1	11	2462	17.88	15.70	0.50	Pass
HT20	MCS0	1	1	2412	18.63	16.16	0.50	Pass
HT20	MCS0	1	6	2437	18.33	16.28	0.50	Pass
HT20	MCS0	1	11	2462	18.53	15.96	0.50	Pass
HT40	MCS0	1	3	2422	36.96	35.48	0.50	Pass
HT40	MCS0	1	6	2437	36.96	35.12	0.50	Pass
HT40	MCS0	1	9	2452	36.46	35.12	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	19.63	30.00	-1.00	18.63	36.00	Pass
11b	1Mbps	1	6	2437	20.01	30.00	-1.00	19.01	36.00	Pass
11b	1Mbps	1	11	2462	19.97	30.00	-1.00	18.97	36.00	Pass
11g	6Mbps	1	1	2412	21.08	30.00	-1.00	20.08	36.00	Pass
11g	6Mbps	1	6	2437	22.34	30.00	-1.00	21.34	36.00	Pass
11g	6Mbps	1	11	2462	22.16	30.00	-1.00	21.16	36.00	Pass
HT20	MCS0	1	1	2412	20.51	30.00	-1.00	19.51	36.00	Pass
HT20	MCS0	1	6	2437	22.21	30.00	-1.00	21.21	36.00	Pass
HT20	MCS0	1	11	2462	21.95	30.00	-1.00	20.95	36.00	Pass
HT40	MCS0	1	3	2422	19.56	30.00	-1.00	18.56	36.00	Pass
HT40	MCS0	1	6	2437	21.83	30.00	-1.00	20.83	36.00	Pass
HT40	MCS0	1	9	2452	21.88	30.00	-1.00	20.88	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.11	17.22
11b	1Mbps	1	6	2437	0.11	17.40
11b	1Mbps	1	11	2462	0.11	17.51
11g	6Mbps	1	1	2412	0.60	13.08
11g	6Mbps	1	6	2437	0.60	14.32
11g	6Mbps	1	11	2462	0.60	14.44
HT20	MCS0	1	1	2412	0.62	12.05
HT20	MCS0	1	6	2437	0.62	13.74
HT20	MCS0	1	11	2462	0.62	13.91
HT40	MCS0	1	3	2422	0.67	10.21
HT40	MCS0	1	6	2437	0.67	13.18
HT40	MCS0	1	9	2452	0.67	12.96


TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-5.52	-1.00	8.00	Pass
11b	1Mbps	1	6	2437	-4.67	-1.00	8.00	Pass
11b	1Mbps	1	11	2462	-4.45	-1.00	8.00	Pass
11g	6Mbps	1	1	2412	-8.93	-1.00	8.00	Pass
11g	6Mbps	1	6	2437	-9.77	-1.00	8.00	Pass
11g	6Mbps	1	11	2462	-8.02	-1.00	8.00	Pass
HT20	MCS0	1	1	2412	-10.30	-1.00	8.00	Pass
HT20	MCS0	1	6	2437	-10.56	-1.00	8.00	Pass
HT20	MCS0	1	11	2462	-9.56	-1.00	8.00	Pass
HT40	MCS0	1	3	2422	-17.30	-1.00	8.00	Pass
HT40	MCS0	1	6	2437	-14.59	-1.00	8.00	Pass
HT40	MCS0	1	9	2452	-13.45	-1.00	8.00	Pass



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos Zhang	Temperature :	25~26°C
		Relative Humidity :	48~49%
Test Voltage :	120Vac / 60Hz	Phase :	Line




Site : CO01-KS
 Condition : FCC PART 15C LISN-L-171013-060103 LINE

mode : Mode 1
 : 352203100057102/352203100057110 #62

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.155	57.23	-8.51	65.74	46.60	0.16	10.47	QP
2	0.155	42.93	-12.81	55.74	32.30	0.16	10.47	Average
3 *	0.162	57.92	-7.46	65.38	47.30	0.17	10.45	QP
4	0.162	43.22	-12.16	55.38	32.60	0.17	10.45	Average
5	0.186	53.38	-10.82	64.20	42.80	0.19	10.39	QP
6	0.186	38.18	-16.02	54.20	27.60	0.19	10.39	Average
7	0.208	49.16	-14.11	63.27	38.60	0.20	10.36	QP
8	0.208	33.86	-19.41	53.27	23.30	0.20	10.36	Average
9	0.226	46.86	-15.75	62.61	36.30	0.21	10.35	QP
10	0.226	32.06	-20.55	52.61	21.50	0.21	10.35	Average
11	0.255	42.35	-19.25	61.60	31.80	0.22	10.33	QP
12	0.255	27.15	-24.45	51.60	16.60	0.22	10.33	Average
13	0.274	42.04	-18.94	60.98	31.50	0.22	10.32	QP
14	0.274	26.84	-24.14	50.98	16.30	0.22	10.32	Average
15	0.323	39.33	-20.29	59.62	28.80	0.23	10.30	QP
16	0.323	24.13	-25.49	49.62	13.60	0.23	10.30	Average



Test Engineer :	Amos Zhang	Temperature :	25~26°C
		Relative Humidity :	48~49%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS
 Condition : FCC PART 15C LISN-N-171013-060103 NEUTRAL
 mode : Mode 1
 : 352203100057102/352203100057110 #62

	Freq	Level	Over Limit	Limit	Read	LISN	Cable	
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	Remark
1	0.153	55.65	-10.17	65.82	44.90	0.28	10.47	QP
2	0.153	43.35	-12.47	55.82	32.60	0.28	10.47	Average
3 *	0.162	57.33	-8.05	65.38	46.60	0.28	10.45	QP
4	0.162	43.03	-12.35	55.38	32.30	0.28	10.45	Average
5	0.185	56.17	-8.07	64.24	45.50	0.28	10.39	QP
6	0.185	38.27	-15.97	54.24	27.60	0.28	10.39	Average
7	0.207	48.24	-15.08	63.32	37.60	0.28	10.36	QP
8	0.207	33.24	-20.08	53.32	22.60	0.28	10.36	Average
9	0.229	47.23	-15.25	62.48	36.60	0.28	10.35	QP
10	0.229	32.13	-20.35	52.48	21.50	0.28	10.35	Average
11	0.259	47.21	-14.26	61.47	36.60	0.28	10.33	QP
12	0.259	29.21	-22.26	51.47	18.60	0.28	10.33	Average
13	0.282	41.20	-19.56	60.76	30.60	0.28	10.32	QP
14	0.282	26.80	-23.96	50.76	16.20	0.28	10.32	Average
15	0.308	42.19	-17.83	60.02	31.61	0.28	10.30	QP
16	0.308	24.69	-25.33	50.02	14.11	0.28	10.30	Average
17	0.358	42.77	-16.01	58.78	32.20	0.29	10.28	QP



Appendix C. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2389.43	48.45	-25.55	74	48.66	31.3	5.14	36.65	235	70	P	H
		2389.82	36.72	-17.28	54	36.92	31.3	5.14	36.64	235	70	A	H
	*	2410	105.33	-	-	105.5	31.33	5.14	36.64	235	70	P	H
	*	2412	100.61	-	-	100.78	31.33	5.14	36.64	235	70	A	H
		2388.26	50.33	-23.67	74	50.54	31.3	5.14	36.65	100	69	P	V
		2389.95	36.41	-17.59	54	36.61	31.3	5.14	36.64	100	69	A	V
	*	2410	104.65	-	-	104.82	31.33	5.14	36.64	100	69	P	V
	*	2410	99.92	-	-	100.09	31.33	5.14	36.64	100	69	A	V
802.11b CH 11 2462MHz	*	2462	103.66	-	-	103.76	31.41	5.16	36.67	100	65	P	H
	*	2462	98.16	-	-	98.26	31.41	5.16	36.67	100	65	A	H
		2486.26	45.43	-28.57	74	45.49	31.44	5.18	36.68	100	65	P	H
		2483.5	32.99	-21.01	54	33.05	31.44	5.18	36.68	100	65	A	H
	*	2462	103.48	-	-	103.58	31.41	5.16	36.67	100	80	P	V
	*	2462	99.45	-	-	99.55	31.41	5.16	36.67	100	80	A	V
		2493.82	46.81	-27.19	74	46.85	31.47	5.18	36.69	100	80	P	V
		2483.5	33.28	-20.72	54	33.34	31.44	5.18	36.68	100	80	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		4824	43.44	-30.56	74	61.91	35.65	8	62.12	100	360	P	H
CH 01		4824	41.74	-32.26	74	60.21	35.65	8	62.12	100	360	P	V
2412MHz													
802.11b		4872	41.17	-32.83	74	59.75	35.61	7.92	62.11	100	360	P	H
CH 06		7308	40.48	-33.52	74	58.24	35.89	9.12	62.77	100	360	P	H
2437MHz		4872	40.93	-33.07	74	59.51	35.61	7.92	62.11	100	360	P	V
		7308	40.35	-33.65	74	58.11	35.89	9.12	62.77	100	360	P	V
802.11b		4926	41.05	-32.95	74	59.81	35.57	7.76	62.09	100	360	P	H
CH 11		7386	41	-33	74	58.7	35.94	9.14	62.78	100	360	P	H
2462MHz		4926	41.59	-32.41	74	60.35	35.57	7.76	62.09	100	360	P	V
		7386	40.51	-33.49	74	58.21	35.94	9.14	62.78	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		2389.69	65.26	-8.74	74	65.47	31.3	5.14	36.65	246	232	P	H
		2389.95	49.28	-4.72	54	49.48	31.3	5.14	36.64	246	232	A	H
	*	2406	104.01	-	-	104.18	31.33	5.14	36.64	246	232	P	H
	*	2408	96.32	-	-	96.49	31.33	5.14	36.64	246	232	A	H
		2389.95	62.26	-11.74	74	62.46	31.3	5.14	36.64	127	297	P	V
		2389.95	46.55	-7.45	54	46.75	31.3	5.14	36.64	127	297	A	V
	*	2418	103.47	-	-	103.65	31.33	5.14	36.65	127	297	P	V
	*	2416	95.58	-	-	95.76	31.33	5.14	36.65	127	297	A	V
802.11g CH 11 2462MHz	*	2458	105.66	-	-	105.76	31.41	5.16	36.67	288	230	P	H
	*	2456	97.44	-	-	97.54	31.41	5.16	36.67	288	230	A	H
		2483.62	63.21	-10.79	74	63.27	31.44	5.18	36.68	288	230	P	H
		2483.56	46.37	-7.63	54	46.43	31.44	5.18	36.68	288	230	A	H
	*	2458	105.18	-	-	105.28	31.41	5.16	36.67	100	301	P	V
	*	2456	97.42	-	-	97.52	31.41	5.16	36.67	100	301	A	V
		2483.5	63.79	-10.21	74	63.85	31.44	5.18	36.68	100	301	P	V
		2483.62	45.67	-8.33	54	45.73	31.44	5.18	36.68	100	301	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g		4824	40.44	-33.56	74	58.91	35.65	8	62.12	100	360	P	H
CH 01		4824	41.6	-32.4	74	60.07	35.65	8	62.12	100	360	P	V
2412MHz													
802.11g		4872	41.75	-32.25	74	60.33	35.61	7.92	62.11	100	360	P	H
CH 06		7308	41.08	-32.92	74	58.84	35.89	9.12	62.77	100	360	P	H
2437MHz		4872	41.38	-32.62	74	59.96	35.61	7.92	62.11	100	360	P	V
		7308	40.04	-33.96	74	57.8	35.89	9.12	62.77	100	360	P	V
802.11g		4926	41.49	-32.51	74	60.25	35.57	7.76	62.09	100	360	P	H
CH 11		7386	40.31	-33.69	74	58.01	35.94	9.14	62.78	100	360	P	H
2462MHz		4926	42.36	-31.64	74	61.12	35.57	7.76	62.09	100	360	P	V
		7386	41.02	-32.98	74	58.72	35.94	9.14	62.78	100	360	P	V
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. 												



**15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		2389.69	67.99	-6.01	74	68.2	31.3	5.14	36.65	241	233	P	H
		2389.82	49.14	-4.86	54	49.34	31.3	5.14	36.64	241	233	A	H
	*	2416	103.55	-	-	103.73	31.33	5.14	36.65	241	233	P	H
	*	2406	96.66	-	-	96.83	31.33	5.14	36.64	241	233	A	H
		2389.56	60.99	-13.01	74	61.2	31.3	5.14	36.65	130	293	P	V
		2389.82	47.13	-6.87	54	47.33	31.3	5.14	36.64	130	293	A	V
	*	2408	103.3	-	-	103.47	31.33	5.14	36.64	130	293	P	V
	*	2408	95.44	-	-	95.61	31.33	5.14	36.64	130	293	A	V
802.11n HT20 CH 11 2462MHz	*	2456	104.58	-	-	104.68	31.41	5.16	36.67	236	234	P	H
	*	2458	96.69	-	-	96.79	31.41	5.16	36.67	236	234	A	H
		2484.52	64.38	-9.62	74	64.44	31.44	5.18	36.68	236	234	P	H
		2483.74	46.9	-7.1	54	46.96	31.44	5.18	36.68	236	234	A	H
	*	2456	103.15	-	-	103.25	31.41	5.16	36.67	124	316	P	V
	*	2458	95.9	-	-	96	31.41	5.16	36.67	124	316	A	V
		2483.5	61.76	-12.24	74	61.82	31.44	5.18	36.68	124	316	P	V
		2483.5	44.11	-9.89	54	44.17	31.44	5.18	36.68	124	316	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

Table with 14 columns: WIFI, Note, Frequency, Level, Over, Limit, Read, Antenna, Cable, Preamp, Ant, Table, Peak, Pol. It contains multiple rows of test data for different channels and frequencies, including a 'Remark' section at the bottom.



**15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Band Edge @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz		2388.78	64.23	-9.77	74	64.44	31.3	5.14	36.65	241	233	P	H
		2389.82	49.26	-4.74	54	49.46	31.3	5.14	36.64	241	233	A	H
	*	2412	97.89	-	-	98.06	31.33	5.14	36.64	241	233	P	H
	*	2410	89.82	-	-	89.99	31.33	5.14	36.64	241	233	A	H
		2489.02	44.36	-29.64	74	44.39	31.47	5.18	36.68	241	233	P	H
		2486.68	33.61	-20.39	54	33.67	31.44	5.18	36.68	241	233	A	H
		2388.65	63.97	-10.03	74	64.18	31.3	5.14	36.65	100	238	P	V
		2389.95	49.62	-4.38	54	49.82	31.3	5.14	36.64	100	238	A	V
	*	2410	97.97	-	-	98.14	31.33	5.14	36.64	100	238	P	V
	*	2410	89.5	-	-	89.67	31.33	5.14	36.64	100	238	A	V
		2488.54	44.17	-29.83	74	44.2	31.47	5.18	36.68	100	238	P	V
		2487.88	34.05	-19.95	54	34.08	31.47	5.18	36.68	100	238	A	V
802.11n HT40 CH 06 2437MHz		2389.3	65.32	-8.68	74	65.53	31.3	5.14	36.65	234	67	P	H
		2389.82	46.79	-7.21	54	46.99	31.3	5.14	36.64	234	67	A	H
	*	2428	103.07	-	-	103.2	31.36	5.16	36.65	234	67	P	H
	*	2426	92.87	-	-	93	31.36	5.16	36.65	234	67	A	H
		2483.8	60.71	-13.29	74	60.77	31.44	5.18	36.68	234	67	P	H
		2483.56	41.12	-12.88	54	41.18	31.44	5.18	36.68	234	67	A	H
		2389.3	63.19	-10.81	74	63.4	31.3	5.14	36.65	100	95	P	V
		2389.69	46.26	-7.74	54	46.47	31.3	5.14	36.65	100	95	A	V
	*	2444	103.43	-	-	103.55	31.39	5.16	36.67	100	95	P	V
	*	2426	93.17	-	-	93.3	31.36	5.16	36.65	100	95	A	V
		2483.8	62.2	-11.8	74	62.26	31.44	5.18	36.68	100	95	P	V
		2483.5	42.92	-11.08	54	42.98	31.44	5.18	36.68	100	95	A	V



802.11n HT40 CH 09 2452MHz		2388	53.24	-20.76	74	53.45	31.3	5.14	36.65	241	233	P	H
		2389.95	39.72	-14.28	54	39.92	31.3	5.14	36.64	241	233	A	H
		2486.2	62.5	-11.5	74	62.56	31.44	5.18	36.68	241	233	P	H
		2483.62	49.94	-4.06	54	50	31.44	5.18	36.68	241	233	A	H
	*	2440	100.3	-	-	100.4	31.39	5.16	36.65	241	233	P	H
	*	2440	92.44	-	-	92.54	31.39	5.16	36.65	241	233	A	H
		2386.83	50.16	-23.84	74	50.37	31.3	5.14	36.65	100	73	P	V
		2389.95	37.77	-16.23	54	37.97	31.3	5.14	36.64	100	73	A	V
	*	2444	99.89	-	-	100.01	31.39	5.16	36.67	100	73	P	V
	*	2444	89.44	-	-	89.56	31.39	5.16	36.67	100	73	A	V
		2485.06	61.35	-12.65	74	61.41	31.44	5.18	36.68	100	73	P	V
		2483.56	38.63	-15.37	54	38.69	31.44	5.18	36.68	100	73	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4842	39.96	-34.04	74	58.53	35.63	7.92	62.12	100	360	P	H
HT40		7266	40.55	-33.45	74	58.33	35.87	9.12	62.77	100	360	P	H
CH 03		4842	39.96	-34.04	74	58.53	35.63	7.92	62.12	100	360	P	V
2422MHz		7266	40.82	-33.18	74	58.6	35.87	9.12	62.77	100	360	P	V
802.11n		4872	41.09	-32.91	74	59.67	35.61	7.92	62.11	100	360	P	H
HT40		7308	40.49	-33.51	74	58.25	35.89	9.12	62.77	100	360	P	H
CH 06		4872	41.34	-32.66	74	59.92	35.61	7.92	62.11	100	360	P	V
2437MHz		7308	40.58	-33.42	74	58.34	35.89	9.12	62.77	100	360	P	V
802.11n		4902	41.03	-32.97	74	59.7	35.58	7.84	62.09	100	360	P	H
HT40		7356	40.85	-33.15	74	58.58	35.92	9.13	62.78	100	360	P	H
CH 09		4902	41.15	-32.85	74	59.82	35.58	7.84	62.09	100	360	P	V
2452MHz		7356	41.31	-32.69	74	59.04	35.92	9.13	62.78	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT40 LF		30.97	18.35	-21.65	40	25.79	23.93	0.61	31.98	-	-	P	H
		154.16	21.6	-21.9	43.5	36.07	16.2	1.27	31.94	-	-	P	H
		188.11	21.82	-21.68	43.5	37.09	15.24	1.4	31.91	-	-	P	H
		213.33	28.62	-14.88	43.5	43.85	15.17	1.52	31.92	100	0	P	H
		266.68	20.28	-25.72	46	31.42	19.1	1.76	32	-	-	P	H
		627.52	20.95	-25.05	46	26.38	24.38	2.57	32.38	-	-	P	H
		46.49	24.11	-15.89	40	39.71	15.62	0.72	31.94	100	0	P	V
		64.92	19.42	-20.58	40	38.02	12.5	0.83	31.93	-	-	P	V
		159.01	21.63	-21.87	43.5	36.4	15.87	1.29	31.93	-	-	P	V
		189.08	22.96	-20.54	43.5	38.23	15.24	1.4	31.91	-	-	P	V
		215.27	24.33	-19.17	43.5	39.57	15.15	1.53	31.92	-	-	P	V
	747.8	22.33	-23.67	46	26.69	25.17	2.73	32.26	-	-	P	V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:


- Level(dBμV/m)
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
- Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
11b	97.59	8.232	0.121	0.13KHz
11g	87.04	1.362	0.734	0.75KHz
11n HT20	86.70	1.275	0.784	0.82KHz
11n HT40	85.79	1.225	0.817	0.82KHz

11b






11g



11n HT20





11n HT40

