

FCC Test Report

(PART 27)

Report No.: RF170425C26-2

FCC ID: MSQZ01KD

Test Model: ASUS_Z01KD

Received Date: Apr. 25, 2017

Test Date: May 18, 2017 ~ Jun. 09, 2017

Issued Date: Aug. 08, 2017

Applicant: ASUSTek COMPUTER INC.

Address: 4F, No. 150, LI-TE Rd., PEITOU, TAIPEI 112, TAIWAN

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan
Hsien 333, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,
R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agency

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	7
2.2 Test Site and Instruments	8
3 General Information	10
3.1 General Description of EUT	10
3.2 Configuration of System under Test	12
3.2.1 Description of Support Units	12
3.3 Test Mode Applicability and Tested Channel Detail	13
3.4 EUT Operating Conditions	18
3.5 General Description of Applied Standards	18
4 Test Types and Results	19
4.1 Output Power Measurement	19
4.1.1 Limits of Output Power Measurement	19
4.1.2 Test Procedures	19
4.1.3 Test Setup	20
4.1.4 Test Results	21
4.2 Frequency Stability Measurement	32
4.2.1 Limits of Frequency Stability Measurement	32
4.2.2 Test Procedure	32
4.2.3 Test Setup	32
4.2.4 Test Results	33
4.3 Occupied Bandwidth Measurement	46
4.3.1 Limits of Occupied Bandwidth Measurement	46
4.3.2 Test Procedure	46
4.3.3 Test Setup	46
4.3.4 Test Result	47
4.4 Band Edge Measurement	54
4.4.1 Limits of Band Edge Measurement	54
4.4.2 Test Setup	54
4.4.3 Test Procedures	54
4.4.4 Test Results	55
4.5 Peak to Average Ratio	67
4.5.1 Limits of Peak to Average Ratio Measurement	67
4.5.2 Test Setup	67
4.5.3 Test Procedures	67
4.5.4 Test Results	67
4.6 Conducted Spurious Emissions	74
4.6.1 Limits of Conducted Spurious Emissions Measurement	74
4.6.2 Test Setup	74
4.6.3 Test Procedure	74
4.6.4 Test Results	75
4.7 Radiated Emission Measurement	88
4.7.1 Limits of Radiated Emission Measurement	88
4.7.2 Test Procedure	88
4.7.3 Deviation from Test Standard	88
4.7.4 Test Setup	89
4.7.5 Test Results	90
5 Pictures of Test Arrangements	114
Appendix – Information on the Testing Laboratories	115

Release Control Record

Issue No.	Description	Date Issued
RF170425C26-2	Original Release	Aug. 08, 2017

1 Certificate of Conformity

Product: ASUS Phone

Brand: ASUS

Test Model: ASUS_Z01KD

Sample Status: Production Unit

Applicant: ASUSTek COMPUTER INC.

Test Date: May 18, 2017 ~ Jun. 09, 2017

Standards: FCC Part 27, Subpart C, L

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :




Date:

Aug. 08, 2017

Ivonne Wu / Supervisor

Approved by :



Date:

Aug. 08, 2017

David Huang / Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2 (WCDMA)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Equivalent Isotropic Radiated Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 27.53(h)	Occupied Bandwidth	Pass	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	Pass	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -37.26 dB at 3465.20 MHz.

Applied Standard: FCC Part 27 & Part 2 (LTE 4)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 27.53(h)	Occupied Bandwidth	Pass	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	Pass	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -28.50 dB at 5235.00 MHz.

Applied Standard: FCC Part 27 & Part 2 (LTE 12)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(C)(10)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 27.53(g)	Occupied Bandwidth	Pass	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	Pass	Meet the requirement of limit.
27.53(g)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(g)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(g)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -26.16 dB at 2122.50 MHz.

Applied Standard: FCC Part 27 & Part 2 (LTE 17)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(C)(10)	Maximum Peak Output Power	Pass	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 27.53(g)	Occupied Bandwidth	Pass	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	Pass	Meet the requirement of limit.
27.53(g)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 27.53(g)	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 27.53(g)	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -33.15 dB at 2130.00 MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9010A	MY52220314	Nov. 16, 2016	Nov. 15, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 13, 2016	Dec. 12, 2017
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Dec. 16, 2016	Dec. 15, 2017
HORN Antenna ETS-Lindgren	3117	00143293	Dec. 29, 2016	Dec. 28, 2017
Double Ridge Guide Horn Antenna EMCO	3115	5619	Dec. 27, 2016	Dec. 26, 2017
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Dec. 13, 2016	Dec. 12, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 14, 2016	Dec. 13, 2017
Fixed Attenuator Mini-Circuits	BW-N10W5+	NA	Jul. 08, 2016	Jul. 07, 2017
MXG Vector signal generator Agilent	N5182B	MY53050430	Oct. 19, 2016	Oct. 18, 2017
Preamplifier Agilent	310N	187226	Jun. 24, 2016	Jun. 23, 2017
Preamplifier Agilent	83017A	MY39501357	Jun. 24, 2016	Jun. 23, 2017
Power Meter Anritsu	ML2495A	1232002	Sep. 08, 2016	Sep. 07, 2017
Power Sensor Anritsu	MA2411B	1207325	Sep. 08, 2016	Sep. 07, 2017
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 24, 2016	Jun. 23, 2017
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 24, 2016	Jun. 23, 2017
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Radio Communication Analyzer Anritsu	MT8820C	6201300640	Aug. 10, 2015	Aug. 09, 2017

- Note:
1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HsinTien Chamber 1.
 3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
 4. The IC Site Registration No. is IC7450I-1.

3 General Information

3.1 General Description of EUT

Product	ASUS Phone	
Brand	ASUS	
Test Model	ASUS_Z01KD	
SKU	BR/NA/SA-2CA US/BR/CO/PE/CL	
Status of EUT	Production Unit	
Power Supply Rating	5.0 Vdc or 9 Vdc (adapter) 5.0 Vdc (host equipment) 3.85 Vdc (Li-ion battery)	
Modulation Type	WCDMA	QPSK
	LTE	QPSK, 16QAM
Frequency Range	WCDMA	1712.4 ~ 1752.6 MHz
	LTE Band 4 (Channel Bandwidth: 1.4 MHz)	1710.7 ~ 1754.3 MHz
	LTE Band 4 (Channel Bandwidth: 3 MHz)	1711.5 ~ 1753.5 MHz
	LTE Band 4 (Channel Bandwidth: 5 MHz)	1712.5 ~ 1752.5 MHz
	LTE Band 4 (Channel Bandwidth: 10 MHz)	1715.0 ~ 1750.0 MHz
	LTE Band 4 (Channel Bandwidth: 15 MHz)	1717.5 ~ 1747.5 MHz
	LTE Band 4 (Channel Bandwidth: 20 MHz)	1720.0 ~ 1745.0 MHz
	LTE Band 12 (Channel Bandwidth: 1.4 MHz)	699.7 ~ 715.3 MHz
	LTE Band 12 (Channel Bandwidth: 3 MHz)	700.5 ~ 714.5 MHz
	LTE Band 12 (Channel Bandwidth: 5 MHz)	701.5 ~ 713.5 MHz
	LTE Band 12 (Channel Bandwidth: 10 MHz)	704.0 ~ 711.0 MHz
	LTE Band 17 (Channel Bandwidth: 5 MHz)	706.5 ~ 713.5 MHz
	LTE Band 17 (Channel Bandwidth: 10 MHz)	709 ~ 711 MHz
	Emission Designator	WCDMA
LTE Band 4 (Channel Bandwidth: 1.4 MHz)		1M09W7D
LTE Band 4 (Channel Bandwidth: 3 MHz)		2M70G7D
LTE Band 4 (Channel Bandwidth: 5 MHz)		4M49W7D
LTE Band 4 (Channel Bandwidth: 10 MHz)		8M97W7D
LTE Band 4 (Channel Bandwidth: 15 MHz)		13M5G7D
LTE Band 4 (Channel Bandwidth: 20 MHz)		18M0W7D
LTE Band 12 (Channel Bandwidth: 1.4 MHz)		1M09W7D
LTE Band 12 (Channel Bandwidth: 3 MHz)		2M70G7D
LTE Band 12 (Channel Bandwidth: 5 MHz)		4M50G7D
LTE Band 12 (Channel Bandwidth: 10 MHz)		8M99W7D
LTE Band 17 (Channel Bandwidth: 5 MHz)		4M50W7D
LTE Band 17 (Channel Bandwidth: 10 MHz)		8M98W7D
Max. ERP Power		LTE Band 12 (Channel Bandwidth: 1.4 MHz)
	LTE Band 12 (Channel Bandwidth: 3 MHz)	57.66mW
	LTE Band 12 (Channel Bandwidth: 5 MHz)	57.36mW
	LTE Band 12 (Channel Bandwidth: 10 MHz)	57.90mW
	LTE Band 17 (Channel Bandwidth: 5 MHz)	56.57mW
	LTE Band 17 (Channel Bandwidth: 10 MHz)	56.86mW



Max. EIRP Power	WCDMA	160.51mW
	LTE Band 4 (Channel Bandwidth: 1.4 MHz)	180.72mW
	LTE Band 4 (Channel Bandwidth: 3 MHz)	181.43mW
	LTE Band 4 (Channel Bandwidth: 5 MHz)	180.59mW
	LTE Band 4 (Channel Bandwidth: 10 MHz)	181.84mW
	LTE Band 4 (Channel Bandwidth: 15 MHz)	183.23mW
	LTE Band 4 (Channel Bandwidth: 20 MHz)	180.09mW
Antenna Type	Fixed Internal Antenna	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:



1. The EUT's accessories list refers to Ext. Pho.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.R.P. / E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

SIM	Band	ERP / EIRP	Radiated Emission
1	WCDMA	X-plane	Y-axis
	LTE Band 4	X-plane	Z-axis
	LTE Band 12	Y-plane	Y-axis
	LTE Band 17	Y-plane	Y-axis

WCDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	EIRP	1312 to 1513	1312, 1413, 1513	WCDMA
-	Frequency Stability	1312 to 1513	1312, 1513	WCDMA
-	Occupied Bandwidth	1312 to 1513	1312, 1413, 1513	WCDMA
-	Band Edge	1312 to 1513	1312, 1513	WCDMA
-	Peak to Average Ratio	1312 to 1513	1312, 1413, 1513	WCDMA
-	Conducuted Emission	1312 to 1513	1312, 1413, 1513	WCDMA
-	Radiated Emission	1312 to 1513	1312, 1413, 1513	WCDMA

LTE Band 4

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Frequency Stability	19957 to 20393	19957, 20393	1.4 MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	19965, 20385	3 MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	19975, 20375	5 MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20000, 20350	10 MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20025, 20325	15 MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20050, 20300	20 MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode		
-	Band Edge	19957 to 20393	19957	1.4 MHz	QPSK	1 RB / 0 RB Offset 6 RB / 0 RB Offset		
			20393	1.4 MHz	QPSK	1 RB / 5 RB Offset 6 RB / 0 RB Offset		
		19965 to 20385	19965	3 MHz	QPSK	1 RB / 0 RB Offset 15 RB / 0 RB Offset		
			20385	3 MHz	QPSK	1 RB / 14 RB Offset 15 RB / 0 RB Offset		
		19975 to 20375	19975	5 MHz	QPSK	1 RB / 0 RB Offset 25 RB / 0 RB Offset		
			20375	5 MHz	QPSK	1 RB / 24 RB Offset 25 RB / 0 RB Offset		
		20000 to 20350	20000	10 MHz	QPSK	1 RB / 0 RB Offset 50 RB / 0 RB Offset		
			20350	10 MHz	QPSK	1 RB / 49 RB Offset 50 RB / 0 RB Offset		
		20025 to 20325	20025	15 MHz	QPSK	1 RB / 0 RB Offset 75 RB / 0 RB Offset		
			20325	15 MHz	QPSK	1 RB / 74 RB Offset 75 RB / 0 RB Offset		
		20050 to 20300	20050	20 MHz	QPSK	1 RB / 0 RB Offset 100 RB / 0 RB Offset		
			20300	20 MHz	QPSK	1 RB / 99 RB Offset 100 RB / 0 RB Offset		
		-	Conducted Emission	19957 to 20393	19957, 20175, 20393	1.4 MHz	QPSK	1 RB / 0 RB Offset
				19965 to 20385	19965, 20175, 20385	3 MHz	QPSK	1 RB / 0 RB Offset
				19975 to 20375	19975, 20175, 20375	5 MHz	QPSK	1 RB / 0 RB Offset
				20000 to 20350	20000, 20175, 20350	10 MHz	QPSK	1 RB / 0 RB Offset
				20025 to 20325	20025, 20175, 20325	15 MHz	QPSK	1 RB / 0 RB Offset
				20050 to 20300	20050, 20175, 20300	20 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	20050 to 20300	20050, 20175, 20300	20 MHz	QPSK	1 RB / 0 RB Offset		

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE Band 12

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode		
-	ERP	23017 to 23173	23017, 23095, 23173	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
		23025 to 23165	23025, 23095, 23165	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
		23035 to 23155	23035, 23095, 23155	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
		23060 to 23130	23060, 23095, 23130	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
-	Frequency Stability	23017 to 23173	23017, 23173	1.4 MHz	QPSK	1 RB / 0 RB Offset		
		23025 to 23165	23025, 23165	3 MHz	QPSK	1 RB / 0 RB Offset		
		23035 to 23155	23035, 23155	5 MHz	QPSK	1 RB / 0 RB Offset		
		23060 to 23130	23060, 23130	10 MHz	QPSK	1 RB / 0 RB Offset		
-	Occupied Bandwidth	23017 to 23173	23017, 23095, 23173	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset		
		23025 to 23165	23025, 23095, 23165	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset		
		23035 to 23155	23035, 23095, 23155	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset		
		23060 to 23130	23060, 23095, 23130	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset		
-	Peak to Average Ratio	23017 to 23173	23017, 23095, 23173	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
		23025 to 23165	23025, 23095, 23165	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
		23035 to 23155	23035, 23095, 23155	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
		23060 to 23130	23060, 23095, 23130	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset		
-	Band Edge	23017 to 23173	23017	1.4 MHz	QPSK	1 RB / 0 RB Offset 6 RB / 0 RB Offset		
			23173	1.4 MHz	QPSK	1 RB / 5 RB Offset 6 RB / 0 RB Offset		
		23025 to 23165	23025	3 MHz	QPSK	1 RB / 0 RB Offset 15 RB / 0 RB Offset		
			23165	3 MHz	QPSK	1 RB / 14 RB Offset 15 RB / 0 RB Offset		
		23035 to 23155	23035	5 MHz	QPSK	1 RB / 0 RB Offset 25 RB / 0 RB Offset		
			23155	5 MHz	QPSK	1 RB / 24 RB Offset 25 RB / 0 RB Offset		
		23060 to 23130	23060	10 MHz	QPSK	1 RB / 0 RB Offset 50 RB / 0 RB Offset		
			23130	10 MHz	QPSK	1 RB / 49 RB Offset 50 RB / 0 RB Offset		
		-	Conducted Emission	23017 to 23173	23017, 23095, 23173	1.4 MHz	QPSK	1 RB / 0 RB Offset
				23025 to 23165	23025, 23095, 23165	3 MHz	QPSK	1 RB / 0 RB Offset
				23035 to 23155	23035, 23095, 23155	5 MHz	QPSK	1 RB / 0 RB Offset
				23060 to 23130	23060, 23095, 23130	10 MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	23060 to 23130	23060, 23095, 23130	10 MHz	QPSK	1 RB / 24 RB Offset		

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE Band 17

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	ERP	23755 to 23825	23755, 23790, 23825	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23780 to 23800	23780, 23790, 23800	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Frequency Stability	23755 to 23825	23755, 23825	5 MHz	QPSK	1 RB / 0 RB Offset
		23780 to 23800	23780, 23800	10 MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	23755 to 23825	23755, 23790, 23825	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23780 to 23800	23780, 23790, 23800	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Peak to Average Ratio	23755 to 23825	23755, 23790, 23825	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23780 to 23800	23780, 23790, 23800	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Band Edge	23755 to 23825	23755	5 MHz	QPSK	1 RB / 0 RB Offset 25 RB / 0 RB Offset
			23825	5 MHz	QPSK	1 RB / 24 RB Offset 25 RB / 0 RB Offset
		23780 to 23800	23780	10 MHz	QPSK	1 RB / 0 RB Offset 50 RB / 0 RB Offset
			23800	10 MHz	QPSK	1 RB / 49 RB Offset 50 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP / EIRP	25 deg. C, 65 % RH	3.85 Vdc	Charles Hsiao
Frequency Stability	25 deg. C, 65 % RH	3.85 Vdc	Anson Lin
Occupied Bandwidth	25 deg. C, 65 % RH	3.85 Vdc	Anson Lin
Band Edge	25 deg. C, 65 % RH	3.85 Vdc	Anson Lin
Peak to Average Ratio	25 deg. C, 65 % RH	3.85 Vdc	Anson Lin
Condcudeted Emission	25 deg. C, 65 % RH	3.85 Vdc	Anson Lin
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao & Karl Lee

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB 971168 D01 Power Meas License Digital Systems v02r02

ANSI/TIA/EIA-603-D 2010

Note: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 698-716 MHz band are limited to 3 watts ERP

4.1.2 Test Procedures

EIRP / ERP Measurement:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5 MHz for WCDMA and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$.

Conducted Power Measurement:

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.3 Test Setup

EIRP / ERP Measurement:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Conducted Power Measurement:



4.1.4 Test Results

Conducted Output Power (dBm)

Band	WCDMA IV		
	Channel	1312	1413
Frequency (MHz)	1712.4	1732.6	1752.6
RMC 12.2K	23.20	23.08	23.10
HSDPA Subtest-1	22.17	22.11	22.28
HSDPA Subtest-2	22.19	22.16	22.29
HSDPA Subtest-3	21.63	21.71	21.78
HSDPA Subtest-4	21.70	21.66	21.80
HSUPA Subtest-1	22.19	22.29	22.37
HSUPA Subtest-2	20.37	20.31	20.40
HSUPA Subtest-3	21.38	21.30	21.34
HSUPA Subtest-4	20.36	20.30	20.35
HSUPA Subtest-5	22.30	22.30	22.40

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 19957	Mid Ch 20175	High Ch 20393		Low Ch 19957	Mid Ch 20175	High Ch 20393	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
4 / 1.4M	1	0	23.25	23.31	22.76	0	22.33	22.35	21.80	1
	1	2	22.71	22.82	22.21	0	21.77	21.87	21.34	1
	1	5	22.47	22.61	22.17	0	21.60	21.66	21.19	1
	3	0	22.67	22.73	22.08	0	21.68	21.78	21.08	1
	3	1	22.49	22.65	22.05	0	21.53	21.65	21.05	1
	3	3	22.31	22.43	22.02	0	21.37	21.41	21.04	1
	6	0	21.97	22.05	21.36	1	20.93	21.05	20.43	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 19965	Mid Ch 20175	High Ch 20385		Low Ch 19965	Mid Ch 20175	High Ch 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
4 / 3M	1	0	23.33	23.36	22.86	0	22.36	22.41	21.87	1
	1	7	22.86	22.92	22.44	0	21.87	21.91	21.27	1
	1	14	22.57	22.71	22.21	0	21.54	21.70	21.14	1
	8	0	22.19	22.28	21.69	1	21.18	21.23	20.63	2
	8	3	22.06	22.15	21.51	1	21.06	21.13	20.50	2
	8	7	21.93	21.99	21.44	1	20.81	20.97	20.39	2
	15	0	22.08	22.15	21.66	1	21.06	21.13	20.50	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 19975	Mid Ch 20175	High Ch 20375		Low CH 19975	Mid CH 20175	High CH 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
4 / 5M	1	0	23.39	23.42	22.93	0	22.42	22.47	21.94	1
	1	12	22.93	22.99	22.47	0	21.94	22.00	21.42	1
	1	24	22.74	22.80	22.16	0	21.71	21.79	21.16	1
	12	0	22.30	22.37	21.85	1	21.30	21.35	20.80	2
	12	6	22.18	22.26	21.65	1	21.16	21.25	20.68	2
	12	13	22.06	22.10	21.56	1	20.99	21.09	20.52	2
	25	0	22.13	22.26	21.68	1	21.16	21.25	20.61	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20000	Mid Ch 20175	High Ch 20350		Low Ch 20000	Mid Ch 20175	High Ch 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
4 / 10M	1	0	23.44	23.47	22.98	0	22.48	22.52	22.02	1
	1	24	23.00	23.04	22.47	0	22.02	22.07	21.48	1
	1	49	22.78	22.86	22.33	0	21.82	21.89	21.32	1
	25	0	22.41	22.47	21.99	1	21.42	21.48	20.86	2
	25	12	22.35	22.38	21.79	1	21.32	21.38	20.72	2
	25	25	22.10	22.22	21.73	1	21.13	21.21	20.67	2
	50	0	22.27	22.38	21.88	1	21.27	21.38	20.76	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20025	Mid Ch 20175	High Ch 20325		Low Ch 20025	Mid Ch 20175	High Ch 20325	
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
4 / 15M	1	0	23.50	23.52	23.06	0	22.55	22.57	22.07	1
	1	37	23.05	23.10	22.69	0	22.09	22.14	21.67	1
	1	74	22.86	22.94	22.44	0	21.86	21.96	21.38	1
	36	0	22.52	22.55	22.10	1	21.50	21.54	21.02	2
	36	19	22.44	22.48	21.91	1	21.41	21.47	20.93	2
	36	39	22.32	22.35	21.88	1	21.26	21.33	20.84	2
	75	0	22.40	22.48	21.99	1	21.41	21.47	20.96	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20050	Mid Ch 20175	High Ch 20300		Low Ch 20050	Mid Ch 20175	High Ch 20300	
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
4 / 20M	1	0	23.55	23.57	23.11	0	22.59	22.61	22.12	1
	1	50	23.11	23.15	22.63	0	22.12	22.17	21.69	1
	1	99	22.98	23.01	22.55	0	21.94	22.02	21.59	1
	50	0	22.60	22.63	22.22	1	21.61	21.63	21.20	2
	50	25	22.55	22.57	22.09	1	21.51	21.56	21.03	2
	50	50	22.45	22.47	22.05	1	21.37	21.44	20.99	2
	100	0	22.55	22.57	22.09	1	21.50	21.56	21.16	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23017	Mid Ch 23095	High Ch 23173		Low Ch 23017	Mid Ch 23095	High Ch 23173	
			699.7 MHz	707.5 MHz	715.3 MHz		699.7 MHz	707.5 MHz	715.3 MHz	
12 / 1.4M	1	0	22.75	23.21	23.03	0	21.77	22.26	22.05	1
	1	2	22.47	22.92	22.60	0	21.51	21.94	21.65	1
	1	5	22.68	23.11	22.84	0	21.65	22.14	21.89	1
	3	0	22.01	22.36	22.13	0	21.85	21.41	21.08	1
	3	1	22.15	22.59	22.36	0	21.11	21.65	21.54	1
	3	3	22.03	22.51	22.30	0	21.01	21.57	21.34	1
	6	0	21.46	21.95	21.75	1	20.41	21.01	20.73	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23025	Mid Ch 23095	High Ch 23165		Low Ch 23025	Mid Ch 23095	High Ch 23165	
			700.5 MHz	707.5 MHz	714.5 MHz		700.5 MHz	707.5 MHz	714.5 MHz	
12 / 3M	1	0	22.83	23.26	23.09	0	21.87	22.31	22.13	1
	1	7	22.59	22.99	22.74	0	21.63	22.03	21.80	1
	1	14	22.64	23.16	22.91	0	21.68	22.20	22.06	1
	8	0	21.61	22.00	21.89	1	20.57	21.02	20.87	2
	8	3	21.74	22.20	22.05	1	20.77	21.24	20.99	2
	8	7	21.64	22.13	21.94	1	20.61	21.15	20.98	2
	15	0	21.61	22.10	21.86	1	20.57	21.11	20.75	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23035	Mid Ch 23095	High Ch 23155		Low Ch 23035	Mid Ch 23095	High Ch 23155	
			701.5 MHz	707.5 MHz	713.5 MHz		701.5 MHz	707.5 MHz	713.5 MHz	
12 / 5M	1	0	22.89	23.31	23.14	0	21.93	22.36	22.19	1
	1	12	22.71	23.03	22.90	0	21.66	22.08	21.92	1
	1	24	22.80	23.21	22.96	0	21.82	22.25	22.11	1
	12	0	21.72	22.11	21.83	1	20.67	21.10	20.87	2
	12	6	21.88	22.30	22.11	1	20.96	21.32	21.20	2
	12	13	21.80	22.23	22.07	1	20.80	21.24	21.04	2
	25	0	21.76	22.20	22.01	1	20.72	21.18	20.91	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23060	Mid Ch 23095	High Ch 23130		Low Ch 23060	Mid Ch 23095	High Ch 23130	
			704.0 MHz	707.5 MHz	711.0 MHz		704.0 MHz	707.5 MHz	711.0 MHz	
12 / 10M	1	0	22.97	23.36	23.20	0	22.00	22.40	22.24	1
	1	24	22.76	23.11	22.96	0	21.80	22.14	21.90	1
	1	49	22.92	23.26	23.03	0	21.93	22.30	22.15	1
	25	0	21.84	22.21	22.03	1	20.80	21.21	21.11	2
	25	12	22.09	22.39	22.24	1	21.00	21.40	21.30	2
	25	25	21.93	22.32	22.15	1	20.89	21.32	21.16	2
	50	0	21.91	22.29	22.13	1	20.85	21.29	21.05	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23755	Mid Ch 23790	High Ch 23825		Low Ch 23755	Mid Ch 23790	High Ch 23825	
			706.5 MHz	710.0 MHz	713.5 MHz		706.5 MHz	710.0 MHz	713.5 MHz	
17 / 5M	1	0	23.21	23.30	23.27	0	22.22	22.35	22.28	1
	1	12	23.03	23.25	23.18	0	22.15	22.28	22.20	1
	1	24	22.95	23.08	23.03	0	21.99	22.11	22.06	1
	12	0	22.11	22.22	22.19	1	21.05	21.22	21.19	2
	12	6	22.17	22.25	22.21	1	21.11	21.27	21.22	2
	12	13	22.22	22.33	22.27	1	21.23	21.35	21.31	2
	25	0	22.08	22.19	22.13	1	21.08	21.19	21.14	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23780	Mid Ch 23790	High Ch 23800		Low Ch 23780	Mid Ch 23790	High Ch 23800	
			709.0 MHz	710.0 MHz	711.0 MHz		709.0 MHz	710.0 MHz	711.0 MHz	
17 / 10M	1	0	23.27	23.35	23.32	0	22.30	22.40	22.38	1
	1	24	23.13	23.30	23.27	0	22.18	22.34	22.28	1
	1	49	23.06	23.16	23.13	0	22.06	22.16	22.13	1
	25	0	22.25	22.35	22.33	1	21.21	21.32	21.24	2
	25	12	22.30	22.38	22.35	1	21.23	21.36	21.33	2
	25	25	22.34	22.44	22.42	1	21.30	21.44	21.38	2
	50	0	22.25	22.33	22.30	1	21.20	21.29	21.22	2

ERP Power (dBm)

LTE Band 12							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23017	699.7	-13.05	32.719	17.52	56.48	H
	23095	707.5	-13.06	32.736	17.53	56.57	
	23173	715.3	-12.99	32.591	17.45	55.60	
	23017	699.7	-18.01	32.69	12.53	17.91	V
	23095	707.5	-18.12	32.81	12.54	17.95	
	23173	715.3	-18.06	32.74	12.53	17.91	
Channel Bandwidth: 1.4 MHz / 16QAM							
Y	23017	699.7	-13.99	32.719	16.58	45.49	H
	23095	707.5	-14.12	32.736	16.47	44.32	
	23173	715.3	-13.89	32.591	16.55	45.20	
	23017	699.7	-19.06	32.69	11.48	14.06	V
	23095	707.5	-19.12	32.81	11.54	14.26	
	23173	715.3	-19.09	32.74	11.50	14.14	

LTE Band 12							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23025	700.5	-12.96	32.719	17.61	57.66	H
	23095	707.5	-13.09	32.736	17.50	56.18	
	23165	714.5	-12.96	32.591	17.48	55.99	
	23025	700.5	-18.04	32.69	12.50	17.78	V
	23095	707.5	-18.20	32.81	12.46	17.62	
	23165	714.5	-17.96	32.74	12.63	18.32	
Channel Bandwidth: 3 MHz / 16QAM							
Y	23025	700.5	-14.02	32.719	16.55	45.18	H
	23095	707.5	-14.16	32.736	16.43	43.91	
	23165	714.5	-13.89	32.591	16.55	45.20	
	23025	700.5	-19.08	32.69	11.46	14.00	V
	23095	707.5	-19.21	32.81	11.45	13.96	
	23165	714.5	-19.06	32.74	11.53	14.22	

LTE Band 12							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23035	701.5	-13.02	32.719	17.55	56.87	H
	23095	707.5	-13.00	32.736	17.59	57.36	
	23155	713.5	-12.88	32.591	17.56	57.03	
	23035	701.5	-18.01	32.69	12.53	17.91	V
	23095	707.5	-18.03	32.81	12.63	18.32	
	23155	713.5	-18.12	32.74	12.47	17.66	
Channel Bandwidth: 5 MHz / 16QAM							
Y	23035	701.5	-13.97	32.719	16.60	45.70	H
	23095	707.5	-14.06	32.736	16.53	44.94	
	23155	713.5	-13.85	32.591	16.59	45.61	
	23035	701.5	-18.96	32.69	11.58	14.39	V
	23095	707.5	-19.17	32.81	11.49	14.09	
	23155	713.5	-19.08	32.74	11.51	14.16	

LTE Band 12							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23060	704.0	-12.95	32.727	17.63	57.90	H
	23095	707.5	-13.08	32.739	17.51	56.35	
	23130	711.0	-13.03	32.728	17.55	56.86	
	23060	704.0	-18.02	32.75	12.58	18.11	V
	23095	707.5	-18.14	32.81	12.52	17.86	
	23130	711.0	-18.23	32.84	12.46	17.62	
Channel Bandwidth: 10 MHz / 16QAM							
Y	23060	704.0	-14.08	32.727	16.50	44.64	H
	23095	707.5	-14.16	32.739	16.43	43.94	
	23130	711.0	-14.08	32.728	16.50	44.65	
	23060	704.0	-19.05	32.75	11.55	14.29	V
	23095	707.5	-19.16	32.81	11.50	14.13	
	23130	711.0	-19.20	32.84	11.49	14.09	

LTE Band 17							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23755	706.5	-13.05	32.719	17.52	56.48	H
	23790	710.0	-13.06	32.736	17.53	56.57	
	23825	713.5	-12.96	32.591	17.48	55.99	
	23755	706.5	-17.96	32.69	12.58	18.11	V
	23790	710.0	-18.12	32.81	12.54	17.95	
	23825	713.5	-18.00	32.74	12.59	18.16	
Channel Bandwidth: 5 MHz / 16QAM							
Y	23755	706.5	-14.08	32.719	16.49	44.56	H
	23790	710.0	-14.04	32.736	16.55	45.14	
	23825	713.5	-14.11	32.591	16.33	42.96	
	23755	706.5	-19.00	32.69	11.54	14.26	V
	23790	710.0	-19.13	32.81	11.53	14.22	
	23825	713.5	-19.05	32.74	11.54	14.26	

LTE Band 17							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
Y	23780	709.0	-13.06	32.727	17.52	56.45	H
	23790	710.0	-13.18	32.739	17.41	55.07	
	23800	711.0	-13.03	32.728	17.55	56.86	
	23780	709.0	-18.10	32.75	12.50	17.78	V
	23790	710.0	-18.12	32.81	12.54	17.95	
	23800	711.0	-18.16	32.84	12.53	17.91	
Channel Bandwidth: 10 MHz / 16QAM							
Y	23780	709.0	-14.11	32.727	16.47	44.33	H
	23790	710.0	-14.09	32.739	16.50	44.66	
	23800	711.0	-14.03	32.728	16.55	45.16	
	23780	709.0	-19.14	32.75	11.46	14.00	V
	23790	710.0	-19.06	32.81	11.60	14.45	
	23800	711.0	-19.18	32.84	11.51	14.16	

EIRP Power (dBm)

WCDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	1312	1712.4	-20.43	42.49	22.06	160.51	H
	1413	1732.6	-20.31	42.33	22.02	159.11	
	1513	1752.6	-20.08	42.10	22.02	159.22	
	1312	1712.4	-24.93	42.99	18.06	63.97	V
	1413	1732.6	-24.66	42.74	18.08	64.27	
	1513	1752.6	-24.19	42.21	18.02	63.39	

LTE Band 4							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	19957	1710.7	-19.94	42.49	22.55	179.68	H
	20175	1732.5	-19.82	42.33	22.51	178.11	
	20393	1754.3	-19.53	42.10	22.57	180.72	
	19957	1710.7	-24.46	42.99	18.53	71.29	V
	20175	1732.5	-24.26	42.74	18.48	70.47	
	20393	1754.3	-23.69	42.21	18.52	71.12	
Channel Bandwidth: 1.4 MHz / 16QAM							
X	19957	1710.7	-20.92	42.49	21.57	143.38	H
	20175	1732.5	-20.73	42.33	21.60	144.44	
	20393	1754.3	-20.63	42.10	21.47	140.28	
	19957	1710.7	-25.44	42.99	17.55	56.89	V
	20175	1732.5	-25.21	42.74	17.53	56.62	
	20393	1754.3	-24.67	42.21	17.54	56.75	

LTE Band 4							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	19965	1711.5	-19.92	42.49	22.57	180.51	H
	20175	1732.5	-19.74	42.33	22.59	181.43	
	20385	1753.5	-19.63	42.10	22.47	176.60	
	19965	1711.5	-24.52	42.99	18.47	70.31	V
	20175	1732.5	-24.27	42.74	18.47	70.31	
	20385	1753.5	-23.71	42.21	18.50	70.79	
Channel Bandwidth: 3 MHz / 16QAM							
X	19965	1711.5	-20.89	42.49	21.60	144.38	H
	20175	1732.5	-20.73	42.33	21.60	144.44	
	20385	1753.5	-20.58	42.10	21.52	141.91	
	19965	1711.5	-25.46	42.99	17.53	56.62	V
	20175	1732.5	-25.22	42.74	17.52	56.49	
	20385	1753.5	-24.62	42.21	17.59	57.41	

LTE Band 4							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	19975	1712.5	-19.96	42.49	22.52	178.73	H
	20175	1732.5	-19.76	42.33	22.57	180.59	
	20375	1752.5	-19.66	42.10	22.44	175.39	
	19975	1712.5	-24.54	42.99	18.45	69.98	V
	20175	1732.5	-24.21	42.74	18.53	71.29	
	20375	1752.5	-23.67	42.21	18.54	71.45	
Channel Bandwidth: 5 MHz / 16QAM							
X	19975	1712.5	-20.86	42.49	21.63	145.38	H
	20175	1732.5	-20.78	42.33	21.55	142.79	
	20375	1752.5	-20.52	42.10	21.58	143.88	
	19975	1712.5	-25.47	42.99	17.52	56.49	V
	20175	1732.5	-25.23	42.74	17.51	56.36	
	20375	1752.5	-24.67	42.21	17.54	56.75	

LTE Band 4							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20000	1715.0	-19.97	42.49	22.52	178.44	H
	20175	1732.5	-19.73	42.33	22.60	181.84	
	20350	1750.0	-19.56	42.10	22.54	179.47	
	20000	1715.0	-24.44	42.99	18.55	71.61	V
	20175	1732.5	-24.13	42.74	18.61	72.61	
	20350	1750.0	-23.61	42.21	18.60	72.44	
Channel Bandwidth: 10 MHz / 16QAM							
X	20000	1715.0	-20.97	42.49	21.52	141.74	H
	20175	1732.5	-20.83	42.33	21.50	141.16	
	20350	1750.0	-20.55	42.10	21.55	142.89	
	20000	1715.0	-25.42	42.99	17.57	57.15	V
	20175	1732.5	-25.13	42.74	17.61	57.68	
	20350	1750.0	-24.72	42.21	17.49	56.10	

LTE Band 4							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20025	1717.5	-20.01	42.49	22.48	176.81	H
	20175	1732.5	-19.77	42.33	22.56	180.18	
	20325	1747.5	-19.47	42.10	22.63	183.23	
	20025	1717.5	-24.43	42.99	18.56	71.78	V
	20175	1732.5	-24.21	42.74	18.53	71.29	
	20325	1747.5	-23.68	42.21	18.53	71.29	
Channel Bandwidth: 15 MHz / 16QAM							
X	20025	1717.5	-20.86	42.49	21.63	145.38	H
	20175	1732.5	-20.84	42.33	21.49	140.83	
	20325	1747.5	-20.53	42.10	21.57	143.55	
	20025	1717.5	-25.54	42.99	17.45	55.59	V
	20175	1732.5	-25.16	42.74	17.58	57.28	
	20325	1747.5	-24.77	42.21	17.44	55.46	

LTE Band 4							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
X	20050	1720.0	-19.93	42.49	22.56	180.09	H
	20175	1732.5	-19.82	42.33	22.51	178.11	
	20300	1745.0	-19.55	42.10	22.55	179.89	
	20050	1720.0	-24.43	42.99	18.56	71.78	V
	20175	1732.5	-24.27	42.74	18.47	70.31	
	20300	1745.0	-23.60	42.21	18.61	72.61	
Channel Bandwidth: 20 MHz / 16QAM							
X	20050	1720.0	-21.08	42.49	21.41	138.20	H
	20175	1732.5	-20.76	42.33	21.57	143.45	
	20300	1745.0	-20.54	42.10	21.56	143.22	
	20050	1720.0	-25.43	42.99	17.56	57.02	V
	20175	1732.5	-25.28	42.74	17.46	55.72	
	20300	1745.0	-24.61	42.21	17.60	57.54	

4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ± 0.5 °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

Note: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



4.2.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	WCDMA				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1712.400003	0.001	1752.600003	0.002	2.5
3.27	1712.400001	0.001	1752.600002	0.001	2.5
4.43	1712.400001	0.001	1752.600001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	WCDMA				Limit (ppm)
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1712.400004	0.002	1752.600001	0.001	2.5
-20	1712.400001	0.001	1752.600002	0.001	2.5
-10	1712.400001	0.001	1752.600003	0.002	2.5
0	1712.400003	0.002	1752.600002	0.001	2.5
10	1712.400002	0.001	1752.600002	0.001	2.5
20	1712.399999	-0.001	1752.599998	-0.001	2.5
30	1712.399996	-0.002	1752.599998	-0.001	2.5
40	1712.399998	-0.001	1752.599997	-0.002	2.5
50	1712.399997	-0.002	1752.599999	-0.001	2.5
55	1712.399998	-0.001	1752.599998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1710.700003	0.002	1754.300003	0.002	2.5
3.27	1710.700002	0.001	1754.300004	0.002	2.5
4.43	1710.700004	0.002	1754.300001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1710.700004	0.002	1754.300002	0.001	2.5
-20	1710.700002	0.001	1754.300004	0.002	2.5
-10	1710.700003	0.002	1754.300003	0.002	2.5
0	1710.700002	0.001	1754.300004	0.002	2.5
10	1710.700002	0.001	1754.300003	0.002	2.5
20	1710.699997	-0.002	1754.299997	-0.002	2.5
30	1710.699997	-0.002	1754.299996	-0.002	2.5
40	1710.699996	-0.002	1754.299999	-0.001	2.5
50	1710.699998	-0.001	1754.299998	-0.001	2.5
55	1710.699998	-0.001	1754.299998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1711.500002	0.001	1753.500004	0.002	2.5
3.27	1711.500003	0.002	1753.500003	0.002	2.5
4.43	1711.500004	0.002	1753.500003	0.002	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1711.500004	0.002	1753.500002	0.001	2.5
-20	1711.500003	0.002	1753.500004	0.002	2.5
-10	1711.500002	0.001	1753.500001	0.001	2.5
0	1711.500004	0.002	1753.500004	0.002	2.5
10	1711.500002	0.001	1753.500002	0.001	2.5
20	1711.499997	-0.002	1753.499998	-0.001	2.5
30	1711.499999	-0.001	1753.499998	-0.001	2.5
40	1711.499998	-0.001	1753.499999	-0.001	2.5
50	1711.499997	-0.002	1753.499998	-0.001	2.5
55	1711.499997	-0.002	1753.499997	-0.002	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1712.500003	0.002	1752.500002	0.001	2.5
3.27	1712.500003	0.002	1752.500002	0.001	2.5
4.43	1712.500003	0.002	1752.500003	0.002	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1712.500002	0.001	1752.500003	0.002	2.5
-20	1712.500003	0.002	1752.500003	0.002	2.5
-10	1712.500004	0.002	1752.500001	0.001	2.5
0	1712.500002	0.001	1752.500001	0.001	2.5
10	1712.500001	0.001	1752.500002	0.001	2.5
20	1712.499996	-0.002	1752.499998	-0.001	2.5
30	1712.499997	-0.002	1752.499996	-0.002	2.5
40	1712.499998	-0.001	1752.499999	-0.001	2.5
50	1712.499999	-0.001	1752.499997	-0.002	2.5
55	1712.499998	-0.001	1752.499998	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1715.000002	0.001	1750.000002	0.001	2.5
3.27	1715.000004	0.002	1750.000002	0.001	2.5
4.43	1715.000002	0.001	1750.000003	0.002	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1715.000003	0.002	1750.000003	0.001	2.5
-20	1715.000003	0.002	1750.000001	0.001	2.5
-10	1715.000003	0.002	1750.000003	0.001	2.5
0	1715.000004	0.002	1750.000003	0.002	2.5
10	1715.000004	0.002	1750.000003	0.002	2.5
20	1714.999998	-0.001	1749.999998	-0.001	2.5
30	1714.999999	-0.001	1749.999997	-0.002	2.5
40	1714.999999	-0.001	1749.999999	-0.001	2.5
50	1714.999996	-0.002	1749.999998	-0.001	2.5
55	1714.999997	-0.002	1749.999996	-0.002	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 15 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1717.500003	0.002	1747.500002	0.001	2.5
3.27	1717.500001	0.001	1747.500002	0.001	2.5
4.43	1717.500003	0.002	1747.500002	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 15 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1717.500003	0.002	1747.500002	0.001	2.5
-20	1717.500003	0.002	1747.500002	0.001	2.5
-10	1717.500003	0.002	1747.500003	0.002	2.5
0	1717.500004	0.002	1747.500003	0.002	2.5
10	1717.500002	0.001	1747.500003	0.002	2.5
20	1717.499996	-0.002	1747.499996	-0.002	2.5
30	1717.499997	-0.002	1747.499999	-0.001	2.5
40	1717.499998	-0.001	1747.499996	-0.002	2.5
50	1717.499998	-0.001	1747.499998	-0.001	2.5
55	1717.499998	-0.001	1747.499996	-0.002	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 20 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	1720.000001	0.001	1745.000004	0.002	2.5
3.27	1720.000001	0.001	1745.000004	0.002	2.5
4.43	1720.000003	0.001	1745.000002	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 4				Limit (ppm)
	Channel Bandwidth: 20 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	1720.000004	0.002	1745.000001	0.001	2.5
-20	1720.000002	0.001	1745.000003	0.002	2.5
-10	1720.000001	0.001	1745.000002	0.001	2.5
0	1720.000003	0.002	1745.000003	0.002	2.5
10	1720.000002	0.001	1745.000003	0.002	2.5
20	1719.999998	-0.001	1744.999996	-0.002	2.5
30	1719.999998	-0.001	1744.999998	-0.001	2.5
40	1719.999998	-0.001	1744.999997	-0.001	2.5
50	1719.999998	-0.001	1744.999997	-0.001	2.5
55	1719.999996	-0.002	1744.999999	-0.001	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 12				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	699.700004	0.005	715.300003	0.004	2.5
3.27	699.700003	0.004	715.300002	0.002	2.5
4.43	699.700002	0.002	715.300001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 12				Limit (ppm)
	Channel Bandwidth: 1.4 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	699.700003	0.005	715.300003	0.004	2.5
-20	699.700002	0.003	715.300002	0.002	2.5
-10	699.700003	0.004	715.300003	0.005	2.5
0	699.700003	0.005	715.300002	0.003	2.5
10	699.700004	0.005	715.300001	0.002	2.5
20	699.699999	-0.002	715.299998	-0.003	2.5
30	699.699997	-0.004	715.299999	-0.002	2.5
40	699.699997	-0.004	715.299999	-0.002	2.5
50	699.699998	-0.003	715.299998	-0.003	2.5
55	699.699998	-0.003	715.299999	-0.002	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 12				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	700.500003	0.004	714.500002	0.002	2.5
3.27	700.500003	0.005	714.500004	0.005	2.5
4.43	700.500004	0.005	714.500001	0.001	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 12				Limit (ppm)
	Channel Bandwidth: 3 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	700.500003	0.005	714.500002	0.003	2.5
-20	700.500002	0.003	714.500003	0.003	2.5
-10	700.500002	0.003	714.500004	0.005	2.5
0	700.500003	0.004	714.500001	0.002	2.5
10	700.500004	0.005	714.500003	0.004	2.5
20	700.499998	-0.002	714.499998	-0.003	2.5
30	700.499999	-0.002	714.499997	-0.005	2.5
40	700.499998	-0.004	714.499996	-0.005	2.5
50	700.499997	-0.005	714.499999	-0.002	2.5
55	700.499998	-0.003	714.499996	-0.006	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 12				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	701.500003	0.004	713.500001	0.002	2.5
3.27	701.500004	0.005	713.500002	0.002	2.5
4.43	701.500003	0.004	713.500004	0.005	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 12				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	701.500003	0.005	713.500001	0.002	2.5
-20	701.500002	0.003	713.500004	0.005	2.5
-10	701.500004	0.005	713.500002	0.003	2.5
0	701.500002	0.002	713.500004	0.005	2.5
10	701.500001	0.002	713.500004	0.005	2.5
20	701.499996	-0.005	713.499999	-0.002	2.5
30	701.499997	-0.005	713.499997	-0.004	2.5
40	701.499997	-0.004	713.499999	-0.002	2.5
50	701.499996	-0.005	713.499999	-0.001	2.5
55	701.499998	-0.002	713.499999	-0.002	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 12				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	704.000004	0.006	711.000002	0.003	2.5
3.27	704.000002	0.003	711.000002	0.002	2.5
4.43	704.000004	0.006	711.000003	0.004	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 12				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	704.000004	0.006	711.000002	0.003	2.5
-20	704.000004	0.005	711.000003	0.004	2.5
-10	704.000003	0.004	711.000003	0.004	2.5
0	704.000003	0.005	711.000001	0.002	2.5
10	704.000002	0.003	711.000003	0.004	2.5
20	703.999999	-0.002	710.999999	-0.002	2.5
30	703.999999	-0.002	710.999996	-0.005	2.5
40	703.999996	-0.006	710.999999	-0.002	2.5
50	703.999997	-0.005	710.999999	-0.002	2.5
55	703.999998	-0.004	710.999997	-0.004	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 17				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	706.500002	0.003	713.500002	0.003	2.5
3.27	706.500002	0.003	713.500004	0.005	2.5
4.43	706.500003	0.004	713.500004	0.005	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 17				Limit (ppm)
	Channel Bandwidth: 5 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	706.500003	0.004	713.500001	0.001	2.5
-20	706.500001	0.001	713.500003	0.004	2.5
-10	706.500002	0.002	713.500004	0.005	2.5
0	706.500002	0.003	713.500002	0.003	2.5
10	706.500002	0.003	713.500002	0.003	2.5
20	706.499997	-0.005	713.499998	-0.003	2.5
30	706.499996	-0.005	713.499999	-0.002	2.5
40	706.499998	-0.002	713.499999	-0.002	2.5
50	706.499998	-0.003	713.499998	-0.003	2.5
55	706.499997	-0.005	713.499998	-0.003	2.5

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 17				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
3.85	709.000003	0.004	711.000003	0.004	2.5
3.27	709.000004	0.006	711.000003	0.004	2.5
4.43	709.000003	0.004	711.000001	0.002	2.5

Note: The applicant defined the normal working voltage of the battery is from 3.27 Vdc to 4.43 Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 17				Limit (ppm)
	Channel Bandwidth: 10 MHz				
	Low Channel		High Channel		
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)	
-30	709.000001	0.001	711.000002	0.002	2.5
-20	709.000002	0.003	711.000003	0.004	2.5
-10	709.000003	0.004	711.000002	0.002	2.5
0	709.000003	0.005	711.000003	0.005	2.5
10	709.000003	0.004	711.000002	0.003	2.5
20	708.999997	-0.004	710.999997	-0.005	2.5
30	708.999997	-0.004	710.999997	-0.004	2.5
40	708.999997	-0.005	710.999998	-0.003	2.5
50	708.999998	-0.002	710.999999	-0.002	2.5
55	708.999998	-0.003	710.999998	-0.003	2.5

4.3 Occupied Bandwidth Measurement


4.3.1 Limits of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

4.3.2 Test Procedure


- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.3 Test Setup



4.3.4 Test Result


WCDMA		
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)
1312	1712.4	4.1428
1413	1732.6	4.1455
1513	1752.6	4.1371



LTE Band 4

Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	1.0882	1.0882	19965	1711.5	2.6993	2.6979
20175	1732.5	1.0873	1.0905	20175	1732.5	2.7011	2.6973
20393	1754.3	1.0873	1.0879	20385	1753.5	2.6997	2.6969


Spectrum Plot of Worst Value



LTE Band 4

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.4882	4.4862	20000	1715.0	8.9648	8.9689
20175	1732.5	4.4876	4.4901	20175	1732.5	8.9592	8.9612
20375	1752.5	4.4904	4.4918	20350	1750.0	8.9717	8.9726

Spectrum Plot of Worst Value



LTE Band 4

Channel Bandwidth: 15 MHz



Channel Bandwidth: 20 MHz

Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	13.473	13.466	20050	1720.0	17.962	17.976
20175	1732.5	13.453	13.443	20175	1732.5	17.913	17.932
20325	1747.5	13.483	13.469	20300	1745.0	17.943	17.960

Spectrum Plot of Worst Value



15 MHz / QPSK

15 MHz / 16QAM



20 MHz / QPSK


20 MHz / 16QAM



LTE Band 12

Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	1.0863	1.0879	23025	700.5	2.6995	2.6947
23095	707.5	1.0870	1.0890	23095	707.5	2.7008	2.6978
23173	715.3	1.0873	1.0873	23165	714.5	2.7039	2.6978


Spectrum Plot of Worst Value



LTE Band 12

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	4.4888	4.4875	23060	704.0	8.9643	8.9690
23095	707.5	4.4958	4.4957	23095	707.5	8.9880	8.9939
23155	713.5	4.4891	4.4908	23130	711.0	8.9511	8.9559


Spectrum Plot of Worst Value



LTE Band 17

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23755	706.5	4.4954	4.4996	23780	709.0	8.9758	8.9762
23790	710.0	4.4944	4.4956	23790	710.0	8.9631	8.9674
23825	713.5	4.4892	4.4923	23800	711.0	8.9535	8.9525

Spectrum Plot of Worst Value



4.4 Band Edge Measurement


4.4.1 Limits of Band Edge Measurement

For operations in the 698-716 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.

However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

For operations in the 1710–1755 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.




4.4.2 Test Setup





4.4.3 Test Procedures

- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 5 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (WCDMA).
- c. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 13 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 1.4 MHz).
- d. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 30 kHz and VB of the spectrum is 100 kHz (LTE Bandwidth 3 MHz).
- e. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (LTE Bandwidth 5 MHz/10 MHz).
- f. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 150 kHz and VB of the spectrum is 470 kHz (LTE Bandwidth 15 MHz).
- g. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 180 kHz and VB of the spectrum is 560 kHz (LTE Bandwidth 20 MHz).
- h. Record the max trace plot into the test report.



4.4.4 Test Results




LTE Band 4
Channel Bandwidth: 3 MHz





LTE Band 4
Channel Bandwidth: 5 MHz









LTE Band 4
Channel Bandwidth: 15 MHz



LTE Band 4
Channel Bandwidth: 20 MHz





LTE Band 12
Channel Bandwidth: 1.4 MHz





LTE Band 12

Channel Bandwidth: 3 MHz





LTE Band 12

Channel Bandwidth: 5 MHz





LTE Band 12
Channel Bandwidth: 10 MHz





LTE Band 17

Channel Bandwidth: 5 MHz



LTE Band 17

Channel Bandwidth: 10 MHz




4.5 Peak to Average Ratio

4.5.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.5.2 Test Setup




4.5.3 Test Procedures

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

4.5.4 Test Results


WCDMA		
Channel	Frequency (MHz)	Peak to Average Ratio (dB)
1312	1712.4	3.13
1413	1732.6	2.97
1513	1752.6	3.11



LTE Band 4

Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	3.43	4.17	19965	1711.5	3.27	4.04
20175	1732.5	3.52	4.26	20175	1732.5	3.36	4.14
20393	1754.3	3.54	4.29	20385	1753.5	3.37	4.12

Spectrum Plot of Worst Value



LTE Band 4

Channel Bandwidth: 5 MHz



Channel Bandwidth: 10 MHz

Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	3.13	3.91	20000	1715.0	3.06	3.81
20175	1732.5	3.36	4.13	20175	1732.5	3.46	4.17
20375	1752.5	3.33	4.10	20350	1750.0	3.16	3.91

Spectrum Plot of Worst Value



5 MHz / QPSK

5 MHz / 16QAM



10 MHz / QPSK


10 MHz / 16QAM



LTE Band 4

Channel Bandwidth: 15 MHz				Channel Bandwidth: 20 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	2.95	3.73	20050	1720.0	2.92	3.62
20175	1732.5	3.39	3.95	20175	1732.5	3.18	3.97
20325	1747.5	3.00	3.73	20300	1745.0	3.03	3.68

Spectrum Plot of Worst Value




LTE Band 12


Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23017	699.7	4.95	5.76	23025	700.5	4.86	5.70
23095	707.5	5.08	5.90	23095	707.5	4.85	5.67
23173	715.3	4.09	4.92	23165	714.5	4.27	5.08

Spectrum Plot of Worst Value


1.4 MHz / QPSK




1.4 MHz / 16QAM




3 MHz / QPSK



3 MHz / 16QAM




LTE Band 12							
Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23035	701.5	4.84	5.67	23060	704.0	4.78	5.60
23095	707.5	4.67	5.52	23095	707.5	4.44	5.28
23155	713.5	4.81	5.63	23130	711.0	4.89	5.69



LTE Band 17

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23755	706.5	4.58	5.34	23780	709.0	4.57	5.38
23790	710.0	5.12	5.92	23790	710.0	4.73	5.55
23825	713.5	4.78	5.55	23800	711.0	4.92	5.73

Spectrum Plot of Worst Value




4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -13 dBm.


4.6.2 Test Setup



4.6.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30 MHz to 8 GHz for LTE Band 12 and LTE Band 17, and from 30 MHz to 18 GHz for WCDMA and LTE Band 4. 10 dB attenuation pad is connected with spectrum. RBW=1 MHz and VBW=3 MHz are used for conducted emission measurement.



4.6.4 Test Results




LTE Band 4
Channel Bandwidth: 1.4 MHz

Channel 1957

Channel 1075




Channel 2093




LTE Band 4

Channel Bandwidth: 3 MHz


Channel 19965



Channel 10175




Channel 20385




LTE Band 4
Channel Bandwidth: 5 MHz


Channel 19975





Channel 10175





Channel 20375



LTE Band 4
Channel Bandwidth: 10 MHz



LTE Band 4
Channel Bandwidth: 15 MHz





LTE Band 4


Channel Bandwidth: 20 MHz

Channel 20050

Channel 17175




Channel 20300




LTE Band 12

Channel Bandwidth: 1.4 MHz


Channel 23017



Channel 23095




Channel 23173




LTE Band 12
Channel Bandwidth: 3 MHz


Channel 23025



Channel 23095




Channel 23165




LTE Band 12
Channel Bandwidth: 5 MHz


Channel 23035



Channel 23095



Channel 23155





LTE Band 12


Channel Bandwidth: 10 MHz

Channel 23060

Channel 23095





Channel 23130




LTE Band 17
Channel Bandwidth: 5 MHz

Channel 23755




Channel 23790



Channel 23825



LTE Band 17
Channel Bandwidth: 10 MHz



4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

- a. The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -13 dBm.

4.7.2 Test Procedure


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- c. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$.

Note: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.7.3 Deviation from Test Standard

No deviation.

4.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results

WCDMA:
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2017-06-09



Site : 966 chamber 1
Condition: PART 27(B4/B17) Horizontal
Remark : Band IV_Link_CH1312
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 3424.80	-50.41	-64.78	-13.00	-37.41	14.37	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Vertical
 Remark : Band IV_Link_CH1312
 Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 3424.80	-51.07	-65.44	-13.00	-38.07	14.37	Peak


Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Horizontal
 Remark : Band IV_Link_CH1413
 Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	133.14	-65.50	-57.84	-13.00	-52.50	-7.66	Peak
2	242.76	-68.58	-62.97	-13.00	-55.58	-5.61	Peak
3	261.66	-71.61	-66.00	-13.00	-58.61	-5.61	Peak
4	412.00	-73.39	-70.37	-13.00	-60.39	-3.02	Peak
5	566.00	-71.86	-70.88	-13.00	-58.86	-0.98	Peak
6	659.80	-70.35	-70.17	-13.00	-57.35	-0.18	Peak
7 pp	3465.20	-50.26	-64.60	-13.00	-37.26	14.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Vertical
 Remark : Band IV_Link_CH1413
 Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	60.51	-61.71	-47.64	-13.00	-48.71	-14.07	Peak
2	120.99	-67.31	-59.12	-13.00	-54.31	-8.19	Peak
3	167.16	-70.84	-63.85	-13.00	-57.84	-6.99	Peak
4	402.20	-73.06	-70.26	-13.00	-60.06	-2.80	Peak
5	565.30	-70.78	-69.76	-13.00	-57.78	-1.02	Peak
6	672.40	-70.26	-70.02	-13.00	-57.26	-0.24	Peak
7 pp	3465.20	-51.15	-65.49	-13.00	-38.15	14.34	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Horizontal
 Remark : Band IV_Link_CH1513
 Tested by: Karl Lee

Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3505.20	-50.71	-64.99	-13.00	-37.71	14.28	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Vertical
 Remark : Band IV_Link_CH1513
 Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 3505.20	-52.16	-66.44	-13.00	-39.16	14.28	Peak

LTE Band 4
 Channel Bandwidth: 20 MHz / QPSK
 Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Horizontal
 Remark : LTE_Band 4_Link_CH20050
 Tested by: Charles Hsiao

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3440.00	-50.79	-65.14	-13.00	-37.79	14.35	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Vertical
 Remark : LTE_Band 4_Link_CH20050
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	3440.00	-50.53	-64.88	-13.00	-37.53	14.35	Peak
2 pp	5160.00	-44.45	-64.37	-13.00	-31.45	19.92	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Horizontal
 Remark : LTE_Band 4_Link_CH20175
 Tested by: Charles Hsiao

Freq	Level	Read Level	Limit	Over	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3465.00	-49.77	-64.11	-13.00	-36.77	14.34	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Vertical
 Remark : LTE_Band 4_Link_CH20175
 Tested by: Charles Hsiao

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3465.00	-50.62	-64.96	-13.00	-37.62	14.34	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Horizontal
 Remark : LTE_Band 4_Link_CH20300
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	98.31	-67.14	-56.91	-13.00	-54.14	-10.23	Peak
2	172.56	-61.28	-54.88	-13.00	-48.28	-6.40	Peak
3	204.69	-65.87	-59.75	-13.00	-52.87	-6.12	Peak
4	484.80	-69.12	-64.28	-13.00	-56.12	-4.84	Peak
5	624.10	-69.88	-70.04	-13.00	-56.88	0.16	Peak
6	951.70	-65.51	-70.62	-13.00	-52.51	5.11	Peak
7	3490.00	-51.17	-65.48	-13.00	-38.17	14.31	Peak
8 pp	5235.00	-45.21	-65.37	-13.00	-32.21	20.16	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Vertical
 Remark : LTE_Band 4_Link_CH20300
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	52.95	-59.60	-45.54	-13.00	-46.60	-14.06	Peak
2	156.90	-67.37	-59.62	-13.00	-54.37	-7.75	Peak
3	278.40	-68.67	-62.91	-13.00	-55.67	-5.76	Peak
4	504.40	-66.48	-61.48	-13.00	-53.48	-5.00	Peak
5	754.30	-71.26	-70.27	-13.00	-58.26	-0.99	Peak
6	855.80	-68.76	-70.37	-13.00	-55.76	1.61	Peak
7	3490.00	-50.63	-64.94	-13.00	-37.63	14.31	Peak
8 pp	5235.00	-41.50	-61.66	-13.00	-28.50	20.16	Peak

LTE Band 12
 Channel Bandwidth: 10 MHz / QPSK
 Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2017-06-08



Site : 966 chamber 1
 Condition: PART 22/24/27 Horizontal
 Remark : LTE_Band 12_Link_CH23060
 Tested by: Charles Hsiao

		Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor Remark
	MHz	dBm	dBm	dBm	dB	dB
1	1408.00	-52.41	-58.77	-13.00	-39.41	6.36 Peak
2 pp	2112.00	-41.40	-52.51	-13.00	-28.40	11.11 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2017-06-08



Site : 966 chamber 1
 Condition: PART 22/24/27 Vertical
 Remark : LTE_Band 12_Link_CH23060
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1408.00	-53.95	-60.31	-13.00	-40.95	6.36	Peak
2 pp	2112.00	-44.47	-55.58	-13.00	-31.47	11.11	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2017-06-08



Site : 966 chamber 1
 Condition: PART 22/24/27 Horizontal
 Remark : LTE_Band 12_Link_CH23095
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	56.73	-71.59	-57.53	-13.00	-58.59	-14.06	Peak
2	130.98	-62.24	-54.59	-13.00	-49.24	-7.65	Peak
3	172.02	-61.26	-54.76	-13.00	-48.26	-6.50	Peak
4	398.00	-73.15	-70.31	-13.00	-60.15	-2.84	Peak
5	512.10	-63.33	-58.90	-13.00	-50.33	-4.43	Peak
6	563.20	-70.63	-69.53	-13.00	-57.63	-1.10	Peak
7	1415.00	-47.26	-53.62	-13.00	-34.26	6.36	Peak
8 pp	2122.50	-39.46	-50.57	-13.00	-26.46	11.11	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2017-06-08



Site : 966 chamber 1
 Condition: PART 22/24/27 Vertical
 Remark : LTE_Band 12_Link_CH23095
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	62.94	-63.76	-50.11	-13.00	-50.76	-13.65	Peak
2	130.71	-69.01	-61.36	-13.00	-56.01	-7.65	Peak
3	227.10	-73.25	-67.43	-13.00	-60.25	-5.82	Peak
4	361.60	-74.68	-69.92	-13.00	-61.68	-4.76	Peak
5	524.00	-71.35	-67.77	-13.00	-58.35	-3.58	Peak
6	563.90	-71.42	-70.32	-13.00	-58.42	-1.10	Peak
7	1415.00	-46.95	-53.31	-13.00	-33.95	6.36	Peak
8 pp	2122.50	-39.16	-50.27	-13.00	-26.16	11.11	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2017-06-08



Site : 966 chamber 1
 Condition: PART 22/24/27 Horizontal
 Remark : LTE_Band 12_Link_CH23130
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit	Over	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1422.00	-57.38	-63.74	-13.00	-44.38	6.36	Peak
2	2133.00	-47.66	-58.94	-13.00	-34.66	11.28	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2017-06-08



Site : 966 chamber 1
 Condition: PART 22/24/27 Vertical
 Remark : LTE_Band 12_Link_CH23130
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1422.00	-55.95	-62.31	-13.00	-42.95	6.36	Peak
2 pp	2133.00	-44.77	-56.05	-13.00	-31.77	11.28	Peak

LTE Band 17
 Channel Bandwidth: 10 MHz / QPSK
 Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Horizontal
 Remark : LTE_Band 17_Link_CH23780
 Tested by: Charles Hsiao

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1	1418.00	-49.06	-55.42	-13.00	-36.06	6.36 Peak
2 pp	2127.00	-47.88	-59.16	-13.00	-34.88	11.28 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Vertical
 Remark : LTE_Band 17_Link_CH23780
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	1418.00	-48.31	-54.67	-13.00	-35.31	6.36	Peak
2	2127.00	-48.89	-60.17	-13.00	-35.89	11.28	Peak

Middle Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Horizontal
 Remark : LTE_Band 17_Link_CH23790
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	94.26	-72.23	-61.78	-13.00	-59.23	-10.45	Peak
2	155.01	-63.46	-55.65	-13.00	-50.46	-7.81	Peak
3	186.33	-61.90	-56.23	-13.00	-48.90	-5.67	Peak
4	426.70	-72.77	-69.43	-13.00	-59.77	-3.34	Peak
5	650.00	-69.53	-69.40	-13.00	-56.53	-0.13	Peak
6	964.30	-64.29	-69.44	-13.00	-51.29	5.15	Peak
7	1420.00	-50.57	-56.93	-13.00	-37.57	6.36	Peak
8 pp	2130.00	-47.95	-59.23	-13.00	-34.95	11.28	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Vertical
 Remark : LTE_Band 17_Link_CH23790
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	57.00	-59.52	-45.46	-13.00	-46.52	-14.06	Peak
2	118.29	-67.63	-59.25	-13.00	-54.63	-8.38	Peak
3	165.27	-68.73	-61.54	-13.00	-55.73	-7.19	Peak
4	382.60	-71.89	-68.27	-13.00	-58.89	-3.62	Peak
5	495.30	-69.15	-64.01	-13.00	-56.15	-5.14	Peak
6	946.10	-62.68	-67.61	-13.00	-49.68	4.93	Peak
7	1420.00	-48.06	-54.42	-13.00	-35.06	6.36	Peak
8 pp	2130.00	-46.15	-57.43	-13.00	-33.15	11.28	Peak

High Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Horizontal
 Remark : LTE_Band 17_Link_CH23800
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit	Over	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1422.00	-53.91	-60.27	-13.00	-40.91	6.36	Peak
2	pp 2133.00	-52.37	-63.65	-13.00	-39.37	11.28	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6

Date: 2017-06-09



Site : 966 chamber 1
 Condition: PART 27(B4/B17) Vertical
 Remark : LTE_Band 17_Link_CH23800
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	1422.00	-52.17	-58.53	-13.00	-39.17	6.36	Peak
2 pp	2133.00	-49.81	-61.09	-13.00	-36.81	11.28	Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---