



KTL Ottawa

Safety - EMI - Telecom - ISO Guide 25

ENGINEERING TEST REPORT

ON:

4 D SECURITY

"OF-3000 REMOTE TRANSMITTER"

FCC ID: MVJTX4DU01

IN ACCORDANCE WITH:

FCC PART 15, SUBPART C

**FOR LOW POWER TRANSMITTERS OPERATING PERIODICALLY
IN THE BAND 40.66 - 40.77 MHz AND ABOVE 70 MHz**

PROJECT NO.: 8R00716

TESTED FOR:

4 D SECURITY

2241 DE LA METROPOLE
LONGEUILLE, QUEBEC

TESTED BY:

KTL OTTAWA INC.
3325 RIVER ROAD, R.R. 5
OTTAWA, ONTARIO K1V 1H2



NVLAP LAB CODE: 100351-0

JULY 1998

This document contains 32 pages including this one.

KTL Ottawa Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. KTL Ottawa Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

This report applies only to the items tested.

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Table of Contents

Section 1. Summary of Test Results

- General
- Summary of Test Data

Section 2. Equipment Under Test

- General Equipment Information
- Description of E.U.T.
- Modifications Incorporated in E.U.T.
- Theory of Operation
- Exercise Program

Section 3. Equipment Configuration

- Equipment Configuration List
- Inter-Connection Cables
- Configuration of E.U.T.

Section 4. Transmission Requirements

- Test Conditions
- Test Results
- Test Data
- Rationale for Compliance
- Graphs

Section 5. Radiated Emissions

- Test Conditions
- Test Results
- Test Data - Radiated Emissions
- Radiated Photographs
- Pre-Scan Data

Section 6. Occupied Bandwidth

- Test Conditions
- Test Results
- Test Data
- Graphs

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Table of Contents, continued

Section 7. Frequency Tolerance

Test Conditions
Test Results
Test Data

Section 8. Periodic Alternate Field Strength Requirements

Test Conditions
Test Results
Test Data

Section 9. Powerline Conducted Emissions

Test Conditions
Test Results
Test Data

Section 10. Block Diagrams

Conducted Emissions
Radiated Prescan
Outdoor Test Site for Radiated Emissions
Occupied Bandwidth

Section 11. Test Equipment List

Annex A - Restricted Bands

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Section 1. Summary of Test Results

Manufacturer: 4 D Security

Model No.: OF-3000

Serial No.: 5

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, Subpart C, Paragraph 15.231. All tests were conducted using measurement procedure ANSI C63.4-1992. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC.

Abstract:

Name of Test	Paragraph Number	Results
Transmission Requirements	15.231(a)	Complies
Radiated Emissions	15.231(b)	Complies
Occupied Bandwidth	15.231(c)	Complies
Frequency Tolerance	15.231(d)	N/A
Periodic Alternate Field Strength Requirements	15.231(e)	N/A
Powerline Conducted Emissions	15.207	N/A

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE. None



NVLAP LAB CODE: 100351-0

TESTED BY: _____ DATE: _____
Tom Tidwell, Senior Technologist

APPROVED BY: _____ DATE: _____
W. Waterhouse, RF Engineering Lab Manager

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Section 2. Equipment Under Test (E.U.T.)**General Equipment Information****Model Number:** OF-3000**Serial Number** 5☐

Production Unit

☒

Pre-Production Unit

Frequency Range: 304 MHz (Fixed)**Operating Frequency(ies) of Sample:** 304 MHz**Type of Emission:** Amplitude Shift Key**Emission Designator:** 40K0L1D**Supply Power Requirement:** 12 Vdc Battery**Duty Cycle Calculation:**

In 100 msec there are:	3 Leading Pulses	= 3 x 3 msec	= 9.0 msec
	21 Shore Pulses	= 1 x 0.5 msec	= 10.5 msec
	17 long Pulses	= 17 x 1 msec	= 36.5 msec
Total RF on time in 100 msec			= 36.5 msec

$$\text{Duty Cycle (dB)} = 20 \text{ Log } \left(\frac{100}{36.5} \right)$$

$$\text{Duty Cycle} = -8.7 \text{ dB}$$

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Description of E.U.T.

The E.U.T. is a remote control car starter / alarm transmitter. The transmitter can be sold as either a two or three button transmitter. The PCB for both versions is identical. The only difference is the plastics.

Modifications Incorporated in E.U.T.

The EUT has not been modified from what is described by the brand name and unique type identification stated above.

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Theory of Operation

The E.U.T. is an amplitude shift keyed (ASK) key-chain FOB transmitter that operates at 304 MHz.

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Justification

The E.U.T. was configured for testing as per typical installation.

The following combinations were investigated to establish worst case configuration:

- (1) Vertical orientation of test sample.
- (2) Horizontal orientation of test sample.
- (3) Test sample oriented on edge.

Exercise Program

The E.U.T. exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to typical use.

Exercise mode:

- (1) The E.U.T. transmitting continuously.

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Section 3. Equipment Configuration

Equipment Configuration List:


Item	Description	Model No.	Serial.	Rev.
(A)	Key-Chain Transmitter	OF-3000	5	

Inter-connection Cables: Not Applicable


EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Configuration of the Equipment Under Test (E.U.T)


Configuration #1



Configuration #2



Configuration #3



EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Section 4. Transmission Requirements

NAME OF TEST: Transmission Requirements	PARA. NO.: 15.231(a)
TESTED BY: Tom Tidwell	DATE: July 23, 1998

Test Conditions: Test Voltage: 12 Vdc
 Temperature: 25 °C
 Humidity: 51 %

Minimum Standard: 15.231(a) Continuous transmissions such as voice, video
 or data transmissions are not permitted.

15.231(a)(1) A manually operated transmitter shall employ
a switch that will automatically deactivate the transmitter
within not more than 5 seconds after being released.

15.231(a)(2) A transmitter activated automatically shall
cease transmission within 5 seconds of activation.

15.231(a)(3) Periodic transmissions at regular pre-
determined intervals are not permitted. However polling
or supervisory transmissions to determine system integrity
of transmitters used in security or safety applications are
allowed if the periodic rate of transmission does not exceed
one transmission of not more than one second duration per
hour for each transmitter.

15.231(a)(4) Intentional radiators which are employed for
radio control purposes during emergencies involving fire,
security, and safety of life, when activated to signal an
alarm, may operate during the pendency of the alarm.

Test Results: Complies.

Test Data: Compliance was determined by verification of technical
specifications and a functional test on the equipment.

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Rationale for Compliance with Transmission Requirements


15.231(a)(1) : Transmitter deactivates immediately upon release of button.

15.231(a)(2) : Not Applicable


15.231(a)(3) : There are no periodic transmissions at regular intervals.

15.231(a)(4) : Not Applicable


EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01




EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01



EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01



EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01



EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01**Section 5. Radiated Emissions**

NAME OF TEST: Radiated Emissions	PARA. NO.: 15.231(b)
TESTED BY: Tom Tidwell	DATE: July 23, 1998

Test Conditions:

Test Voltage:	12 Vdc
Temperature:	25 °C
Humidity:	51 %

Minimum Standard:**Permissible Field Strength Limits (Momentarily Operated Devices)**

Fundamental Frequency (MHz)	Field Strength of Fundamental Microvolts/Meter at 3 meters; (watts)	Field Strength of Unwanted Emissions Microvolts/Meter at 3 meters; (watts)
40.66 - 40.70	2,250	225
70-130	1, 250	125
130-174	1,250 to 3,750*	125 to 375
174-260 (note 1)	3,750	375
260-470 (note 1)	3,750 to 12,500*	375 to 1,250
Above 470	12,500	1,250

Notes:

# Use quasi-peak or averaging meter.	For 130 - 174 MHz: FS (microvolts/m) = (56.82 x F) - 6136
* Linear interpolation with frequency F in MHz	For 260 - 470 MHz: FS (microvolts/m) = (41.67 x F) - 7083

Any emissions that fall within the restricted bands of 15.205 shall not exceed the following limits:

Frequency (MHz)	Field Strength (µV/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

Test Results: Complies. The worst-case emission level is 71.4 dBµV/m @ 3m at 304.22 MHz. This is 3.6 dB below the specification limit.

Test Data: See attached table.

Above 1 GHz a spectrum analyzer and low noise amplifier are used to measure emission levels. The spectrum analyzer resolution bandwidth was set to 1 MHz and video bandwidth was 3 MHz.

In the case of handheld equipment, the E.U.T. is rotated in three planes to obtain worst-case results.

Test Data - Radiated Emissions

Page 18 of 30


EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Radiated Photographs (Worst Case Configuration)

Configuration 1




Configuration 2



EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Radiated Photographs (Worst Case Configuration)

Configuration 3



EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Section 6. Occupied Bandwidth

NAME OF TEST: Occupied Bandwidth	PARA. NO.: 15.231(c)
TESTED BY: Tom Tidwell	DATE: July 23, 1998

Test Conditions: Test Voltage: 12 Vdc
Temperature: 25 °C
Humidity: 51 %

Minimum Standard: 15.231(c) The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.


Test Results: Complies. See attached graph.

Test Data: See attached graph.

Allowable BW = 304 MHz x 0.25% = 0.76 MHz

Measured BW = 0.042 MHz

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01



EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Section 7. Frequency Tolerance Devices in the Frequency Band 40.66 - 40.77 MHz

NAME OF TEST: Frequency Tolerance	PARA. NO.: 15.231(d)
TESTED BY:	DATE:

Test Conditions:

Test Voltage: _____ VAC
Temperature: _____ °C
Humidity: _____ %

Minimum Standard:

15.231(d) For devices operating within the frequency band 40.66 - 40.70 MHz, the bandwidth of the emission shall be confined within the band edges and the frequency tolerance of the carrier shall be $\pm 0.01\%$. This frequency tolerance shall be maintained for a temperature variation of -30 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary power supply voltage from 85% to 115% of the rated supply voltage at a temperature of 25 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Results:

Complies/Does Not Comply. See attached graph and data.

Test Data:

See attached graph.

EQUIPMENT: Remote Transmitter
*FCC ID: MVJTX4DU01***Section 8. Periodic Alternate Field Strength Requirements**

NAME OF TEST: Periodic Alternate Field Strength Requirements PARA. NO.: 15.231(d)

TESTED BY:

DATE:

Test Conditions:

Test Voltage: _____ VAC

Temperature: _____ °C

Humidity: _____ %

Minimum Standard:

15.231(e) Intentional radiators may operate at a periodic rate exceeding that specified in paragraph (a) of this section and may be employed for any type of operation, including operation prohibited in paragraph (a) of this section, provided the intentional radiator complies with the provisions of paragraphs (b) through (d) of this section, except the field strength table in paragraph (b) of this section is replaced by the following.

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.6 - 40.70	1,000	100
70 - 130	500	50
130 - 174	500 to 1,500	50 to 150
174 - 260	1,500	150
260-470	1,500 to 5,000	150 to 500
Above 470	5,000	500

In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

Test Results:

Complies/Does Not Comply.

Test Data:

See attached table.

EQUIPMENT: Remote Transmitter
*FCC ID: MVJTX4DU01***Section 9. Powerline Conducted Emissions**

NAME OF TEST: Powerline Conducted Emissions	PARA. NO.: 15.207
TESTED BY:	DATE:

Test Conditions: Test Voltage: _____ VAC
 Temperature: _____ °C
 Humidity: _____ %

Minimum Standard:

Frequency(MHz)	Maximum Powerline Conducted RF Voltage	
	μV	dBμV
0.45 - 30.0	250	48

Test Results: Complies/Does not Comply. See attached graphs and table.

Test Data: See attached graphs and table.

Method Of Measurement: (Procedure ANSI C63.4-1992)

Measurements were made using a spectrum analyzer with 10 kHz RBW, Peak detector. Any emissions that are close to the limit are measured using a test receiver with 10 kHz bandwidth, CISPR Quasi-Peak detector.

Broadband emissions are identified by switching the receiver detector function from Quasi-Peak to Average. If the amplitude of the emission drops by 6 dB or more then the emission is classified as broadband and the Quasi-Peak level is reduced by a factor of 13 dB.

All emissions within 10 dB of limit have been recorded.

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Measurement Data:

Conductor	Frequency (MHz)	CISPR (dBμV)	Average (dBμV)	BB/NB	BB Correction (dB)	Result (dBμV)

NOT APPLICABLE

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Conducted Photographs (Worst Case Configuration)

SIDE VIEW


NOT APPLICABLE

FRONT VIEW


EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Section 10. Block Diagrams

Conducted Emissions




Radiated Prescan




EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Outdoor Test Site For Radiated Emissions



The spectrum was searched up to the 10th harmonic of the fundamental frequency of operation.

Occupied Bandwidth



EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Section 11. Test Equipment List

Equipment List - Radiated Emissions

CAL Cycle	Equipment	Manufacturer	Model #	Serial/Asset #	Last Cal.	Next Cal.
1 Year	Dipole Antenna Set	EMCO	3121C	1029	Oct. 28/97	Oct. 28/98
1 Year	Receiver	Rohde & Schwarz	ESVP	892661/014	Mar. 31/98	Mar. 31/99
1 Year	Spectrum Analyzer	Hewlett-Packard	8565E	FA000981	May 9/97	May 9/98
1 Year	Spectrum Analyzer	Hewlett-Packard	8566B	2311A02238	Sept. 30/97	Sept. 30/98
1 Year	Spectrum Analyzer Display	Hewlett-Packard	8566B	2314A04759	Sept. 30/97	Sept. 30/98
1 Year	Quasi-Peak Adapter	Hewlett Packard	85650A	2043A00302	Sept. 30/97	Sept. 30/98
2 Year	Horn Antenna	EMCO	3115	4336	Oct. 30/97	Oct. 30/99
1 Year	Low Noise Amplifier	Avantek	AWT-8035	1005	Oct. 24/97	Oct. 24/98

Note: N/A = Not Applicable
NCR = No Cal Required

KTL Ottawa

FCC PART 15, SUBPART C
FOR LOW POWER TRANSMITTERS
PROJECT NO.: 8R00716
ANNEX A

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

ANNEX A
RESTRICTED BANDS

EQUIPMENT: Remote Transmitter
FCC ID: MVJTX4DU01

Section A Restricted Bands of Operation

(a) Except as shown in paragraph (d) of this section , only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.15
0.49 - 0.51	16.69475-16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425-16.80475	960-1240	7.25-7.75
3.020 - 3.026	25.5-25.67	1300-1427	8.025-8.5
4.125 - 4.128	37.5-38.25	1435-1626.6	9.0-9.2
4.17725 - 4.17775	73-74.6	1645.5-1646.5	9.3-9.5
4.20725 - 4.20775	74.8-75.2	1660-1710	10.6-12.7
6.215 - 6.218	108-121.94	1718.8-1722.2	13.25-13.4
6.31175 - 6.31225	123-138	2220-2300	14.47-14.5
8.291 - 8.294	149.9-150.05	2310-2390	15.35-16.2
8.362 - 8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625 - 8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425 - 8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29 - 12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975 - 12.52025	240-285	3345.8-3358	36.43-36.5
12.57675 - 12.57725	322-335.4	3600-4400	Above 38.6
13.36 - 13.41			