

# REPORT OF MEASUREMENT

## CERTIFICATION

Product : Communications Receiver (Pager Receiver)

Applicant : Intron Co., Ltd.

Grantee Name : Intron Co., Ltd.

FCC ID. : N2MINP-150

Trade Name : APEX

Model No. : INP-150

Report No. : 341-066

Date : September 30, 1998

KOREA ACADEMY OF INDUSTRIAL TECHNOLOGY(KAITECH)

Address : 222-13, Guro-Dong, Guro-Gu, Seoul 152-053, Korea  
Tel. : (02)860-1462~4. Telefax : (02)860~1468

## TABLE OF CONTENTS

I. GENERAL INFORMATION .....		1
1. Applicant's Name and Mailing Address		
2. Manufacturer's Name and Mailing Address		
3. Equipment Descriptions		
4. Rules and Regulations		
5. Measuring Procedure		
6. Date of Measurement		
7. Statement of Compliance		
II. GENERAL REQUIREMENTS OF THE EUT .....		2
1. Labelling Requirement (Section 15.19)		
2. Information to User (Sections 15.21)		
3. Special Accessories (Section 15.27)		
III. RADIATED EMISSION MEASUREMENT (Section 15.109).....		3-7
1. Test Procedure		
2. Photograph for the worst case configuration		
3. Sample Calculation		
4. Measurement Data		
IV. TEST EQUIPMENTS USED FOR MEASUREMENT.....		8

## ATTACHMENTS

1. Statement for Section 15.37 of the Rules
2. Proposed FCC ID. Label and Marking
3. Manual for Installation and Operating Instruction
4. Block Diagram & Schematic Diagram
5. Description of Circuit Function
6. Photographs: See the illustration of photographs attached

I. GENERAL INFORMATION

1. Applicant's Name and Mailing Address : Intron Co., Ltd.  
2nd Fl. Chung Bong Bldg., 218-25, Poi-Dong, Kangnam-Ku,  
Seoul, Korea 135-260

2. Manufacturer's Name and Mailing Address : Intron Co., Ltd.  
2nd Fl. Chung Bong Bldg., 218-25, Poi-Dong, Kangnam-Ku,  
Seoul, Korea 135-260

3. Equipment Descriptions

3.1 Tuning Frequency : 144.000MHz ~ 174.100MHz (25kHz Spacing)

3.2 Detect Method : Superheterodyne Detector

3.3 Local Oscillator : 1st Local Osc. Frequency = Tuning Frequency - 21.4MHz(1st IF)  
2nd Local Osc. Frequency = 20.945MHz (2nd IF : 455kHz)

3.4 Used Crystal : 1st Local Crystal = 1st Local Osc. Frequency/2  
2nd Local Crystal = 20.945MHz

3.5 Power Supply : DC 1.5V (Battery)

4. Rules and Regulations : FCC Part 15, Subpart B

5. Measuring Procedure : ANSI C63.4-1992

6. Date of Measurement

6.1 Line Conducted : Not Applicable

6.2 Radiated Emission : September 29, 1998

7. Statement of Compliance

We, KAITECH, HEREBY STATE THAT the measurements shown in this report were made in accordance with the procedures indicated and the emission emitted by this equipment was found to be within the limits applicable.

Measured by :

S. J. KimSeok-Jin Kim  
Senior Engineer

Review by :

  
Chang Ho Ko  
Team Leader  
EMC Team

II. GENERAL REQUIREMENTS OF THE EUT

## 1. Labelling Requirement (Section 15.19)

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

1.1 Location on Enclosure : Manual for Installation and Operating Instruction1.2 How Applied : Printing

## 2. Information to User (Section 15.21)

The following or similar statements were provided in the manual for user instruction.  
Please refer page 45 of the attached manual for details.

**CAUTION** : Any changes or modifications in construction of this device which are not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

## 3. Special Accessories (Section 15.27)

3.1 Were the special Accessories provided?  yes,  no

3.2 If yes, details for the special accessories are as follows :

3.3 If yes, were the appropriate instructions provided on the first page of the text concerned with the device?  yes,  no

3.4 Are these accessories provided of the type which can be readily obtained from multiple retail outlets?  yes,  no

And therefore does the manual specify what additional components or accessories are required to used in order to comply with the Rules?  yes,  no

### III. RADIATED EMISSION MEASUREMENT (Section 15.109)

#### 1. Test Procedure

##### 1.1 Preliminary Testing for Reference

This pager receiver(EUT) is designed to operate in the band 144.000MHz to 174.100MHz by changing a local oscillator installed in internal PCB. According to section 15.31(m), the measurements were performed with three equipments which were selected as bottom, middle, and top frequency in the operating band.

Preliminary testing was performed in a KAITECH absorber-lined room to determine the emission characteristics of the EUT. The EUT was placed on the wooden table which has dimensions of 0.8 meters in height, 1 meter in length and 1.5 meters in width. Receiving antenna(Biconical antenna : 30 to 300MHz, Log-periodic antenna : 200 to 1000MHz or Horn Antenna : 1 to 18GHz) was placed at the distance of 1 meter from the EUT.

An attempt was made to maximize the emission level with the various configurations of the EUT while rotating the table and varying antenna height.

Emissions level from the EUT with various configurations were examined on a Spectrum Analyzer connected with a RF amplifier and graphed by a plotter.

##### 1.2 Final Radiated Emission Test at a Absorber-Lined Room

The final measurement of radiated field strength was carried out in a KAITECH Absorber-Lined Room that was listed up at FCC according to the "Radiated Emissions Testing" procedure specified by ANSI C63.4.

Based on the test results in preliminary test, measurement was made in same test set up and configuration which produced maximum emission level. Receiving antenna was installed at 3-meter distance from the EUT, and was connected to an EMI receiver or spectrum analyzer(for above 1GHz) with a RF amplifier.

Turntable was rotated through 360 degrees and receiving antenna height was varied from 1 to 4 meters above the ground plane to read maximum emission level.

If necessary, the radiated emission measurements could be performed at a closer distance than specified distance to ensure higher accuracy and their results were extrapolated to the specified distance using an inverse linear distance extrapolation factor(20dB/decade) as per Section 15.31(f).

The maximum emission level from the EUT occurred in such configuration as shown in the following photograph.

## 4 Measurement Data

#### 4.1 Operating Frequency (Bottom : 144.000MHz Tuning)

- Resolution Bandwidth :  CISPR Quasi-Peak (6dB Bandwidth : 120kHz)  
 Peak (3dB Bandwidth : 300kHz)
- Measurement Distance : 3 Meter

### Note

Note : Detect Mode (P : Peak, Q : Quasi-Peak, A : Average)  
 \* D.M. : Polarization (H : Horizontal, V : Vertical)

\* D.M. : Detect Mode (P : Peak, S : Suppression)  
 A.P. : Antenna Polarization (H : Horizontal, V : Vertical)

A.P. : Antenna Polarization Factor

A.F. : Antenna F  
G.I. : Cable Loss

C.L. : Cable Loss  
A.C. : Amplifier C.

A.G. : Amplifier Gain  
 D.C.F. : Distance Correction Factor

D.C.F. : Distance Correction Factor

$$** \text{ Margin (dB)} = \text{Emission Level (dB)} - \text{Limit (dB)}$$

\*\*\* Margin (dB) = EMI  
\*\*\* < means less than. The observed EMI receiver(ESVS30) noise floor level was 2.0dB/N. And all other emissions not reported on data were more than 30dB below the permitted level.



KAITECH Log No. 341 - 066

#### 4.3 Operating Frequency (Top : 174.100MHz Tuning)

- Resolution Bandwidth :  CISPR Quasi-Peak (6dB Bandwidth : 120kHz)  
 Peak (3dB Bandwidth : 300kHz)
- Measurement Distance : 3 Meter

### Note

Note  
\*      D.M.    : Detect Mode (P : Peak, Q : Quasi-Peak, A : Average)  
      A.P.    : Antenna Polarization (H : Horizontal, V : Vertical)  
      A.F.    : Antenna Factor  
      C.L.    : Cable Loss  
      A.G.    : Amplifier Gain  
      D.C.F.    : Distance Correction Factor  
 $M_{\text{min}} \text{ (dB)} = \text{Emission Level (dB)} - \text{Limit (dB)}$

\*\* Margin (dB) = Emission Level (dB) - Limit (dB)

\*\*\* Margin (dB) = Emission -  $2.0dB/N$   
\*\*\* < means less than. The observed EMI receiver(ESVS30) noise floor level was 2.0dB/N. And all other emissions not reported on data were more than 30dB below the permitted level.

KAITECH Log No. 341 - 066

IV. TEST EQUIPMENT USED FOR MEASUREMENTS

<u>Equipment</u>	<u>Model No.</u>	<u>Manufacturer</u>	<u>Serial No.</u>	<u>Effective Cal. Duration</u>
[x] EMI Receiver (20MHz-1GHz)	ESVS30	R & S	830516/002	06/29/98-06/29/99
[x] Spectrum Analyzer (9kHz-26.5GHz)	8563A	H. P.	3222A02069	01/30/98-01/30/99
[ ] Spectrum Analyzer (100Hz-22GHz)	8566B	H. P.	3014A07057	05/29/98-05/29/99
[ ] Quasi-Peak Adapter (10kHz-1GHz)	85650A	H. P.	3107A01511	05/29/98-05/29/99
[ ] RF-Preselector (20Hz-2GHz)	85685A	H. P.	3010A01181	05/29/98-05/29/99
[ ] Test Receiver (9kHz-30MHz)	ESH3	R & S	860905/001	06/29/98-06/29/99
[x] Pre-Amplifier (0.1-3000MHz, 30dB)	8347A	H. P.	2834A00543	05/29/98-05/29/99
[ ] Pre-Amplifier (1-26.5GHz, 35dB)	8449B	H. P.	3008A00302	06/29/98-06/29/99
[ ] LISN(50Ω, 50µH) (10kHz-100MHz)	3825/2	EMCO	9010-1710	-
[ ] LISN(50Ω, 50µH) (10kHz-100MHz)	3825/2	EMCO	9011-1720	-
[x] Plotter	7470A	H. P.	3104A21292	-
[ ] Tuned Dipole Ant. (30MHz-300MHz)	VHA 9103	Schwarzbeck	-	*
[ ] Tuned Dipole Ant. (300MHz-1GHz)	UHA 9105	Schwarzbeck	-	*
[x] Biconical Ant. (30MHz-300MHz)	BBA 9106	Schwarzbeck	-	*
[x] Log Periodic Ant. (200MHz-1GHz)	3146	EMCO	-	*
[ ] Horn Ant. (1GHz-18GHz)	3115	EMCO	-	*
[ ] DC Power Supply	6260B	H.P.	1145A04822	-
[ ] Shielded Room	(5.0m x 4.5m)	SIN-MYUNG	-	-

\* Each set of antennas has been calibrated to ensure correlation with ANSI C63.5 standard.  
 The calibration of antennas is traceable to Korea Standard Research Institute(KSRI).