



HARNESS INFORMATION MODEL : 750HP

- 4P
- RED : (+) 12V DC POWER INPUT(15A)
 - WHITE : (+) 12V FLASHING LIGHT OUTPUT(10A)
 - BROWN : (+) 12V DC SIREN OUTPUT(1A)
 - BLACK : (-) GROUND

- 8P
- YELLOW : (+) IGNITION INPUT
 - VIOLET : (+) POSITIVE DOOR TRIGGER INPUT
 - GREEN : (-) NEGATIVE DOOR TRIGGER INPUT
 - BLUE : (-) NEGATIVE TRUNK TRIGGER INPUT
 - PINK : (-) DOME LIGHT OUTPUT(500mA)
 - GRAY : (-) TRUNK RELEASE OUTPUT(500mA)
 - BROWN : (-) CHANNEL 3 OUTPUT(500mA)
 - ORANGE : (-) STARTER KILL / GROUND
ARMING OUTPUT(500mA)

- 3P
- BLUE : (-/+) DOOR UNLOCK OUTPUT (+/-500mA)
 - RED : (+) 12V DC OUTPUT(+500mA)
 - GREEN : (-/+) DOOR LOCK OUTPUT (+/-500mA)

- 4P
- BLACK
 - BLUE
 - RED
 - GREEN
- PLUG IN SHOCK
SENSOR
(DUAL STAGE)

- 2P
- GRAY
 - BLACK
- PLUG IN VALET

- 2P
- BLACK
 - RED
- PLUG IN L E D

FCC ID : N2R750HPRX

This device complies with FCC Rules part 15. Operation is subject to the following two conditions:
1) This device may not cause harmful interference and 2) This device must accept any interference that may be received, including interference that may cause undesired operation.

PROGRAMMING DIP SWITCH

SW#	ON	OFF
SW1	PASSIVE ARMING	ACTIVE ARMING
SW2	PASSIVE LOCKING	ACTIVE LOCKING

B JUMP PROGRAMMING

+	-
<input type="checkbox"/>	<input type="checkbox"/>
DOOR LOCK	DOOR UNLOCK