

HARNESS INFORMATION MODEL : P-50

- RED : (+) 12V DC POWER INPUT (15A)
- WHITE : (+) 12V FLASHING LIGHT OUTPUT (10A)
- BLACK : (-) GROUND
- YELLOW : (+) IGNITION INPUT
- ORANGE : (-) STARTER KILL / GROUND
- 9P — ARMING OUTPUT (-500mA)
- VIOLET : (-) DOME LIGHT OUTPUT (-500mA)
- GRAY : (-) CH2 OUTPUT (-500mA)
- GREEN : (-) CH3 OUTPUT (-500mA)
- BLUE : (-+) 2 STAGE DOOR UNLOCK OUTPUT
(-+500mA)

- BLUE : (-+) DOOR UNLOCK OUTPUT (-+500mA)
- 3P — RED : (+) 12V DC OUTPUT (+500mA)
- GREEN : (-+) DOOR LOCK OUTPUT (-+500mA)

FCC ID : N2RP-50RX

This device complies with FCC Rules part 15. Operation is subject to the following two conditions: (1) This device may not cause harmful interference and (2) This device must accept any interference that may be received, including interference that may cause undesired operation.

RED WIRE LOOP
PASSIVE ARMING : CUTTING
ACTIVE ARMING : UNCUTTING
B-JUMPS

Please note the FCC ID on the right side of the receiver module.