

FCC TEST REPORT

For

Magic Box S

Model Number: DE9989

FCC ID: N2UDE9989

Report Number : WT138001510

Test Laboratory : Shenzhen Academy of Metrology and Quality
Inspection
National Testing Center for Digital Electronic Products
Site Location : Bldg. Metrology and Quality Inspection, Longzhu
Road, Shenzhen, Guangdong, China
Tel : 0086-755-26941599
Fax : 0086-755-26941545
Web : www.smq.com.cn

Test report declaration

Applicant : A.E. Yayincilik Film REK.BILG.VE ORG.HIZ.LTD.STI
Address : Menekseli Sk. 22, Levent – Istanbul 34330, Turkey
Manufacturer : Shenzhen Deyu Baina Technology Co., Ltd.
Address : 4th FL,Building J,WeiKangDe Industrial Park, ShangXue
Area, JiHua RD,BanTian Committee,LongGang,SZ P.R.China
EUT : Magic Box S
Description
Model No : DE9989
Trade mark : Blu.boo
Serial Number : N/A
FCC ID : N2UDE9989

Test Standards:

FCC Part 15 15.207, 15.209, 15.247(2012)

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with FCC Rules Part 15.207, 15.209 and 15.247.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.



Project Engineer:	 _____ (Wu Feiyun)	Date:	<u>July 1,2013</u>
Checked by:	 _____ (Yang Dongping)	Date:	<u>July 1,2013</u>
Approved by:	 _____ (Lin Bin)	Date:	<u>July 1,2013</u>

TABLE OF CONTENTS

TEST REPORT DECLARATION	2
1. TEST RESULTS SUMMARY	5
2. GENERAL INFORMATION	6
2.1. Report information.....	6
2.2. Laboratory Accreditation and Relationship to Customer	6
2.3. Measurement Uncertainty	7
3. PRODUCT DESCRIPTION.....	8
3.1. EUT Description.....	8
3.2. Related Submittal(s) / Grant (s)	8
3.3. Block Diagram of EUT Configuration	8
3.4. Operating Condition of EUT.....	9
3.5. Support Equipment List	9
3.6. Test Conditions	9
3.7. Special Accessories.....	9
3.8. Equipment Modifications	9
4. TEST EQUIPMENT USED.....	10
5. CONDUCTED DISTURBANCE TEST	11
5.1. Test Standard and Limit	11
5.2. Test Procedure	11
5.3. Test Arrangement.....	11
5.4. Test Data	11
6. RADIATED DISTURBANCE TEST	15
6.1. Test Standard and Limit	15
6.2. Test Procedure	15
6.3. Test Arrangement.....	15
6.4. Test Data	16
7. 20DB BANDWIDTH MEASUREMENT	19
7.1. LIMITS OF 20dB BANDWIDTH MEASUREMENT	19
7.2. TEST PROCEDURE.....	19
7.3. TEST SETUP.....	19
7.4. EUT OPERATING CONDITIONS.....	19
7.5. Test Data	19
8. CARRIER FREQUENCY SEPARATION MEASUREMENT.....	24
8.1. LIMITS OF Carrier frequency separation measurement.....	24
8.2. TEST PROCEDURES	24
8.3. TEST SETUP	24
8.4. EUT OPERATING CONDITIONS.....	24
8.5. Test Data	24
9. NUMBER OF HOPPING CHANNEL	25
9.1. LIMITS OF 9. NUMBER OF HOPPING CHANNEL.....	25
9.2. TEST PROCEDURE.....	26
9.3. TEST SETUP	26

9.4.	EUT OPERATING CONDITION	26
9.5.	Test Data	26
10.	TIME OF OCCUPANCY	27
10.1.	LIMITS OF TIME OF OCCUPANCY	27
10.2.	TEST PROCEDURE	28
10.3.	EUT OPERATING CONDITION	28
10.4.	TEST RESULTS	28
11.	PEAK POWER	32
11.1.	LIMITS OF Peak Power	32
11.2.	TEST PROCEDURE	32
11.3.	EUT OPERATING CONDITION	32
11.4.	TEST RESULTS	32
12.	BAND EDGES MEASUREMENT	36
12.1.	LIMITS OF BAND EDGES MEASUREMENT	36
12.2.	TEST PROCEDURE	36
12.3.	EUT OPERATING CONDITION	37
12.4.	TEST RESULTS	37

1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	FCC Rules	Test Results
20dB bandwidth measurement	15.247 (a) (1)	Pass
Carrier frequency separation measurement	15.247 (a) (1)	Pass
Number of hopping channel	15.247 (a) (1) III	Pass
Time of occupancy	15.247 (a) (1) III	Pass
Peak output power	15.247 (b) (1)	Pass
Band edge compliance measurement	15.247 (d)	Pass
Radiated spurious emission & Radiated restricted band measurement	15.247 (d) / 15.205 & 15.209	Pass
Conducted emission test for power port	15.207	Pass

Remark: "N/A" means "Not applicable."

2. GENERAL INFORMATION

2.1. Report information

- 2.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.
- 2.1.2. The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 2.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at Bldg. of Metrology & Quality Inspection, Longzhu Road, Nanshan District, Shenzhen, Guangdong, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number are 979748 (semi anechoic chamber).

The Laboratory is listed in Voluntary Control Council for Interference by Information Technology Equipment (VCCI), and the registration number are R-1974(open area test site) , R-1966(semi anechoic chamber),C-2117(mains ports conducted interference measurement) and T-180(telecommunication ports conducted interference measurement).

The Laboratory is registered to perform emission tests with Industry Canada (IC), and the registration number is IC4174.

TUV Rhineland accredits the Laboratory for conformance to IEC and EN standards, the registration number is E2024086Z02.

2.3.Measurement Uncertainty

Conducted Emission

9kHz~30MHz 3.5dB

Radiated Emission

30MHz~1000MHz 4.5dB

1GHz~18GHz 4.6dB

3. PRODUCT DESCRIPTION

3.1. EUT Description

Description : Magic Box S

Manufacturer : Shenzhen Deyu Baina Technology Co., Ltd.

Model Number : DE9989

Operate Frequency : 2.402GHz~2.480GHz

Antenna Designation : PCB Antenna

3.2. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: N2UDE9989, filing to comply with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

3.3. Block Diagram of EUT Configuration



Figure 1 EUT setup

3.4. Operating Condition of EUT

Test Mode 1: Bluetooth

3.5. Support Equipment List

Table 2 Support Equipment List

Name	Model No	S/N	Manufacturer
Notebook	R51	--	IBM
Adaptor for Notebook	02K6654	--	IBM

3.6. Test Conditions

Date of test: June.09-July 1, 2013

Date of EUT Receive: June 09,2013

Temperature: 23-24 °C

Relative Humidity: 53-56%

3.7. Special Accessories

Not available for this EUT intended for grant.

3.8. Equipment Modifications

Not available for this EUT intended for grant.

4. TEST EQUIPMENT USED

Table 3 Test Equipment

No.	Equipment	Manufacturer	Model No.	Last Cal.	Cal. Interval
SB2603	EMI Test Receiver	Rohde & Schwarz	ESCS30	Jan.21, 2013	1 Year
SB3321	AMN	Rohde & Schwarz	ESH2-Z5	Jan.21, 2013	1 Year
SB2604	AMN	Rohde & Schwarz	ESH3-Z5	Jan.21, 2013	1 Year
SB8501/09	EMI Test Receiver	Rohde & Schwarz	ESU40	May.17, 2013	1 Year
SB8501/04	Bilog Antenna	Chase	VULB9163	Jan.21, 2013	1 Year
SB3435	Horn Antenna	Rohde & Schwarz	HF906	Jan.21, 2013	1 Year
SB3435/01	Amplifier(1-18GHz)	Rohde & Schwarz	---	Jan.21, 2013	1 Year
SB3435/02	Amplifier(18-40GHz)	Rohde & Schwarz	---	May.17, 2013	1 Year
SB5392/02	Horn Antenna	Rohde & Schwarz	AT4560	May.17, 2013	1 Year
SB3450/01	3m Semi-anechoic chamber	Albatross Projects	9X6X6	Oct.12, 2012	2 Years

5. CONDUCTED DISTURBANCE TEST

5.1. Test Standard and Limit

5.1.1. Test Standard

FCC Part 15 15.207

5.1.2. Test Limit

Table 4 Conducted Disturbance Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

* Decreasing linearly with logarithm of the frequency

* The lower limit shall apply at the transition frequency.

5.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions form both sides of AC line. According to the requirements in Section 7 and 13 of ANSI C63.4-2003. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.

5.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

5.4. Test Data

The emissions don't show in below are too low against the limits. Refer to the test curves.

Test mode 1: Bluetooth


Table 5 Conducted Disturbance Test Data

Model No.: C3537								
Test mode: 1								
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average		
			Reading (dB μ V)	Emission Level (dB μ V)	Limits (dB μ V)	Reading (dB μ V)	Emission Level (dB μ V)	Limits (dB μ V)
Line	0.170	9.7	34.5	44.2	65.0	23.4	33.1	55.0
	0.218	9.7	40.4	50.1	62.9	28.8	38.5	52.9
	0.338	9.7	21.3	31.0	59.3	1.9	11.6	49.3
	0.450	9.7	21.2	30.9	56.9	6.5	16.2	46.9
	0.674	9.8	19.8	29.6	56	9.4	19.2	46
	0.898	9.8	29.8	39.6	56	19.9	29.7	46
Neutral	0.154	9.7	34.4	44.1	65.8	21.5	31.2	55.8
	0.202	9.7	23.8	33.5	63.5	9.4	19.1	53.5
	0.246	9.7	32.5	42.2	61.9	20.4	30.1	51.9
	0.714	9.8	23.6	33.4	56	14.4	24.2	46
	0.914	9.8	27.1	36.9	56	22.2	32.0	46
	0.970	9.8	23.9	33.7	56	13.3	23.1	46

REMARKS: 1. Emission level(dBuV)=Read Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB) =LISN Factor (dB) + Cable Factor (dB)+Limiter Factor(dB)
 3. The other emission levels were very low against the limit.


Conducted Disturbance

EUT: M/N:DE9989
Op Cond: Bluetooth
Test Spec: L
Comment: AC 120V/60Hz



Conducted Disturbance

EUT: M/N:DE9989
Op Cond: Bluetooth
Test Spec: N
Comment: AC 120V/60Hz



6. RADIATED DISTURBANCE TEST

6.1. Test Standard and Limit

6.1.1. Test Standard

FCC Part 15 15.209

6.1.2. Test Limit

Table 6 Radiated Disturbance Test Limit

FREQUENCY MHz	FIELD STRENGTHS LIMITS ($\mu\text{V/m}$)	FIELD STRENGTHS LIMITS dB ($\mu\text{V/m}$)
Fundamental	50000	94.0
Harmonics	500	54.0
30 ~ 88	100	40.0
88 ~ 216	150	43.5
216 ~ 960	200	46.0
960 ~	500	54.0

* The lower limit shall apply at the transition frequency.

* The test distance is 3m.

6.2. Test Procedure

The EUT is placed on a turntable, which is 0.8 meter above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna is used as a receiving antenna. Both horizontal and vertical polarization of the antenna is set on test. In order to find out the max emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 8 and 13 of ANSI C63.4-2003.

Radiated measurements were performed on the frequency range from 30MHz to 25GHz. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz, $\text{VBW} \geq \text{RBW}$. All readings above 1 GHz are AV and PK values. $\text{RBW}=1\text{MHz}$ and $\text{VBW}=10\text{Hz}$ for AV value, $\text{RBW}=1\text{MHz}$ and $\text{VBW} \geq \text{RBW}$ for peak value.

Measurements were made at 3 meters

6.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

The EUT is set in continuous transmission mode.

6.4. Test Data

The emissions don't show in below are too low against the limits.

Table 7 General Radiated Emission Data

Model No.: DE9989						
Test mode: Channel B						
Below 1GHz						
Frequency MHz	Emission (dBuV/m)	Read Value (dBuV)	Correction Factor (dB/m)	Polarization	Limits (dBuV/m)	Note
--						
--						
--						
Above 1GHz						
Frequency MHz	Emission (dBuV/m)	Read Value (dBuV)	Correction Factor (dB/m)	Polarization	Limits (dBuV/m)	Note
--						
--						
--						

REMARKS: 1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.

Model No.: DE9989						
Test mode: Channel M						
Below 1GHz						
Frequency MHz	Emission (dBuV/m)	Read Value (dBuV)	Correction Factor (dB/m)	Polarization	Limits (dBuV/m)	Note
--						
--						
--						
Above 1GHz						

Frequency MHz	Emission (dBuV/m)	Read Value (dBuV)	Correction Factor (dB/m)	Polarization	Limits (dBuV/m)	Note
4882.075	61.0	58.7	2.3	V	74	PK
4882.075	31.0	28.7	2.3	V	54	AV
--						

REMARKS: 1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.

Model No.: DE9989						
Test mode: Channel T						
Below 1GHz						
Frequency MHz	Emission (dBuV/m)	Read Value (dBuV)	Correction Factor (dB/m)	Polarization	Limits (dBuV/m)	Note
--						
--						
--						
Above 1GHz						
Frequency MHz	Emission (dBuV/m)	Read Value (dBuV)	Correction Factor (dB/m)	Polarization	Limits (dBuV/m)	Note
--						
--						
--						

REMARKS: 1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.

Table 8 Restricted Band Radiated Emission Data

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	
6.31175 - 6.31225	123 - 138	2200 - 2300	
8.291 - 8.294	149.9 - 150.05	2310 - 2390	
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	
12.29 - 12.293	167.72 - 173.2	3332 - 3339	
12.51975 -	240 - 285	3345.8 - 3358	
12.52025	322 - 335.4	3600 - 4400	
12.57675 -			
12.57725			
13.36 - 13.41			

Except as shown in table 9 to table 15, all other emission of the above band were less than the limit 20dB.

7. 20dB BANDWIDTH MEASUREMENT

7.1.LIMITS OF 20dB BANDWIDTH MEASUREMENT

CFR 47 (FCC) part 15.247 (a) (1) and DA 00-705

7.2.TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and $VBW \geq RBW$. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

7.3.TEST SETUP




7.4.EUT OPERATING CONDITIONS

Test mode 1


7.5.Test Data

Table 9 20dB Bandwidth Test Data Basic rate


CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)	results
2402	1.117	Pass
2441	1.109	Pass
2480	1.117	Pass



Date: 14.June.2013 19:57:23




Date: 14.JUN.2013 19:56:40




Date: 14.JUN.2013 19:55:44

Table 10 20dB Bandwidth Test Data EDR

CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)	results
2402	1.377	Pass
2441	1.393	Pass
2480	1.385	Pass



Date: 14.JUN.2013 19:53:09



Date: 14.JUN.2013 19:51:34




* Att 0 dB
Ref -10.00 dBm

* RBW 100 kHz
* VBW 300 kHz
* SWT 5ms

M1[1]

-27.92 dBm
2.479968100 GHz

1Pk
Max



Date: 14.JUN.2013 19:53:58

8. CARRIER FREQUENCY SEPARATION MEASUREMENT

8.1.LIMITS OF Carrier frequency separation measurement

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

8.2.TEST PROCEDURES

- (a) Connect test port of mobile phone to spectrum analyzer and universal communication tester.
- (b) Set the mobile phone to transmit maximum output power at 2.4GHz and switch off frequency hopping function, then set the measured frequency number to two adjacent channels separately and test the carrier frequency separation with spectrum analyzer.

8.3.TEST SETUP




8.4.EUT OPERATING CONDITIONS

Test mode 1

8.5.Test Data

Frequency	Frequency	frequency	Result
[GHz]	[GHz]	separation	
		[MHz]	
2.442	2.441	1.029	Pass



Date: 14.JUN.2013 22:56:24

9. NUMBER OF HOPPING CHANNEL

9.1.LIMITS OF 9. NUMBER OF HOPPING CHANNEL

Number of hopping channel should be compliance with the requirements in part15.247 (a) (1) iii.

9.2. TEST PROCEDURE

- (a) Connect test port of mobile phone to spectrum analyzer and universal communication tester.
- (b) Set the mobile phone to transmit maximum output power at 2.4GHz and switch on frequency hopping function, then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer.
- (c) Count the quantity of peaks to get the number of hopping channels.

9.3. TEST SETUP



9.4. EUT OPERATING CONDITION

Test mode 1

9.5. Test Data


Table 11 Test

Hopping numbers	LIMIT	results
79	>15	Pass

Note: in case of AFH mode, minimum number of hopping channels is 20.



* Att 0 dB
Ref -10.00 dBm
* RBW 1 MHz
* VBW 3 MHz
SWT 2.5ms



Date: 14.JUN.2013 19:29:54

10. TIME OF OCCUPANCY

10.1.LIMITS OF TIME OF OCCUPANCY

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

10.2.TEST PROCEDURE

- (a) Connect test port of mobile phone to spectrum analyzer and universal communication tester.
- (b) Set the mobile phone to transmit maximum output power at 2.4GHz and switch on frequency hopping function.
- (c) Set the span of spectrum analyzer to 0 Hz, and set the resolution bandwidth to 1 MHz and the video bandwidth to 1 MHz, then get the time domain measured diagram. and set sweep time to 2 times of one burst occupancy time, and measure the time of occupancy of one burst.
- (d) Set the resolution bandwidth to 1 MHz and the video bandwidth to 3 MHz, and set the sweep time to a period (0.4 seconds multiplied by the number of hopping channels employed), and count the number of the bursts.
- (e) Calculate the time of occupancy in a period with time occupancy of a burst and quantity of bursts.

10.3.EUT OPERATING CONDITION

Test mode 1

10.4.TEST RESULTS



	Time of Single Slot [ms]	Numbers of slots in a period 3.16s	Time of occupied in a period [s]	Limit [s]	Result
DH1	0.424	32	0.135	≤ 0.4	Pass
DH3	1.36	16	0.217	≤ 0.4	Pass
DH5	2.92	11	0.321	≤ 0.4	Pass

AFH mode



For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to 10 * (# of pulses in 0.8 s) * pulse width.

	Time of Single Slot [ms]	Numbers of slots in a period 3.16s	Time of occupied in a period [s]	Limit [s]	Result
AFH Mode DH5	2.92	11	0.079	≤ 0.4	Pass



DH1



DH3



DH5



11. PEAK POWER

11.1.LIMITS OF Peak Power

Compliance with part 15.247 (b) (1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watt.

11.2.TEST PROCEDURE

- (a) Connect test port of EUT to universal communication tester.
- (b) Set the EUT to transmit maximum output power at 2.4GHz and switch off frequency hopping function.
- (c) Then set the EUT to transmit at high, middle and low frequency and measure the conducted output power separately.


11.3.EUT OPERATING CONDITION

Test mode 1


11.4.TEST RESULTS

Measurement Results (Basic Rate)


Channel	Channel No.	Center Freq. [MHz]	Meas. Level (Cond.) [dBm]	Limit [dBm]	Result
Bottom	0	2402	6.57	< 21	Pass
Middle	39	2441	7.20	< 21	Pass
Top	78	2480	7.36	< 21	Pass



Date: 1.JUL.2013 09:16:36




Date: 1.JUL.2013 09:18:34




Date: 1.JUL.2013 09:21:40

Measurement Results (Modulation: EDR)


Channel	Channel No.	Center Freq. [MHz]	Meas. Level (Cond.) [dBm]	Limit [dBm]	Result
Bottom	0	2402	5.78	< 21	Pass
Middle	39	2441	5.96	< 21	Pass
Top	78	2480	6.32	< 21	Pass



Date: 1.JUL.2013 09:24:07



Date: 1.JUL.2013 09:23:20



Date: 1.JUL.2013 09:22:06

12. BAND EDGES MEASUREMENT

12.1. LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

12.2. TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

12.3.EUT OPERATING CONDITION


Test mode 1

12.4.TEST RESULTS


The measured plots are attached on the following. Test data shows compliance with the band edge requirement in part 15.247(d).

Bluetooth Basic Rate

Copy of FCC Electric Field Strength 1-18GHz




Copy of FCC Electric Field Strength 1-18GHz




Peak detector shows compliance with AV limit, Average test is omitted.

Bluetooth EDR

Copy of FCC Electric Field Strength 1-18GHz



Copy of FCC Electric Field Strength 1-18GHz



Peak detector shows compliance with AV limit, Average test is omitted.

13. CONDUCTED SPURIOUS EMISSIONS

13.1. LIMITS OF BAND EDGES MEASUREMENT

Below -20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

13.2. TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


The bandedges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal

13.3. hopping mode. EUT OPERATING CONDITION


Test mode 1

13.4. TEST RESULTS

Bluetooth Basic
Low channel




Date: 1.JUL.2013 09:37:52




Date: 1.JUL.2013 09:28:25

Mid channel




Date: 1.JUL.2013 09:43:14




Date: 1.JUL.2013 09:30:28

High Channel




Date: 1.JUL.2013 09:45:15




Date: 1.JUL.2013 09:31:36

Band Edge with Hopping On




Date: 1.JUL.2013 09:48:31




Date: 1.JUL.2013 09:46:56

Bluetooth EDR Low channel




Date: 1.JUL.2013 10:08:55




Date: 1.JUL.2013 09:35:19

Mid Channel




Date: 1.JUL.2013 09:54:58




Date: 1.JUL.2013 09:30:28

High Channel




Date: 1.JUL.2013 09:53:38




Date: 1.JUL.2013 09:33:11

Band Edge with Hopping On



Date: 1.JUL.2013 09:50:00



Date: 1.JUL.2013 09:52:02